

MPE ESTIMATION

FCC ID: 2BEXJ-Q8

1, According to §1.1310, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

For WIFI:

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (Numerical)	MPE (mW/cm ²)
2462	13.68	13±1(14)	25.12	3.01	2	0.01

$$Pd = \frac{Pout * G}{4\pi r^2} :$$

Note:

Note: The estimation distance is 20cm

Note: PK Output power= conducted power in mW.

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna in cm

Conducted power see the test report HK2504151895-E, antenna gain=3.01dBi

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01 which is< 1.0, RF Exposure testing is not required.

-----The End-----