



# 시험성적서

## TEST REPORT

페이지(page) : ( 1 )/ ( 총(Total) 19 )

성적서 번호 Report No.		ICRT-TR-E232966-0A		
신청자 Client	기관명 Name	DREXIA Tomasz Wojtasik		
	주 소 Address	ul. Regatowa 19a, 93-482 Łódź		
시험대상품목 Sample description	RFID Reader 13.56MHz			
모델명 Type designation	RS-H0-06P BZ MS			
정 격 Ratings	DC 12 V / 24 V			
시험장소 Place of test	<input checked="" type="checkbox"/> 고정시험(Inside test) <input type="checkbox"/> 현장시험(Field test) 주소지(Address): 112, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea			
시험기간 Date of test	18. Sep. 2023 ~ 25. Oct. 2023			
시험방법/항목 Test Method/Item	FCC Part 15 Subpart C §15.225			
시험결과 Test Results	Refer to 3. Test Summary			
확인 Affirmation	작성자 Tested by 성 명 Name      Si-Yeon, Hwang	(서명) (Signature)	기술책임자 Technical Manager 성 명 Name      Tae-Yang, Yoon	(서명) (Signature)

위 성적서는 고객이 제공한 시료에 대한 시험결과입니다.

The above test report is certified that the above mentioned products have been tested for the sample.

위 성적서는 KS Q ISO/IEC 17025 및 한국인정기구(KOLAS)인정과 관련이 없습니다.

The above test report is not related to accreditation by KS Q ISO/IEC 17025 and Korea Laboratory Accreditation scheme.

위 성적서는 주식회사 아이씨알의 승인 없이는 일부 복제에 대해 금지됩니다.

The test report is prohibited for some reproduction without the approval of the ICR.

2023. 11. 21

주식회사 아이씨알 대표이사

The head of INTERNATIONAL CERTIFICATION REGISTRAR



본 성적서의 진위 확인은 G4B 혹은 ICR 홈페이지에서 가능합니다.

The authenticity of the test report can be checked on the G4B or ICR website.

경기도 김포시 양촌읍 황금3로7번길 112 / Tel: 02-6351-9001 ~ 6



## Contents

1. Applicant & Manufacturer & Test Laboratory Information.....	4
2. Equipment under Test(EUT) Information.....	5
3. Test Summary.....	6
4. Used equipment on test .....	7
5. Test Result_DC 12 V .....	8
6. Test Result_DC 24 V .....	14



페이지(page) : ( 3 ) / ( 총(Total) 19 )

### Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
ICRT-TR-E232966-0A	2023. 11. 21	Initial Issue	All



## **1. Applicant & Manufacturer & Test Laboratory Information**

### **1.1 Applicant information**

Applicant	DREXIA Tomasz Wojtasik
Address	ul. Regatowa 19a, 93-482 Łódź
Contact Person	Piotr Opara
Telephone No.	48422072668
E-mail	t.wojtasik@drexia.pl

### **1.2 Manufacturer Information**

Manufacturer	DREXIA Tomasz Wojtasik
Address	Ekonomiczna 30 93-426 Łódź Poland

### **1.3 Test Laboratory Information**

Conducted tests were performed at	
Laboratory	ICR Co., Ltd.
Address	112, 113, Hwanggeum 3-ro 7beon-gil, Hagun-ri, Yangchon-eup, Gimpo-si, Gyeonggi-do, Korea
Telephone No.	+82-2-6351-9002
Fax No.	+82-2-6351-9007
RRA No.	KR0165
KOLAS No.	KT652



## 2. Equipment under Test(EUT) Information

### 2.1 General Information

Product Name	RFID Reader 13.56MHz
Brand Name	-
Model Name	RS-H0-06P BZ MS
Additional Model Name	-
FCC ID	2BEXQRSH006PBZMS1
Power Supply	DC 12 V / 24 V

### 2.2 Additional Information

Equipment Class	DXX-Low Power communications Device Transmitter	
Operating Frequency	13.56 MHz	
Channel Number	1	
Modulation Type	ASK	
Maximum output power	DC 12 V	66.06 dB $\mu$ V/m
	DC 24 V	65.66 dB $\mu$ V/m
Antenna Type	PCB Antenna	

### 2.3 Mode of operation during the test

- The EUT is continuous transmission mode during the test with set at Low Channel, Middle Channel, and High Channel. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, YZ, XZ planes.

### 2.4 Modifications of EUT

- None



### 3. Test Summary

#### 3.1 Test standards and results

FCC Part 15 Subpart C			
Clause	Test items	Applied	Results
§15.215 (c)	20 dB Bandwidth	<input checked="" type="checkbox"/>	PASS
§15.225 (e)	Frequency Stability Tolerance	<input checked="" type="checkbox"/>	PASS
§15.225 (a)(b)(c)	In-Band Emissions	<input checked="" type="checkbox"/>	PASS
§15.225 (d) §15.209	Out-of-Band Emissions	<input checked="" type="checkbox"/>	PASS

#### 3.2 Purpose of the test

- To determine whether the equipment under test fulfills the requirements of the standards stated in FCC Part 15 Subpart C Section 15.225.

#### 3.3 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013, FCC CFR 47 PART 15.

#### 3.4 Configuration of Test System

##### 3.4.1 Radiated emission test

Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

#### 3.5 Antenna requirement

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### 3.5.1 Result: Pass

The transmitter has a **PCB Antenna**.



#### 4. Used equipment on test

	Description	Model Name	Manufacturer	Serial Number	Next Cal
<input checked="" type="checkbox"/>	SIGNAL GENERATOR	SMB100A	R&S	180607	2024.03.02
<input checked="" type="checkbox"/>	SIGNAL ANALYZER	FSV 40-N	R&S	101936	2024.03.03
<input checked="" type="checkbox"/>	ATTENUATOR	PFA40K2-10	PSATEK	-	2024.03.07
<input checked="" type="checkbox"/>	DC BLOCK	PDCB-00012650-SMSF-3	PSATEK INC.	-	2024.05.02
<input checked="" type="checkbox"/>	CHAMBER	SH-641	ESPEC	92001266	2024.03.03
<input checked="" type="checkbox"/>	LOOP ANTENNA	HFH2-Z2	R&S	100271	2025.03.08
<input checked="" type="checkbox"/>	BI-Log ANTENNA	VULB 9162	R&S	120	2024.12.26
<input checked="" type="checkbox"/>	SIGNAL CONDITIONING UNIT	SCU 08	R&S	100746	2024.04.03
<input checked="" type="checkbox"/>	EMI TEST RECEIVER	ESR26	R&S	101462	2024.04.04
<input checked="" type="checkbox"/>	DC POWER SUPPLY	AGILANT	E3632A	MY51300069	2024.03.03

※ All test equipment used is calibration on a regular basis.



## 5. Test Result DC 12 V

### 5.1 20 dB Bandwidth

#### 5.1.1 Operating environment


Temperature : 21 °C  
Relative humidity : 45 %

#### 5.1.2 Measurement method

Standard : §15.215 (c)

#### 5.1.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth(RBW) is set to 1% to 5% of the OBW. The Video bandwidth is set to 3 times the RBW. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.




#### 5.1.4 Test data

Operating mode : Transmit mode  
Test Result : Pass

#### 5.1.5 Measured Result

Modulation Type	Frequency (MHz)	Measured Value (MHz)		Limit (MHz)
		99% Occupied Bandwidth	20 dB Bandwidth	
ASK	13.56	0.0105	0.0004	do not exceed range in 13.110-14.010 MHz.

#### 5.1.6 Measured Graph Occupied Bandwidth & 20 dB Bandwidth





## 5.2 Frequency Stability Tolerance

### 5.2.1 Operating environment

Temperature : 21 °C

Relative humidity : 45 %


### 5.2.2 Measurement method

Standard : §15.225 (e)

### 5.2.3 Test setup

Measurement procedures were implemented according to the test method of ANSI C63.10: 2013.

Part 15.225 requires that devices operating in the 13.553 ~ 13.567 MHz shall maintain the carrier frequency within 0.01% of the operating frequency over the temperature variation of -20 degrees to +50 degrees C at nominal voltage.



### 5.2.4 Test data

Operating mode : Transmit mode

Test Result : Pass

### 5.2.5 Measured Results

Modulation type	Voltage (%)	Power (DC)	Temperature (°C)	Frequency (Hz)	Freq. DEV (Hz)	Deviation (%)	Limit (%)
ASK	100%	12	50	13 560 200	200	0.0015	0.01
	100%		40	13 560 400	400	0.0029	
	100%		30	13 560 400	400	0.0029	
	100%		20	13 560 400	400	0.0029	
	100%		10	13 560 400	400	0.0029	
	100%		0	13 560 400	400	0.0029	
	100%		-10	13 560 400	400	0.0029	
	100%		-20	13 560 400	400	0.0029	
	85%	10.2	20	13 560 400	400	0.0029	
	115%	13.8	20	13 560 400	400	0.0029	

## 5.3 Radiated Emissions

### 5.3.1 Operating environment

Temperature : 23 °C

Relative humidity : 44 %

### 5.3.2 Measurement method


Standard : §15.225 (a)(b)(c)(d)

### 5.3.3 Test setup


The radiated emissions measurements were performed on the 3 m, Semi-Anechoic Chamber. The EUT was placed on a non-conductive turntable above the ground plane.

The frequency spectrum from 9 kHz to 1 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

#### 5.3.4 Test setup layout Below 30 MHz



### 5.3.5 Test setup layout 30 MHz to 1 GHz



### 5.3.6 Regulation

The EUT must comply with field strength limits defined in section 15.225(a), (b) and (c) of cfr47 FCC Part 15, Subpart C:

Frequency (MHz)	Limit at 30m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)
13.110 to 13.410 and 13.710 to 14.010	40.5	80.5
13.410 to 13.553 and 13.567 to 13.710	50.5	90.5
13.553 to 13.567	84.0	124.0

According to §15.225(d), The field strength of any emissions appearing outside of the 13.110 to 14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009 ~ 0.490	2 400 / F (kHz)	-	300
0.490 ~ 1.705	24 000 / F (kHz)	-	30
1.705 ~ 30	30	29.54	30
30 ~ 88	100	40.00	3
88 ~ 216	150	43.52	3
216 ~ 960	200	46.02	3
Above 960	500	53.98	3

The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector and above 1 000 MHz are based on the average value of measured emissions.



### 5.3.7 Test data for Radiated Electric Field Emissions

Operating mode : Transmit mode

Test Result : Pass

### 5.3.8 Measurement Results (13.553 ~ 13.567) MHz

Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
13.560	46.36	Peak	H	19.7	66.06	124.00	57.94
13.560	44.85	Peak	V	19.7	64.55	124.00	59.45


※ Ant. Pol. : Antenna Polarization

※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain

※ Result = Reading + Corr. Factor

※ Margin =Limit - Result

### 5.3.9 Measured Graph (13.111 MHz ~ 14.01 MHz)



#### Final Result

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)	Corr. (dB)	Comment
13.559511	44.85	124.00	79.15	5000.0	9.000	V	300.0	19.7	
13.559601	46.36	124.00	77.64	5000.0	9.000	H	257.0	19.7	

Acc. to above test data, the field strength level of 13.56 MHz is 66.06 dB $\mu$ V/m and the worst limit subject to 15.225 (b) and (c) is 80.5 dB $\mu$ V/m, so the EUT meets the requirement.




### 5.3.10 Spurious Emission Test

### 5.3.11 Measurement Results for Below 30 MHz

Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
It was not found any emissions peaks found from the EUT.							

### 5.3.12 Measurement Results for below 1 GHz



### Final Result

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
179.962000	39.13	43.50	4.37	1000.0	120.000	100.0	V	59.0	-26.7
204.018000	40.98	43.50	2.52	1000.0	120.000	100.0	V	173.0	-25.1
227.977000	43.22	46.00	2.78	1000.0	120.000	100.0	V	119.0	-23.8
251.936000	34.56	46.00	11.44	1000.0	120.000	100.0	V	298.0	-22.6
347.966000	42.39	46.00	3.61	1000.0	120.000	100.0	V	298.0	-19.8
372.022000	41.09	46.00	4.91	1000.0	120.000	100.0	V	173.0	-19.5



## 6. Test Result DC 24 V

### 6.1 20 dB Bandwidth

#### 6.1.1 Operating environment


Temperature : 21 °C  
Relative humidity : 45 %

#### 6.1.2 Measurement method

Standard : §15.215 (c)

#### 6.1.3 Test setup

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth(RBW) is set to 1% to 5% of the OBW. The Video bandwidth is set to 3 times the RBW. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.




#### 6.1.4 Test data

Operating mode : Transmit mode  
Test Result : Pass

#### 6.1.5 Measured Result

Modulation Type	Frequency (MHz)	Measured Value (MHz)		Limit (MHz)
		99% Occupied Bandwidth	20 dB Bandwidth	
ASK	13.56	0.0094	0.0003	do not exceed range in 13.110-14.010 MHz.

#### 6.1.6 Measured Graph Occupied Bandwidth & 20 dB Bandwidth





## 6.2 Frequency Stability Tolerance

### 6.2.1 Operating environment

Temperature : 21 °C

Relative humidity : 45 %


### 6.2.2 Measurement method

Standard : §15.225 (e)

### 6.2.3 Test setup

Measurement procedures were implemented according to the test method of ANSI C63.10: 2013.

Part 15.225 requires that devices operating in the 13.553 ~ 13.567 MHz shall maintain the carrier frequency within 0.01% of the operating frequency over the temperature variation of -20 degrees to +50 degrees C at nominal voltage.



### 6.2.4 Test data

Operating mode : Transmit mode

Test Result : Pass

### 6.2.5 Measured Results

Modulation type	Voltage (%)	Power (DC)	Temperature (°C)	Frequency (Hz)	Freq. DEV (Hz)	Deviation (%)	Limit (%)
ASK	100%	12	50	13 560 200	200	0.0015	0.01
	100%		40	13 560 400	400	0.0029	
	100%		30	13 560 400	400	0.0029	
	100%		20	13 560 400	400	0.0029	
	100%		10	13 560 400	400	0.0029	
	100%		0	13 560 400	400	0.0029	
	100%		-10	13 560 400	400	0.0029	
	100%		-20	13 560 400	400	0.0029	
	85%	10.2	20	13 560 400	400	0.0029	
	115%	13.8	20	13 560 400	400	0.0029	

## 6.3 Radiated Emissions

### 6.3.1 Operating environment

Temperature : 23 °C

Relative humidity : 44 %

### 6.3.2 Measurement method


Standard : §15.225 (a)(b)(c)(d)

### 6.3.3 Test setup


The radiated emissions measurements were performed on the 3 m, Semi-Anechoic Chamber. The EUT was placed on a non-conductive turntable above the ground plane.

The frequency spectrum from 9 kHz to 1 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

#### 6.3.4 Test setup layout Below 30 MHz



### 6.3.5 Test setup layout 30 MHz to 1 GHz



### 6.3.6 Regulation

The EUT must comply with field strength limits defined in section 15.225(a), (b) and (c) of cfr47 FCC Part 15, Subpart C:

Frequency (MHz)	Limit at 30m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)
13.110 to 13.410 and 13.710 to 14.010	40.5	80.5
13.410 to 13.553 and 13.567 to 13.710	50.5	90.5
13.553 to 13.567	84.0	124.0

According to §15.225(d), The field strength of any emissions appearing outside of the 13.110 to 14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

According to §15.209(a), for an intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009 ~ 0.490	2 400 / F (kHz)	-	300
0.490 ~ 1.705	24 000 / F (kHz)	-	30
1.705 ~ 30	30	29.54	30
30 ~ 88	100	40.00	3
88 ~ 216	150	43.52	3
216 ~ 960	200	46.02	3
Above 960	500	53.98	3

The emission limits shown in the above table are based on measurement instrumentation employing a CISPR quasi-peak detector and above 1 000 MHz are based on the average value of measured emissions.



### 6.3.7 Test data for Radiated Electric Field Emissions

Operating mode : Transmit mode

Test Result : Pass

### 6.3.8 Measurement Results (13.553 ~ 13.567) MHz

Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
13.562	45.96	Peak	H	19.7	65.66	124.00	58.34
13.559	44.75	Peak	V	19.7	64.45	124.00	59.55


※ Ant. Pol. : Antenna Polarization

※ Corr. Factor. : Antenna Factor + Cable Loss - Amplifier Gain

※ Result = Reading + Corr. Factor

※ Margin =Limit - Result

### 6.3.9 Measured Graph (13.111 MHz ~ 14.01 MHz)



#### Final Result

Frequency (MHz)	MaxPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azim uth (deg)	Corr. (dB)	Comment
13.559421	44.75	124.00	79.25	5000.0	9.000	V	350.0	19.7	
13.561938	45.96	124.00	78.04	5000.0	9.000	H	236.0	19.7	

Acc. to above test data, the field strength level of 13.56 MHz is 65.66 dB $\mu$ V/m and the worst limit subject to 15.225 (b) and (c) is 80.5 dB $\mu$ V/m, so the EUT meets the requirement.




### 6.3.10 Spurious Emission Test

### 6.3.11 Measurement Results for Below 30 MHz

Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Ant. Pol. (H/V)	Corr. Factor (dB)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
It was not found any emissions peaks found from the EUT.							

### 6.3.12 Measurement Results for below 1 GHz



### Final Result

Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
179.962000	40.18	43.50	3.32	1000.0	120.000	100.0	V	46.0	-26.7
204.018000	40.89	43.50	2.61	1000.0	120.000	100.0	V	176.0	-25.1
227.977000	43.29	46.00	2.71	1000.0	120.000	100.0	V	275.0	-23.8
252.033000	40.40	46.00	5.60	1000.0	120.000	100.0	V	301.0	-22.6
324.007000	41.76	46.00	4.24	1000.0	120.000	100.0	V	275.0	-20.9
347.966000	42.39	46.00	3.61	1000.0	120.000	100.0	V	275.0	-19.8

- END OF REPORT -