



SPECIFICATION FOR APPROVAL

CUSTOMER NAME:

PRODUCT NAME: 5G L=130mm+MHF

CUSTOMER P/N:

Ren Feng P/N: U00T02S000N01697 REV: A

	MANUFACTURER SIGNATURE	CUSTOMER SIGNATURE
CHECKED BY:	Yang Zhen	
AUDITOR BY:	Song Jun	
APPROVED BY:	Yao Ding Jun	
DATE:	2022-08-08	



Contents

<i>Item</i>	<i>Description</i>
1、-----	Change resume
2、-----	Specification table
3、-----	Finished drawing
4、-----	Test report
5、-----	ROHS/ Raw Materials List

1、Change resume


[illegible]

2、Specification table:


Product main technical parameters

Main technical specifications		Main technical specifications	
Frequency Range (MHZ)	5150-5850	Frequency Range (MHZ)	51550-5850
Impedance (Ω)	50	Impedance(Ω)	50
Peak Gain (dBi)	5.08	Peak Gain(dBi)	5.08
VSWR	≤ 2.0	VSWR	≤ 2.0
Radiation	Omni-directional	Radiation	Omni-directional
Connector Type	Copper	Connector Type	Copper
Physical Properties		Physical Properties	
Antenna cover	PCB	Antenna cover	PCB
Operating Temp	-20℃~+70℃	Operating Temp	-20℃~+70℃
Storage Temp	-20℃~+70℃	Storage Temp	-20℃~+70℃

3、Finished drawing :




4 、 Test report




WIFI 5G-2





XY



XZ



YZ



WIFI 5G-2		
频率 (MHZ)	增益 (dBi)	效率 (%)
5150	4.67	66.54
5500	4.9	68.07
5850	5.08	70.53

5、ROHS/ Raw Materials List:

Meet RoHS requirements.

Component coding	component name	The raw materials team needs materials	usage quantity	unit	Material manufacturer	UL certification	remark
1	PCB	FR-4	1	pc	good luck	/	
2	Cable	tinn/FEP	1	pc	Cable/Sea Unicom	/	
3	Copper	phosphor bronze	1	pc	Color beauty	/	
4	gum	3M300LSE	1	pc	Pengsheng	/	