



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-TRF-01 Rev 1.1

Report No.: GZCR231000104602

Page: 1 of 24

FCC ID: 2BEYB-TP-WE-WRB9B

TEST REPORT

Application No.: GZCR2310001046AT
Applicant: Comba Network (Singapore) Pte Ltd
Address of Applicant: 80 Playfair Road, Kapo Factory Building, #01-18. Singapore 367998
Manufacturer: COMBA NETWORK SYSTEMS COMPANY LTD
Address of Manufacturer: No.10, Shenzhou Road, Guangzhou Science City, Guangzhou, Guangdong, P.R. China
Factory: COMBA NETWORK SYSTEMS COMPANY LTD
Address of Factory: No.10, Shenzhou Road, Guangzhou Science City, Guangzhou, Guangdong, P.R. China
Equipment Under Test (EUT):
EUT Name: LTE800 Digital Wireless Repeater
Model No.: TP-WE-WR-DSL080B220P43Q-UK-MW
Trade Mark: Comba
Standard(s) : 47 CFR Part 2
47 CFR Part 20
47 CFR Part 90
Date of Receipt: 2023-10-11
Date of Test: 2023-10-16 to 2023-11-10
Date of Issue: 2024-04-08

| | |
|---------------------|--------------|
| Test Result: | Pass* |
|---------------------|--------------|

* In the configuration tested, the EUT complied with the standards specified above.

Ricky Liu

Ricky Liu
Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

| Revision Record | | | |
|-----------------|------------------|------------|----------|
| Version | Report No. | Date | Remark |
| 01 | GZCR231000104602 | 2024-04-08 | Original |
| | | | |
| | | | |

| | | | |
|--------------------------|--|---|--|
| Authorized for issue by: | | | |
| | |  | |
| | | Kevin Zhang/Project Engineer | |
| | |  | |
| | | Jerry Chan/Reviewer | |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2 Test Summary

| Item | Standard | Method | Requirement | Result |
|--|----------------------|--|----------------------------------|--------|
| Out-of-band rejection | KDB935210 D05 v01r04 | KDB935210 D05 v01r04 clause 4.3 | KDB935210 D05 v01r04 clause 4.3 | Pass |
| Input-versus-output signal comparison | 47 CFR Part 2 | ANSI C63.26-2015 clause 5.4 | Part 2.1049 | Pass |
| Input/output output power and amplifier/booster gain | 47 CFR Part 90 | KDB935210 D05 v01r04 clause 4.5 | Part 90.635 Part 90.219(e)(2) | Pass* |
| Emission MASK | | KDB935210 D05 v01r04 clause 4.4 | Part 90.210 | Pass |
| Noise Figure | | KDB935210 D05 v01r04 clause 4.6 | Part 90.219(e)(2) | Pass |
| Intermodulation emissions | | KDB935210 D05 v01r04 clause 4.7 | Part 90.219(d)(6) | Pass |
| Conducted spurious emissions | | KDB935210 D05 v01r04 clause 4.7 | Part 90.691 | Pass |
| Noise | | KDB935210 D05 v01r04 clause 4.7 | Part 90.219(d)(6) | Pass |
| Frequency stability | | 47 CFR Part 2.1055 KDB935210 D05 v01r04 clause 4.8 ANSI C63.26-2015 Clause 5.6 | Part 90.213 | Pass |
| Radiated spurious emissions | | KDB935210 D05 v01r04 clause 3.8 ANSI C63.26-2015 Clause 5.5 | Part 90.691 | Pass |

* : According to KDB 935210 D02 Signal Booster Certification v04r02 clause V.J for device support output power higher than 5W ERP limit of Section 90.219(e)(1), the specific station authorizations are required the conditions.

Note:

E.U.T./ EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

The present report covers requirements for 806-817MHz/851-862MHz.



3 Contents

| | Page |
|--|------|
| 1 Covers Page | 1 |
| 2 Test Summary | 3 |
| 3 Contents | 4 |
| 4 General Information | 6 |
| 4.1 Details of EUT | 6 |
| 4.2 Description of Support Units | 6 |
| 4.3 Test Environment | 7 |
| 4.4 Measurement Uncertainty | 7 |
| 4.5 Test Signals and Test Channels | 8 |
| 4.6 Test Location | 9 |
| 4.7 Test Facility | 9 |
| 4.8 Deviation from Standards | 9 |
| 4.9 Abnormalities from Standard Conditions | 9 |
| 5 Equipment List | 10 |
| 6 Radio Spectrum Matter Test Results | 12 |
| 6.1 Out-of-band rejection | 12 |
| 6.1.1 E.U.T. Operation | 12 |
| 6.1.2 Test Setup | 12 |
| 6.1.3 Measurement Record | 12 |
| 6.2 Input versus output comparison | 13 |
| 6.2.1 E.U.T. Operation | 13 |
| 6.2.2 Test Setup | 13 |
| 6.2.3 Measurement Record | 13 |
| 6.3 Input/output output power and amplifier/booster gain | 14 |
| 6.3.1 E.U.T. Operation | 14 |
| 6.3.2 Test Setup | 14 |
| 6.3.3 Measurement Record | 14 |
| 6.4 Emissions MASK | 15 |
| 6.4.1 E.U.T. Operation | 16 |
| 6.4.2 Test Setup | 16 |
| 6.4.3 Measurement Record | 16 |
| 6.5 Noise Figure | 17 |
| 6.5.1 E.U.T. Operation | 17 |
| 6.5.2 Test Setup | 17 |
| 6.5.3 Measurement Record | 17 |
| 6.6 Intermodulation emissions | 18 |
| 6.6.1 E.U.T. Operation | 18 |
| 6.6.2 Test Setup | 18 |
| 6.6.3 Measurement Record | 18 |
| 6.7 Conducted Spurious emissions | 19 |
| 6.7.1 E.U.T. Operation | 19 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

| | | |
|-------------|---|-----------|
| 6.7.2 | Test Setup..... | 19 |
| 6.7.3 | Measurement Record..... | 19 |
| 6.8 | Noise..... | 20 |
| 6.8.1 | E.U.T. Operation..... | 20 |
| 6.8.2 | Test Setup..... | 20 |
| 6.8.3 | Measurement Record..... | 20 |
| 6.9 | Frequency Stability..... | 21 |
| 6.9.1 | E.U.T. Operation..... | 21 |
| 6.9.2 | Test Setup..... | 21 |
| 6.9.3 | Measurement Record..... | 21 |
| 6.10 | Radiated Spurious emission..... | 22 |
| 6.10.1 | E.U.T. Operation..... | 22 |
| 6.10.2 | Test Setup..... | 22 |
| 6.10.3 | Test procedure..... | 23 |
| 6.10.4 | Measurement Record..... | 23 |
| 7 | Test Setup Photographs..... | 24 |
| 8 | EUT Constructional Details (EUT Photos)..... | 24 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4 General Information

4.1 Details of EUT

| | | |
|--|--|-------------------------|
| Power Supply: | AC 120V, 50~60Hz | |
| Test Voltage: | AC 120V | |
| Cable: | AC mains (1.5m, unshielded) | |
| Operating Temperature: | -25 to +55 °C | |
| Operating Humidity: | 5% to 95% | |
| Frequency Range: | Uplink | 806-817MHz & 817-824MHz |
| | Downlink | 851-862MHz & 862-869MHz |
| Support Technology: | LTE/Analog FM | |
| Support Channel BW: | LTE | 5MHz/10MHz |
| | FM | 6.25kHz/12.5kHz/25kHz |
| Declared Class Type: | Class B Signal Booster (without audio low pass filter) | |
| Interface: | Antenna Port | 2 (4.3-10 Female) |
| | Debug Port | 1 (RJ-45) |
| Normal Output Power: (per antenna port) | Uplink | 27dBm |
| | Downlink | 40dBm |
| Normal Gain: | Uplink | 90dB |
| | Downlink | 95dB |
| Declared Antenna Type: | External Dedicated Antenna | |
| Declared Permission | 10dBi or less | |
| Antenna Gain: | | |
| Software Version: | V01.00.00.00 | |

4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|---|--------------|-------------------------|------------|
| Notebook | LENOVO | Lenovo Xiaoxinchao 5000 | PF0TNMG8 |
| Mathced load and attenuator supplied by the client | / | / | / |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4.3 Test Environment

| Environment Parameter | Selected Values During Test | |
|-----------------------|-----------------------------|-------------|
| Ralative Humidity | Ambient | |
| Value | Temperature (°C) | Voltage (V) |
| TNVN | Asmbient | AC 120 |
| TLVL | -30 | AC 102 |
| TLVH | -30 | AC 138 |
| THVL | +50 | AC 102 |
| THVH | +50 | AC 138 |

VN: Normal Voltage, TN: Normal Teperature

VL: Lower Extreme Voltege, VH: Higher Extreme Voltage

TL: Lower Extreme Teperature, TH: Higher Extreme Teperature

4.4 Measurement Uncertainty

| No. | Item | Measurement Uncertainty |
|-----|--------------------------------|--|
| 1 | RF Output Power | ±0.75dB |
| 2 | Transmitter unwanted emissions | ±0.75dB |
| 3 | Radiated Spurious Emission | ±5.06dB (30MHz-1GHz; 3m); ±4.46dB (30MHz-1GHz; 10m); ±5.08dB (1GHz-6GHz); ±5.14dB (6GHz-18GHz) |
| 4 | Occupied Channel Bandwidth | ± 3% |

Remark:
The test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



4.5 Test Signals and Test Channels

EUT supporting digitally modulated signal LTE 5MHz/10MHz only declared by applicant, 4.1MHz AWGN signal substituted for LTE 5MHz/10MHz as test signals in the report.

| Downlink: 851-862MHz | | | |
|----------------------|----------------------|-------------|----------------------|
| Test Channel | Test Frequency (MHz) | Test Signal | Stimulus Condition |
| LCH | 853.5 | 4.1MHz AWGN | a single test signal |
| MCH | 856.5 | | |
| HCH | 859.5 | | |
| MCH | 865.5 | 4kHz FM | a single test signal |
| MCH | 865.5 | 11.3kHz FM | |
| MCH | 865.5 | 16kHz FM | |

| Uplink: 806-817MHz | | | |
|--------------------|----------------------|-------------|----------------------|
| Test Channel | Test Frequency (MHz) | Test Signal | Stimulus Condition |
| LCH | 808.5 | 4.1MHz AWGN | a single test signal |
| MCH | 811.5 | | |
| HCH | 814.5 | | |
| MCH | 811.5 | 4kHz FM | a single test signal |
| MCH | 811.5 | 11.3kHz FM | |
| MCH | 811.5 | 16kHz FM | |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,
Guangdong, China 510663

Tel: +86 20 82155555

No tests were sub-contracted.

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

● ISED (Registration No.: 4620B, CAB identifier: CN0052)

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

● VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.8 Deviation from Standards

None

4.9 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

5 Equipment List

Conducted test equipment

| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
|---|-------------------------|-----------|--------------|------------|--------------|
| Temperature Chamber | GZ GongWen Co.Ltd. | GDJW-100 | EMC0039 | 2023-06-29 | 2024-06-28 |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight | N9010A | EMC2138 | 2023-08-23 | 2024-08-22 |
| MXA Signal Analyzer (10Hz-50GHz) | KEYSIGHT | N9020B | SEM004-24 | 2023-03-20 | 2024-03-19 |
| 4X4 Power Sensor Unit | TST | TSPS2023R | EMC2257 | 2023-08-23 | 2024-08-22 |
| Test Software | TST | V2.0 | GZE100-78 | N/A | N/A |
| ESG vector signal generator (250kHz-6GHz) | Agilent Technologies | E4438C | SEM006-03 | 2023-02-20 | 2024-02-19 |

Radiated Emissions (30MHz-1GHz)

| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
|---|---------------------------------------|----------------------|--------------|------------|--------------|
| EMI Test Receiver (1Hz-8GHz) | Rohde & Schwarz | ESW8 | EMC2229 | 2023-02-20 | 2024-02-19 |
| 966 Anechoic Chamber | Shenzhen C.R.T Technology Co., LTD | 9mX6mX6m | EMC2230 | 2022-04-12 | 2025-04-11 |
| Network Analyzer (100k-8.5GHz) | KEYSIGHT | ENA Series E5071C | EMC2191 | 2023-03-02 | 2024-03-01 |
| Amplifier (9k-1000MHz) | SONOMA | 310 | EMC2237 | 2023-04-13 | 2024-04-12 |
| TRILOG Broadband Antenna (25M-2GHz) | SCHWARZBECK | VULB 9168 | EMC2238 | 2022-04-20 | 2025-04-19 |
| Horn Antenna 1-18GHz | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120D | EMC2251 | 2022-08-02 | 2025-08-01 |
| Coaxial Cable | Times Microwave | TMC- AMI19394A | EMC239 | 2022-05-18 | 2024-05-17 |
| TRILOG Broadband Antenna (25M-2GHz) | SCHWARZBECK | VULB 9168 | SEM003-18 | 2022-03-03 | 2025-03-02 |
| EMI Test Receiver (1Hz- 8GHz) | Rohde & Schwarz | ESW8 | EMC2220 | 2023-05-19 | 2024-05-18 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

| Radiated test equipment (above 1GHz) | | | | | |
|---|--------------------------------|---------------|--------------|------------|--------------|
| Equipment | Manufacturer | Model No | Inventory No | Cal Date | Cal Due Date |
| 1GHz-26.5 GHz Pre-Amplifier | Agilent | 8449B | EMC0521 | 2022-12-16 | 2023-12-15 |
| Microwave Broadband Preamplifier (18-40GHz) | SCHWARZBECK | BBV 9721 | EMC2172 | 2023-08-21 | 2024-08-20 |
| EMI Test Receiver (10Hz-26.5GHz) | Rohde & Schwarz | ESIB26 | EMC0522 | 2022-12-16 | 2023-12-15 |
| EXA Signal Analyzer (10Hz-44GHz) | Keysight | N9010A | EMC2138 | 2023-08-23 | 2024-08-22 |
| Chamber cable (Above 1GHz) | Scoflex | KMKM-8.0m | EMC0545 | 2022-08-24 | 2024-08-23 |
| Chamber Cable (Below 1GHz) | Scoflex | KMKM-8.0m | EMC0546 | 2022-08-24 | 2024-08-23 |
| Trilog Broadband Antenna (25MHz-1GHz) | SCHWARZBECK | VULB 9160 | EMC2025 | 2022-09-07 | 2025-09-06 |
| Horn Antenna (1GHz-18GHz) | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120D | EMC2026 | 2022-09-21 | 2025-09-20 |
| Horn Antenna 1-18GHz | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120D | EMC2251 | 2022-02-02 | 2025-08-01 |
| Horn Antenna (14-40GHz) | SCHWARZBECK | BBHA 9170 | EMC2041 | 2023-06-18 | 2026-06-17 |
| Broad-Band Horn Antenna (15-40GHz) | Schwarzbeck | BBHA 9170 | SEM003-15 | 2021-7-11 | 2024-07-10 |
| 966 Anechoic Chamber | C.R.T | 9m x 6m x 6m | EMC2142 | 2020-12-20 | 2023-12-19 |
| Test Software E3 | Audix | Ver.6.120110a | GZE100-61 | N/A | N/A |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6 Radio Spectrum Matter Test Results

6.1 Out-of-band rejection

Test Requirement: KDB 935210 D05 clause 4.3

Test Method: KDB 935210 D05 clause 4.3

Limit: Within the passband


6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.1.2 Test Setup



6.1.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


6.2 Input versus output comparison

| | |
|-------------------|--|
| Test Requirement: | 47 CFR Part 2.1049 |
| Test Method: | KDB 935210 D05 clause 4.4 |
| Requirement: | FCC Part 90.219 (e)(4): A signal booster must be designed such that all signals that it retransmits meet the following requirements: (i) The signals are retransmitted on the same channels as received. Minor departures from the exact provider or reference frequencies of the input signals are allowed, provided that the retransmitted signals meet the requirements of § 90.213 frequency stability. (ii) There is no change in the occupied bandwidth of the retransmitted signals. (iii) The retransmitted signals continue to meet the unwanted emissions limits of § 90.210 emission mask applicable to the corresponding received signals (assuming that these received signals meet the applicable unwanted emissions limits by a reasonable margin). |
| Limit: | 1. The spectral plots of the output signal and the input signal are similar (in passband and rolloff characteristic features and relative spectral locations). 2. Compliance with the emission mask of the EUT output refer to report clause 6.4 emission mask. |

6.2.1 E.U.T. Operation

| | |
|------------------------|--|
| Operating Environment: | |
| Temperature: | 24.4 °C |
| Humidity: | 58 % RH |
| Atmospheric Pressure: | 1008 mbar |
| EUT Operation: | Drive the EUT to the maximum output power at maximum gain. |

6.2.2 Test Setup



6.2.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



6.3 Input/output output power and amplifier/booster gain

Test Requirement: 47 CFR Part 90.635, 90.219(e)(1)

Test Method: KDB 935210 D05 clause 4.5

Limit:

1. The effective radiated power and antenna height for base stations may not exceed 1 kilowatt (30 dBw) and 304 m. (1,000 ft.) above average terrain (AAT), respectively, or the equivalent thereof as determined from the Table. These are maximum values, and applicants will be required to justify power levels and antenna heights requested.
2. The output power capability of a signal booster must be designed for deployments providing a radiated power not exceeding 5 Watts ERP for each retransmitted channel.


6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.3.2 Test Setup



6.3.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



6.4 Emissions MASK

Test Requirement: 47 CFR Part 90.210
 Test Method: KDB 935210 D05 clause 4.4
 Limit:

90.210 (d) MASK D

For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88)$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is the lesser attenuation.

90.210 (g) MASK G

For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 10 kHz, but no more than 250 percent of the authorized bandwidth: At least $116 \log(f_d/6.1)$ dB, or $50 + 10 \log(P)$ dB, or 70 dB, whichever is the lesser attenuation.
- (2) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least $43 + 10 \log(P)$ dB.

90.210 (h) MASK H

For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of 4 kHz or less: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 4 kHz, but no more than 8.5 kHz: At least $107 \log(f_d/4)$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 8.5 kHz, but no more than 15 kHz: At least $40.5 \log(f_d/1.16)$ dB.
- (4) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 15 kHz, but no more than 25 kHz: At least $116 \log(f_d/6.1)$ dB.
- (5) On any frequency removed from the center of the authorized bandwidth by more than 25 kHz: At least $43 + 10 \log(P)$ dB.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


6.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.4.2 Test Setup



6.4.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


6.5 Noise Figure

Test Requirement: 47 CFR Part 90.219(e)(2)
 Test Method: KDB 935210 D05 clause 4.6
 Limit: The noise figure of a signal booster must not exceed 9 dB in either direction.

6.5.1 E.U.T. Operation

Operating Environment:
 Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar
 EUT Operation: Set the EUT to the maximum gain.

6.5.2 Test Setup



6.5.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

6.6 Intermodulation emissions

Test Requirement: 47 CFR Part 90.219(d)(6)

Test Method: KDB 935210 D05 clause 4.7.2

Limit: Good engineering practice must be used in regard to the radiation of intermodulation products and noise, such that interference to licensed communications systems is avoided. In the event of harmful interference caused by any given deployment, the FCC may require additional attenuation or filtering of the emissions and/or noise from signal boosters or signal booster systems, as necessary to eliminate the interference.

(i) In general, the ERP of intermodulation products should not exceed -30 dBm in 10 kHz measurement bandwidth.


6.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.6.2 Test Setup



6.6.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



6.7 Conducted Spurious emissions

Test Requirement: 47 CFR Part 90.691,

Test Method: KDB 935210 D05 clause 3.6

Limit: Part 90.691 :

1. For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.
2. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


6.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.7.2 Test Setup



6.7.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



6.8 Noise

Test Requirement: 47 CFR Part 90.219(d)(6)

Test Method: KDB 935210 D05 clause 4.7.2

Limit: Good engineering practice must be used in regard to the radiation of intermodulation products and noise, such that interference to licensed communications systems is avoided. In the event of harmful interference caused by any given deployment, the FCC may require additional attenuation or filtering of the emissions and/or noise from signal boosters or signal booster systems, as necessary to eliminate the interference.

(ii) In general, the ERP of noise within the passband should not exceed -43 dBm in 10 kHz measurement bandwidth.

(iii) In general, the ERP of noise on spectrum more than 1 MHz outside of the passband should not exceed -70 dBm in a 10 kHz measurement bandwidth.


6.8.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Set the EUT to the maximum gain.

6.8.2 Test Setup



6.8.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



6.9 Frequency Stability

Test Requirement: 47 CFR Part 90.213

Test Method: 47 CFR Part 2.1055
KDB 935210 D05 clause 4.8
ANSI C63.26-2015 clause 5.6

Limit: 806-809≤1.0 ppm; 851-854≤1.0 ppm
809-824≤1.5 ppm; 854-869≤1.5 ppm


6.9.1 E.U.T. Operation

Operating Environment:

Temperature: 24.4 °C Humidity: 58 % RH Atmospheric Pressure: 1008 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.9.2 Test Setup



6.9.3 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



6.10 Radiated Spurious emission

Test Requirement: 47 CFR Part 90.691

Test Method: KDB 935210 D05 clause 3.8
ANSI C63.26-2015 clause 5.5

Limit: For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


6.10.1 E.U.T. Operation

Operating Environment:


Temperature: 25.3 °C Humidity: 62 % RH Atmospheric Pressure: 1020 mbar

EUT Operation: Drive the EUT to the maximum output power at maximum gain.

6.10.2 Test Setup



below 1GHz



above 1GHz

6.10.3 Test procedure

1. Scan from 30MHz to 40GHz, find the maximum radiation frequency to measure.
2. The technique used to find the Spurious Emissions of the transmitter was the antenna substitution method. Substitution method was performed to determine the actual ERP/EIRP emission levels of the EUT.

Below 1GHz test procedure as below:

- 1) The EUT was powered on and placed on a table in the chamber. The antenna of the transmitter was extended to its maximum length. modulation mode and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- 2) Rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3) Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4) The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5) A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6) The output power into the substitution antenna was then measured.
- 7) Steps 5) and 6)were repeated with both antennas vertically polarized.
- 8) Calculate power in dBm by the following formula:

Level (dBm) = Read Level (dBm) + Correction Factor (dB)

Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber.
 - 2) Calculate power in dBm by the following formula:
- Level (dBm) = Read Level (dBm) + Correction Factor (dB)

6.10.4 Measurement Record

Please refer to Appendix - Test Data and Result for report GZCR231000104602.



7 Test Setup Photographs

Refer to Appendix - Test Setup Photos for GZCR2310001046AT.

8 EUT Constructional Details (EUT Photos)

Refer to Appendix -External and Internal Photos for GZCR2310001046AT.

- End of the Report -



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com