



## 13. Radio Frequency Exposure

### 13.1 Applicable Standards

<input type="checkbox"/>	§1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																														
<input type="checkbox"/>	§1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where $R > \lambda / 2\pi$ .																																														
TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION																																																
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">RF Source Frequency</th> <th style="text-align: center;"><math>f_L</math> MHz</th> <th style="text-align: center;"><math>f_H</math> MHz</th> <th style="text-align: center;"><math>\lambda_L / 2\pi</math></th> <th style="text-align: center;">Minimum Distance</th> <th style="text-align: center;"><math>\lambda_H / 2\pi</math></th> <th style="text-align: center;">Threshold ERP</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">0.3</td><td style="text-align: center;">—</td><td style="text-align: center;">1.34</td><td style="text-align: center;">159 m</td><td style="text-align: center;">—</td><td style="text-align: center;">35.6 m</td><td style="text-align: center;">1,920 <math>R^2</math></td> </tr> <tr> <td style="text-align: center;">1.34</td><td style="text-align: center;">—</td><td style="text-align: center;">30</td><td style="text-align: center;">35.6 m</td><td style="text-align: center;">—</td><td style="text-align: center;">1.6 m</td><td style="text-align: center;">3,450 <math>R^2/f^2</math></td> </tr> <tr> <td style="text-align: center;">30</td><td style="text-align: center;">—</td><td style="text-align: center;">300</td><td style="text-align: center;">1.6 m</td><td style="text-align: center;">—</td><td style="text-align: center;">159 mm</td><td style="text-align: center;">3.83 <math>R^2</math></td> </tr> <tr> <td style="text-align: center;">300</td><td style="text-align: center;">—</td><td style="text-align: center;">1,500</td><td style="text-align: center;">159 mm</td><td style="text-align: center;">—</td><td style="text-align: center;">31.8 mm</td><td style="text-align: center;">0.0128 <math>R^2/f</math></td> </tr> <tr> <td style="text-align: center;">1,500</td><td style="text-align: center;">—</td><td style="text-align: center;">100,000</td><td style="text-align: center;">31.8 mm</td><td style="text-align: center;">—</td><td style="text-align: center;">0.5 mm</td><td style="text-align: center;">19.2 <math>R^2</math></td> </tr> </tbody> </table>							RF Source Frequency	$f_L$ MHz	$f_H$ MHz	$\lambda_L / 2\pi$	Minimum Distance	$\lambda_H / 2\pi$	Threshold ERP	0.3	—	1.34	159 m	—	35.6 m	1,920 $R^2$	1.34	—	30	35.6 m	—	1.6 m	3,450 $R^2/f^2$	30	—	300	1.6 m	—	159 mm	3.83 $R^2$	300	—	1,500	159 mm	—	31.8 mm	0.0128 $R^2/f$	1,500	—	100,000	31.8 mm	—	0.5 mm	19.2 $R^2$
RF Source Frequency	$f_L$ MHz	$f_H$ MHz	$\lambda_L / 2\pi$	Minimum Distance	$\lambda_H / 2\pi$	Threshold ERP																																										
0.3	—	1.34	159 m	—	35.6 m	1,920 $R^2$																																										
1.34	—	30	35.6 m	—	1.6 m	3,450 $R^2/f^2$																																										
30	—	300	1.6 m	—	159 mm	3.83 $R^2$																																										
300	—	1,500	159 mm	—	31.8 mm	0.0128 $R^2/f$																																										
1,500	—	100,000	31.8 mm	—	0.5 mm	19.2 $R^2$																																										
<p>Subscripts L and H are low and high; <math>\lambda</math> is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.</p>																																																
<input checked="" type="checkbox"/>	§ 1.1307(b)(3)(i)(B).	Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$																																														
$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>Where</p> $x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$ <p>and</p> $ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p><math>d</math> = the separation distance (cm);</p>																																																



### 13.2 EUT Specification

Frequency band (Operating)	<input type="checkbox"/> WLAN: 2412MHz ~ 2462MHz <input type="checkbox"/> WLAN: 5150MHz ~ 5250MHz <input type="checkbox"/> WLAN: 5250MHz ~ 5350MHz <input type="checkbox"/> WLAN: 5470MHz ~ 5725MHz <input type="checkbox"/> WLAN: 5725MHz ~ 5850MHz <input type="checkbox"/> Bluetooth: 2402MHz ~ 2480MHz <input checked="" type="checkbox"/> RFID: 902MHz~928MHz
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption
<b>Remark:</b> The maximum conducted output power is <u>27.18 dBm (522.396 mW)</u> at <u>902.75MHz (with 7.5 dBi antenna gain.)</u>	

### 13.3 Result

Channel Frequency (MHz)	Max. Conducted output power(dBm)	Max. Tune up power (dBm)	Antena Cable Loss(dB)	Antena Gain (dBi)	Max.Tune up e.r.p. Power (dBm)	Max. Tune up e.r.p power (mW)	Limit (mW)
902.75	27.18	27.68	0.5	8	33.03	2009.09	1841.61
914.75	27.11	27.61	0.5	8	32.96	1976.97	1866.09
927.25	27.08	27.58	0.5	8	32.93	1963.36	1891.59

No non-compliance noted.

-----THE END OF REPORT-----