

MPE ESTIMATION

FCC ID: 2BF2OE27

1, According to §1.1310, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

2, Estimation Result

For WIFI:

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (Numerical)	MPE (mW/cm ²)
2437	14.64	14±1(15)	31.62	2.23	1.67	0.01052
$Pd = \frac{P_{out} * G}{4\pi r^2}$;						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power in mW.						
G=power gain of the antenna in the direction of interest relative to an isotropic radiator						
R=distance to the center of radiation of the antenna in cm						
Conducted power see the test report HK2507013568-E, antenna gain=2.23dBi						

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01052 which is< 1.0, RF Exposure testing is not required.

-----The End-----