



DC Fast Charging Station

- FOR USE WITH ELECTRIC VEHICLES.

- POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.



CONFORMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 32380-SI2023
FCC ID: 2BF33- SI2023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

Model No. SDC240

AC Input	480V / 3P+N+GND	Rated 304A/240kW@50Hz/60Hz
DC Output A#(CCS1)	150~1000VDC	Max. 250A (@50°C)
DC Output B#(CCS1)	150~1000VDC	Max. 250A (@50°C)
Electrical Enclosure	Type 3R (Rainproof)	
Temperature Rating	-30 ~ 50°C	
Net Weight	480kg	
S/N	2305WYKF22-00010001	
Manufactured	XX/XX/XXXX	

Wagawoo. Inc



DC Fast Charging Station

- FOR USE WITH ELECTRIC VEHICLES.

- POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.



CONFORMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 32380-SI2023
FCC ID: 2BF33- SI2023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

Model No. SDC180

AC Input	480V / 3P+N+GND	Rated 228A/180kW@50Hz/60Hz
DC Output A#(CCS1)	150~1000VDC	Max. 250A (@50°C)
DC Output B#(CCS1)	150~1000VDC	Max. 250A (@50°C)
Electrical Enclosure	Type 3R (Rainproof)	
Temperature Rating	-30 ~ 50°C	
Net Weight	448kg	
S/N	2305WYKF22-00010001	
Manufactured	XX/XX/XXXX	

Wagawoo. Inc



DC Fast Charging Station

- FOR USE WITH ELECTRIC VEHICLES.

- POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.



CONFORMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 32380-SI2023
FCC ID: 2BF33- SI2023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

Model No. SDC150

AC Input	480V / 3P+N+GND	Rated 190A/150kW@50Hz/60Hz
DC Output A#(CCS1)	150~1000VDC	Max. 250A (@50°C)
DC Output B#(CCS1)	150~1000VDC	Max. 250A (@50°C)
Electrical Enclosure	Type 3R (Rainproof)	
Temperature Rating	-30 ~ 50°C	
Net Weight	432kg	
S/N	2305WYKF22-00010001	
Manufactured	XX/XX/XXXX	

Wagawoo. Inc



DC Fast Charging Station

- FOR USE WITH ELECTRIC VEHICLES.

- POUR UTILISATION AVEC DES VÉHICULES ÉLECTRIQUES.



CONFORMS TO UL STD.2202
CERTIFIED TO CSA STD.C22.2#346



CAN ICES-3(A)/NMB-3(A)
IC: 32380-SI2023
FCC ID: 2BF33- SI2023
4G module
Contains FCC ID:XMR201909EC25AFX
Contains IC:10224A-2019EC25AFX

Model No. SDC120

AC Input	480V / 3P+N+GND	Rated 152A/120kW@50Hz/60Hz
DC Output A#(CCS1)	150~1000VDC	Max. 250A (@50°C)
DC Output B#(CCS1)	150~1000VDC	Max. 250A (@50°C)
Electrical Enclosure	Type 3R (Rainproof)	
Temperature Rating	-30 ~ 50°C	
Net Weight	416kg	
S/N	2305WYKF22-00010001	
Manufactured	XX/XX/XXXX	

Wagawoo. Inc



Label Location