



RF EXPOSURE REPORT

Applicant	:	Synamedia Americas LLC
Address of Applicant	:	1715 N Brown Rd Building B, Lawrenceville, GA 30043, USA
Manufacturer	:	Wuxi Weida Intelligent Electronics Co., Ltd.
Address of Manufacturer	:	3rd Floor, Building A, No.789 Nanhu Avenue, Wuxi City, Jiangsu Province (High end Sensor Manufacturing Base), China
Equipment under Test	:	Bluetooth remote control
Model No.	:	B042-01-W9
FCC ID	:	2BF5E-B042
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24041304-1E02
Issue Date	:	2024/05/22
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	General Test Information.....	5
1.1.	Description of EUT.....	5
1.2.	Accessories of EUT	5
1.3.	Test laboratory	5
2.	RF Exposure evaluation for FCC.....	6
3.	Photos of the EUT	7

Test Report Declare

Applicant	:	Synamedia Americas LLC
Address of Applicant	:	1715 N Brown Rd Building B, Lawrenceville, GA 30043, USA
Equipment under Test	:	Bluetooth remote control
Model No.	:	B042-01-W9
Manufacturer	:	Wuxi Weida Intelligent Electronics Co., Ltd.
Address of Manufacturer	:	3rd Floor, Building A, No.789 Nanhу Avenue, Wuxi City, Jiangsu Province (High end Sensor Manufacturing Base), China

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24041304-1E02		
Date of Receipt:	2024/04/23	Date of Test:	2024/04/23~2024/05/22

Prepared By:

Tiger Mo/Engineer

Approved By:

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/05/22	

1. General Test Information

1.1. Description of EUT

EUT Name	:	Bluetooth remote control
Model Number	:	B042-01-W9
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	Battery 1.5V*2(Size: AAA)

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“” means to be chosen or applicable; “” means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF EXPOSURE EVALUATION FOR FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance

Mode	Antenna	Frequency [MHz]	Target (dBm)	Tolerance \pm (dB)
GFSK (Peak)	Ant1	2402	-5.91	2
		2440	-5.03	2
		2480	-5.08	2

Estimation Result

Worse case is as below: [2440 MHz, -3.03 dBm, (0.498 mW) output power]

$(0.498/5) \cdot [\sqrt{2.440(\text{GHz})}] = 0.156 < 3.0 \text{ for 1-g SAR}$

Then SAR evaluation is not required.

3. Photos of the EUT

Please refer to DDT-Q24041304-2E appendix I

-----End Report-----