

 Split time	<p>Click [Split time] to enter the setting of the video segmentation time. Video segmentation time is optional: 1 minute/3 minutes/5 minutes</p> <p><i>The system defaults to 3 minutes</i></p>
 Collision Sensitivity	<p>Click [Collision Sensitivity] to set the sensitivity</p> <p>Off/Low/Middle/High</p>
 Microphone	<p>Click [Microphone] to turn on/off audiorecording.</p>
 Rear mirror image	<p>Click [Rear Mirror Image] to turn on/off the mirroring function, which can adjust 180° flip the rear view image horizontally, making it easier for customers to install the camera flexibly.</p>
 Reverse Line Calibration	<p>Click [Reverse Line Calibration] to enter the reversing settings. The screen will display the status and the reversing line frame on/off when reversing. You can adjust the reversing line according to the size of your car.</p>

c) System Setting



 <i>Language</i>	Click [Language] to set the display Language to Simplified Chinese/Traditional Chinese/English/Russian/Spanish/French/German/Japanese/Korean/Arabic/Italian/Portuguese
 <i>Screen Rotation</i>	Click [Screen Rotation] to rotate the screen 180 degrees for easy installation
 <i>Tip sound</i>	Click [Tip sound] to turn off/on the touch and boot sound.
 <i>Date & Time</i>	Click [Date & Time] to set the screen display time and timestamp of the video recorded by the camera at the same time. You can setup separately year/month/day/time/minutes/second/12H system/24H system.

 Storage info	Click [Storageinfo] to view the SD card storage space
 Format	Click [Format] to format all data information. We recommend manually formatting the TF card when first inserted to ensure sufficient card capacity. Note: We recommend that user manually format the TF card regularly.
 Factory reset	Click [Factory reset] to enter the Restore the factory settings. You can restore all the settings to the initial state
 Firmware version	Click on [Firmware version] to view the version information of the device. Please provide this interface to the after-sales customer service staff when you need our help.

6. Parking Monitor

This function will be triggered when the hardwire kit is connected, (as photo)

Option: Off/Low/Middle/High

ZKCAMSPY Hardwire Kit:
ASIN: [B0BZP4HT5V](https://www.amazon.com/dp/B0BZP4HT5V)





Made in China