

# TEST REPORT

## For WiFi-5GHz Band




Report No. ....	<b>CHTW24080052</b>	Report Verification:
Project No. ....	<b>SHT2311064901EW</b>	
FCC ID ....	<b>2BFB9-SID-ATMET</b>	
Applicant's name ....	<b>Shenzhen AOTO Electronics Co., Ltd.</b>	
Address.....	Room 1805, Tower 2, Shum Yip Jinyuan Building, Qingshuihe Street, Luohu District, Shenzhen, China	
Product Name .....	<b>Meeting card</b>	
Trade Mark .....	<b>AOTO</b>	
Model No. ....	<b>ATMET2K</b>	
Listed Model(s) .....	ATMET4K,ATMET8K,ATMET2KA,ATMET4KA,ATMET8KA, ATMET2KB,ATMET4KB,ATMET8KB,ATMET2KC,ATMET4KC, ATMET8KC	
Standard .....	<b>FCC CFR Title 47 Part 15 Subpart E § 15.407</b>	
Date of receipt of test sample.....	Dec.05, 2023	
Date of testing.....	Dec.05, 2023 - Aug.11, 2024	
Date of issue.....	Aug.12, 2024	
Result.....	<b>PASS</b>	


Compiled by  
(Position+Printed name+Signature): File administrators Kiki Kong



Supervised by  
(Position+Printed name+Signature): Project Engineer Kiki Kong



Approved by  
(Position+Printed name+Signature): RF Manager Xu yang



**Testing Laboratory Name .....** **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

## Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	3
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	4
<u>3.</u>	<u>SUMMARY</u>	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	6
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	7
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Test sample information	7
4.5.	Support unit used in test configuration and system	8
4.6.	Testing environmental condition	8
4.7.	Statement of the measurement uncertainty	8
4.8.	Equipment Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	11
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	Maximum Conducted Output Power	13
5.4.	Power Spectral Density	15
5.5.	26dB bandwidth and 99% Occupy bandwidth	17
5.6.	6dB Bandwidth	18
5.7.	Band edge	19
5.8.	Radiated Spurious Emissions	26
5.9.	Frequency stability	33
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	34
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS</u>	36
<u>8.</u>	<u>APPENDIX REPORT</u>	36

## 1. **TEST STANDARDS AND REPORT VERSION**

### 1.1. **Test Standards**

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart E § 15.407](#): General technical requirements
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB789033 D02 v02r01](#): GUIDELINES FOR COMPLIANCE TESTING OF UNLICENSED NATIONAL INFORMATION INFRASTRUCTURE (U-NII) DEVICES PART 15, SUBPART E
- [KDB662911 D01 Multiple Transmitter Output v02r01](#): Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
- [KDB662911 D02 MIMO with Cross-Polarized Antennas v01](#): MIMO with Cross-Polarized Antenna

### 1.2. **Report version**

Revision No.	Date of issue	Description
N/A	2024-08-12	Original

## 2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247(c)	PASS	Xiangyu Wei
5.2	AC Conducted Emission	15.207	N/A	N/A
5.3	Maximum Conducted Output Power	15.407(a)	PASS	Xiangyu Wei
5.4	Maximum Power Spectral Density	15.407(a)	PASS	Xiangyu Wei
5.5	26dB Bandwidth and 99% Occupied bandwidth	15.407(a)	PASS	Xiangyu Wei
5.6	6dB Bandwidth	15.407(a)	PASS	Xiangyu Wei
5.7	Band edge	15.407(b)	PASS	Yifan Wang
5.8	Radiated Spurious Emissions	15.209	PASS	Yifan Wang
5.9	Frequency Stability	15.407(g)	PASS	Xiangyu Wei

Note:

- The measurement uncertainty is not included in the test result.

### 3. **SUMMARY**

#### 3.1. Client Information

Applicant:	Shenzhen AOTO Electronics Co., Ltd.
Address:	Room 1805, Tower 2, Shum Yip Jinyuan Building, Qingshuihe Street, Luohu District, Shenzhen, China
Manufacturer:	Shenzhen AOTO Electronics Co., Ltd.
Address:	Room 1805, Tower 2, Shum Yip Jinyuan Building, Qingshuihe Street, Luohu District, Shenzhen, China
Factory:	HuiZhou AOTO Electronic Technology Co., Ltd.
Address:	No. 7 Yongda Road, West District, Dayawan, 516083 Huizhou PEOPLE'S REPUBLIC OF CHINA.

#### 3.2. Product Description

Main unit information:	
Product Name:	Meeting card
Trade Mark:	AOTO
Model No.:	ATMET2K
Listed Model(s):	ATMET4K, ATMET8K, ATMET2KA, ATMET4KA, ATMET8KA, ATMET2KB, ATMET4KB, ATMET8KB, ATMET2KC, ATMET4KC, ATMET8KC
Power supply:	DC 12.0V
Hardware version:	V1.0.1.0.T1
Software version:	ATMET210_V1.02.0.CTM0112

### 3.3. Radio Specification Description

5G WIFI			
Support type <sup>*1</sup>	<input checked="" type="checkbox"/> 802.11a	<input checked="" type="checkbox"/> 802.11n(HT20)	<input checked="" type="checkbox"/> 802.11n(HT40)
	<input checked="" type="checkbox"/> 802.11ac(HT20)	<input checked="" type="checkbox"/> 802.11ac(HT40)	<input checked="" type="checkbox"/> 802.11ac(HT80)
	<input checked="" type="checkbox"/> 802.11ax(HE20)	<input checked="" type="checkbox"/> 802.11ax(HE40)	<input checked="" type="checkbox"/> 802.11ax(HE80)
Function:	<input type="checkbox"/> Outdoor AP	<input type="checkbox"/> Indoor AP	<input type="checkbox"/> Fixed P2P
	<input checked="" type="checkbox"/> Client		
DFS type:	<input type="checkbox"/> master devices	<input type="checkbox"/> Slave devices with radar detection	<input checked="" type="checkbox"/> Slave devices without radar detection
Modulation:	BPSK, QPSK, 16QAM, 64QAM		
Operation frequency:	<input checked="" type="checkbox"/> Band I: 5150MHz~5250MHz		
	<input type="checkbox"/> Band II: 5250MHz~5350MHz		
	<input type="checkbox"/> Band III: 5470MHz~5725MHz		
	<input checked="" type="checkbox"/> Band IV: 5725MHz~5850MHz		
Supported Bandwidth	20MHz:	802.11n,802.11a,802.11ac,802.11ax	
	40MHz:	802.11n,802.11ac,802.11ax	
	80MHz:	802.11n,802.11ac,802.11ax	
Antenna technology:	<input type="checkbox"/> SISO	<input checked="" type="checkbox"/> MIMO	
Antenna Delivery:	<input type="checkbox"/> 1*TX+1*RX	<input checked="" type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna type:	Monopole Antenna		
Antenna gain:	Antenna 0: 5.52dBi Antenna 1: 5.52dBi		

Note:

\*1: only show the RF function associated with this report.

### 3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: <a href="mailto:cs@szhtw.com.cn">cs@szhtw.com.cn</a> <a href="http://www.szhtw.com.cn">http://www.szhtw.com.cn</a>	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

## 4. TEST CONFIGURATION

### 4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below .

Band	Test Channel	20MHz		40MHz		80MHz	
		Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
I	CH <sub>L</sub>	36	5180	38	5190	-	-
	CH <sub>M</sub>	44	5220	-	-	42	5210
	CH <sub>H</sub>	48	5240	46	5230	-	-
IV	CH <sub>L</sub>	149	5745	151	5755	-	-
	CH <sub>M</sub>	157	5785	-	-	155	5775
	CH <sub>H</sub>	165	5825	159	5795	-	-

### 4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11a	6Mbps
802.11n(HT20)/802.11ac(HT20)/802.11ax(HE20)	MCS0
802.11n(HT40)/802.11ac(HT40)/802.11ax(HE40)	MCS0
802.11ac(HT80)/802.11ax(HE80)	MCS0

### 4.3. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

### 4.4. Test sample information

Test item	HTW sample no.
RF Conducted test items	Please refer to the description in the appendix report
RF Radiated test items	YPHT23110649002
EMI test items	-

Note:

RF Conducted test items: Maximum Conducted Output Power, Maximum Power Spectral Density , 26dB Bandwidth and 99% Occupy bandwith , 6dB Bandwidth ,Frequency Stability

RF Radiated test items: Band edge, Radiated Spurious Emission

EMI test items : AC Conducted Emission

#### 4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
<input checked="" type="checkbox"/> No			
Item	Equipment	Trade Name	Model No.
1			
2			

#### 4.6. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

#### 4.7. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	Maximum Conducted Output Power	1.07
3	Maximum Power Spectral Density	1.07
4	26dB Bandwidth and 99% Occupied bandwidth	0.002%
5	6dB Bandwidth	0.002%
6	Radiated Band Edge Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
7	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
8	Frequency Stability	0.05ppm

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=1.96$ .

## 4.8. Equipment Used during the Test

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2023/08/22	2024/08/21
●	Signal & Spectrum Analyzer	R&S	HTWE0262	FSW26	103440	2023/08/22	2024/08/21
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2023/05/23	2024/05/22
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2024/5/25	2025/5/24
●	Test software	Tonscend	N/A	JS1120	N/A	N/A	N/A

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2023/8/22	2024/8/21
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2023/8/18	2024/8/17
●	Protection Network	SCHWARZBECK	HTWE0567	VTSD9561FN	00899	2023/8/18	2024/8/17
●	ISN	FCC	HTWE0148	FCC-TLISN-T2-02	20371	2023/8/18	2024/8/17
●	ISN	FCC	HTWE0150	FCC-TLISN-T8-02	20375	2023/8/18	2024/8/17
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission – 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/4/6	2024/4/5
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2024/04/08	2027/04/07
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated Emission - 30MHz~1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2023/4/6	2026/4/5
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2023/8/22	2024/8/21
●	Ultra-Broadband Antenna	SCHWARZBEC K	HTWE0119	VULB9163	546	2023/2/22	2026/2/21
●	Pre-Amplifier	SCHWARZBEC K	HTWE0295	BBV 9742	/	2023/5/25	2024/5/24
●	Pre-Amplifier	SCHWARZBEC K	HTWE0295	BBV 9742	/	2024/5/24	2025/5/23
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

● Radiated emission-Above 1GHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/4/17	2026/4/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2023/8/22	2024/8/21
●	Horn Antenna	SCHWARZBEC K	HTWE0126	BBHA 9120D	1011	2023/2/14	2026/2/13
●	Horn Antenna	SCHWARZBEC K	HTWE0103	BBHA9170	BBHA9170472	2023/2/20	2026/2/19
●	Broadband Pre-amplifier	SCHWARZBEC K	HTWE0551	SCU18F	100855	2023/5/25	2024/5/24
●	Broadband Pre-amplifier	SCHWARZBEC K	HTWE0551	SCU18F	100855	2024/6/6	2025/6/5
●	Test Software	R&S	N/A	EMC32	N/A	N/A	N/A

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna Requirement

#### Requirement

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

##### **FCC CFR Title 47 Part 15 Subpart C Section 15.407(a) :**

Systems operating in the NII band, if transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### TEST RESULT

Passed       Not Applicable

The product has two external antennas, both two are 5.52dBi antenna gain, and the product is a CDD device with the same gain, according to KDB 662911 D01 section F, the Directional gain=Gant + Array gain

For power spectral density measurements on all devices,


Array gain=10log(Nant/Nss) dB,

So the Directional gain=5.52+10log(2/1)=8.53dBi

For power measurements on IEEE 802.11 devices,

Array gain=0 dB for Nant≤4

So the Directional gain=5.52+0=5.52dBi which is less than 6 dBi requirement,please refer to the below antenna photo.



## 5.2. AC Conducted Emission


### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST MODE:

Please refer to the clause 4.3

### TEST RESULT

Passed

Not Applicable

### 5.3. Maximum Conducted Output Power

#### LIMIT

##### FCC CFR Title 47 Part 15 Subpart E Section 15.407(a):

For the 5.15~5.25GHz band:

- Outdoor AP  
The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 1W (30dBm).  
if  $G_{Tx} > 6\text{dBi}$ , then  $P_{out} = 30 - (G_{Tx} - 6)$ . e.i.r.p. at any elevation angle above 30 degrees  $\leq 125\text{mW}$  (21dBm)
- Indoor AP  
The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 1W (30dBm).  
if  $G_{Tx} > 6\text{dBi}$ , then  $P_{out} = 30 - (G_{Tx} - 6)$ .
- Point-to-point AP  
The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 1W (30dBm).  
if  $G_{Tx} > 23\text{dBi}$ , then  $P_{out} = 30 - (G_{Tx} - 23)$ .
- Client devices  
The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 250W (24dBm).  
if  $G_{Tx} > 6\text{dBi}$ , then  $P_{out} = 24 - (G_{Tx} - 6)$ .

For the 5.25~5.35GHz band:

The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 250mW (24dBm) or  $11\text{dBm} + 10 \log B$ , where B is the 26dB emission bandwith in MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $P_{out} = 24 - (G_{Tx} - 6)$ .


For the 5.47~5.725GHz band:

The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 250mW (24dBm) or  $11\text{dBm} + 10 \log B$ , where B is the 26dB emission bandwith in MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $P_{out} = 24 - (G_{Tx} - 6)$ .

For the 5.725~5.85GHz band:

- Point-to-multipoint systems (P2M)  
The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 1W (30dBm).  
if  $G_{Tx} > 6\text{dBi}$ , then  $P_{out} = 30 - (G_{Tx} - 6)$ .
- Point-to-point systems (P2P)  
The maximum conducted output power ( $P_{out}$ ) shall not exceed the lesser of 1W (30dBm).

#### TEST CONFIGURATION



**TEST PROCEDURE**

1. The EUT was tested according to KDB789033 Section E-3-b)
2. The maximum conducted output power may be measured using a broadband AVG RF power meter.
3. Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor.
4. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.
5. Record the measurement data.

**6. TEST MODE:**

Please refer to the clause 4.3

**TEST RESULT**

Passed       Not Applicable

**TEST Data**

Refer to the appendix report on the section 8

## 5.4. Power Spectral Density

### LIMIT

FCC CFR Title 47 Part 15 Subpart E Section 15.407(a):

For the 5.15~5.25GHz band:

- Outdoor AP  
The peak power spectral density (PSD) shall not exceed the lesser of 17dBm/MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $\text{PSD} = 17 - (G_{Tx} - 6)$ .
- Indoor AP  
The peak power spectral density (PSD) shall not exceed the lesser of 17dBm/MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $\text{PSD} = 17 - (G_{Tx} - 6)$ .
- Point-to-point AP  
The peak power spectral density (PSD) shall not exceed the lesser of 17dBm/MHz.  
if  $G_{Tx} > 23\text{dBi}$ , then  $\text{PSD} = 17 - (G_{Tx} - 23)$ .
- Client devices  
The peak power spectral density (PSD) shall not exceed the lesser of 11dBm/MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $\text{PSD} = 11 - (G_{Tx} - 6)$ .

For the 5.25~5.35GHz band:

The peak power spectral density (PSD) shall not exceed the lesser of 11dBm/MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $\text{PSD} = 11 - (G_{Tx} - 6)$ .


For the 5.47~5.725GHz band:

The peak power spectral density (PSD) shall not exceed the lesser of 11dBm/MHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $\text{PSD} = 11 - (G_{Tx} - 6)$ .

For the 5.725~5.85GHz band:

- Point-to-multipoint systems (P2M)  
The peak power spectral density (PSD) shall not exceed the lesser of 30dBm/500kHz.  
if  $G_{Tx} > 6\text{dBi}$ , then  $\text{PSD} = 30 - (G_{Tx} - 6)$ .
- Point-to-point systems (P2P)  
The peak power spectral density (PSD) shall not exceed the lesser of 30dBm/500kHz.

### TEST CONFIGURATION



**TEST PROCEDURE**

1. According KDB 789033 D02 – Section F
2. Analyzer was setting as follow:  
Center frequency: test channel  
Span was set to encompass the entire emission bandwidth of the signal  
RBW=1MHz for devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz  
RBW=500kHz for devices operating in the band 5.725-5.85 GHz  
VBW  $\geq$  3 RBW  
Number of sweep points  $> 2 \times (\text{span}/\text{RBW})$   
Sweep time = auto  
Detector = Peak  
Trigger was set to free run for all modes, trace was averaged over 100 sweeps
3. The peak search function of the spectrum analyzer was used to find the peak of the spectrum.

**TEST MODE:**

Please refer to the clause 4.3

**TEST RESULT**

Passed       Not Applicable

**TEST Data**


Refer to the appendix report on the section 8

## 5.5. 26dB bandwidth and 99% Occupy bandwidth

### LIMIT

The bandwidth at 26dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating at its maximum duty cycle, at its maximum power control level, as defined in KDB 789033 D02, and at the appropriate frequencies. The spectrum analyzer's bandwidth measurement function is configured to measure the 26dB bandwidth.

### TEST CONFIGURATION



### TEST PROCEDURE

1. According KDB 789033 D02 – Section C, 26dB bandwidth test as follow
  - a) Set RBW = approximately 1% of the emission bandwidth.
  - b) Set the VBW > RBW.
  - c) Detector = Peak.
  - d) Trace mode = max hold.
  - e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
2. According KDB 789033 D02 – Section D, 99% bandwidth test as follow
  - a). Set center frequency to the nominal EUT channel center frequency.
  - b). Set span = 1.5 times to 5.0 times the OBW.
  - c). Set RBW = 1% to 5% of the OBW
  - d). Set VBW  $\geq 3 \text{ RBW}$
  - e). Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
  - f). Use the 99% power bandwidth function of the instrument

### TEST MODE:

Please refer to the clause 4.3

### TEST RESULT

Passed       Not Applicable

### TEST Data

Refer to the appendix report on the section 8


## 5.6. 6dB Bandwidth

### LIMIT

#### FCC CFR Title 47 Part 15 Subpart E Section 15.407(e)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
Center Frequency = test channel center frequency  
Span=2 x emission bandwidth  
RBW = 100 kHz, VBW  $\geq 3 \times$  RBW  
Sweep time= auto couple  
Detector = Peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

### TEST MODE:

Please refer to the clause 4.3

### TEST RESULT

Passed       Not Applicable

### TEST Data

Refer to the appendix report on the section 8

## 5.7. Band edge

### LIMIT

FCC CFR Title 47 Part 15 Subpart E Section 15.407(b)


Un-restricted band emissions above 1GHz			
Operating Band	Frequency	EIRP Limit	Value
5150-5250MHz	Above 1GHz	-27dBm/MHz(68.2dB <sub>u</sub> V/m)@3m	Peak
5250-5350MHz	Above 1GHz	-27dBm/MHz(68.2dB <sub>u</sub> V/m)@3m	Peak
5470-5725MHz	Above 1GHz	-27dBm/MHz(68.2dB <sub>u</sub> V/m)@3m	Peak
5725-5850 MHz	1GHz-5.65GHz	-27 dBm/MHz(68.2dB <sub>u</sub> V/m)@3m	Peak
	5.65GHz-5.7GHz	-27* dBm/MHz to 10dBm/MHz (68.2* dB <sub>u</sub> V/m to 105.2dB <sub>u</sub> V/m)	Peak
	5.7GHz-5.72GHz	10* dBm/MHz to 15.6dBm/MHz (105.6* dB <sub>u</sub> V/m to 110.8dB <sub>u</sub> V/m)	Peak
	5.72GHz-5.725GHz	15.6* dBm/MHz to 27dBm/MHz (110.8dB <sub>u</sub> V/m to* 122.2dB <sub>u</sub> V/m)	Peak
	5.85GHz-5.855GHz	27dBm/MHz to 15.6* dBm/MHz (122.2dB <sub>u</sub> V/m to 110.8* dB <sub>u</sub> V/m)	Peak
	5.855GHz-5.875GHz	15.6dBm/MHz to 10* dBm/MHz (110.8dB <sub>u</sub> V/m to 105.2* dB <sub>u</sub> V/m)	Peak
	5.875GHz-5.925GHz	10dBm/MHz to -27* dBm/MHz (105.6dB <sub>u</sub> V/m to 68.2* dB <sub>u</sub> V/m)	Peak
	Above 5.925GHz	-27 dBm/MHz(68.2dB <sub>u</sub> V/m)@3m	Peak

\* Increase/Decreases with the linearity of the frequency.

For emission above 1GHz and in restricted band, according to FCC KDB 789033 D02 General UNII Test Procedure, all emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.  $E[\text{dB}\mu\text{V}/\text{m}] = \text{EIRP}[\text{dBm}] + 95.2$ , for  $d = 3$  meters.

### TEST CONFIGURATION

Radiated:



**TEST PROCEDURE**

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:  
RBW=1MHz, VBW=3MHz PEAK detector for Peak value.  
RBW=1MHz, VBW=3MHz RMS detector for Average value.

**TEST MODE:**

Please refer to the clause 4.3

**TEST RESULTS**

Passed       Not Applicable

## Radiated Band Edge Test Data

Band: I		Worst mode: 802.11a					Test channel: CH <sub>L</sub>			
Test value					Horizontal					
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit	
1	5000.00	53.75	31.40	6.09	41.10	10.00	60.14	68.20	-8.06	Peak
2	5150.07	55.09	31.90	6.28	41.04	10.00	62.23	68.20	-5.97	Peak

Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit	
1	5150.07	4.39	31.90	0.00	0.00	10.00	46.29	54.00	-7.71	Average

Band: I		Worst mode: 802.11a					Test channel: CH <sub>H</sub>			
Test value					Horizontal					
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	5350.06	41.03	31.40	6.33	40.93	10.00	47.83	68.20	-20.37	Peak
2	5459.88	41.16	31.80	6.60	40.84	10.00	48.72	68.20	-19.48	Peak
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	5350.06	30.83	31.40	6.33	40.93	10.00	37.63	54.00	-16.37	Average
2	5459.88	30.93	31.80	6.60	40.84	10.00	38.49	54.00	-15.51	Average

Band: I		Worst mode: 802.11n(HT40)							Test channel: CH <sub>L</sub>			
Test value								Horizontal				
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark		
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit			
1	5150.07	53.11	31.90	6.28	41.04	10.00	60.25	68.20	-7.95	Peak		
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark		
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit			
1	5150.07	6.16	31.90	0.00	0.00	10.00	48.06	54.00	-5.94	Average		

Band: I		Worst mode: 802.11n(HT40)							Test channel: CH <sub>H</sub>			
Test value								Horizontal				
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark		
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit			
1	5350.06	41.38	31.40	6.33	40.93	10.00	48.18	68.20	-20.02	Peak		
2	5459.88	40.93	31.80	6.60	40.84	10.00	48.49	68.20	-19.71	Peak		
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark		
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit			
1	5350.06	31.37	31.40	6.33	40.93	10.00	38.17	54.00	-15.83	Average		
2	5459.88	31.22	31.80	6.60	40.84	10.00	38.78	54.00	-15.22	Average		
Band: I		Worst mode: 802.11n(HT40)							Test channel: CH <sub>H</sub>			
Test value								Vertical				
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark		
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit			
1	5350.06	42.43	31.40	6.33	40.93	10.00	49.23	68.20	-18.97	Peak		
2	5459.88	42.56	31.80	6.60	40.84	10.00	50.12	68.20	-18.08	Peak		
Mark	Frequency	Reading	Antenna	Cable	Preamp	Aux	Level	Limit	Over	Remark		
	MHz	dB <sub>UV</sub> /m	dB	dB	dB	dB	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	limit			
1	5350.06	32.72	31.40	6.33	40.93	10.00	39.52	54.00	-14.48	Average		
2	5459.88	31.68	31.80	6.60	40.84	10.00	39.24	54.00	-14.76	Average		

Band: I		Worst mode: 802.11ac(HT80)						Test channel: CH <sub>L</sub>						
Test value						Horizontal								
<hr/>														
<hr/>														
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5150.07	21.94	31.90	0.00	0.00	10.00	63.84	68.20	-4.36	Peak				
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5150.07	8.28	31.90	0.00	0.00	10.00	50.18	54.00	-3.82	Average				
Band: I		Worst mode: 802.11ac(HT80)						Test channel: CH <sub>L</sub>						
Test value						Vertical								
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5150.07	22.20	31.90	0.00	0.00	10.00	64.10	68.20	-4.10	Peak				
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5150.07	8.09	31.90	0.00	0.00	10.00	49.99	54.00	-4.01	Average				
Band: I		Worst mode: 802.11ac(HT80)						Test channel: CH <sub>H</sub>						
Test value						Horizontal								
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5350.06	45.12	31.40	6.33	40.93	10.00	51.92	68.20	-16.28	Peak				
2	5459.88	42.91	31.80	6.60	40.84	10.00	50.47	68.20	-17.73	Peak				
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5350.06	35.48	31.40	6.33	40.93	10.00	42.28	54.00	-11.72	Average				
2	5459.88	32.47	31.80	6.60	40.84	10.00	40.03	54.00	-13.97	Average				
Band: I		Worst mode: 802.11ac(HT80)						Test channel: CH <sub>H</sub>						
Test value						Vertical								
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5350.06	49.77	31.40	6.33	40.93	10.00	56.57	68.20	-11.63	Peak				
2	5459.88	50.19	31.80	6.60	40.84	10.00	57.75	68.20	-10.45	Peak				
<hr/>														
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark				
1	5350.06	41.87	31.40	6.33	40.93	10.00	48.67	54.00	-5.33	Average				
2	5459.88	38.43	31.80	6.60	40.84	10.00	45.99	54.00	-8.01	Average				

Band: IV		Worst mode: 802.11a						Test channel: CH <sub>L</sub>		
Frequency (MHz)	Read Level (dBuV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Pream p Factor (dB)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Test value	Polarization
5650	42.8	31.6	6.53	10	40.75	50.18	68.2	-18.02	Vertical	Peak
5700.007	50.67	31.8	6.61	10	40.73	58.35	105.2	-17.02	Vertical	Peak
5720.045	57.73	31.84	6.68	10	40.73	65.52	110.8	-16.02	Vertical	Peak
5650	43.67	31.6	6.53	10	40.75	51.05	68.2	-17.15	Horizontal	Peak
5700.007	42.51	31.8	6.61	10	40.73	50.19	105.2	-16.15	Horizontal	Peak
5720.045	47.23	31.84	6.68	10	40.73	55.02	110.8	-15.15	Horizontal	Peak
Band: IV		Worst mode: 802.11a						Test channel: CH <sub>H</sub>		
Frequency (MHz)	Read Level (dBuV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Pream p Factor (dB)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Test value	Polarization
5849.961	58.26	32.2	6.72	10	40.68	66.5	122.2	-55.7	Vertical	Peak
5875.003	44.83	32.25	6.75	10	40.67	53.16	122.2	-69.04	Vertical	Peak
5925.008	42.7	32.3	6.82	10	40.65	51.17	68.2	-17.03	Vertical	Peak
5849.961	47.2	32.2	6.72	10	40.68	55.44	122.2	-66.76	Horizontal	Peak
5875.003	41.9	32.25	6.75	10	40.67	50.23	122.2	-71.97	Horizontal	Peak
5925.008	42.31	32.3	6.82	10	40.65	50.78	68.2	-17.42	Horizontal	Peak
Band: IV		Worst mode: 802.11n(HT40)						Test channel: CH <sub>L</sub>		
Frequency (MHz)	Read Level (dBuV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Pream p Factor (dB)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Test value	Polarization
5650	46.16	31.6	6.53	10	40.75	53.54	68.2	-14.66	Vertical	Peak
5700.007	56.13	31.8	6.61	10	40.73	63.81	105.2	-13.66	Vertical	Peak
5720.045	68.42	31.84	6.68	10	40.73	76.21	110.8	-12.66	Vertical	Peak
5650	44.07	31.6	6.53	10	40.75	51.45	68.2	-16.75	Horizontal	Peak
5700.007	47.46	31.8	6.61	10	40.73	55.14	105.2	-15.75	Horizontal	Peak
5720.045	58.15	31.84	6.68	10	40.73	65.94	110.8	-14.75	Horizontal	Peak
Band: IV		Worst mode: 802.11n(HT40)						Test channel: CH <sub>H</sub>		
Frequency (MHz)	Read Level (dBuV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Pream p Factor (dB)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Test value	Polarization
5849.961	59.65	32.2	6.72	10	40.68	67.89	122.2	-54.31	Vertical	Peak
5875.003	43.98	32.25	6.75	10	40.67	52.31	122.2	-69.89	Vertical	Peak
5925.008	42.93	32.3	6.82	10	40.65	51.4	68.2	-16.8	Vertical	Peak
5849.961	45.6	32.2	6.72	10	40.68	53.84	122.2	-68.36	Horizontal	Peak
5875.003	42.06	32.25	6.75	10	40.67	50.39	122.2	-71.81	Horizontal	Peak
5925.008	43.05	32.3	6.82	10	40.65	51.52	68.2	-16.68	Horizontal	Peak

Band: IV			Worst mode: 802.11ax(HE80)				Test channel: CH <sub>L</sub>			
Frequency (MHz)	Read Level (dBuV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Pream p Factor (dB)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Test value	Polariz ation
5650	58.97	31.6	6.53	10	40.75	66.35	68.2	-1.85	Vertical	Peak
5700.007	66.54	31.8	6.61	10	40.73	74.22	105.2	-30.98	Vertical	Peak
5720.045	68.9	31.84	6.68	10	40.73	76.69	110.8	-34.11	Vertical	Peak
5650	50.79	31.6	6.53	10	40.75	58.17	68.2	-10.03	Horizontal	Peak
5700.007	58.05	31.8	6.61	10	40.73	65.73	105.2	-39.47	Horizontal	Peak
5720.045	57.94	31.84	6.68	10	40.73	65.73	110.8	-45.07	Horizontal	Peak

Band: IV			Worst mode: 802.11ax(HE80)				Test channel: CH <sub>H</sub>			
Frequency (MHz)	Read Level (dBuV)	Antenn a Factor (dB/m)	Cable Loss (dB)	Aux Factor (dB)	Pream p Factor (dB)	Level (dBuV/ m)	Limit Line (dBuV/ m)	Over Limit (dB)	Test value	Polariz ation
5849.961	65.02	32.2	6.72	10	40.68	73.26	122.2	-48.94	Vertical	Peak
5875.003	59.34	32.25	6.75	10	40.67	67.67	122.2	-54.53	Vertical	Peak
5925.008	51.78	32.3	6.82	10	40.65	60.25	68.2	-7.95	Vertical	Peak
5849.961	59.8	32.2	6.72	10	40.68	68.04	122.2	-54.16	Horizontal	Peak
5875.003	52.71	32.25	6.75	10	40.67	61.04	122.2	-61.16	Horizontal	Peak
5925.008	45.38	32.3	6.82	10	40.65	53.85	68.2	-14.35	Horizontal	Peak

## Remark:

1. Final Level =Receiver Read level + Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. Pre-scan all modulation mode and antenna. 802.11a, 802.11n, 802.11ac, 802.11ax mode in the report only displays the worst antenna information. The worst antenna is antenna 1.

## 5.8. Radiated Spurious Emissions

### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209 and Part 15 Subpart E Section 15.407

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40\*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40\*log(30/3)= Limit dBuV/m @30m + 40.


Unwanted emissions below 1GHz and Restricted band emissions above 1GHz		
Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

### TEST CONFIGURATION


- 9KHz ~30MHz



- 30MHz ~ 1GHz



➤ Above 1GHz



### TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - a) Span shall wide enough to fully capture the emission being measured;
  - b) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - c) From 1 GHz to 10<sup>th</sup> harmonic:  
RBW=1MHz, VBW=3MHz Peak detector for Peak value.  
RBW=1MHz, VBW=3MHz RMS detector for Average value.

### TEST MODE:

Please refer to the clause 4.3


### TEST RESULT

Passed       Not Applicable

### TEST Data

#### TEST DATA FOR 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

**TEST DATA FOR 30MHz-1GHz**

Remark:

Transd=Cable loss+ Antenna factor- Pre-amplifier; Margin=Limit -Level

**TEST DATA FOR Above 1GHz**

U-NII-1		Worst mode: 802.11a					Test channel: CH <sub>L</sub>		
Polarization:				Horizontal					
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	48.08	35.14	7.35	40.89	49.68	68.20	-18.52	Peak
2	7508.69	45.63	36.18	7.69	41.09	48.41	68.20	-19.79	Peak
3	8002.06	46.38	37.00	8.00	40.81	50.57	68.20	-17.63	Peak
4	8506.17	45.18	37.21	8.42	41.55	49.26	68.20	-18.94	Peak

Polarization:		Vertical							
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.86	35.14	7.35	40.89	49.46	68.20	-18.74	Peak
2	8002.06	44.81	37.00	8.00	40.81	49.00	68.20	-19.20	Peak
3	8506.17	43.64	37.21	8.42	41.55	47.72	68.20	-20.48	Peak
4	10999.95	41.17	40.50	10.00	42.30	49.37	68.20	-18.83	Peak

U-NII-1		Worst mode: 802.11a					Test channel: CH <sub>M</sub>		
Polarization:				Horizontal					
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	45.31	35.14	7.35	40.89	46.91	68.20	-21.29	Peak
2	8002.06	44.96	37.00	8.00	40.81	49.15	68.20	-19.05	Peak
3	8506.17	43.46	37.21	8.42	41.55	47.54	68.20	-20.66	Peak
4	12024.96	39.12	39.53	10.72	42.30	47.07	68.20	-21.13	Peak

Polarization:		Vertical							
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.48	35.14	7.35	40.89	49.08	68.20	-19.12	Peak
2	8002.06	43.98	37.00	8.00	40.81	48.17	68.20	-20.03	Peak
3	8506.17	44.80	37.21	8.42	41.55	48.88	68.20	-19.32	Peak
4	11457.21	39.89	40.46	10.33	42.30	48.38	68.20	-19.82	Peak

U-NII-1		Worst mode: 802.11a					Test channel: CH <sub>H</sub>		
Polarization:				Horizontal					
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.58	35.14	7.35	40.89	49.18	68.20	-19.02	Peak
2	8002.06	44.59	37.00	8.00	40.81	48.78	68.20	-19.42	Peak
3	8506.17	43.16	37.21	8.42	41.55	47.24	68.20	-20.96	Peak
4	11515.68	38.60	40.47	10.37	42.30	47.14	68.20	-21.06	Peak

Polarization:		Vertical							
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.15	35.14	7.35	40.89	48.75	68.20	-19.45	Peak
2	8002.06	43.47	37.00	8.00	40.81	47.66	68.20	-20.54	Peak
3	9228.06	40.42	38.97	9.28	40.99	47.68	68.20	-20.52	Peak
4	12024.96	39.76	39.53	10.72	42.30	47.71	68.20	-20.49	Peak

U-NII-1		Worst mode: 802.11n(HT40)					Test channel: CH <sub>L</sub>		
Polarization:					Horizontal				
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	7009.96	48.96	35.14	7.35	40.89	50.56	68.20	-17.64	Peak
2	8002.06	45.03	37.00	8.00	40.81	49.22	68.20	-18.98	Peak
3	8506.17	45.14	37.21	8.42	41.55	49.22	68.20	-18.98	Peak
4	11545.04	39.72	40.41	10.39	42.30	48.22	68.20	-19.98	Peak

Polarization:		Vertical							
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	48.51	35.07	7.34	40.89	50.03	68.20	-18.17	Peak
2	8002.06	45.76	37.00	8.00	40.81	49.95	68.20	-18.25	Peak
3	8506.17	44.88	37.21	8.42	41.55	48.96	68.20	-19.24	Peak
4	11486.41	39.84	40.49	10.35	42.30	48.38	68.20	-19.82	Peak

U-NII-1		Worst mode: 802.11n(HT40)					Test channel: CH <sub>H</sub>		
Polarization:					Horizontal				
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	47.15	35.07	7.34	40.89	48.67	68.20	-19.53	Peak
2	8002.06	44.75	37.00	8.00	40.81	48.94	68.20	-19.26	Peak
3	8506.17	43.06	37.21	8.42	41.55	47.14	68.20	-21.06	Peak
4	10427.37	38.02	39.93	9.72	40.69	46.98	68.20	-21.22	Peak

Polarization:		Vertical							
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	47.25	35.07	7.34	40.89	48.77	68.20	-19.43	Peak
2	8002.06	44.86	37.00	8.00	40.81	49.05	68.20	-19.15	Peak
3	8506.17	42.91	37.21	8.42	41.55	46.99	68.20	-21.21	Peak
4	11370.05	39.32	40.31	10.27	42.30	47.60	68.20	-20.60	Peak

U-NII-1		Worst mode: 802.11ax(HE80)					Test channel: CH <sub>M</sub>		
Polarization:					Horizontal				
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	7009.96	49.03	35.14	7.35	40.89	50.63	68.20	-17.57	Peak
2	8002.06	46.71	37.00	8.00	40.81	50.90	68.20	-17.30	Peak
3	9636.16	40.12	39.17	9.34	41.16	47.47	68.20	-20.73	Peak
4	11515.68	40.41	40.47	10.37	42.30	48.95	68.20	-19.25	Peak

Polarization:		Vertical							
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	7009.96	43.25	35.14	7.35	40.89	44.85	68.20	-23.35	Peak
2	8002.06	43.97	37.00	8.00	40.81	48.16	68.20	-20.04	Peak
3	10400.86	39.81	39.90	9.71	40.60	48.82	68.20	-19.38	Peak
4	12024.96	40.71	39.53	10.72	42.30	48.66	68.20	-19.54	Peak

U-NII-3		Worst mode: 802.11a					Test channel: CH <sub>L</sub>		
Polarization:					Horizontal				
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.68	35.14	7.35	40.89	49.28	68.20	-18.92	Peak
2	8002.06	44.48	37.00	8.00	40.81	48.67	68.20	-19.53	Peak
3	8506.17	42.52	37.21	8.42	41.55	46.60	68.20	-21.60	Peak
4	11428.08	38.33	40.43	10.31	42.30	46.77	68.20	-21.43	Peak
Polarization:					Vertical				
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.99	35.14	7.35	40.89	49.59	68.20	-18.61	Peak
2	8002.06	45.18	37.00	8.00	40.81	49.37	68.20	-18.83	Peak
3	8506.17	43.05	37.21	8.42	41.55	47.13	68.20	-21.07	Peak
4	10944.09	39.76	40.50	9.97	42.30	47.93	68.20	-20.27	Peak

U-NII-3		Worst mode: 802.11a					Test channel: CH <sub>M</sub>		
Polarization:					Horizontal				
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	7009.96	47.97	35.14	7.35	40.89	49.57	68.20	-18.63	Peak
2	8002.06	45.19	37.00	8.00	40.81	49.38	68.20	-18.82	Peak
3	8506.17	43.30	37.21	8.42	41.55	48.38	68.20	-19.82	Peak
4	10805.68	39.33	40.31	9.91	41.92	47.63	68.20	-20.57	Peak
Polarization:					Vertical				
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	6992.14	47.72	35.07	7.34	40.89	49.24	68.20	-18.96	Peak
2	8002.06	44.95	37.00	8.00	40.81	49.14	68.20	-19.06	Peak
3	8506.17	44.22	37.21	8.42	41.55	48.30	68.20	-19.90	Peak
4	11486.41	38.99	40.49	10.35	42.30	47.53	68.20	-20.67	Peak

U-NII-3		Worst mode: 802.11a					Test channel: CH <sub>H</sub>		
Polarization:					Horizontal				
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	6992.14	47.69	35.07	7.34	40.89	49.21	68.20	-18.99	Peak
2	8002.06	45.02	37.00	8.00	40.81	49.21	68.20	-18.99	Peak
3	8506.17	44.77	37.21	8.42	41.55	48.85	68.20	-19.35	Peak
4	10888.51	38.95	40.48	9.95	42.19	47.19	68.20	-21.01	Peak
Polarization:					Vertical				
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	6992.14	47.09	35.07	7.34	40.89	48.61	68.20	-19.59	Peak
2	8002.06	44.69	37.00	8.00	40.81	48.88	68.20	-19.32	Peak
3	8506.17	44.96	37.21	8.42	41.55	49.04	68.20	-19.16	Peak
4	11515.68	38.11	40.47	10.37	42.30	46.65	68.20	-21.55	Peak

U-NII-3		Worst mode: 802.11n(HT40)					Test channel: CH <sub>L</sub>		
Polarization:		Horizontal							
<hr/>									
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	47.28	35.07	7.34	40.89	48.80	68.20	-19.40	Peak
2	7508.69	47.15	36.18	7.69	41.09	49.93	68.20	-18.27	Peak
3	8002.06	45.37	37.00	8.00	40.81	49.56	68.20	-18.64	Peak
4	8506.17	44.67	37.21	8.42	41.55	48.75	68.20	-19.45	Peak
Polarization:		Vertical							
<hr/>									
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	47.77	35.07	7.34	40.89	49.29	68.20	-18.91	Peak
2	8002.06	45.17	37.00	8.00	40.81	49.36	68.20	-18.84	Peak
3	8996.12	42.82	37.99	9.10	41.10	48.81	68.20	-19.39	Peak
4	11515.68	39.43	40.47	10.37	42.30	47.97	68.20	-20.23	Peak
U-NII-3		Worst mode: 802.11n(HT40)					Test channel: CH <sub>H</sub>		
Polarization:		Horizontal							
<hr/>									
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	48.16	35.07	7.34	40.89	49.68	68.20	-18.52	Peak
2	8002.06	45.02	37.00	8.00	40.81	49.21	68.20	-18.99	Peak
3	8506.17	45.26	37.21	8.42	41.55	49.34	68.20	-18.86	Peak
4	10888.51	38.87	40.48	9.95	42.19	47.11	68.20	-21.09	Peak
Polarization:		Vertical							
<hr/>									
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	6992.14	46.90	35.07	7.34	40.89	48.42	68.20	-19.78	Peak
2	8002.06	45.04	37.00	8.00	40.81	49.23	68.20	-18.97	Peak
3	8506.17	45.19	37.21	8.42	41.55	49.27	68.20	-18.93	Peak
4	10374.42	38.75	39.82	9.69	40.65	47.61	68.20	-20.59	Peak
U-NII-3		Worst mode: 802.11ax(HE80)					Test channel: CH <sub>M</sub>		
Polarization:		Horizontal							
<hr/>									
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	7009.96	46.70	35.14	7.35	40.89	48.30	68.20	-19.90	Peak
2	7508.69	44.38	36.18	7.69	41.09	47.16	68.20	-21.04	Peak
3	8002.06	46.12	37.00	8.00	40.81	50.31	68.20	-17.89	Peak
4	8506.17	45.68	37.21	8.42	41.55	49.76	68.20	-18.44	Peak
Polarization:		Vertical							
<hr/>									
Mark	Frequency MHz	Reading dB <sub>UV</sub> /m	Antenna dB	Cable dB	Preamp dB	Level dB <sub>UV</sub> /m	Limit dB <sub>UV</sub> /m	Over limit	Remark
1	7009.96	46.88	35.14	7.35	40.89	48.48	68.20	-19.72	Peak
2	8002.06	44.21	37.00	8.00	40.81	48.40	68.20	-19.80	Peak
3	8506.17	43.73	37.21	8.42	41.55	47.81	68.20	-20.39	Peak
4	11515.68	41.04	40.47	10.37	42.30	49.58	68.20	-18.62	Peak

## Remark:


- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- The emission levels of other frequencies are very lower than the limit and not show in test report.
- Measuring frequencies from 1 GHz to 40GHz.
- Pre-scan all modulation mode and antenna. 802.11a, 802.11n, 802.11ac, 802.11ax mode in the report only displays the worst antenna information. The worst antenna is antenna 1.

## 5.9. Frequency stability

### LIMIT

Within Operation Band

### TEST CONFIGURATION



Note : Measurement setup for testing on Antenna connector

### TEST PROCEDURE

1. The equipment under test was connected to an external power supply.
2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.
3. The EUT was placed inside the temperature chamber.
4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency.
5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency.
6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached..

### TEST MODE:

Please refer to the clause 4.3



### TEST RESULT



Passed       Not Applicable

Refer to the appendix report on the section 8

## 6. TEST SETUP PHOTOS

Radiated Emission





## 7. **EXTERNAL AND INTERNAL PHOTOS**

Refer to the test report No. CHTW24080050

## 8. **APPENDIX REPORT**