

# FCC Test Report

**Report No.** : 1812C50035012501

---

**Applicant** : Zhejiang Sunseeker Industrial Co., Ltd.

---

**Address** : Jinde Road 988, Jiangdong Industrial Park  
Jinhua, Zhejiang, Jinhua, 321000, China

---

**Product Name** : 2.4G Wi-Fi&Bluetooth module

---

**Report Date** : Apr. 21, 2025

---

**Shenzhen Anbotek Compliance Laboratory Limited**



## Contents

|                                                 |    |
|-------------------------------------------------|----|
| 1. General Information.....                     | 5  |
| 1.1. Client Information .....                   | 5  |
| 1.2. Description of Device (EUT) .....          | 5  |
| 1.3. Auxiliary Equipment Used During Test ..... | 6  |
| 1.4. Description of Test Configuration.....     | 6  |
| 1.5. Description Of Test Setup .....            | 7  |
| 1.6. Test Equipment List .....                  | 8  |
| 1.7. Measurement Uncertainty .....              | 9  |
| 1.8. Description of Test Facility .....         | 9  |
| 1.9. Disclaimer .....                           | 10 |
| 2. Summary of Test Results .....                | 11 |
| 3. Conducted Emission Test .....                | 12 |
| 3.1. Test Standard and Limit .....              | 12 |
| 3.2. Test Setup .....                           | 12 |
| 3.3. Test Procedure .....                       | 12 |
| 3.4. Test Data .....                            | 12 |
| 4. Radiation Spurious Emission.....             | 15 |
| 4.1. Test Standard and Limit .....              | 15 |
| 4.2. Test Setup .....                           | 15 |
| 4.3. Test Procedure .....                       | 16 |
| 4.4. Test Data .....                            | 17 |
| 5. Maximum Peak Output Power Test .....         | 23 |
| 5.1. Test Standard and Limit .....              | 23 |
| 5.2. Test Setup .....                           | 23 |
| 5.3. Test Procedure .....                       | 23 |
| 5.4. Test Data .....                            | 24 |
| 6. Antenna Requirement .....                    | 25 |
| 6.1. Test Standard and Requirement.....         | 25 |
| 6.2. Antenna Connected Construction .....       | 25 |
| APPENDIX I -- TEST SETUP PHOTOGRAPH .....       | 26 |
| APPENDIX II -- EXTERNAL PHOTOGRAPH.....         | 26 |

## TEST REPORT

Applicant : Zhejiang Sunseeker Industrial Co., Ltd.  
Manufacturer : Iton Technology Corp.  
Product Name : 2.4G Wi-Fi&Bluetooth module  
Model No. : BW436S-44B1  
Trade Mark : N/A  
Rating(s) : Input: DC 3.3V

**Test Standard(s) : FCC Part15 Subpart C, Section 15.247**  
**Test Method(s) : ANSI C63.10: 2020**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt Jan. 24, 2025

Date of Test Jan. 24, 2025 to Mar. 28, 2025

Prepared by



(Lene Chen)

Approved & Authorized Signer



(Hugo Chen)

### Revision History

| Report Version | Description             | Issued Date   |
|----------------|-------------------------|---------------|
| R00            | Original Issue.(Note 1) | Apr. 21, 2025 |
|                |                         |               |
|                |                         |               |

**Note 1:**

This is a Class II application which was based on the certified FCC ID: 2BFD7-44B1. The difference between the original device and current one described as following:

1. Change the new antenna.
2. Change the Product Name to “2.4G Wi-Fi&Bluetooth module”.
3. Delete reference models.

The changes are not related with the other RF parameters, only conducted emission and radiation spurious emission (below 1G) were retested.



## 1. General Information

### 1.1. Client Information

|              |   |                                                                                                                      |
|--------------|---|----------------------------------------------------------------------------------------------------------------------|
| Applicant    | : | Zhejiang Sunseeker Industrial Co., Ltd.                                                                              |
| Address      | : | Jinde Road 988, Jiangdong Industrial Park Jinhua, Zhejiang, Jinhua, 321000, China                                    |
| Manufacturer | : | Iton Technology Corp.                                                                                                |
| Address      | : | 7 Floor East, Building C, Shenzhen International Innovation Center, No.1006 Shennan Rd. Futian Dist, Shenzhen, China |
| Factory      | : | Iton Technology Corp.                                                                                                |
| Address      | : | 7 Floor East, Building C, Shenzhen International Innovation Center, No.1006 Shennan Rd. Futian Dist, Shenzhen, China |

### 1.2. Description of Device (EUT)

|                                                                                                                                                                                              |   |                                                                                       |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------|
| Product Name                                                                                                                                                                                 | : | 2.4G Wi-Fi&Bluetooth module                                                           |
| Model No.                                                                                                                                                                                    | : | BW436S-44B1                                                                           |
| Trade Mark                                                                                                                                                                                   | : | N/A                                                                                   |
| Test Power Supply                                                                                                                                                                            | : | DC 3.3V by USB to TTL Serial board                                                    |
| Test Sample No.                                                                                                                                                                              | : | 1-2-1(Normal Sample), 1-2-2(Engineering Sample)                                       |
| Adapter                                                                                                                                                                                      | : | N/A                                                                                   |
| <b>RF Specification</b>                                                                                                                                                                      |   |                                                                                       |
| Operation Mode                                                                                                                                                                               | : | <input checked="" type="checkbox"/> BT BDR <input checked="" type="checkbox"/> BT EDR |
| Operation Frequency                                                                                                                                                                          | : | 2402~2480MHz                                                                          |
| Number of Channel                                                                                                                                                                            | : | 79 Channels                                                                           |
| Modulation Type                                                                                                                                                                              | : | GFSK, $\pi/4$ -DQPSK, 8-DPSK                                                          |
| <b>Remark:</b> 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) All of the RF specification are provided by customer. |   |                                                                                       |

### 1.3. Auxiliary Equipment Used During Test

| Description           | Rating(s)                                                                                |
|-----------------------|------------------------------------------------------------------------------------------|
| Notebook              | Model: N19W3<br>Input: 19V/3.42A;20V/3.25A<br>CMIIT ID:2020AJ3862                        |
| CH340 USB TO TTL UART | Model: MCS-71 Pro<br>Manufacturer: Mercury electronics technologies                      |
| Adapter               | Model: PA-1650-58<br>Input: AC100-240~50/60Hz, 1.6A<br>CMIIT KP06503020                  |
| Dipole Antenna        | Gain: 2.37dBi for 2.4G<br>Manufacturer: Suzhou Wavelink Electronics Technology Co., Ltd. |



### 1.4. Description of Test Configuration

| Channel   | Freq. (MHz) | Channel | Freq. (MHz) | Channel   | Freq. (MHz) | Channel | Freq. (MHz) | Channel   | Freq. (MHz) |
|-----------|-------------|---------|-------------|-----------|-------------|---------|-------------|-----------|-------------|
| <b>00</b> | <b>2402</b> | 17      | 2419        | 34        | 2436        | 51      | 2453        | 68        | 2470        |
| 01        | 2403        | 18      | 2420        | 35        | 2437        | 52      | 2454        | 69        | 2471        |
| 02        | 2404        | 19      | 2421        | 36        | 2438        | 53      | 2455        | 70        | 2472        |
| 03        | 2405        | 20      | 2422        | 37        | 2439        | 54      | 2456        | 71        | 2473        |
| 04        | 2406        | 21      | 2423        | 38        | 2440        | 55      | 2457        | 72        | 2474        |
| 05        | 2407        | 22      | 2424        | <b>39</b> | <b>2441</b> | 56      | 2458        | 73        | 2475        |
| 06        | 2408        | 23      | 2425        | 40        | 2442        | 57      | 2459        | 74        | 2476        |
| 07        | 2409        | 24      | 2426        | 41        | 2443        | 58      | 2460        | 75        | 2477        |
| 08        | 2410        | 25      | 2427        | 42        | 2444        | 59      | 2461        | 76        | 2478        |
| 09        | 2411        | 26      | 2428        | 43        | 2445        | 60      | 2462        | 77        | 2479        |
| 10        | 2412        | 27      | 2429        | 44        | 2446        | 61      | 2463        | <b>78</b> | <b>2480</b> |
| 11        | 2413        | 28      | 2430        | 45        | 2447        | 62      | 2464        |           |             |
| 12        | 2414        | 29      | 2431        | 46        | 2448        | 63      | 2465        |           |             |
| 13        | 2415        | 30      | 2432        | 47        | 2449        | 64      | 2466        |           |             |
| 14        | 2416        | 31      | 2433        | 48        | 2450        | 65      | 2467        |           |             |
| 15        | 2417        | 32      | 2434        | 49        | 2451        | 66      | 2468        |           |             |
| 16        | 2418        | 33      | 2435        | 50        | 2452        | 67      | 2469        |           |             |

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with channel 0, 39 and 78.

1.5. Description Of Test Setup



### 1.6. Test Equipment List

| Item | Equipment                                         | Manufacturer    | Model No.         | Serial No.       | Last Cal.     | Cal. Interval |
|------|---------------------------------------------------|-----------------|-------------------|------------------|---------------|---------------|
| 1.   | L.I.S.N.<br>Artificial Mains<br>Network           | Rohde & Schwarz | ENV216            | 100055           | Sep. 09, 2024 | 1 Year        |
| 2.   | Three Phase<br>V-type Artificial<br>Power Network | CYBERTEK        | EM5040DT          | E215040DT00<br>1 | Jan. 13, 2025 | 1 Year        |
| 3.   | EMI Test Receiver                                 | Rohde & Schwarz | ESCI              | 100627           | Jan. 13, 2025 | 1 Year        |
| 4.   | EMI Test Receiver                                 | Rohde & Schwarz | ESR26             | 101481           | Jan. 14, 2025 | 1 Year        |
| 5.   | MXA Spectrum<br>Analysis                          | Agilent         | N9020A            | MY51170037       | Sep. 09, 2024 | 1 Year        |
| 6.   | EMI Preamplifier                                  | SKET Electronic | LNPA-0118G-<br>45 | SKET-PA-002      | Jan. 13, 2025 | 1 Year        |
| 7.   | Double Ridged<br>Horn Antenna                     | SCHWARZBECK     | BBHA 9120D        | 02555            | Oct. 16, 2022 | 3 Year        |
| 8.   | Bilog Broadband<br>Antenna                        | Schwarzbeck     | VULB9163          | 345              | Oct. 23, 2022 | 3 Year        |
| 9.   | Loop Antenna                                      | Schwarzbeck     | FMZB1519B         | 00053            | Sep. 12, 2024 | 1 Year        |
| 10.  | Horn Antenna                                      | A-INFO          | LB-180400-KF      | J211060628       | Jan. 22, 2024 | 3 Year        |
| 11.  | Pre-amplifier                                     | SONOMA          | 310N              | 186860           | Jan. 14, 2025 | 1 Year        |
| 12.  | EMI Test Software<br>EZ-EMC                       | SHURPLE         | N/A               | N/A              | N/A           | N/A           |
| 13.  | MXA Spectrum<br>Analysis                          | KEYSIGHT        | N9020A            | MY53280032       | Sep. 09, 2024 | 1 Year        |
| 14.  | MXG RF Vector<br>Signal Generator                 | Agilent         | N5182A            | MY47420647       | Jan. 14, 2025 | 1 Year        |
| 15.  | Signal Generator                                  | Agilent         | E4421B            | MY41000743       | Oct. 10, 2024 | 1 Year        |
| 16.  | DC Power Supply                                   | IVYTECH         | IV3605            | 1804D360510      | Sep. 09, 2024 | 1 Year        |
| 17.  | Constant<br>Temperature<br>Humidity Chamber       | ZHONGJIAN       | ZJ-KHWS80B        | N/A              | Oct. 14, 2024 | 1 Year        |
| 18.  | Spectrum<br>Analyzer                              | Rohde & Schwarz | FSV40-N           | 102150           | May. 06, 2024 | 1 Year        |

### 1.7. Measurement Uncertainty

| Parameter                                                                                                                                                                                                                       | Uncertainty                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| Conducted emissions (AMN 150kHz~30MHz)                                                                                                                                                                                          | 3.8dB                                                     |
| Dwell Time                                                                                                                                                                                                                      | 2%                                                        |
| Occupied Bandwidth                                                                                                                                                                                                              | 925Hz                                                     |
| Conducted Output Power                                                                                                                                                                                                          | 0.76dB                                                    |
| Conducted Spurious Emission                                                                                                                                                                                                     | 1.24dB                                                    |
| Radiated spurious emissions (Below 30MHz)                                                                                                                                                                                       | 3.53dB                                                    |
| Radiated spurious emissions (30MHz~1GHz)                                                                                                                                                                                        | Horizontal: 3.92dB; Vertical: 4.52dB                      |
| Radiated spurious emissions (above 1GHz)                                                                                                                                                                                        | 1G-6GHz: 4.78dB;<br>6G-18GHz: 4.88dB<br>18G-40GHz: 5.68dB |
| The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032.<br>This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                                                           |

### 1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### FCC-Registration No.: 434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

#### ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

#### Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

Sogood Industrial Zone Laboratory & 1/F. of Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

### 1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

## 2. Summary of Test Results

| Standard Section                                            | Test Item                   | Result |
|-------------------------------------------------------------|-----------------------------|--------|
| 15.203/15.247(c)                                            | Antenna Requirement         | PASS   |
| 15.207                                                      | Conducted Emission          | PASS   |
| 15.205/15.209                                               | Spurious Emission           | PASS   |
| 15.247(b)(1)                                                | Conducted Peak Output Power | PASS   |
| <b>Remark:</b> "N/A" is an abbreviation for Not Applicable. |                             |        |


### 3. Conducted Emission Test

#### 3.1. Test Standard and Limit

| Test Standard | FCC Part15 Section 15.207 |                                |               |
|---------------|---------------------------|--------------------------------|---------------|
| Test Limit    | Frequency                 | Maximum RF Line Voltage (dBuV) |               |
|               |                           | Quasi-peak Level               | Average Level |
|               | 150kHz~500kHz             | 66 ~ 56 *                      | 56 ~ 46 *     |
|               | 500kHz~5MHz               | 56                             | 46            |
|               | 5MHz~30MHz                | 60                             | 50            |

**Remark:** (1) \*Decreasing linearly with logarithm of the frequency.  
(2) The lower limit shall apply at the transition frequency.

#### 3.2. Test Setup



#### 3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

#### 3.4. Test Data


##### PASS

During the test, pre-scan all modes, only the worst case is recorded in the report.

Please to see the following pages.

### Conducted Emission Test Data

Test Site: 1# Shielded Room  
Operating Condition: GFSK (2402MHz)  
Test Specification: DC 3.3V by USB to TTL Serial board  
Comment: Live Line  
Temp.(°C)/Hum.(%RH): 22.1°C/50%RH




| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.2020      | 26.43          | 17.82       | 44.25         | 63.52        | -19.27          | QP       |        |
| 2   | 0.2020      | 17.85          | 17.82       | 35.67         | 53.52        | -17.85          | AVG      |        |
| 3   | 0.4820      | 22.22          | 17.85       | 40.07         | 56.30        | -16.23          | QP       |        |
| 4   | 0.7740      | 13.60          | 17.87       | 31.47         | 46.00        | -14.53          | AVG      |        |
| 5   | 0.8220      | 23.15          | 17.87       | 41.02         | 56.00        | -14.98          | QP       |        |
| 6   | 1.2300      | 13.63          | 17.85       | 31.48         | 46.00        | -14.52          | AVG      |        |
| 7   | 1.3740      | 23.86          | 17.86       | 41.72         | 56.00        | -14.28          | QP       |        |
| 8   | 1.5820      | 13.07          | 17.85       | 30.92         | 46.00        | -15.08          | AVG      |        |
| 9   | 1.6940      | 21.81          | 17.85       | 39.66         | 56.00        | -16.34          | QP       |        |
| 10  | 1.9140      | 10.68          | 17.85       | 28.53         | 46.00        | -17.47          | AVG      |        |
| 11  | 2.0020      | 20.18          | 17.85       | 38.03         | 56.00        | -17.97          | QP       |        |
| 12  | 2.2380      | 7.63           | 17.85       | 25.48         | 46.00        | -20.52          | AVG      |        |

Note: Result = Reading + Factor Over Limit = Result - Limit

**Conducted Emission Test Data**

Test Site: 1# Shielded Room  
 Operating Condition: GFSK (2402MHz)  
 Test Specification: DC 3.3V by USB to TTL Serial board  
 Comment: Neutral Line  
 Temp.(°C)/Hum.(%RH): 22.1°C/50%RH



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit (dBuV) | Over Limit (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|--------------|-----------------|----------|--------|
| 1   | 0.2017      | 15.85          | 17.82       | 33.67         | 53.54        | -19.87          | AVG      |        |
| 2   | 0.4812      | 22.22          | 17.85       | 40.07         | 56.32        | -16.25          | QP       |        |
| 3   | 0.7711      | 12.60          | 17.87       | 30.47         | 46.00        | -15.53          | AVG      |        |
| 4   | 1.0997      | 26.55          | 17.86       | 44.41         | 56.00        | -11.59          | QP       |        |
| 5   | 1.2291      | 12.13          | 17.85       | 29.98         | 46.00        | -16.02          | AVG      |        |
| 6   | 1.4182      | 26.02          | 17.86       | 43.88         | 56.00        | -12.12          | QP       |        |
| 7   | 1.5766      | 11.07          | 17.85       | 28.92         | 46.00        | -17.08          | AVG      |        |
| 8   | 1.9080      | 23.78          | 17.85       | 41.63         | 56.00        | -14.37          | QP       |        |
| 9   | 2.3090      | 7.51           | 17.85       | 25.36         | 46.00        | -20.64          | AVG      |        |
| 10  | 2.3460      | 20.70          | 17.85       | 38.55         | 56.00        | -17.45          | QP       |        |
| 11  | 3.4356      | 5.69           | 17.85       | 23.54         | 46.00        | -22.46          | AVG      |        |
| 12  | 3.7594      | 16.28          | 17.86       | 34.14         | 56.00        | -21.86          | QP       |        |

Note: Result = Reading + Factor    Over Limit = Result - Limit



## 4. Radiation Spurious Emission

### 4.1. Test Standard and Limit

| Test Standard | FCC Part15 C Section 15.209 and 15.205 |                                  |                |            |                          |
|---------------|----------------------------------------|----------------------------------|----------------|------------|--------------------------|
| Test Limit    | Frequency (MHz)                        | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark     | Measurement distance (m) |
|               | 0.009MHz~0.490MHz                      | 2400/F(kHz)                      | -              | -          | 300                      |
|               | 0.490MHz~1.705MHz                      | 24000/F(kHz)                     | -              | -          | 30                       |
|               | 1.705MHz~30MHz                         | 30                               | -              | -          | 30                       |
|               | 30MHz~88MHz                            | 100                              | 40.0           | Quasi-peak | 3                        |
|               | 88MHz~216MHz                           | 150                              | 43.5           | Quasi-peak | 3                        |
|               | 216MHz~960MHz                          | 200                              | 46.0           | Quasi-peak | 3                        |
|               | 960MHz~1000MHz                         | 500                              | 54.0           | Quasi-peak | 3                        |
|               | Above 1000MHz                          | 500                              | 54.0           | Average    | 3                        |
|               |                                        | -                                | 74.0           | Peak       | 3                        |

**Remark:**

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

### 4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

### 4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9\*6\*6 Chamber. The device is evaluated in xyz orientation.

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 120kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW =1MHz, VBW =3MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

For average measurement: use duty cycle correction factor method (DCCF)

Average level = Peak level + DCCF

#### 4.4. Test Data

##### PASS


During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.

**Test Results (30~1000MHz)**


Test Mode: GFSK (2402MHz)  
Power Source: DC 3.3V by USB to TTL Serial board  
Polarization: Horizontal  
Temp.(°C)/Hum.(%RH): 25.1°C/55%RH



Note: Result = Reading + Factor    Over Limit = Result - Limit

### Test Results (30~1000MHz)

Test Mode: GFSK (2402MHz)  
Power Source: DC 3.3V by USB to TTL Serial board  
Polarization: Vertical  
Temp.(°C)/Hum.(%RH): 25.1°C/55%RH



Note: Result = Reading + Factor    Over Limit = Result - Limit

**Test Results (1GHz-25GHz)**

|                    |                   |                  |                      |                   |                    |              |
|--------------------|-------------------|------------------|----------------------|-------------------|--------------------|--------------|
| Test Mode: CH00    |                   |                  | Test channel: Lowest |                   |                    |              |
| Peak value:        |                   |                  |                      |                   |                    |              |
| Frequency<br>(MHz) | Reading<br>(dBuV) | Factor<br>(dB/m) | Result<br>(dBuV/m)   | Limit<br>(dBuV/m) | Over Limit<br>(dB) | polarization |
| 4804.00            | 28.82             | 15.27            | 44.09                | 74.00             | -29.91             | Vertical     |
| 7206.00            | 29.70             | 18.09            | 47.79                | 74.00             | -26.21             | Vertical     |
| 9608.00            | 31.09             | 23.76            | 54.85                | 74.00             | -19.15             | Vertical     |
| 12010.00           | *                 |                  |                      | 74.00             |                    | Vertical     |
| 14412.00           | *                 |                  |                      | 74.00             |                    | Vertical     |
| 4804.00            | 29.05             | 15.27            | 44.32                | 74.00             | -29.68             | Horizontal   |
| 7206.00            | 30.48             | 18.09            | 48.57                | 74.00             | -25.43             | Horizontal   |
| 9608.00            | 28.94             | 23.76            | 52.70                | 74.00             | -21.30             | Horizontal   |
| 12010.00           | *                 |                  |                      | 74.00             |                    | Horizontal   |
| 14412.00           | *                 |                  |                      | 74.00             |                    | Horizontal   |
| Average value:     |                   |                  |                      |                   |                    |              |
| Frequency<br>(MHz) | Reading<br>(dBuV) | Factor<br>(dB/m) | Result<br>(dBuV/m)   | Limit<br>(dBuV/m) | Over Limit<br>(dB) | polarization |
| 4804.00            | 18.20             | 15.27            | 33.47                | 54.00             | -20.53             | Vertical     |
| 7206.00            | 18.73             | 18.09            | 36.82                | 54.00             | -17.18             | Vertical     |
| 9608.00            | 20.11             | 23.76            | 43.87                | 54.00             | -10.13             | Vertical     |
| 12010.00           | *                 |                  |                      | 54.00             |                    | Vertical     |
| 14412.00           | *                 |                  |                      | 54.00             |                    | Vertical     |
| 4804.00            | 17.40             | 15.27            | 32.67                | 54.00             | -21.33             | Horizontal   |
| 7206.00            | 19.54             | 18.09            | 37.63                | 54.00             | -16.37             | Horizontal   |
| 9608.00            | 18.25             | 23.76            | 42.01                | 54.00             | -11.99             | Horizontal   |
| 12010.00           | *                 |                  |                      | 54.00             |                    | Horizontal   |
| 14412.00           | *                 |                  |                      | 54.00             |                    | Horizontal   |

**Test Results (1GHz-25GHz)**

| Test Mode: CH39 |                |               | Test channel: Middle |                |                 |              |
|-----------------|----------------|---------------|----------------------|----------------|-----------------|--------------|
| Peak value:     |                |               |                      |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m)      | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4882.00         | 28.84          | 15.42         | 44.26                | 74.00          | -29.74          | Vertical     |
| 7323.00         | 29.55          | 18.02         | 47.57                | 74.00          | -26.43          | Vertical     |
| 9764.00         | 30.10          | 23.80         | 53.90                | 74.00          | -20.10          | Vertical     |
| 12205.00        | *              |               |                      | 74.00          |                 | Vertical     |
| 14646.00        | *              |               |                      | 74.00          |                 | Vertical     |
| 4882.00         | 28.75          | 15.42         | 44.17                | 74.00          | -29.83          | Horizontal   |
| 7323.00         | 30.47          | 18.02         | 48.49                | 74.00          | -25.51          | Horizontal   |
| 9764.00         | 28.64          | 23.80         | 52.44                | 74.00          | -21.56          | Horizontal   |
| 12205.00        | *              |               |                      | 74.00          |                 | Horizontal   |
| 14646.00        | *              |               |                      | 74.00          |                 | Horizontal   |
| Average value:  |                |               |                      |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m)      | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4882.00         | 17.93          | 15.42         | 33.35                | 54.00          | -20.65          | Vertical     |
| 7323.00         | 18.83          | 18.02         | 36.85                | 54.00          | -17.15          | Vertical     |
| 9764.00         | 19.97          | 23.80         | 43.77                | 54.00          | -10.23          | Vertical     |
| 12205.00        | *              |               |                      | 54.00          |                 | Vertical     |
| 14646.00        | *              |               |                      | 54.00          |                 | Vertical     |
| 4882.00         | 17.31          | 15.42         | 32.73                | 54.00          | -21.27          | Horizontal   |
| 7323.00         | 19.10          | 18.02         | 37.12                | 54.00          | -16.88          | Horizontal   |
| 9764.00         | 18.76          | 23.80         | 42.56                | 54.00          | -11.44          | Horizontal   |
| 12205.00        | *              |               |                      | 54.00          |                 | Horizontal   |
| 14646.00        | *              |               |                      | 54.00          |                 | Horizontal   |

**Test Results (1GHz-25GHz)**

| Test Mode: CH78 |                |               | Test channel: Highest |                |                 |              |
|-----------------|----------------|---------------|-----------------------|----------------|-----------------|--------------|
| Peak value:     |                |               |                       |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4960.00         | 29.11          | 15.58         | 44.69                 | 74.00          | -29.31          | Vertical     |
| 7440.00         | 29.56          | 17.93         | 47.49                 | 74.00          | -26.51          | Vertical     |
| 9920.00         | 30.65          | 23.83         | 54.48                 | 74.00          | -19.52          | Vertical     |
| 12400.00        | *              |               |                       | 74.00          |                 | Vertical     |
| 14880.00        | *              |               |                       | 74.00          |                 | Vertical     |
| 4960.00         | 28.82          | 15.58         | 44.40                 | 74.00          | -29.60          | Horizontal   |
| 7440.00         | 30.50          | 17.93         | 48.43                 | 74.00          | -25.57          | Horizontal   |
| 9920.00         | 29.32          | 23.83         | 53.15                 | 74.00          | -20.85          | Horizontal   |
| 12400.00        | *              |               |                       | 74.00          |                 | Horizontal   |
| 14880.00        | *              |               |                       | 74.00          |                 | Horizontal   |
| Average value:  |                |               |                       |                |                 |              |
| Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Result (dBuV/m)       | Limit (dBuV/m) | Over Limit (dB) | polarization |
| 4960.00         | 19.05          | 15.58         | 34.63                 | 54.00          | -19.37          | Vertical     |
| 7440.00         | 19.84          | 17.93         | 37.77                 | 54.00          | -16.23          | Vertical     |
| 9920.00         | 20.52          | 23.83         | 44.35                 | 54.00          | -9.65           | Vertical     |
| 12400.00        | *              |               |                       | 54.00          |                 | Vertical     |
| 14880.00        | *              |               |                       | 54.00          |                 | Vertical     |
| 4960.00         | 18.75          | 15.58         | 34.33                 | 54.00          | -19.67          | Horizontal   |
| 7440.00         | 20.47          | 17.93         | 38.40                 | 54.00          | -15.60          | Horizontal   |
| 9920.00         | 18.66          | 23.83         | 42.49                 | 54.00          | -11.51          | Horizontal   |
| 12400.00        | *              |               |                       | 54.00          |                 | Horizontal   |
| 14880.00        | *              |               |                       | 54.00          |                 | Horizontal   |

**Remark:**


1. During the test, pre-scan the GFSK,  $\pi/4$ QPSK, 8DPSK modulation, and found the GFSK modulation is worse case, the report only record this mode.
2. Result = Reading + Factor
3. "\*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

## 5. Maximum Peak Output Power Test

### 5.1. Test Standard and Limit

|               |                                                                                                                                                                                                                                                                                    |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 C Section 15.247 (b)(1)                                                                                                                                                                                                                                                 |
| Test Limit    | For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. |

### 5.2. Test Setup



### 5.3. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
2. Spectrum Setting:
  - RBW > the 20 dB bandwidth of the emission being measured
  - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
  - VBW  $\geq$  RBW
  - Sweep = auto
  - Detector function = peak
  - Trace = max hold

#### 5.4. Test Data

|              |         |           |      |                       |         |
|--------------|---------|-----------|------|-----------------------|---------|
| Temperature: | 25.6 °C | Humidity: | 48 % | Atmospheric Pressure: | 101 kPa |
|--------------|---------|-----------|------|-----------------------|---------|

| Test Mode | Antenna | Frequency[MHz] | Conducted Peak Power[dBm] | Conducted Limit[dBm] | Verdict |
|-----------|---------|----------------|---------------------------|----------------------|---------|
| DH5       | Ant1    | 2402           | 9.86                      | ≤20.97               | PASS    |
|           |         | 2441           | 9.73                      | ≤20.97               | PASS    |
|           |         | 2480           | 9.38                      | ≤20.97               | PASS    |
| 2DH5      | Ant1    | 2402           | 6.75                      | ≤20.97               | PASS    |
|           |         | 2441           | 6.31                      | ≤20.97               | PASS    |
|           |         | 2480           | 6.19                      | ≤20.97               | PASS    |
| 3DH5      | Ant1    | 2402           | 7.18                      | ≤20.97               | PASS    |
|           |         | 2441           | 6.75                      | ≤20.97               | PASS    |
|           |         | 2480           | 6.60                      | ≤20.97               | PASS    |

Note: For pre-scan, the result is less than original, so the original data is referenced.

## 6. Antenna Requirement

### 6.1. Test Standard and Requirement

|               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard | FCC Part15 Section 15.203 /247(c)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Requirement   | <p>1) 15.203 requirement:<br/>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement:<br/>Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p> |

### 6.2. Antenna Connected Construction

The antenna is a Dipole Antenna, and the best case gain of the antenna is 2.37dBi. It complies with the standard requirement.

## **APPENDIX I -- TEST SETUP PHOTOGRAPH**

Please refer to separated files Appendix I -- Test Setup Photograph

## **APPENDIX II -- EXTERNAL PHOTOGRAPH**

Please refer to separated files Appendix II -- External Photograph

----- End of Report -----