

**RF Exposure Evaluation  
For  
Shenzhen Liris Lighting Co, Ltd.  
RF Remote controller  
Test Model: RF-RC-OV-12K**


Prepared for : Shenzhen Liris Lighting Co, Ltd.  
Address : 401&501 Building B, NO. 6 HengKeng Hexixincun, Guancheng  
Community, Guanhu Street, Longhua District, SHENZHEN  
Guangdong 518110 CHINA

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.  
Address : No.44-1,Qianfeng North Road, Shiqi, Panyu District, Guangzhou,  
Guangdong, China


Tel : (+86) 020-39166689  
Fax : (+86) 020-39166619  
Web : [www.LCS-cert.com](http://www.LCS-cert.com)  
Mail : [webmaster@LCS-cert.com](mailto:webmaster@LCS-cert.com)

Date of receipt of test sample : July 16, 2025  
Number of tested samples : 2  
Sample No. : A250609025-1, A250609025-2  
Serial number : Prototype  
Date of Test : July 16, 2025 ~ July 17, 2025  
Date of Report : August 04, 2025


| <b>RF Exposure Evaluation</b>  |  |
|--|--|
| <b>Report Reference No.</b> ..... : <b>LCSC07155012EB</b>  |  |
| Date of Issue..... : August 04, 2025   |  |
| <b>Testing Laboratory Name</b> ..... : <b>Guangzhou LCS Compliance Testing Laboratory Ltd.</b>   |  |
| Address..... : No.44-1,Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China   |  |
| Testing Location/ Procedure..... : Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>  |  |
| <b>Applicant's Name</b> ..... : <b>Shenzhen Liris Lighting Co, Ltd.</b>  |  |
| Address..... : 401&501 Building B, NO. 6 HengKeng Hexixincun, Guancheng Community, Guanhu Street, Longhua District, SHENZHEN Guangdong 518110 CHINA  |  |
| <b>Test Specification</b>  |  |
| Standard..... : FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06<br>FCC CFR 47 part1 1.1310<br>FCC CFR 47 part2 2.1093  |  |
| <b>Test Report Form No.</b> ..... : TRF-4-E-215 A/0  |  |
| TRF Originator..... : Guangzhou LCS Compliance Testing Laboratory Ltd.   |  |
| Master TRF..... : Dated 2011-03  |  |
| <b>Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved.</b><br>This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. |  |
| <b>Test Item Description</b> ..... : <b>RF Remote controller</b>   |  |
| Trade Mark..... : N/A  |  |
| Test Model..... : RF-RC-OV-12K   |  |
| Ratings..... : Please Refer to Page 6  |  |
| Result ..... : <b>PASS</b>   |  |

**Compiled by:**

Lifeng Le / Administrator

**Supervised by:**

Justin Zhu / Technique principal

**Approved by:**

Gavin Liang/ Manager

## RF Exposure Evaluation

|                          |  |                        |
|--------------------------|--|------------------------|
| <b>Test Report No. :</b> | <b>LCSC07155012EB</b>                                      | <u>August 04, 2025</u> |
|                          |  | Date of issue          |
| EUT.....                 | : RF Remote controller                                     |                        |
| Test Model.....          | : RF-RC-OV-12K   |                        |
| <b>Applicant.....</b>    | <b>: Shenzhen Liris Lighting Co, Ltd.</b>                  |                        |
|                          | 401&501 Building B, NO. 6 HengKeng Hexixincun, Guancheng   |                        |
| Address.....             | : Community, Guanhu Street, Longhua District,SHENZHEN      |                        |
|                          | Guangdong 518110 CHINA                                     |                        |
| Telephone.....           | : /  |                        |
| Fax.....                 | : /  |                        |
| <b>Manufacturer.....</b> | <b>: Shenzhen Liris Lighting Co, Ltd.</b>                  |                        |
| Address.....             | : 401&501 Building B, NO. 6 HengKeng Hexixincun, Guancheng |                        |
|                          | Community, Guanhu Street, Longhua District,SHENZHEN        |                        |
|                          | Guangdong 518110 CHINA                                     |                        |
| Telephone.....           | : /  |                        |
| Fax.....                 | : /  |                        |
| <b>Factory.....</b>      | <b>: Shenzhen Liris Lighting Co, Ltd.</b>                  |                        |
| Address.....             | : 401&501 Building B, NO. 6 HengKeng Hexixincun, Guancheng |                        |
|                          | Community, Guanhu Street, Longhua District,SHENZHEN        |                        |
|                          | Guangdong 518110 CHINA                                     |                        |
| Telephone.....           | : /  |                        |
| Fax.....                 | : /  |                        |

| <b>Test Result</b>   | <b>PASS</b> |
|--|-------------|
| The test report merely corresponds to the test sample.<br>It is not permitted to copy extracts of these test result without the written permission of the test laboratory. |             |

## Revision History

| Report Version | Issue Date      | Revision Content | Revised By |
|----------------|-----------------|------------------|------------|
| 000            | August 04, 2025 | Initial Issue    | ---        |
|                |                 |                  |            |
|                |                 |                  |            |

## TABLE OF CONTENTS

| Description                                      | Page |
|--|------|
| 1. PRODUCT INFORMATION.....                      | 6    |
| 2. EVALUATION METHOD AND LIMIT.....              | 7    |
| 3. REFER EVALUATION METHOD.....                  | 8    |
| 4. CONDUCTED POWER.....                          | 8    |
| 5. EVALUATION RESULTS.....                       | 8    |
| 6. CONCLUSION.....                               | 8    |
| 7. DESCRIPTION OF TEST FACILITY.....             | 8    |
| 8. STATEMENT OF THE MEASUREMENT UNCERTAINTY..... | 9    |

## 1. Product Information

|                            |   |
|----------------------------|---|
| EUT                        | : RF Remote controller                        |
| Test Model                 | : RF-RC-OV-12K                                |
| Ratings                    | : DC 3V by 2*AAA Batteries                    |
| Hardware version           | : /   |
| Software version           | : /   |
| 433MHz Operation frequency | : 433.92MHz                                   |
| Channel Number             | : 1   |
| Modulation Type            | : ASK   |
| Antenna Description        | : Internal Antenna, 0dBi(Max)                 |
| Exposure category          | : General population/uncontrolled environment |
| EUT Type                   | : Production Unit                             |
| Device Type                | : Portable Device                             |

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

## 2.Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f$  (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion.

- a) The  $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg}] + [\sum \text{ of MPE ratios}]$  is  $\leq 1.0$ .
- b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all  $\leq 0.04$ , and the  $[\sum \text{ of MPE ratios}]$  is  $\leq 1.0$ .

### 3. Refer Evaluation Method

[ANSI C95.1-1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.  
[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.  
[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.  
[FCC CFR 47 part2 2.1093](#): Radiofrequency radiation exposure evaluation: portable devices

### 4. Conducted Power Test Procedure

TX frequency range: 433.92MHz

Device category: Portable device (Distance: 5mm)

Max. Field Strength: 49.54dBuV/m @3m

$EIRP = E-104.8 + 20\log D = 49.54 - 104.8 + 20\log 3 = -45.72 \text{ dBm}$

Maximum Conducted Output Power: -45.72dBm

Tune up:  $-45 \pm 1 \text{ dBm}$

### 5. Evaluation Results

| Band/Mode | f (GHz) | Antenna Distance (mm) | RF output power |         | SAR Test Exclusion Threshold | SAR Test Exclusion |
|-----------|---------|-----------------------|-----------------|---------|------------------------------|--------------------|
|           |         |                       | dBm             | mW      |                              |                    |
| ASK       | 0.43392 | 5                     | -44             | 0.00004 | 0.00001 < 3.0                | Yes                |

Remark:

1. Output power including tune up tolerance;
2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to determine SAR test exclusion.

### 6. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

### 7. Description of Test Facility

CNAS Registration Number is L11555

A2LA Certificate Number: 5099.01

FCC Designation Number is CN1379

Test Firm Registration Number: 729882

## 8. Statement of The Measurement Uncertainty

ISO Guide 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with NAMAS document NIS 81.

| Test Item                  | Frequency Range | Uncertainty | Note |
|----------------------------|-----------------|-------------|------|
| Radiation Uncertainty      | 9KHz~30MHz      | ±3.10dB     | (1)  |
|                            | 30MHz~200MHz    | ±2.96dB     | (1)  |
|                            | 200MHz~1000MHz  | ±3.10dB     | (1)  |
|                            | 1GHz~26.5GHz    | ±4.20dB     | (1)  |
| Conduction Uncertainty     | 150kHz~30MHz    | ±1.63dB     | (1)  |
| Power disturbance          | 30MHz~300MHz    | ±1.60dB     | (1)  |
| Occupied Channel Bandwidth | 0.01MHz~26.5GHz | 5%          | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....THE END OF REPORT.....