

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0	614	1.63	*(100)	6			
3.0–30	1842/f	4.89/f	*(900/f²)	6			
30–300	61.4	0.163	1.0	6			
300–1500		12/2	f/300	6			
1500–100,000			5	6			
	(B) Limits for General Population/Uncontrolled Exposure						
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f²)	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500–100,000			1.0	30			

f = frequency in MHz

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Shenzhen ZKT Technology Co., Ltd.













Test Result of RF Exposure Evaluation

For 2.4G WIFI

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
802.11b	14.839	30.47	0.008925	1.0	PASS
802.11g	17.361	54.46	0.015952	1.0	PASS
802.11n20	17.26	53.21	0.015585	1.0	PASS
802.11n40	17.644	58.13	0.017027	1.0	PASS

For BLE

Mode	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm2)	Limit (mW/cm2)	Result
GFSK	4.38	2.74	0.000344	1.0	PASS

Note: Only one single wireless transmission mode can be used at the same time

Remark: BT ANT gain 1=-2dBi

WIFI ANT gain 2=1.68dBi

So a SAR test is not required

Shenzhen ZKT Technology Co., Ltd.









