

Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District,
Shenzhen

SPECIFICATION FOR APPROVAL

Name: WIFI/BT

Item No: TX2506G-1

Custoer name: _____

Company stamp: _____


drawing			Customer approve
MADE	CHECKED	APPROVED	
QIU			
DATE: 2023.10.25			DATE

Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District,
Shenzhen

View 1 TX2506G-1

Antenna Type: FPCB Antenna





View 2 TX2506G-1 (140mm / +2mm)



Shenzhen Zhisheng Technology Co., LTD


Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District, Shenzhen





Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District, Shenzhen



2.3 VSWR




Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District, Shenzhen

Frequency(MHz)	2412	2480	2500	5700	5800
VSWR	1.1	1.1	1.2	1.6	2.0







3、3D



























Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District, Shenzhen

FETUKEJI													
Frequency ID	1	3	5	7	9	11	12	12	14	16	18	20	22
Frequency (MHz)	2400.0	2420.0	2440.0	2460.0	2480.0	2500.0	5150.0	5700.0	5720.0	5740.0	5760.0	5780.0	5800.0
Efficiency (dBi)	-2.44	-2.50	-1.91	-1.59	-1.47	-2.10	-1.19	-1.49	-1.08	-2.62	-1.42	-1.52	-1.55
Gain (dBi)	2.22	2.61	3.43	3.80	2.91	2.38	2.12	3.39	3.13	2.22	3.61	3.78	3.82
Efficiency (%)	57.02	56.28	64.38	69.33	71.29	61.70	69.01	71.01	78.01	54.67	72.14	70.49	70.06
Directivity (dB)	4.66	5.11	5.34	5.39	4.38	4.48	4.28	4.88	5.21	4.85	5.03	5.30	4.37
Peak Gain Position (Theta)	144.00	141.00	144.00	124.00	144.00	145.00	86.00	80.00	127.00	79.00	86.00	141.00	81.00
Peak Gain Position (Phi)	180.00	180.00	180.00	210.00	180.00	180.00	90.00	90.00	90.00	90.00	270.00	60.00	90.00
Efficiency ThetaPol (%)	39.41	39.00	45.30	49.26	50.37	43.36	20.93	22.93	23.88	24.09	23.92	23.84	23.39
Efficiency PhiPol (%)	17.60	17.28	19.08	20.07	20.92	18.34	46.08	48.08	54.13	30.58	48.22	46.65	46.67
Upper Hem. Efficiency (%)	21.62	20.70	23.32	25.75	27.24	23.07	30.45	33.45	36.85	26.01	33.82	32.02	31.23
Lower Hem. Efficiency (%)	35.39	35.57	41.06	43.58	44.04	38.62	35.56	37.56	41.16	28.66	38.32	38.47	38.83




Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District,
Shenzhen



Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District, Shenzhen



Shenzhen Zhisheng Technology Co., LTD

Second floor, Building 5, Jiuyang Industrial Park, Heping Village, Fuyong Town, Baoan District,
Shenzhen

