

ISO CARD



Specification

Model	ISO Card
Material	PVC
Frequency	13.56MHz
Chipset	NTAG213
Size	85.6X54X0.84mm
Reading Range	1 to 5cm
With Overlay	Yes
printing	Without number printed
Service Life	100,000 times
Working Temperature	-25~ 55℃
Package	200pcs/box, 2000pcs/carton

Application:

1. Access control
2. identification
3. hotel card
4. school card
5. library
6. Parking
7. shopping



Hotel



Access control



Library



Parking



Shopping



Logistics

FCC Warning:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 0cm between the radiator and your body.