



Test report No:
2430820R-RF-US-P06V03

FCC TEST REPORT

Product Name	Argo
Trademark	
Model and /or type reference	A1810-00001
FCC ID	2BFKL810-00001
Applicant's name / address	Digilens. 1276 Hammerwood Ave Sunnyvale C.A 94089.
Test method requested, standard	47 CFR FCC Part 15 (Section 15.247) ANSI C63.10: 2013
Verdict Summary	IN COMPLIANCE
Tested by (name / position & signature)	Tim Cao / Project Manager 
Approved by (name / position & signature)	Jack Zhang / Manager 
Date of issue	2024-10-10
Report Version	V1.0
Report template No	Template_FCC 15.247-RF-V1.0

INDEX

	page
General conditions	5
Environmental conditions	5
Possible test case verdicts	6
Abbreviations	6
Document History	7
Remarks and Comments.....	7
Used Equipment	8
Uncertainty	11
1 General Information.....	12
1.1 General Description of the Item(s)	12
1.2 Antenna Information	13
1.3 Channel List	14
2 Description of Test Setup	15
2.1 Operating mode(s) used for tests.....	15
2.2 Auxiliary equipment /Accessories/Test software for the EUT	15
2.3 Test Configuration / Block diagram used for tests	16
2.4 Testing process	18
3 Verdict summary section	19
3.1 Standards.....	19
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	19
3.3 Overview of results.....	20
3.4 Power setting in test	21
3.5 Test Matrix	21
3.6 Test Facility.....	22
4 Test Items of limit/setup/procedure	23
4.1 20dB Emission Bandwidth	23
4.1.1 Limit	23
4.1.2 Test Setup.....	23
4.1.3 Test Procedure	23
4.2 Maximum Conducted Output Power	24
4.3.1 Limit	24
4.3.2 Test Setup.....	24
4.3.3 Test Procedure	24
4.3 Carrier Frequency Separation.....	25

4.4.1 Limit	25
4.4.2 Test Setup	25
4.4.3 Test Procedure	25
4.4 Time of Occupancy	26
4.5.1 Limit	26
4.5.2 Test Setup	26
4.5.3 Test Procedure	26
4.5 Number of hopping Frequencies	27
4.6.1 Limit	27
4.6.2 Test Setup	27
4.6.3 Test Procedure	27
4.6 Band edge measurements	28
4.7.1 Limit	28
4.7.2 Test Setup	28
4.7.3 Test Procedure	28
4.7 Conducted Spurious Emission	29
4.8.1 Limit	29
4.8.2 Test Setup	29
4.8.3 Test Procedure	29
4.8 Duty cycle	30
4.9.1 Limit	30
4.9.2 Test Setup	30
4.9.3 Test Procedure	30
4.9 Emissions in Restricted Bands	31
4.10.1 Limit	31
4.10.2 Test Setup	33
4.10.3 Test Procedure	34
4.10 AC Power Line Conducted Emission	35
4.11.1 Limit	35
4.11.2 Test Setup	35
4.11.3 Test Procedure	35
4.11 Antenna Requirement	36
4.12.1 Limit	36
4.12.2 Antenna Connector Construction:	36
5 Test setup photo and EUT Photo	37
6 Test Result	38
Appendix A: 20dB Emission Bandwidth	38

Appendix B: Maximum conducted output power	43
Appendix C: Carrier frequency separation	44
Appendix D: Time of occupancy	46
Appendix E: Number of hopping channels	51
Appendix F: Band edge measurements.....	53
Appendix G: Conducted Spurious Emission.....	77
Appendix H: Duty Cycle.....	145
Appendix I: Emissions in Restricted Band.....	150
Appendix J: AC Power Line Conducted Emission	170

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Jul. 04, 2024
Date (start test)	Jul. 30, 2024
Date (finish test)	Aug. 25, 2024

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2430820R-RF-US-P06V03	V1.0	Initial issue of report.	2024-10-10

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with 47 CFR FCC Part 15 (Section 15.247).
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.1 General Description of the Item(s);
 - Chapter 1.2 Antenna Information;
 - Chapter 1.3Channel List.

USED EQUIPMENT

Conducted Test/ TR8

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
Wireless Connectivity Tester	R&S	CMW 270	102593	2024.05.15	2025.05.14	V 4.0.60	N/A
Coaxial Cable	N/A	N/A	2477	2023.10.08	2024.10.07	N/A	N/A
Coaxial Cable	N/A	N/A	2478	2023.10.08	2024.10.07	N/A	N/A
High and low temperature and fast temperature change test box	ASTUOD	ASTD-FBT-225K	N/A	2024.04.21	2025.04.20	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-1909	THM-032	2024.05.17	2025.05.16	N/A	N/A
Test system							
Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
MAX Signal Analyzer	Keysight	N9010A	MY48030494	2023.11.08	2024.11.07	A.14.03	N/A
RF Control Unit	Tonscend	JS0806-2	22G8060594	2024.01.31	2025.01.30	N/A	N/A
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2024.05.12	2025.05.11	B.01.96	N/A
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2024.05.12	2025.05.11	N/A	N/A
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2024.07.06	2025.07.05	B.01.95	N/A
Test Software	Tonscend	TS1120	JS1120-3	N/A	N/A	N/A	V3.0.22

AC Power Line Conducted Emission / TR1

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100726	2024.07.06	2025.07.05	4.42 SP1	N/A
Two-Line V-Network	R&S	ENV 216	101044	2023.11.08	2024.11.07	N/A	N/A
Two-Line V-Network	R&S	ENV 216	101189	2024.07.06	2025.07.05	N/A	N/A
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	2024.07.06	2025.07.05	N/A	N/A
Coaxial Cable	Huber+Suhner	RG 223	TR1-C1	2024.07.06	2025.07.05	N/A	N/A
Impedance Stabilization Network	Teseq GmbH	ISN T800	57318	2024.01.20	2025.01.19	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-1909	THM-011	2024.05.17	2025.05.16	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	N/A

Radiated Emission(9KHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EMI Test Receiver	R&S	ESCI	100176	2024.05.12	2025.05.11	4.42 SP3	N/A
Loop Antenna	R&S	HFH2-Z2E	101149	2024.03.27	2025.03.26	N/A	N/A
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2024.03.20	2025.03.19	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-1909	THM-021	2024.05.17	2025.05.16	N/A	N/A
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2024.04.27	2025.04.26	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

Radiated Emission (1GHz-40GHz) / AC5

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
EXA Spectrum Analyzer	Keysight	N9020B	MY60112218	2023.11.08	2024.11.07	A.31.05	N/A
Pre-Amplifier	SKET	LNPA_0118G-45	SK2021090101	2024.04.27	2025.04.26	N/A	N/A
Preamplifier	CHENGYI	EMC184045SE	980263	2024.07.06	2025.07.05	N/A	N/A
DRG Horn	ETS-Lindgren	3117	00123988	2023.09.16	2024.09.15	N/A	N/A
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2024.05.30	2025.05.29	N/A	N/A
Filter Switch Box	MVE	MSW-F196	C070001S	2024.04.20	2025.04.19	N/A	N/A
Coaxial Cable	ROSENBERGER	LA1-C011-2000/3000	AC5-40G	2024.01.25	2025.01.24	N/A	N/A
Coaxial Cable	ROSENBERGER	LA1-C011-2000/3000	AC5-40G-2	2024.05.26	2025.05.25	N/A	N/A
Cable	Rosenberger	LA1-C011-1000	0523	2024.05.26	2025.05.25	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-1909	THM-001	2024.07.11	2025.07.10	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-1909	THM-024	2024.05.17	2025.05.16	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%. The Uncertainties is comply with standard required as below.

Test item	Uncertainty
AC Power Line Conducted Emission	9kHz~150kHz: 2.80dB 150kHz~30MHz: 2.40dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 3.50 dB 300MHz~1GHz: 3.60 dB Vertical: 30MHz~200MHz: 3.60 dB 300MHz~1GHz: 3.50 dB
Radiated Emission(1GHz~26.5GHz)	Horizontal: 1GHz~18GHz: 5.00 dB Vertical: 1GHz~18GHz: 4.80 dB Horizontal: 18GHz~26.5GHz: 5.30 dB Vertical: 18GHz~26.5GHz: 4.90 dB
20dB Bandwidth	± 1 kHz
Carrier Frequency Separation	± 1 kHz
Number of Hopping Frequencies	± 1 kHz
Time of Occupancy (Dwell Time)	± 0.1 us
Peak OutputPower	± 1.27 dB
Emissions in non-restricted frequency bands	± 1.0 dB
Radiated Emission Band Edge	± 3.9 dB

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Product Name..... :	Argo
Model No. :	A1810-00001
Trademark. :	
FCC ID :	2BFKL810-00001
Hardware Version :	Argo PVT
Software Version..... :	B1.0001.2112
Manufacturer..... :	Digilens.
Manufacturer Address..... :	1276 Hammerwood Ave Sunnyvale C.A 94089.
Factory :	Goertek Inc.
Factory address :	No.268 Dongfang Road High-Tech Industrial Development District, Weifang Shandong, China

Wireless specification..... :	Bluetooth (BR/EDR)					
Operating frequency range(s)..... :	2402~2480MHz					
Type of Modulation..... :	GFSK					
PHYS :	☒	GFSK	☒	Pi/4 DQPSK	☒	8DPSK
Data Rate :	☒	1Mbit/s	☒	2Mbit/s	☒	3Mbit/s
Number of channel..... :	79					

Rated power supply	Voltage and Frequency	
	☐	AC: 220 - 240 V, 50/60 Hz
	☐	AC: 100 - 240 V, 50/60 Hz
	☒	DC: 5 Vdc
	☐	Poe:
	☒	Battery: 3.87 Vdc , 800 mAh
Mounting position	☐	Tabletop equipment
	☐	Wall/Ceiling mounted equipment
	☐	Floor standing equipment
	☒	Hand-held/Portable equipment
	☐	Other:

1.2 Antenna Information

Antenna model / type number.....:	Ebony-G Antenna		
Antenna serial number	F-0Y-SV-0318-001-00		
Antenna Delivery	☒	1TX + 1RX	
	☐	2TX + 2RX	
	☐	Others:	
Antenna technology.....:	☒	SISO	
	☐	MIMO	☐ CDD
			☐ Beam-forming
Antenna Type.....:	☐	External	☐ Dipole
			☐ Sectorized
	☒	Internal	☐ Ceramic Chip
			☐ PIFA
			☒ FPC
			☐ Others.....
Antenna Gain	3.80 dBi		

1.3 Channel List

Bluetooth Working Frequency of Each Channel: (For FHSS)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A

Note: The general description of the Item(s), antenna information and channel list in clause 1 are provided and confirmed by the client.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Test Mode For Bluetooth	Mode 1: Transmitter-1Mbps(GFSK_DH5)
	Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
	Mode 3: Transmitter-3Mbps(8DPSK_DH5)
	Mode 4: Transmitter-Hopping-1Mbps(GFSK_DH5)
	Mode 5: Transmitter-Hopping-2Mbps(Pi/4 DQPSK_DH5)
	Mode 6: Transmitter-Hopping-3Mbps(8DPSK_DH5)

Note 1: Regards to the frequency band operation: the lowest, middle and highest frequency channel were selected to perform the test, then shown on this report.

Note 2: For portable device, radiated tests was verified over X, Y, Z axis, and shown the worst case on this report.


2.2 Auxiliary equipment /Accessories/Test software for the EUT

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) Notebook	Think pad x220	Lenovo	Adapter
(2) USB Control Cable	N/A	N/A	N/A
(3) USB Control Cable	N/A	N/A	N/A
software	Type / Version	Manufacturer	Supplied by
QRCT	V4.0	N/A	N/A


Accessories Information	Cable		
	Length used during test [m]	Attached during test	Shielded
(2)USB Control Cable	1	☒	☒
(3)USB Control Cable	8	☒	☒

2.3 Test Configuration / Block diagram used for tests


Test setup Diagram- AC Line Conducted Emission Test



Test setup Diagram- Conducted test



Test setup Diagram- Radiated Emission



2.4 Testing process

1	Setup the EUT as shown in Section 2.3.
2	Execute the “QRCT” on the notebook.
3	Configure the test mode, the test channel, and the data rate.
4	Verify that the EUT works properly.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
CFR 47, FCC Part 15 C	2024	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test Item of FCC	Standard(s)	Verdict	Remark
20dB Emission Bandwidth	FCC 15.247(a)(1)	PASS	Test data please refer to Appendix A
Maximum conducted output power	FCC 15.247(b)(1)	PASS	Test data please refer to Appendix B
Carrier Frequency Separation	FCC 15.247(a)(1)	PASS	Test data please refer to Appendix C
Time of Occupancy (Dwell Time)	FCC 15.247(a)(1)(iii)	PASS	Test data please refer to Appendix D
Number of Hopping Frequencies	FCC 15.247(a)(1)(iii)	PASS	Test data please refer to Appendix E
Band edge measurements	FCC 15.247(d)	PASS	Test data please refer to Appendix F
Conducted Spurious Emission	FCC 15.247(d), FCC 15.209	PASS	Test data please refer to Appendix G
Duty Cycle	ANSI C63.10:2013	PASS	Test data please refer to Appendix H
Emissions in Restricted Bands	FCC 15.247(b)(3)	PASS	Test data please refer to Appendix I
AC Power Line Conducted Emission	FCC 15.207	PASS	Test data please refer to Appendix J
Antenna Requirement	FCC 15.203	PASS	---

3.4 Power setting in test

Mode	Channel	Frequency (MHz)	Power Setting
Mode 1	00	2402	11
	39	2441	11
	78	2480	11
Mode 2	00	2402	11
	39	2441	11
	78	2480	11
Mode 3	00	2402	11
	39	2441	11
	78	2480	11

3.5 Test Matrix

Test item	Model : Argo	
	GJ23DVT10245	GJ23DVT10136
20dB Emission Bandwidth	☒	☐
Maximum conducted output power	☒	☐
Carrier frequency separation	☒	☐
Time of occupancy	☒	☐
Number of Hopping Frequencies	☒	☐
Band edge measurements	☐	☒
Conducted Spurious Emission	☒	☐
Duty cycle	☒	☐
Emissions in Restricted Bands	☐	☒
AC Power Line Conducted Emission	☐	☒

Note1: The only difference between sample #1 and sample #2 is whether to keep the original antenna, sample #1 is a conduction test product that removes the original antenna and is equipped with SMA wires, and sample #2 is a complete product that retains the original antenna.

3.6 Test Facility

USA : FCC Designation Number: CN1199

4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE


4.1 20dB Emission Bandwidth

VERDICT: PASS

4.1.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(a)
☒	For frequency hopping systems operating in 2400-2483.5 MHz band, within frequency range.
☐	For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
☐	For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

4.1.2 Test Setup



4.1.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	6.9	Occupied bandwidth tests
☒ ANSI C63.10	6.9.2	Occupied bandwidth—relative measurement procedure


4.2 Maximum Conducted Output Power

VERDICT: PASS

4.2.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(b)
☒	Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.	
☒	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.	
☐	For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels	

4.2.2 Test Setup



4.2.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		7.8	Evaluation of frequency-hopping device parameters
☒	ANSI C63.10		7.8.5	Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices


4.3 Carrier Frequency Separation

VERDICT: PASS

4.3.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(a)
☐	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	
☒	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	
☐	The 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period;	
☐	The 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.	
☐	Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz.	

4.3.2 Test Setup



4.3.3 Test Procedure

References Rule		Chapter	Description
☒	ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒	ANSI C63.10	7.8.2	Carrier frequency separation


4.4 Time of Occupancy

VERDICT: PASS

4.4.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(a)
☒	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
☐	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period
☐	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.
☐	Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

4.4.2 Test Setup




4.4.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒ ANSI C63.10	7.8.4	Time of occupancy (dwell time)

4.5 Number of hopping Frequencies**VERDICT: PASS****4.5.1 Limit**

Standard	FCC Part 15 Subpart C Paragraph 15.247(a)
☒	For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
☐	For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is less than 250 kHz, shall use at least 50 hopping frequencies.
☐	For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is higher than 250 kHz, shall use at least 25 hopping frequencies.
☐	For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

4.5.2 Test Setup**4.5.3 Test Procedure**

References Rule	Chapter	Description
☒ ANSI C63.10	7.8.	Evaluation of frequency-hopping device parameters
☒ ANSI C63.10	7.8.3	Number of Hopping Frequencies

4.6 Band edge measurements


VERDICT: PASS

4.6.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(d) ,15.209		
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.6.2 Test Setup



4.6.3 Test Procedure

Test Method			
	References Rule	Chapter	Description
☐	DA 00-705	N/A	duty cycle correction factor
☒	ANSI C63.10	6.10	Band-edge testing
☒	ANSI C63.10	6.10.5	Restricted-band band-edge measurements
☐	ANSI C63.10	6.10.6	Marker-delta method
☐	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☐	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.7 Conducted Spurious Emission

VERDICT: PASS


4.7.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(d)
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

4.7.2 Test Setup




4.7.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	7.8	Evaluation of frequency-hopping device parameters
☒ ANSI C63.10	7.8.6	Band-edge measurements for RF conducted emissions

4.8 Duty cycle**VERDICT: PASS****4.8.1 Limit**

N/A

4.8.2 Test Setup**4.8.3 Test Procedure**

References Rule		Chapter	Description
☒	ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level

4.9 Emissions in Restricted Bands**VERDICT: PASS****4.9.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.205

Restricted Bands of operation

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

Restricted Band Emissions Limit

FCC Part 15 Subpart C Paragraph 15.209


Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength ($\text{dB}\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).


Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.9.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




4.9.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10	11.12.1	Radiated emission measurements
	☒	ANSI C63.10	11.12.2.7	Radiated spurious emission test
	☒	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	☒	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.10 AC Power Line Conducted Emission**VERDICT: PASS****4.10.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.207

Frequency range [MHz]	Limit: QP [dB(μ V) ¹⁾]	Limit: AV [dB(μ V) ¹⁾]
0,15 - 0,50	66 – 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50

¹⁾ At the transition frequency, the lower limit applies.²⁾ The limit decreases linearly with the logarithm of the frequency.**NOTE 1:** The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.**NOTE 2:** Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.**4.10.2 Test Setup****4.10.3 Test Procedure**

	References Rule	Chapter	Item
☒	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.11 Antenna Requirement**VERDICT: PASS****4.11.1 Limit****Standard**

FCC Part 15 Subpart C Paragraph 15.247(d) ,15.209

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.11.2 Antenna Connector Construction:

- | | |
|-------------------------------------|--|
| ☒ | The use of a permanently attached antenna |
| ☐ | The antenna use of a unique coupling to the intentional radiator |
| ☐ | The use of a nonstandard antenna jack or electrical connector |

Please refer to the attached document "Internal Photograph" to show the antenna connector.

5 TEST SETUP PHOTO AND EUT PHOTO


Remark: The test setup photo and EUT Photo please see appendix.

6 TEST RESULT

Appendix A: 20dB Emission Bandwidth

TestMode	Antenna	Frequency[MHz]	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.939	2401.574	2402.513	N/A	Pass
		2441	0.936	2440.571	2441.507	N/A	Pass
		2480	0.942	2479.574	2480.516	N/A	Pass
2DH5	Ant1	2402	1.290	2401.397	2402.687	N/A	Pass
		2441	1.332	2440.361	2441.693	N/A	Pass
		2480	1.299	2479.379	2480.678	N/A	Pass
3DH5	Ant1	2402	1.305	2401.382	2402.687	N/A	Pass
		2441	1.305	2440.382	2441.687	N/A	Pass
		2480	1.320	2479.373	2480.693	N/A	Pass

Test Graphs





DH5-Ant1-2441



DH5-Ant1-2480




2DH5-Ant1-2402



2DH5-Ant1-2441



2DH5-Ant1-2480



3DH5-Ant1-2402



3DH5-Ant1-2441



3DH5-Ant1-2480


Appendix B: Maximum conducted output power


Test Mode	Antenna	Frequency[MHz]	Conducted Power[dBm]	EIRP Power[dBm]	Conducted Limit[dBm]	EIRP Limit[dBm]	Verdict
Mode 1	Ant1	2402	15.93	19.73	≤20.97	≤36	PASS
		2441	16.77	20.57	≤20.97	≤36	PASS
		2480	12.76	16.56	≤20.97	≤36	PASS
Mode 2	Ant1	2402	16.59	20.39	≤20.97	≤36	PASS
		2441	17.28	21.08	≤20.97	≤36	PASS
		2480	13.18	16.98	≤20.97	≤36	PASS
Mode 3	Ant1	2402	17.10	20.90	≤20.97	≤36	PASS
		2441	17.81	21.61	≤20.97	≤36	PASS
		2480	13.63	17.43	≤20.97	≤36	PASS
Note 1: EIRP Power = Conducted Power + Antenna gain							
Note 2: The Antenna gain please refer to clause 1.2							

Appendix C: Carrier frequency separation


TestMode	Antenna	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	0.724	≥0.628	PASS
2DH5	Ant1	Hop	1.004	≥0.888	PASS
3DH5	Ant1	Hop	1.012	≥0.880	PASS

Test Graphs





2DH5-Ant1-Hop-PASS





3DH5-Ant1-Hop-PASS

Appendix D: Time of occupancy


TestMode	Antenna	Frequency[MHz]	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.379	320	0.121	≤0.4	PASS
DH3	Ant1	Hop	1.635	160	0.262	≤0.4	PASS
DH5	Ant1	Hop	2.883	106.67	0.308	≤0.4	PASS
2DH1	Ant1	Hop	0.384	320	0.123	≤0.4	PASS
2DH3	Ant1	Hop	1.637	160	0.262	≤0.4	PASS
2DH5	Ant1	Hop	2.884	106.67	0.308	≤0.4	PASS
3DH1	Ant1	Hop	0.384	320	0.123	≤0.4	PASS
3DH3	Ant1	Hop	1.635	160	0.262	≤0.4	PASS
3DH5	Ant1	Hop	2.885	106.67	0.308	≤0.4	PASS

Test Graphs







DH3-Ant1-Hop-PASS




DH5-Ant1-Hop-PASS




2DH1-Ant1-Hop-PASS




2DH3-Ant1-Hop-PASS




2DH5-Ant1-Hop-PASS



3DH1-Ant1-Hop-PASS



3DH3-Ant1-Hop-PASS





3DH5-Ant1-Hop-PASS

Appendix E: Number of hopping channels


TestMode	Antenna	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
3DH5	Ant1	Hop	79	≥ 15	PASS

Test Graphs






2DH5-Ant1-Hop-PASS



3DH5-Ant1-Hop-PASS


Appendix F: Band edge measurements

Profile: 2430820R	Page No.: 1
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 17:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	49.310	15.159	-24.690	74.000	34.151	PK

Profile: 2430820R	Page No.: 2
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	36.967	2.816	-17.033	54.000	34.151	AV

Profile: 2430820R	Page No.: 3
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	49.511	15.360	-24.489	74.000	34.151	PK

Profile: 2430820R	Page No.: 4
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	36.485	2.334	-17.515	54.000	34.151	AV

Profile: 2430820R	Page No.: 5
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2480MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2483.500	53.228	18.772	-20.772	74.000	34.456	PK
2	*	2483.742	53.829	19.371	-20.171	74.000	34.458	PK

Profile: 2430820R	Page No.: 6
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2480MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	38.504	4.048	-15.496	54.000	34.456	AV

Profile: 2430820R	Page No.: 7
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:10
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2480MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	49.357	14.901	-24.643	74.000	34.456	PK

Profile: 2430820R	Page No.: 8
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 1 : Transmit at 2480MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	37.800	3.344	-16.200	54.000	34.456	AV

Profile: 2430820R	Page No.: 9
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:13
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	50.765	16.614	-23.235	74.000	34.151	PK

Profile: 2430820R	Page No.: 10
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	36.726	2.575	-17.274	54.000	34.151	AV

Profile: 2430820R	Page No.: 11
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:51
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	48.781	14.630	-25.219	74.000	34.151	PK

Profile: 2430820R	Page No.: 12
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	36.479	2.328	-17.521	54.000	34.151	AV

Profile: 2430820R	Page No.: 13
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2480MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2483.500	51.992	17.536	-22.008	74.000	34.456	PK
2	*	2483.632	53.685	19.228	-20.315	74.000	34.458	PK

Profile: 2430820R	Page No.: 14
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2480MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	38.452	3.996	-15.548	54.000	34.456	AV

Profile: 2430820R	Page No.: 15
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2480MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	50.195	15.739	-23.805	74.000	34.456	PK

Profile: 2430820R	Page No.: 16
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 18:58
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 2 : Transmit at 2480MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	37.720	3.264	-16.280	54.000	34.456	AV

Profile: 2430820R	Page No.: 17
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:00
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2402MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	48.960	14.809	-25.040	74.000	34.151	PK

Profile: 2430820R	Page No.: 18
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2402MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	36.805	2.654	-17.195	54.000	34.151	AV

Profile: 2430820R	Page No.: 19
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:02
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2402MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	49.734	15.583	-24.266	74.000	34.151	PK

Profile: 2430820R	Page No.: 20
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:03
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2402MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	36.432	2.281	-17.568	54.000	34.151	AV

Profile: 2430820R	Page No.: 21
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2480MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	53.282	18.826	-20.718	74.000	34.456	PK

Profile: 2430820R	Page No.: 22
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2480MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	38.360	3.904	-15.640	54.000	34.456	AV

Profile: 2430820R	Page No.: 23
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	51.035	16.579	-22.965	74.000	34.456	PK

Profile: 2430820R	Page No.: 24
Engineer: Yuliu	
Site: AC5	Time: 2024/08/05 - 19:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Argo	Power: Battery Powered
Note: Mode 3 : Transmit at 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	37.914	3.458	-16.086	54.000	34.456	AV

Note:


- " * ", means this data is the worst emission level.
- Measurement Level = Reading Level + Factor(Probe+Cable-Amp)


Appendix G: Conducted Spurious Emission

Test Result for Band edge:


TestMode	Antenna	ChName	Frequency[MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	15.55	-46.84	≤-4.45	PASS
DH5	Ant1	High	2480	12.73	-54.77	≤-7.27	PASS
DH5	Ant1	Low	Hop_2402	15.73	-46.06	≤-4.27	PASS
DH5	Ant1	High	Hop_2480	15.14	-43.52	≤-4.86	PASS
2DH5	Ant1	Low	2402	14.54	-50.02	≤-5.46	PASS
2DH5	Ant1	High	2480	11.57	-55.11	≤-8.43	PASS
2DH5	Ant1	Low	Hop_2402	14.44	-49.55	≤-5.56	PASS
2DH5	Ant1	High	Hop_2480	11.43	-46.87	≤-8.57	PASS
3DH5	Ant1	Low	2402	13.89	-45.08	≤-6.11	PASS
3DH5	Ant1	High	2480	11.65	-55.5	≤-8.35	PASS
3DH5	Ant1	Low	Hop_2402	14.03	-49.55	≤-5.97	PASS
3DH5	Ant1	High	Hop_2480	13.23	-49.42	≤-6.77	PASS

Test Graphs







DH5-Ant1-2480-PASS




DH5-Ant1-Hop_2402-PASS




DH5-Ant1-Hop_2480-PASS




2DH5-Ant1-2402-PASS




2DH5-Ant1-2480-PASS




2DH5-Ant1-Hop_2402-PASS




2DH5-Ant1-Hop_2480-PASS




3DH5-Ant1-2402-PASS



3DH5-Ant1-2480-PASS



3DH5-Ant1-Hop_2402-PASS



3DH5-Ant1-Hop_2480-PASS


Test Result for Spurious Emission:


TestMode	Antenna	Frequency[MHz]	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	30~1000	15.55	-68.91	≤-4.45	PASS
DH5	Ant1	2402	1000~3000	15.55	-63.59	≤-4.45	PASS
DH5	Ant1	2402	3000~5000	15.55	-53.43	≤-4.45	PASS
DH5	Ant1	2402	5000~7000	15.55	-66.35	≤-4.45	PASS
DH5	Ant1	2402	7000~9000	15.55	-66.72	≤-4.45	PASS
DH5	Ant1	2402	9000~11000	15.55	-66.69	≤-4.45	PASS
DH5	Ant1	2402	11000~13000	15.55	-66.88	≤-4.45	PASS
DH5	Ant1	2402	13000~15000	15.55	-64.97	≤-4.45	PASS
DH5	Ant1	2402	15000~17000	15.55	-64.21	≤-4.45	PASS
DH5	Ant1	2402	17000~19000	15.55	-62.06	≤-4.45	PASS
DH5	Ant1	2402	19000~21000	15.55	-62.34	≤-4.45	PASS
DH5	Ant1	2402	21000~23000	15.55	-61.35	≤-4.45	PASS
DH5	Ant1	2402	23000~25000	15.55	-58.13	≤-4.45	PASS
DH5	Ant1	2441	30~1000	16.14	-68.41	≤-3.86	PASS
DH5	Ant1	2441	1000~3000	16.14	-64.39	≤-3.86	PASS
DH5	Ant1	2441	3000~5000	16.14	-53.81	≤-3.86	PASS
DH5	Ant1	2441	5000~7000	16.14	-66.78	≤-3.86	PASS
DH5	Ant1	2441	7000~9000	16.14	-66.45	≤-3.86	PASS
DH5	Ant1	2441	9000~11000	16.14	-66.42	≤-3.86	PASS
DH5	Ant1	2441	11000~13000	16.14	-66.59	≤-3.86	PASS
DH5	Ant1	2441	13000~15000	16.14	-65.39	≤-3.86	PASS
DH5	Ant1	2441	15000~17000	16.14	-64.04	≤-3.86	PASS
DH5	Ant1	2441	17000~19000	16.14	-62.18	≤-3.86	PASS
DH5	Ant1	2441	19000~21000	16.14	-62.63	≤-3.86	PASS
DH5	Ant1	2441	21000~23000	16.14	-61.35	≤-3.86	PASS
DH5	Ant1	2441	23000~25000	16.14	-58.16	≤-3.86	PASS
DH5	Ant1	2480	30~1000	12.73	-68.07	≤-7.27	PASS
DH5	Ant1	2480	1000~3000	12.73	-64.78	≤-7.27	PASS
DH5	Ant1	2480	3000~5000	12.73	-65.26	≤-7.27	PASS
DH5	Ant1	2480	5000~7000	12.73	-67.24	≤-7.27	PASS
DH5	Ant1	2480	7000~9000	12.73	-66.28	≤-7.27	PASS
DH5	Ant1	2480	9000~11000	12.73	-66.87	≤-7.27	PASS
DH5	Ant1	2480	11000~13000	12.73	-66.68	≤-7.27	PASS
DH5	Ant1	2480	13000~15000	12.73	-64.68	≤-7.27	PASS
DH5	Ant1	2480	15000~17000	12.73	-64.05	≤-7.27	PASS
DH5	Ant1	2480	17000~19000	12.73	-62.41	≤-7.27	PASS
DH5	Ant1	2480	19000~21000	12.73	-61.59	≤-7.27	PASS
DH5	Ant1	2480	21000~23000	12.73	-61.28	≤-7.27	PASS
DH5	Ant1	2480	23000~25000	12.73	-58.15	≤-7.27	PASS
2DH5	Ant1	2402	30~1000	14.54	-68.71	≤-5.46	PASS
2DH5	Ant1	2402	1000~3000	14.54	-64.87	≤-5.46	PASS
2DH5	Ant1	2402	3000~5000	14.54	-56.31	≤-5.46	PASS
2DH5	Ant1	2402	5000~7000	14.54	-67.74	≤-5.46	PASS
2DH5	Ant1	2402	7000~9000	14.54	-66.17	≤-5.46	PASS
2DH5	Ant1	2402	9000~11000	14.54	-66.92	≤-5.46	PASS
2DH5	Ant1	2402	11000~13000	14.54	-66.35	≤-5.46	PASS
2DH5	Ant1	2402	13000~15000	14.54	-65.12	≤-5.46	PASS

2DH5	Ant1	2402	15000~17000	14.54	-63.55	≤-5.46	PASS
2DH5	Ant1	2402	17000~19000	14.54	-62.18	≤-5.46	PASS
2DH5	Ant1	2402	19000~21000	14.54	-62.55	≤-5.46	PASS
2DH5	Ant1	2402	21000~23000	14.54	-60.88	≤-5.46	PASS
2DH5	Ant1	2402	23000~25000	14.54	-58.21	≤-5.46	PASS
2DH5	Ant1	2441	30~1000	15.02	-68.04	≤-4.98	PASS
2DH5	Ant1	2441	1000~3000	15.02	-65.04	≤-4.98	PASS
2DH5	Ant1	2441	3000~5000	15.02	-57.33	≤-4.98	PASS
2DH5	Ant1	2441	5000~7000	15.02	-66.97	≤-4.98	PASS
2DH5	Ant1	2441	7000~9000	15.02	-67.22	≤-4.98	PASS
2DH5	Ant1	2441	9000~11000	15.02	-66.47	≤-4.98	PASS
2DH5	Ant1	2441	11000~13000	15.02	-67.08	≤-4.98	PASS
2DH5	Ant1	2441	13000~15000	15.02	-64.73	≤-4.98	PASS
2DH5	Ant1	2441	15000~17000	15.02	-64.41	≤-4.98	PASS
2DH5	Ant1	2441	17000~19000	15.02	-62.58	≤-4.98	PASS
2DH5	Ant1	2441	19000~21000	15.02	-61.31	≤-4.98	PASS
2DH5	Ant1	2441	21000~23000	15.02	-61.39	≤-4.98	PASS
2DH5	Ant1	2441	23000~25000	15.02	-57.44	≤-4.98	PASS
2DH5	Ant1	2480	30~1000	11.57	-68.35	≤-8.43	PASS
2DH5	Ant1	2480	1000~3000	11.57	-64.55	≤-8.43	PASS
2DH5	Ant1	2480	3000~5000	11.57	-65.2	≤-8.43	PASS
2DH5	Ant1	2480	5000~7000	11.57	-66.45	≤-8.43	PASS
2DH5	Ant1	2480	7000~9000	11.57	-66.85	≤-8.43	PASS
2DH5	Ant1	2480	9000~11000	11.57	-66.31	≤-8.43	PASS
2DH5	Ant1	2480	11000~13000	11.57	-67.07	≤-8.43	PASS
2DH5	Ant1	2480	13000~15000	11.57	-64.82	≤-8.43	PASS
2DH5	Ant1	2480	15000~17000	11.57	-64.33	≤-8.43	PASS
2DH5	Ant1	2480	17000~19000	11.57	-61.44	≤-8.43	PASS
2DH5	Ant1	2480	19000~21000	11.57	-61.97	≤-8.43	PASS
2DH5	Ant1	2480	21000~23000	11.57	-61.46	≤-8.43	PASS
2DH5	Ant1	2480	23000~25000	11.57	-58.76	≤-8.43	PASS
3DH5	Ant1	2402	30~1000	13.89	-68.81	≤-6.11	PASS
3DH5	Ant1	2402	1000~3000	13.89	-64.89	≤-6.11	PASS
3DH5	Ant1	2402	3000~5000	13.89	-57.4	≤-6.11	PASS
3DH5	Ant1	2402	5000~7000	13.89	-67.41	≤-6.11	PASS
3DH5	Ant1	2402	7000~9000	13.89	-66.86	≤-6.11	PASS
3DH5	Ant1	2402	9000~11000	13.89	-66.92	≤-6.11	PASS
3DH5	Ant1	2402	11000~13000	13.89	-66.73	≤-6.11	PASS
3DH5	Ant1	2402	13000~15000	13.89	-65.38	≤-6.11	PASS
3DH5	Ant1	2402	15000~17000	13.89	-64.48	≤-6.11	PASS
3DH5	Ant1	2402	17000~19000	13.89	-61.74	≤-6.11	PASS
3DH5	Ant1	2402	19000~21000	13.89	-62.34	≤-6.11	PASS
3DH5	Ant1	2402	21000~23000	13.89	-61.17	≤-6.11	PASS
3DH5	Ant1	2402	23000~25000	13.89	-58.76	≤-6.11	PASS
3DH5	Ant1	2441	30~1000	12.96	-68.18	≤-7.04	PASS
3DH5	Ant1	2441	1000~3000	12.96	-65.1	≤-7.04	PASS
3DH5	Ant1	2441	3000~5000	12.96	-55.01	≤-7.04	PASS
3DH5	Ant1	2441	5000~7000	12.96	-67.32	≤-7.04	PASS
3DH5	Ant1	2441	7000~9000	12.96	-67.08	≤-7.04	PASS
3DH5	Ant1	2441	9000~11000	12.96	-66.8	≤-7.04	PASS
3DH5	Ant1	2441	11000~13000	12.96	-66.63	≤-7.04	PASS


3DH5	Ant1	2441	13000~15000	12.96	-65.19	≤-7.04	PASS
3DH5	Ant1	2441	15000~17000	12.96	-64.03	≤-7.04	PASS
3DH5	Ant1	2441	17000~19000	12.96	-62.5	≤-7.04	PASS
3DH5	Ant1	2441	19000~21000	12.96	-61.87	≤-7.04	PASS
3DH5	Ant1	2441	21000~23000	12.96	-61.04	≤-7.04	PASS
3DH5	Ant1	2441	23000~25000	12.96	-58.39	≤-7.04	PASS
3DH5	Ant1	2480	30~1000	11.65	-69.18	≤-8.35	PASS
3DH5	Ant1	2480	1000~3000	11.65	-64.68	≤-8.35	PASS
3DH5	Ant1	2480	3000~5000	11.65	-64.77	≤-8.35	PASS
3DH5	Ant1	2480	5000~7000	11.65	-67.34	≤-8.35	PASS
3DH5	Ant1	2480	7000~9000	11.65	-65.89	≤-8.35	PASS
3DH5	Ant1	2480	9000~11000	11.65	-66.79	≤-8.35	PASS
3DH5	Ant1	2480	11000~13000	11.65	-67.28	≤-8.35	PASS
3DH5	Ant1	2480	13000~15000	11.65	-64.25	≤-8.35	PASS
3DH5	Ant1	2480	15000~17000	11.65	-63.81	≤-8.35	PASS
3DH5	Ant1	2480	17000~19000	11.65	-62.52	≤-8.35	PASS
3DH5	Ant1	2480	19000~21000	11.65	-61.64	≤-8.35	PASS
3DH5	Ant1	2480	21000~23000	11.65	-61.44	≤-8.35	PASS
3DH5	Ant1	2480	23000~25000	11.65	-58.28	≤-8.35	PASS

Test Graphs







DH5-Ant1-2402-1000~3000-PASS




DH5-Ant1-2402-3000~5000-PASS




DH5-Ant1-2402-5000~7000-PASS




DH5-Ant1-2402-7000~9000-PASS




DH5-Ant1-2402-9000~11000-PASS




DH5-Ant1-2402-11000~13000-PASS




DH5-Ant1-2402-13000~15000-PASS




DH5-Ant1-2402-15000~17000-PASS




DH5-Ant1-2402-17000~19000-PASS




DH5-Ant1-2402-19000~21000-PASS




DH5-Ant1-2402-21000~23000-PASS




DH5-Ant1-2402-23000~25000-PASS




DH5-Ant1-2441-30~1000-PASS




DH5-Ant1-2441-1000~3000-PASS




DH5-Ant1-2441-3000~5000-PASS




DH5-Ant1-2441-5000~7000-PASS




DH5-Ant1-2441-7000~9000-PASS




DH5-Ant1-2441-9000~11000-PASS




DH5-Ant1-2441-11000~13000-PASS




DH5-Ant1-2441-13000~15000-PASS




DH5-Ant1-2441-15000~17000-PASS




DH5-Ant1-2441-17000~19000-PASS




DH5-Ant1-2441-19000~21000-PASS




DH5-Ant1-2441-21000~23000-PASS




DH5-Ant1-2441-23000~25000-PASS




DH5-Ant1-2480-30~1000-PASS




DH5-Ant1-2480-1000~3000-PASS




DH5-Ant1-2480-3000~5000-PASS




DH5-Ant1-2480-5000~7000-PASS




DH5-Ant1-2480-7000~9000-PASS




DH5-Ant1-2480-9000~11000-PASS




DH5-Ant1-2480-11000~13000-PASS




DH5-Ant1-2480-13000~15000-PASS




DH5-Ant1-2480-15000~17000-PASS




DH5-Ant1-2480-17000~19000-PASS



DH5-Ant1-2480-19000~21000-PASS



DH5-Ant1-2480-21000~23000-PASS



DH5-Ant1-2480-23000~25000-PASS