


FCC PART 15.247
TEST REPORT

For

WISEASY TECHNOLOGY PTE. LTD.

70 Anson Road, #18-02, Hub Synergy Point, Singapore 079905

FCC ID: 2BFPO-P053

Report Type: Original Report	Product Name: EMV Android POS
Report Number:	RKSA250707003-00C
Report Date:	2025-08-19
Reviewed By:	Bard Liu 
Approved By:	Kyle Xu 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S.Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §1.1307(b) & §2.1093 - RF EXPOSURE.....	13
FCC §15.203 – ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
TEST SYSTEM SETUP.....	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
TEST RESULTS SUMMARY	16
TEST DATA: SEE APPENDIX	16
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	17
APPLICABLE STANDARD	17
TEST SYSTEM SETUP.....	17
EMI TEST RECEIVER SETUP.....	18
TEST PROCEDURE	18
TEST RESULTS SUMMARY	19
TEST DATA: SEE APPENDIX	19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST DATD: SEE APPENDIX	20
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATD: SEE APPENDIX	21
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22

TEST DATD: SEE APPENDIX	22
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATD: SEE APPENDIX	23
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATD: SEE APPENDIX	24
FCC §15.247(d) - BAND EDGES TESTING	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATD: SEE APPENDIX	25
APPENDIX - TEST DATA.....	26
AC LINE CONDUCTED EMISSIONS	26
RADIATED EMISSIONS & RESTRICTED BANDS EMISSIONS	29
CHANNEL SEPARATION TEST	48
20 dB BANDWIDTH TEST	50
QUANTITY OF HOPPING CHANNEL TEST	53
TIME OF OCCUPANCY (DWELL TIME).....	55
PEAK OUTPUT POWER MEASUREMENT	61
BAND EDGES.....	64
EUT PHOTOGRAPHS	67
TEST SETUP PHOTOGRAPHS	68

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA250707003-00C	R1V1	2025-08-19	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	WISEASY TECHNOLOGY PTE. LTD.
Tested Model	P053
Product Name	EMV Android POS
Power Supply	DC 7.4V from battery or DC 5V charging by adapter
Maximum Output Power:	GFSK: 9.58 dBm $\pi/4$ -DQPSK: 8.86 dBm 8DPSK: 9.31 dBm
RF Function:	Classic BT
Operating Band/Frequency:	2402-2480 MHz
Channel Number:	79
Channel Separation:	1 MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
★Maximum Antenna Gain:	0.84 dBi

Adapter Information:

Model: TPA-418G050200UU01

Input: 100-240V, 50/60Hz, 0.3A

Output: 5.0V, 2.0A 10.0W

Note: The maximum antenna gain was declared by the manufacturer.

All measurement and test data in this report was gathered from production sample serial number: RKSA250707003-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2025-07-07.)

Objective

This test report is prepared for *WISEASY TECHNOLOGY PTE. LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF Test Tool: QRCT3.0

★Power level: Default

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.

Equipment Modifications


No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To Port
Power Cable	1.5	AC Source/LISN	Adapter
USB Cable	1.0	Adapter	EUT

Block Diagram of Test Setup**For Conducted Emissions:**

For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b)(1)& §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2024-11-08	2027-11-07
Narda	6dB Attenuator	773-6	10690812-2-1	2024-11-08	2027-11-07
BACL	Active Loop Antenna	1313-1A	4041511	2024-11-22	2027-11-21
Sonoma Instrument	Pre-amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2025-04-09	2026-04-08
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2024-12-02	2025-12-01
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2025-04-09	2026-04-08
SELECTOR	Amplifier	EM18G40G	060726	2025-04-09	2026-04-08
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2024-08-05	2025-08-04
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-11	011	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-12	012	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-13	013	2025-04-09	2026-04-08
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2025-04-09	2026-04-08
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
XHFDZ	RG316 Coaxial Cable	SMA-316	XHF-1175	Each time	N/A

Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2025-04-08	2026-04-07
Rohde & Schwarz	LISN	ENV216	101115	2025-04-08	2026-04-07
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2025-04-08	2026-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2025-04-08	2026-04-07

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. f (GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Calculated Data:

Mode	Max Tune-up Conducted Power★		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
BT	9.7	9.33	5	2.9	3.0	Yes

Note:

1. For the above tune up power were declared by the manufacturer.

Result: No SAR test is required.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT have an FPC antenna which permanently attached to the unit. fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW
150 kHz - 30 MHz	9 kHz	30 kHz

Test Procedure

ANSI C63.10-2020 clause 6.2

During the conducted emission test, the EUT or adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

$$\begin{aligned}\text{Factor (dB)} &= \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)} \\ \text{Level (dB}\mu\text{V)} &= \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)}\end{aligned}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Level (dB}\mu\text{V)} - \text{Limit (dB}\mu\text{V)}$$



Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

Test System Setup**9 kHz - 30 MHz:****30 MHz - 1 GHz:**

Above 1 GHz:

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	QP/ Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak
	/	/	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	/	Average

Test Procedure

According to ANSI C63.10-2020 clause 6.4, 6.5 and 6.6.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Note: The QuasiPeak (dB μ V/m), MaxPeak (dB μ V/m), Average (dB μ V/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.


Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH


Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

According to ANSI C63.10-2020 sub-clause 6.9.2

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard


Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.4

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Zero span, centered on a hopping channel.
- b. RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c. Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d. Detector function: Peak.
- e. Trace: Max hold.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard


According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.5

a. Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix

FCC §15.247(d) - BAND EDGES TESTING


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2020 sub-clause 7.8.7

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Note: Offset (10.5dB) = Attenuator (10dB) + Cable Loss (0.5dB)

Test Datd: See Appendix


APPENDIX - TEST DATA

AC LINE CONDUCTED EMISSIONS

Environmental Conditions & Test Information


Test Date:	2025-07-12
Temperature:	27.1 °C
Relative Humidity:	65 %
ATM Pressure:	100.8 kPa
Test Result:	Pass
Test Engineer:	Myles Miao

EUT operation mode: Transmitting in GFSK Mode low channel (maximum output power mode)



Site : CE
Condition : limit\FCC PART 15.207
Project No. : RKSA250707003
Model : P053
Phase : L
Voltage : 120V/60Hz
Mode : BT
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz,Sweep Time: Auto
Temperature : 27.1℃
Humidity : 65%
Atmospheric pressure: 100.8KPa
Test Engineer : Myles Miao

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV		dB	dBuV	dB	
1	0.158	26.78	20.22	47.00	65.54	-18.54	Peak
2	0.190	24.05	20.22	44.27	64.05	-19.78	Peak
3	0.317	19.43	20.23	39.66	59.79	-20.13	Peak
4	0.494	17.44	20.18	37.62	56.11	-18.49	Peak
5	0.669	20.11	20.28	40.39	56.00	-15.61	Peak
6	13.581	23.75	20.42	44.17	60.00	-15.83	Peak



Site : CE
Condition : limit\FCC PART 15.207
: DET:Peak
Project No. : RKSA250707003
Model : P053
Phase : N
Voltage : 120V/60Hz
Mode : BT
Test Equipment : ENV216, ESR3
Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
Temperature : 27.1°C
Humidity : 65%
Atmospheric pressure: 100.8KPa
Test Engineer : Myles Miao

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.162	25.78	20.22	46.00	65.38	-19.38	Peak
2	0.191	22.77	20.22	42.99	64.01	-21.02	Peak
3	0.700	19.79	20.30	40.09	56.00	-15.91	Peak
4	1.101	14.34	20.10	34.44	56.00	-21.56	Peak
5	13.447	19.99	20.41	40.40	60.00	-19.60	Peak
6	16.912	20.65	20.54	41.19	60.00	-18.81	Peak

RADIATED EMISSIONS & RESTRICTED BANDS EMISSIONS

Environmental Conditions & Test Information

Test Item:	SPURIOUS EMISSIONS			
	9 kHz-30MHz	30 MHz – 1 GHz	1 GHz - 18 GHz	18 GHz - 25 GHz
Test Date:	2025-07-25	2025-07-14	2025-07-15	2025-07-31
Temperature:	25.1 °C	24.3 °C	26.2 °C	24.7 °C
Relative Humidity:	48%	46%	50 %	50 %
ATM Pressure:	101.2 kPa	100.4 kPa	100.2 kPa	101.3 kPa
Test Result:	Pass	Pass	Pass	Pass
Test Engineer:	Link Xia	Link Xia	Destine Hu	Hugh Wu

EUT operation mode: Transmitting


After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

Dipole Antenna:


9 kHz-30 MHz: (Transmitting maximum output power GFSK Mode low channel)

Parallel(worst case)

9kHz-150kHz



150kHz-30MHz



Project No. RKSA250707003
Date: 25.JUL.2025 12:07:22

Tester: Link Xia

Project No. RKSA250707003
Date: 25.JUL.2025 12:10:53

Tester: Link Xia

9kHz-150kHz


Frequency (kHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
20.28	47.51	PK	-0.56	121.46	73.95
25.36	45.57	PK	-0.59	119.52	73.95
39.46	44.63	PK	-2.12	115.68	71.05
51.86	42.06	PK	-4.03	113.31	71.25

150kHz-30MHz

Frequency (MHz)	Corrected Amplitude (dB μ V/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dB μ V/m) @3m	Margin (dB)
0.15	48.36	PK	-11.34	104.08	55.72
1.22	43.18	PK	-28.34	65.88	22.70
4.39	40.87	PK	-31.97	69.54	28.67
6.18	30.64	PK	-32.24	69.54	38.90

30 MHz - 1 GHz (Transmitting in maximum output power GFSK mode):**Low Channel: 2402 MHz****Common Information**


Project No: RKSA250707003
 EUT Model: P053
 Test Mode: Transmitting in BT mode low channel
 Standard: FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
 Test Equipment: ESCI, JB3, 310N
 Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
 Temperature: 24.3°C
 Humidity: 46%
 Barometric Pressure: 100.4 kPa
 Test Engineer: Link Xia
 Test Date: 2025/7/14

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.121250	28.92	40.00	11.08	V	-4.8
66.011250	21.90	40.00	18.10	V	-16.8
131.001250	29.58	43.50	13.92	V	-11.1
141.307500	29.37	43.50	14.13	V	-11.3
206.297500	22.84	43.50	20.66	V	-12.5
875.233750	34.02	46.00	11.98	V	0.6

1 GHz - 18 GHz:**GFSK:****Low Channel: 2402 MHz****Common Information**


Project No.:	RKSA250707003
EUT Model:	P053
Test Mode:	Transmitting in BT_1DH5 mode low channel
Standard:	FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	26.2℃
Humidity:	50%
Atmospheric Pressure:	100.2kPa
Test Engineer:	Destine Hu
Test Date:	2025/7/15

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1061.200000	---	23.48	54.00	30.52	V	-15.0
1061.200000	36.74	---	74.00	37.26	V	-15.0
2128.800000	---	29.29	54.00	24.71	H	-9.9
2128.800000	41.97	---	74.00	32.03	H	-9.9
3597.600000	35.77	---	74.00	38.23	H	-6.0
3597.600000	---	34.17	54.00	19.83	H	-6.0
6440.000000	---	36.09	54.00	17.91	V	-0.8
6440.000000	45.72	---	74.00	28.28	V	-0.8
10968.800000	---	42.32	54.00	11.68	V	6.6
10968.800000	49.31	---	74.00	24.69	V	6.6
16728.400000	---	43.60	54.00	10.40	V	9.9
16728.400000	53.75	---	74.00	20.25	V	9.9

Middle Channel: 2441 MHz**Common Information**


Project No.: RKSA250707003
 EUT Model: P053
 Test Mode: Transmitting in BT_1DH5 mode middle channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 26.2℃
 Humidity: 50%
 Atmospheric Pressure: 100.2kPa
 Test Engineer: Destine Hu
 Test Date: 2025/7/15

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1190.400000	---	21.52	54.00	32.48	V	-14.5
1190.400000	35.30	---	74.00	38.70	V	-14.5
1989.400000	---	25.45	54.00	28.55	V	-10.1
1989.400000	37.03	---	74.00	36.97	V	-10.1
7398.800000	---	40.10	54.00	13.90	V	2.7
7398.800000	50.30	---	74.00	23.70	V	2.7
12090.800000	---	43.92	54.00	10.08	V	9.0
12090.800000	54.69	---	74.00	19.31	V	9.0
14545.600000	---	46.12	54.00	7.88	H	11.8
14545.600000	55.80	---	74.00	18.20	H	11.8
14617.000000	---	46.41	54.00	7.59	H	11.6
14617.000000	53.49	---	74.00	20.51	H	11.6

High Channel: 2480 MHz**Common Information**

Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_1DH5 mode high channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2°C
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
1061.200000	---	23.31	54.00	30.69	V	-15.0
1061.200000	37.22	---	74.00	36.78	V	-15.0
2132.200000	---	27.09	54.00	26.91	V	-9.9
2132.200000	42.85	---	74.00	31.15	V	-9.9
3597.600000	36.16	---	74.00	37.84	H	-6.0
3597.600000	---	32.98	54.00	21.02	H	-6.0
6892.200000	---	37.09	54.00	16.91	V	1.0
6892.200000	45.13	---	74.00	28.87	V	1.0
11261.200000	---	43.43	54.00	10.57	V	7.4
11261.200000	51.32	---	74.00	22.68	V	7.4
14936.600000	---	46.14	54.00	7.86	V	10.5
14936.600000	55.43	---	74.00	18.57	V	10.5

$\pi/4$ -DQPSK:

Low Channel: 2402 MHz

Common Information

Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_2DH5 mode low channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2°C
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15




Critical_Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
1064.600000	---	24.54	54.00	29.46	V	-15.0
1064.600000	38.79	---	74.00	35.21	V	-15.0
2128.800000	---	31.53	54.00	22.47	V	-9.9
2128.800000	42.36	---	74.00	31.64	V	-9.9
3597.600000	---	33.19	54.00	20.81	V	-6.0
3597.600000	35.82	---	74.00	38.18	V	-6.0
6803.800000	---	37.22	54.00	16.78	V	0.6
6803.800000	45.62	---	74.00	28.38	V	0.6
11247.600000	---	43.33	54.00	10.67	H	7.4
11247.600000	53.24	---	74.00	20.76	H	7.4
14977.400000	54.24	---	74.00	19.76	V	10.4
14977.400000	---	45.78	54.00	8.22	V	10.4

Middle Channel: 2441 MHz**Common Information**


Project No.: RKSA250707003
 EUT Model: P053
 Test Mode: Transmitting in BT_2DH5 mode middle channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 26.2°C
 Humidity: 50%
 Atmospheric Pressure: 100.2kPa
 Test Engineer: Destine Hu
 Test Date: 2025/7/15

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1136.000000	35.94	---	74.00	38.06	V	-14.7
1136.000000	---	21.52	54.00	32.48	V	-14.7
1999.600000	---	25.10	54.00	28.90	V	-10.0
1999.600000	37.29	---	74.00	36.71	V	-10.0
6538.600000	---	36.09	54.00	17.91	H	-0.7
6538.600000	48.44	---	74.00	25.56	H	-0.7
14504.800000	54.25	---	74.00	19.75	H	12.0
14504.800000	---	46.74	54.00	7.26	H	12.0
14596.600000	55.37	---	74.00	18.63	H	11.6
14596.600000	---	44.65	54.00	9.35	H	11.6
17792.600000	---	43.91	54.00	10.09	V	11.2
17792.600000	55.23	---	74.00	18.77	V	11.2

High Channel: 2480 MHz**Common Information**


Project No.: RKSA250707003
 EUT Model: P053
 Test Mode: Transmitting in BT_2DH5 mode high channel
 Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 26.2°C
 Humidity: 50%
 Atmospheric Pressure: 100.2kPa
 Test Engineer: Destine Hu
 Test Date: 2025/7/15

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1061.200000	40.42	---	74.00	33.58	V	-15.0
1061.200000	---	25.70	54.00	28.30	V	-15.0
1187.000000	---	22.70	54.00	31.30	V	-14.5
1187.000000	34.13	---	74.00	39.87	V	-14.5
2122.000000	---	26.88	54.00	27.12	V	-9.9
2122.000000	38.10	---	74.00	35.90	V	-9.9
4791.000000	---	32.98	54.00	21.02	V	-3.4
4791.000000	44.46	---	74.00	29.54	V	-3.4
8860.800000	---	43.08	54.00	10.92	H	4.7
8860.800000	50.76	---	74.00	23.24	H	4.7
14049.200000	---	46.32	54.00	7.68	H	11.2
14049.200000	54.17	---	74.00	19.83	H	11.2

8DPSK:**Low Channel: 2402 MHz****Common Information**


Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_3DH5 mode low channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2°C
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
1061.200000	39.03	---	74.00	34.97	V	-15.0
1061.200000	---	26.06	54.00	27.94	V	-15.0
2128.800000	38.59	---	74.00	35.41	V	-9.9
2128.800000	---	26.58	54.00	27.42	V	-9.9
3597.600000	---	35.37	54.00	18.63	V	-6.0
3597.600000	37.40	---	74.00	36.60	V	-6.0
5828.000000	---	37.06	54.00	16.94	H	-1.0
5828.000000	44.22	---	74.00	29.78	H	-1.0
9904.600000	51.79	---	74.00	22.21	H	6.1
9904.600000	---	41.83	54.00	12.17	H	6.1
14589.800000	---	46.00	54.00	8.00	H	11.7
14589.800000	55.67	---	74.00	18.33	H	11.7

Middle Channel: 2441 MHz**Common Information**


Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_3DH5 mode middle channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2℃
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1057.800000	---	20.64	54.00	33.36	V	-15.0
1057.800000	33.22	---	74.00	40.78	V	-15.0
1197.200000	---	21.78	54.00	32.22	V	-14.5
1197.200000	33.36	---	74.00	40.64	V	-14.5
1996.200000	---	27.11	54.00	26.89	V	-10.0
1996.200000	37.09	---	74.00	36.91	V	-10.0
5998.000000	---	37.64	54.00	16.36	V	-0.6
5998.000000	46.29	---	74.00	27.71	V	-0.6
14093.400000	55.43	---	74.00	18.57	H	11.3
14093.400000	---	45.34	54.00	8.66	H	11.3
14583.000000	52.98	---	74.00	21.02	H	11.7
14583.000000	---	46.87	54.00	7.13	H	11.7

High Channel: 2480 MHz**Common Information**


Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_3DH5 mode high channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2℃
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
1061.200000	---	27.69	54.00	26.31	V	-15.0
1061.200000	38.69	---	74.00	35.31	V	-15.0
2132.200000	---	27.39	54.00	26.61	V	-9.9
2132.200000	39.97	---	74.00	34.03	V	-9.9
4060.000000	---	31.55	54.00	22.45	H	-4.9
4060.000000	40.47	---	74.00	33.53	H	-4.9
7385.200000	---	40.42	54.00	13.58	H	2.6
7385.200000	48.56	---	74.00	25.44	H	2.6
12104.400000	---	44.56	54.00	9.44	V	9.0
12104.400000	54.56	---	74.00	19.44	V	9.0
16997.000000	53.76	---	74.00	20.24	V	10.9
16997.000000	---	45.88	54.00	8.12	V	10.9

Band Edge:**GFSK:****Left Side****Common Information**


Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_1DH5 mode low channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2°C
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB)
2380.224000	---	44.67	54.00	9.33	V	0.2
2380.224000	58.23	---	74.00	15.77	V	0.2
2380.784000	---	43.85	54.00	10.15	V	0.2
2380.784000	60.53	---	74.00	13.47	V	0.2

Right Side**Common Information**

Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_1DH5 mode high channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2°C
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
2487.424000	---	42.00	54.00	12.00	V	0.4
2487.424000	60.39	---	74.00	13.61	V	0.4

$\pi/4$ -DQPSK:

Left Side

Common Information

Project No.:

EUT Model:

Test Mode:

Standard:

Test Equipment:

Receiver Setting:

Temperature:

Humidity:

Atmospheric Pressure:

Test Engineer:

Test Date:

RKSA250707003

P053

Transmitting in BT_2DH5 mode low channel

FCC Part 15.247& FCC Part 15.205& FCC Part 15.209

ESU40,3115,PAM-0118P

RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto

26.2℃


50%

100.2kPa

Destine Hu

2025/7/15

Full Spectrum




Critical_Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
2380.280000	---	43.12	54.00	10.88	V	0.2
2380.280000	59.95	---	74.00	14.05	V	0.2

Right Side**Common Information**

Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_2DH5 mode high channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2℃
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15


Full Spectrum

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
2484.736000	---	42.17	54.00	11.83	V	0.4
2484.736000	61.37	---	74.00	12.63	V	0.4

8DPSK:**Left Side****Common Information**


Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_3DH5 mode low channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2°C
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
2380.112000	---	43.71	54.00	10.29	V	0.2
2380.112000	59.20	---	74.00	14.80	V	0.2



Right Side**Common Information**

Project No.: RKSA250707003
EUT Model: P053
Test Mode: Transmitting in BT_3DH5 mode high channel
Standard: FCC Part 15.247& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 26.2℃
Humidity: 50%
Atmospheric Pressure: 100.2kPa
Test Engineer: Destine Hu
Test Date: 2025/7/15

Full Spectrum**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB)
2494.264000	---	39.72	54.00	14.28	V	0.4
2494.264000	60.32	---	74.00	13.68	V	0.4

18 GHz - 25 GHz (GFSK Mode low channel):



Project No :RKSA250707003
Date: 31.JUL.2025 19:56:23

Tester :Hugh Wu

Project No :RKSA250707003
Date: 31.JUL.2025 20:29:46

Tester :Hugh Wu

Frequency (GHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
19.66	---	38.73	54	15.27	H	11.3
19.66	48.65	---	74	25.35	H	11.3
20.20	---	38.56	54	15.44	V	12.46
20.20	48.71	---	74	25.29	V	12.46

Note: The test distance is 3m. The limit is 74dB μ V/m(Peak) and 54dB μ V/m(Average).

CHANNEL SEPARATION TEST**Environmental Conditions & Test Information**


Test Date:	2025-07-25
Temperature:	24.5 °C
Relative Humidity:	52 %
ATM Pressure:	101.4 kPa
Test Result:	Pass
Test Engineer:	Jason Lu

EUT operation mode: Transmitting

Mode	Channel	Result (MHz)	Limit (MHz)	Result
GFSK	Low	1.005	0.844	Pass
	Middle	1.005	0.844	Pass
	High	1.001	0.844	Pass


Note: Only GFSK mode result is reported since EDR($\pi/4$ -DQPSK, 8DPSK) has the exact same channel plan.
Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:22:04

BDR (GFSK): Middle Channel



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:33:35

BDR (GFSK): High Channel



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:43:57


20 dB BANDWIDTH TEST**Environmental Conditions & Test Information**

Test Date:	2025-07-24
Temperature:	24.7 °C
Relative Humidity:	54 %
ATM Pressure:	101.5kPa
Test Result:	Pass
Test Engineer:	Jason Lu

EUT operation mode: Transmitting


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.903
	Middle	2441	0.900
	High	2480	0.885
EDR ($\pi/4$-DQPSK)	Low	2402	1.263
	Middle	2441	1.266
	High	2480	1.266
EDR (8DPSK)	Low	2402	1.251
	Middle	2441	1.254
	High	2480	1.251

BDR (GFSK): Low Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:29:02

BDR (GFSK): Middle Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:36:28

BDR (GFSK): High Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:45:03

EDR ($\pi/4$ -DQPSK): Low Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:46:54

EDR($\pi/4$ -DQPSK): Middle Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:49:43


EDR ($\pi/4$ -DQPSK): High Channel




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:51:37



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:53:30



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:56:10



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:58:19


QUANTITY OF HOPPING CHANNEL TEST**Environmental Conditions & Test Information**

Test Date:	2025-07-25
Temperature:	24.5 °C
Relative Humidity:	52 %
ATM Pressure:	101.4 kPa
Test Result:	Pass
Test Engineer:	Jason Lu

EUT operation mode: Hopping


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:08:50

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:15:29

EDR (8DPSK): Number of Hopping Channels



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:20:44

TIME OF OCCUPANCY (DWELL TIME)**Environmental Conditions & Test Information**

Test Date:	2025-07-25
Temperature:	24.5 °C
Relative Humidity:	52 %
ATM Pressure:	101.4 kPa
Test Result:	Pass
Test Engineer:	Jason Lu


EUT operation mode: Hopping

Mode		Channel	BurstWidth (ms)	TotalHops (Num)	Dwell time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Middle	0.410	320	0.13	0.4	Pass
	DH3		1.676	180	0.30	0.4	Pass
	DH5		2.942	110	0.32	0.4	Pass
EDR ($\pi/4$ -DQPSK)	2DH1		0.418	310	0.13	0.4	Pass
	2DH3		1.681	150	0.25	0.4	Pass
	2DH5		2.966	100	0.30	0.4	Pass
EDR (8DPSK)	3DH1		0.417	310	0.13	0.4	Pass
	3DH3		1.676	140	0.23	0.4	Pass
	3DH5		2.966	130	0.39	0.4	Pass

Note: Dwell time = BurstWidth (Pulse time) * TotalHops


TotalHops (31.6s) = hopping numbers (3.16s)*10

BDR (GFSK): Pulse time, Middle Channel, DH1




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:44:11

BDR (GFSK): Pulse time, Middle Channel, DH3




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:48:25

BDR (GFSK): Pulse time, Middle Channel, DH5




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:52:04

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH1




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:46:22

EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH3




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:49:31


EDR ($\pi/4$ -DQPSK): Pulse time, Middle Channel, 2DH5




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:53:02



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:47:30




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:50:23



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:53:55


BDR Mode (GFSK):

Hopping Numbers-DH1




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:58:33

Hopping Numbers-DH3



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:59:17


Hopping Numbers-DH5



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:03:48


EDR Mode ($\pi/4$ -DQPSK):

Hopping Numbers-2DH1




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:04:19

Hopping Numbers-2DH3



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:04:55


Hopping Numbers-2DH5



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:05:38


EDR Mode (8DPSK):

Hopping Numbers-3DH1




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:06:13

Hopping Numbers-3DH3



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 11:06:51

Hopping Numbers-3DH5



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:57:15


PEAK OUTPUT POWER MEASUREMENT**Environmental Conditions & Test Information**

Test Date:	2025-07-24
Temperature:	24.7 °C
Relative Humidity:	54 %
ATM Pressure:	101.5kPa
Test Result:	Pass
Test Engineer:	Jason Lu

EUT operation mode: Transmitting


Mode	Channel	Frequency (MHz)	Result (dBm)	Limit (dBm)
GFSK	Low	2402	9.58	21
	Middle	2441	9.38	
	High	2480	8.94	
$\pi/4$ DQPSK	Low	2402	8.86	
	Middle	2441	8.59	
	High	2480	8.20	
8DPSK	Low	2402	9.31	
	Middle	2441	9.15	
	High	2480	8.79	

BDR (GFSK): 2402MHz




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:30:38

BDR (GFSK): 2441MHz




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:37:58

BDR (GFSK): 2480MHz




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:45:42

EDR($\pi/4$ -DQPSK): 2402MHz




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:48:31

EDR($\pi/4$ -DQPSK): 2441MHz




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:50:26


EDR($\pi/4$ -DQPSK): 2480MHz




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:52:15



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:54:48



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:57:13



ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 24.JUL.2025 13:59:00

BAND EDGES**Environmental Conditions & Test Information**

Test Date:	2025-07-25
Temperature:	24.5 °C
Relative Humidity:	52 %
ATM Pressure:	101.4 kPa
Test Result:	Pass
Test Engineer:	Jason Lu


EUT operation mode: Transmitting & Hopping

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	Result (dBc)	Limit (dBc)
GFSK	Low	2402	49.55	20
	High	2480	50.78	
$\pi/4$ DQPSK	Low	2402	49.20	
	High	2480	48.89	
8DPSK	Low	2402	48.46	
	High	2480	48.76	
GFSK (Hopping)	Low	2402	52.54	
	High	2480	51.93	
$\pi/4$ DQPSK (Hopping)	Low	2402	49.12	
	High	2480	48.56	
8DPSK (Hopping)	Low	2402	49.68	
	High	2480	48.94	


Band Edge

BDR (GFSK): Left Side




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:37:50

BDR (GFSK): Right Side




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:40:26

EDR ($\pi/4$ -DQPSK): Left Side




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:47:59

EDR ($\pi/4$ -DQPSK): Right Side




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:50:34

EDR (8DPSK): Left Side




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:58:00


EDR (8DPSK): Right Side




ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 10:01:12

BDR (GFSK): Left Side - Hopping


ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:32:14

BDR (GFSK): Right Side - Hopping


ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:35:15

EDR ($\pi/4$ -DQPSK): Left Side - Hopping


ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:42:58

EDR ($\pi/4$ -DQPSK): Right Side - Hopping

ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:45:16

EDR (8DPSK): Left Side - Hopping

ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:53:04

EDR (8DPSK): Right Side - Hopping

ProjectNo.:RKSA250707003 Tester:Jason Lu
Date: 25.JUL.2025 09:55:25

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******