

FCC ID:2BFTW-SPDJH1

Maximum Permissible Exposure (MPE)

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

BT:

Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type:FPC antenna

Antenna gain:2 dBi;

R=20cm

mW=10^{^(dBm/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(0/10)}=1

Channel Freq. (MHz)	modulation	conducted pow er	Tune-up pow er (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up pow er		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
2402	DH5	5.01	5±1	6	3.981	2.00	1.58	0.0013	1
2441		5.18	5±1	6	3.981	2.00	1.58	0.0013	1
2480		5.8	5±1	6	3.981	2.00	1.58	0.0013	1
2402	2DH5	4.99	5±1	6	3.981	2.00	1.58	0.0013	1
2441		5.19	5±1	6	3.981	2.00	1.58	0.0013	1
2480		5.84	5±1	6	3.981	2.00	1.58	0.0013	1
2402	3DH5	5.37	5.5±1	6.5	4.467	2.00	1.58	0.0014	1
2441		5.59	5.5±1	6.5	4.467	2.00	1.58	0.0014	1
2480		6.05	5.5±1	6.5	4.467	2.00	1.58	0.0014	1

BLE:

Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type:FPC antenna

Antenna gain:2 dBi;

R=20cm

mW=10^{^(dBm/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(0/10)}=1

Channel Freq. (MHz)	modulation	conducted pow er	Tune-up pow er (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up pow er		Gain			
				(dBm)	(mV)	(dBi)	Numeric	(mW/cm ²)	(mW/cm ²)
2402	BLE	-0.61	-0.5±1	0.5	1.122	2.00	1.58	0.0004	1
2440		-0.58	-0.5±1	0.5	1.122	2.00	1.58	0.0004	1
2480		-0.15	-0.5±1	0.5	1.122	2.00	1.58	0.0004	1

2.4GWIFI:

Measurement Result

Operation Frequency: 2412MHz~2462MHz

Power density limited: 1mW/ cm²

Antenna Type:FPC antenna

Antenna gain:2 dBi;

R=20cm

mW=10^{^(dBm/10)}

antenna gain Numeric=10^{^(dBi/10)}= 10^{^(0/10)}=1

Channel Freq. (MHz)	modulation	conducted power	Tune-up pow er (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up pow er		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Numeric		
2412	B	15.48	15±1	16	39.811	2.00	1.58	0.0126	1
2437		15.21	15±1	16	39.811	2.00	1.58	0.0126	1
2462		14.79	15±1	16	39.811	2.00	1.58	0.0126	1
2412	G	14.65	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2437		14.44	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2462		14.04	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2412	N20	14.68	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2437		14.41	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2462		14.00	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2422	N40	14.80	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2437		14.76	14.5±1	15.5	35.481	2.00	1.58	0.0112	1
2452		14.34	14.5±1	15.5	35.481	2.00	1.58	0.0112	1

5GWIFI:

Measurement Result

Operation Frequency: 5150MHz~5850MHz

Power density limited: 1mW/ cm²

Antenna Type:FPC antenna

Antenna gain:3 dBi;

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(0/10)}=1$

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mV)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
5240	AC20	14.284	15±1	16	39.811	3.00	2.00	0.0158	1
5270	N40	12.923	13±1	14	25.119	3.00	2.00	0.0100	1
5610	AC80	12.394	13±1	14	25.119	3.00	2.00	0.0100	1
5775	AC80	12.702	13±1	14	25.119	3.00	2.00	0.0100	1

BT+BLE+2.4GWIFI+5GWIFI=0.0013+0.004+0.00126+0.0158=0.02236<1

Conclusion:

For the max result : $0.0001 \leq 1.0$ for Max Power Density, compliance RF exposure..

Signature: 

Date: 2024-05-16

NAME AND TITLE (Please print or type): alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.