



RF Exposure Evaluation Declaration

Product Name	UltraPeace-Instant H. Pylori Urea Breath Test Kit System
Model No.	UP100
Brand Name	Ultra PEACE
Bluetooth Specification	Bluetooth: V4.2
Operating Frequency	2402~2480MHz
Antenna gain	-0.5dBi

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1. FCC Limits

According to FCC KDB 447498 Section 4.3 - General SAR test exclusion guidance

For 100 MHz to 6 GHz and test separation distances \leq 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}$

where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz
2. Power and distance are rounded to the nearest mW and mm before calculation
3. The result is rounded to one decimal place for comparison
4. The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

1.2. Test Result

Mode	Frequency Band (MHz)	Output Power (dBm)	Output Power (mW)	FCC Extremity SAR Test Exclusion Threshold (mW)
BLE	2402~2480	0.48	1.12	3

So, this device can complies the SAR test exclusion.

————— The End —————