

**FCC TEST REPORT**
FCC ID:2BG3K-BT-3301**Report Number**.....: **ZHT-240516027E**

Date of Test.....: May 16, 2024 to June 20, 2024

Date of issue.....: June 20, 2024

Test Result: PASS

Testing Laboratory.....: **Guangdong Zhonghan Testing Technology Co., Ltd.**Address: Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community,
Fuhai Street, Bao'an District, Shenzhen, Guangdong, China**Applicant's name**: **XUTHUS INT'L LOGISTICS LTD**Address: ROOM 419 BULDING 2, ZHIMEI HUIZHI INDUSTRIAL
PARK, FUZHOU ROAD, FUYONG, SHENZHEN, CHINA**Manufacturer's name**: **XUTHUS INT'L LOGISTICS LTD**Address: ROOM 419 BULDING 2, ZHIMEI HUIZHI INDUSTRIAL
PARK, FUZHOU ROAD, FUYONG, SHENZHEN, CHINA**Test specification:**

Standard.....: FCC CFR Title 47 Part 15 Subpart C

Test procedure.....: /

Non-standard test method: N/A

This device described above has been tested by ZHT, and the test result show that the equipment under test (EUT) is in compliance with the FCC requirement. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Product name.....: **LED WIRELESS CHARGING SPEAKER**

Trademark: /

Model/Type reference.....: BT-3301, BT-3302 BT-3303, BT-3304, BT-3305, BT-3306, BT-3307,
BT-3308, BT-3309Model Difference.....: BT-3301 is tested model, other models are derivative models. The
models are identical in circuit, only different on the model names.
So the test data of BT-3301 can represent the remaining models.Ratings.....: Input: Type-C: 5V, or 3.7V by Built-in Battery
Wireless charging Output: 15W Max

Testing procedure and testing location:

Testing Laboratory.....: Guangdong Zhonghan Testing Technology Co., Ltd.

Address.....: Room 104, Building 1, Yibaolai Industrial Park, Qiaotou
Community, Fuhai Street, Bao'an District, Shenzhen,
Guangdong, China

Tested by (name + signature).....: Leon Li

Leon Li

Reviewer (name + signature).....: Baret Wu

Baret Wu

Approved (name + signature).....: Levi Lee

Levi Lee



TABLE OF CONTENT

1. VERSION	4
2. TEST SUMMARY	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 Test mode	7
3.3 Block Diagram of EUT Configuration	7
3.4 Test Conditions	7
3.5 Description Of Support Uni/ (Conducted Mode)	8
3.6 EQUIPMEN/ LIST FOR ALL TEST ITEMS	9
4. CONDUCTED EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION Limi/	11
4.1.2 TEST PROCEDURE	11
4.1.3 DEVIATION FROM TEST STANDARD	11
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 Test Result	13
5. RADIATED EMISSION MEASUREMENT	15
5.1 Radiated Emission Limi/	15
5.2 Anechoic Chamber Test Setup Diagram	16
5.3 Test Procedure	16
5.4 DEVIATION FROM TEST STANDARD	16
5.5 Test Result	17
6. BANDWIDTH TEST	20
7. ANTENNA REQUIREMENT	22
8. TEST SETUP PHOTO	23
9. EUT CONSTRUCTIONAL DETAILS	23

1. VERSION

Report No.	Version	Description	Approved
ZHT-240516027E	Rev.01	Initial issue of report	June 20, 2024

2. TEST SUMMARY

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	Pass
Spurious Emission	15.209(a)(f)	Pass
20dB Bandwidth	15.215	Pass

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District
Shenzhen, Guangdong, China

FCC Registration Number: 255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF conducted power	$\pm 0.16\text{dB}$
3	Conducted spurious emissions	$\pm 0.21\text{dB}$
4	All radiated emissions (9k-30MHz)	$\pm 4.68\text{dB}$
5	All radiated emissions (<1G)	$\pm 4.68\text{dB}$
6	All radiated emissions (>1G)	$\pm 4.89\text{dB}$
7	Temperature	$\pm 0.5^{\circ}\text{C}$
8	Humidity	$\pm 2\%$
9	Occupied Bandwidth	$\pm 4.96\%$

3. GENERAL INFORMATION


3.1 GENERAL DESCRIPTION OF EUT

Product Name:	LED WIRELESS CHARGING SPEAKER
Test Model No:	BT-3301
Hardware version:	V1.0
Software version:	V1.0
Operation Frequency:	110-205KHz
Modulation type:	MSK
Antenna Type:	Coil Antenna
Antenna gain:	0dBi
Ratings :	Input: Type-C: 5V, or 3.7V by Built-in Battery Wireless charging Output: 15W Max

3.2 Test mode

Test Modes:	
Mode 1	Wireless charging(5W)
Mode 2	Wireless charging(7.5W)
Mode 3	Wireless charging(10W)
Mode 4	Wireless charging(15W)
Note: 1. All modes were tested, only the worst-case was recorded in the report. Mode 4 is the worst mode. 2.The EUT does not support portable use, and wireless charging output is not supported when only powered by batteries.	

3.3 Block Diagram of EUT Configuration



3.4 Test Conditions

Temperature: 23~26℃

Relative Humidity: 54~63 %

3.5 Description Of Support Uni/ (Conducted Mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support uni/ or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-2	AC Adapter	N/A	HW-059200CHQ	N/A	AE
E-3	Wireless charging load	N/A	EESON	N/A	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

3.6 EQUIPMEN/ LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	Mar 10, 2024	Mar 09, 2025
2	Loop antenna	EMCI	LAP600	Mar 10, 2024	Mar 09, 2025
3	Amplifier	Schwarzbeck	BBV 9743 B	Mar 10, 2024	Mar 09, 2025
4	Amplifier	Schwarzbeck	BBV 9718 B	Mar 10, 2024	Mar 09, 2025
5	Bilog Antenna	Schwarzbeck	VULB9168	Aug. 04, 2023	Aug. 03, 2024
6	Horn Antenna	Schwarzbeck	BBHA9120D	Mar 16, 2024	Mar 15, 2025
7	Horn Antenna	A.H.SYSTEMS	SAS574	Mar 10, 2024	Mar 09, 2025
8	Amplifier	AEROFLEX	100KHz-40GHz	Mar 10, 2024	Mar 09, 2025
9	Spectrum Analyzer	R&S	FSV40	Mar 10, 2024	Mar 09, 2025
10	966 Anechoic Chamber	EMToni	9m6m6m	Nov. 25, 2021	Nov. 24, 2024
11	Spectrum Analyzer	KEYSIGHT	N9020A	Mar 10, 2024	Mar 09, 2025
12	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	Mar 10, 2024	Mar 09, 2025
13	Single Generator	Agilent	N5182A	Mar 10, 2024	Mar 09, 2025
14	Power Sensor	MWRFTest	MW100-RFCB	Mar 10, 2024	Mar 09, 2025
15	Audio analyzer	R&S	UPL	Mar 10, 2024	Mar 09, 2025
16	Single Generator	R&S	SMB100A	Mar 10, 2024	Mar 09, 2025
17	Power Amplifier Shielding Room	EMToni	2m3m3m	Nov. 25, 2021	Nov. 24, 2024

Conduction Test equipment

Equipment	Manufacturer	Model	Last Cal.	Next Cal.
Receiver	R&S	ESCI	Mar 10, 2024	Mar 09, 2025
LISN	R&S	ENV216	Mar 10, 2024	Mar 09, 2025
ISN CAT 6	Schwarzbeck	NTFM 8158	Mar 10, 2024	Mar 09, 2025
ISN CAT 5	Schwarzbeck	CAT5 8158	Mar 10, 2024	Mar 09, 2025
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	Mar 10, 2024	Mar 09, 2025
Current Transformer Clamp	Schwarzbeck	SW 9605	Mar 10, 2024	Mar 09, 2025
CE Shielding Room	EMToni	9m4m3m	Nov. 25, 2021	Nov. 24, 2024

4. CONDUCTED EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limi/

FREQUENCY (MHz)	Limit (dBuV)		Standard
	QP	AVG	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipmen/ powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 4




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.8700	27.09	10.05	37.14	56.00	-18.86	QP	P	
2	0.8700	23.84	10.05	33.89	46.00	-12.11	AVG	P	
3	0.9915	26.88	10.06	36.94	56.00	-19.06	QP	P	
4	0.9915	15.00	10.06	25.06	46.00	-20.94	AVG	P	
5	1.0859	27.40	10.06	37.46	56.00	-18.54	QP	P	
6	1.0859	10.77	10.06	20.83	46.00	-25.17	AVG	P	
7	1.2255	27.60	10.06	37.66	56.00	-18.34	QP	P	
8	1.2255	12.05	10.06	22.11	46.00	-23.89	AVG	P	
9	1.6034	27.98	10.06	38.04	56.00	-17.96	QP	P	
10	1.6034	11.79	10.06	21.85	46.00	-24.15	AVG	P	
11	1.7384	29.69	10.06	39.75	56.00	-16.25	QP	P	
12 *	1.7384	27.23	10.06	37.29	46.00	-8.71	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 4



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.8655	26.01	10.05	36.06	56.00	-19.94	QP	P	
2	0.8655	19.75	10.05	29.80	46.00	-16.20	AVG	P	
3	0.9915	27.03	10.06	37.09	56.00	-18.91	QP	P	
4	0.9915	14.86	10.06	24.92	46.00	-21.08	AVG	P	
5	1.1625	27.91	10.06	37.97	56.00	-18.03	QP	P	
6	1.1625	11.92	10.06	21.98	46.00	-24.02	AVG	P	
7	1.3154	27.54	10.06	37.60	56.00	-18.40	QP	P	
8	1.3154	10.89	10.06	20.95	46.00	-25.05	AVG	P	
9	1.6080	28.88	10.06	38.94	56.00	-17.06	QP	P	
10	1.6080	13.39	10.06	23.45	46.00	-22.55	AVG	P	
11	1.7340	29.21	10.06	39.27	56.00	-16.73	QP	P	
12 *	1.7340	23.34	10.06	33.40	46.00	-12.60	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

5. RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 1GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

5.1 Radiated Emission Limi/

Limi/ for frequency below 30MHz


Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.490	2400/F(kHz)	300	Quasi-peak Value
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Limi/ for frequency Above 30MHz


Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.00	Quasi-peak Value
88MHz-216MHz	43.50	Quasi-peak Value
216MHz-960MHz	46.00	Quasi-peak Value
960MHz-1GHz	54.00	Quasi-peak Value
Above 1GHz	54.00	Average Value
	74.00	Peak Value

5.2 Anechoic Chamber Test Setup Diagram

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.

5.3 Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on an antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.

5.4 DEVIATION FROM TEST STANDARD

No deviation



5.5 Test Result


Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz


Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	coaxial
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 4






30MHz-1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 4





Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz	Test Modes:	Mode 4



Remarks:

1. Factor = Antenna Factor + Cable Loss – Preamplifier Factor
2. Level = Reading + Factor
3. Margin = Emission Level- Limit.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.



6. BANDWIDTH TEST


1. Set RBW = 10 Hz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude poin/ (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



Temperature:	25.7 °C	Relative Humidity:	55%
Pressure:	101kPa		

Frequency (KHz)	20dB bandwidth (KHz)	Result
117.2	0.432	Pass



7. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is Coil Antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details	

8. TEST SETUP PHOTO

Reference to the appendix I for details.

9. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

******* END OF REPORT *******