

# RF Exposure Evaluation Report

Product Name: Car Smart Screenr  
 Model No.: WL101  
 FCC ID: 2BG5V-WL101

## 1. RF Exposure Evaluation

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

## 2. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

## 3. Test Procedure

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Equation from page 18 of OET Bulletin 65, Edition 97-01

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator  
 R = distance to the centre of radiation of the antenna

#### 4. EUT RF EXPOSURE EVALUATION

BT ANT:0dBi;  
 2.4G-WIFI ANT:3dBi;  
 5G-WIFI ANT:7.21dBi;

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

The Max Conducted Peak Output Power data refer to report No.:DACE240523005RL001,  
 DACE240523005RL002,DACE240523005RL003.

worst mode and channel:

Test channel (MHz)	PK Power (dBm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (mW)	Calculated value (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
802.11g-2412	16.07	16±1	17	50.119	0.019894955	1.0
3-DH5-2402	-3.87	-3±1	-2	0.631	0.000125529	1.0
802.11ac(VHT20-5200)	15.01	15±1	16	39.811	0.041662272	1.0
802.11ac(VHT20)-5825	17.61	17±1	18	63.096	0.066030252	1.0

Note: Just the worst case mode was shown in report.

EUT RF Exposure Evaluation simultaneous transmission operations

According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits :

Simultaneous transmission mode	The sum of the ratios	SUM	Limit
EDR+2.4G WIFI+5GWIFI	0.000125529+0.019894955+0.06603025 2	0.086050736	1

conclusion :0.003182095< 1.0, So there is no sar requirement

Note: EDR and WiFi support simultaneous transmission, only the worst mode is evaluated in the report

EUT wifi module and ANT should be installed and operated with minimum distance 20cm between the radiator and your body.

Conclusion: the sum of the ratios is less than the limit value of 1.0, so there is no sar requirement.