

Page: 1 of 48

ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT





EUT Description: Wireless module installed in resistance cable machine

Applicant: Amp Fit, Inc.

651 N. Broad St. Suite 308, Middletown, Delaware, United

States 19709

Manufacturer: Amp Fit, Inc.

651 N. Broad St. Suite 308, Middletown, Delaware, United

States 19709

Brand Name: muRata

Model No.: LBEE5QD1ZM

FCC Host Model: amp

Report Number: TERF2504001583E2

FCC ID 2BG7RAMP1

Date of EUT Received: April 30, 2025

Date of Test: May 6, 2025~July 28, 2025

Issue Date: August 7, 2025

Approved By____

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Central RF Lab The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT comply with FCC rule part §15.247.

The results of this report relate only to the sample identified in this report.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 2 of 48

Revision History							
Report Number	Revision	Description	Issue Date	Revised By	Remark		
TERF2504001583E2	00	Original	June 24, 2025	Susan Lin			
TERF2504001583E2	01	Update section 7.4	July 29, 2025	Susan Lin	*		
TERF2504001583E2	02	Update section 3, 8.6.3 and 8.6.4	August 7, 2025	Susan Lin	*		

Note:

1 . The remark "*" indicates modification of the report upon requests from certification body.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 3 of 48

Contents

1	GENERAL INFORMATION	4
2	SYSTEM TEST CONFIGURATION	7
3	SUMMARY OF TEST RESULTS	10
4	DESCRIPTION OF TEST MODES	11
5	MEASUREMENT UNCERTAINTY	13
6	MEASUREMENT EQUIPMENT USED	14
7	PEAK OUTPUT POWER MEASUREMENT	15
8	RADIATED BANDEDGE AND SPURIOUS EMISSION MEASUREMENT	17

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 4 of 48

GENERAL INFORMATION

1.1 **Product Description**

EUT Description:	Wireless module installed in resistance cable machine
Brand Name:	muRata
Model No.:	LBEE5QD1ZM
FCC Host Model:	amp
Hardware Version:	N/A
Firmware Version:	1.0
EUT Series No.:	C4410GQB02823
Power Supply:	12Vdc from AC/DC Adapter
Test Software (Name/Version):	Tera Term Version 4.84

1.2 **RF Specification**

Radio Technology:	BT BR+EDR
Channel number:	79 channels
Modulation type:	GFSK + π/4DQPSK + 8DPSK
Transmit Power:	5.75 dBm
Frequency Range:	2.402GHz – 2.480GHz
Dwell Time:	≦ 0.4s

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 5 of 48

Antenna Designation

Antenna	Supplier	Antenna	Freq.	Peak Antenna
Type		Part No.	(MHz)	Gain (dBi)
FPC	Cortec Technology Inc.	NB1577-A150BF	2402~2480	3.23

Note: Antenna information is provided by the applicant.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

www.sgs.com.tw



Page: 6 of 48

Test Methodology of Applied Standards

FCC Part 15, Subpart C §15.247 FCC KDB 558074 D01 15.247 Meas. Guidance v05r02 ANSI C63.10:2013

1.5 **Test Facility**

Laboratory	Test Site Address	Test Site Name	FCC Designa- tion number	IC CAB identifier	
		SAC 1			
		SAC 2			
		SAC 3			
	No 424 West Keep Dood Now Toingi	Conduction 1			
	No.134, Wu Kung Road, New Taipei	Conducted 1	TW0027		
	Industrial Park, Wuku District, New Taipei City, Taiwan.	Conducted 2	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
	Taiper City, Taiwaii.	Conducted 3			
		Conducted 4			
		Conducted 5			
SGS Taiwan Ltd.		Conducted 6			
Central RF Lab.		Conduction C		TW3702	
(TAF code 3702)		SAC C			
		SAC D			
		SAC G			
	No 2 Kaii 4at Dd. Cwiahan Diatriat	Conducted A			
	No.2, Keji 1st Rd., Guishan District,	Conducted B	TW0028		
	Taoyuan City, Taiwan 333	Conducted C			
		Conducted D			
		Conducted E			
		Conducted F			
		Conducted G			

Note: Test site name is remarked on the equipment list in each section of this report as an indication where measurements occurred in specific test site and address.

1.6 **Special Accessories**

There is no special accessory used while test was conducted.

1.7 **Equipment Modifications**

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 7 of 48

SYSTEM TEST CONFIGURATION

2.1 **EUT Configuration**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 **EUT Exercise**

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

Test Procedure 2.3

2.3.1 **Conducted Emissions**

The EUT is placed on a table which is 0.8 m above ground plane. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz. The CISPR Quasi-Peak and Average detector mode is employed. The two LISNs provide 50uH/50 ohm of coupling impedance for the measuring instrument. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

2.3.2 **Conducted Test (RF)**

The active antenna port of the unlicensed wireless device is connected to the spectrum analyzer with attenuator to protect the instrumentation. If a second antenna port is available, it is tested at one operating frequency, with other port(s) appropriately terminated, to verify it has similar output characteristics as the fully tested port.

2.3.3 Radiated Emissions

The EUT is placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 8 of 48

2.4 Measurement Results Explanation Example

2.4.1 Radiated Emission Test Sites For Measurements From 9 kHz To 30 MHz

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-ane choic chamber, the measurements correspond to those obtained at an open-field test site.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

2.4.2 For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuation factor between EUT conducted port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly EUT RF output level.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非只有铅明,此数些结甲磺胺别对对格里名含,同时世缘里属是例如于。大数型土壤大公司电面连可,不可如必遏制。


除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd.



Page: 9 of 48

2.5 **Test Configuration**





2.6 **Control Unit(s)**

Conducted Emission Test Site: Conducted F								
EQUIPMENT TYPE MFR MODEL NUMBER SERIAL NUMBER LAST CAL. (mm/dd/yyyy) (mm/dd/y								
Notebook	Lenovo	T14	P0003332	N/A	N/A			
Adapter	AMIGO	AMS115- 1202000FU	N/A	N/A	N/A			
Test Kit	Waveshare	PL2303 USB UART Board	N/A	N/A	N/A			

Radiated Emission Test Site: SAC D							
FOLUPMENT TYPE MER MODEL NUMBER SERIAL NUMBER					CAL DUE. (mm/dd/yyyy)		
Notebook	Lenovo	L412	S0011357	N/A	N/A		
Adapter	AMIGO	AMS115- 1202000FU	N/A	N/A	N/A		
Test Kit	Waveshare	PL2303 USB UART Board	N/A	N/A	N/A		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司



Page: 10 of 48

SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.247(b)(1)	Peak Output Power	Compliant
§15.247(d) §15.209	Radiated Band Edge and Spurious Emission	Compliant

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 11 of 48

DESCRIPTION OF TEST MODES

4.1 Operated in 2400 ~ 2483.5MHz Band

2400~2483.5 MHz							
СН	Freq. (MHz)	СН	Freq. (MHz)	СН	Freq. (MHz)	СН	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司



Page: 12 of 48

4.2 The Worst Test Modes and Channel Details

- 1 The EUT has been tested under operating condition.
- 2 Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.
- 3 The field strength of radiated emission was measured as the EUT positioned in different orthogonal planes (E1/E2/H) based on actual usage of the EUT to pre-scan the emissions for determining the worst case scenario.
- 4 Investigation has been done on all the possible configurations for searching the worst case.

ANTNNA PORT CONDUCTED TEST						
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	PACKET TYPE		
	Peak Output Power					
	0 to 78	0,39,78	GFSK	DH5		
Bluetooth	0 to 78	0,39,78	π/4-DQPSK	2DH5		
	0 to 78	0,39,78	8-DPSK	3DH5		
MODE	AVAILABLE	TESTED	MODULATION	PACKET		
MODE	CHANNEL	CHANNEL	MODULATION	TYPE		
	TRANSMIT RAI	DIATED EMISSION TE	ST (BELOW 1 GHz)			
Bluetooth	0 to 78	39	GFSK	DH5		
TRANSMIT RADIATED EMISSION TEST (ABOVE 1 GHz)						
Bluetooth	0 to 78	0,39,78	GFSK,8-DPSK	DH5,3DH5		

Note: The field strength of radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for channel Low, Mid and High, the worst case position was reported.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非只有铅明,此数些结甲磺胺别对对格里名含,同时世缘里属是例如于。大数型土壤大公司电面连可,不可如必遏制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 13 of 48

MEASUREMENT UNCERTAINTY

Test Items	U	ncertair	nty
AC Power Line Conducted Emission	+/-	1.54	dB
Output Power measurement	+/-	0.97	dB
Emission Bandwidth	+/-	1.38	Hz
Conducted emission measurement	+/-	0.77	dB
Frequency Separation	+/-	1.48	Hz
Number of hopping frequency	+/-	1.48	Hz
Time of Occupancy	+/-	1.48	Hz
Temperature	+/-	0.6	°C
Humidity	+/-	3	%
DC / AC Power Source	+/-	1	%

Radiated Spurious Emission Measurement Uncertainty					
	+/-	1.89	dB	9kHz~30MHz	
Polarization: Vertical	+/-	4.1	dB	30MHz - 1000MHz	
Polarization: Vertical	+/-	3.37	dB	1GHz - 18GHz	
	+/-	3.83	dB	18GHz - 40GHz	
	+/-	1.89	dB	9kHz~30MHz	
Polarization: Horizontal	+/-	4.1	dB	30MHz - 1000MHz	
Polarization. Horizontal	+/-	3.37	dB	1GHz - 18GHz	
	+/-	3.83	dB	18GHz - 40GHz	
	+/-	2	dB	33GHz-50GHz	
	+/-	1.59	dB	50GHz-60GHz	
Radiated Spurious Emission	+/-	1.71	dB	60GHz-90GHz	
	+/-	1.64	dB	90GHz-140GHz	
	+/-	3.84	dB	140GHz-220GHz	

Note:

- 1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
- 2. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 14 of 48

MEASUREMENT EQUIPMENT USED

6.1 **Conducted Measurement**

Conducted Emission Test Site: Conducted F								
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.			
				(mm/dd/yyyy)	(mm/dd/yyyy)			
Attenuator	Marvelous	MVE2213-10	RF04	11/14/2024	11/13/2025			
Attenuator	Woken	WATT-218FS-10	RF12	11/14/2024	11/13/2025			
DC Block	PASTERNACK	PE8210	RF38	11/14/2024	11/13/2025			
Power Meter	Anritsu	ML2496A	2138005	09/25/2024	09/24/2025			
Power Sensor	Anritsu	MA2411B	1911395	09/25/2024	09/24/2025			
Power Sensor	Anritsu	MA2411B	1911396	09/25/2024	09/24/2025			
Spectrum Analyzer	KEYSIGHT	N9010B	MY63440390	02/13/2025	02/12/2026			
Test Software	SGS Taiwan	Radio Test	Ver.21	N.C.R	N.C.R			
rest software	565 TalWall	Software	VCI.ZI	14.0.11	14.0.11			

Radiated Measurement 6.2

	Radiated Emission Test Site: SAC D						
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER LAST CAL. (mm/dd/yyy		CAL DUE. (mm/dd/yyyy)		
Attenuator	Woken	WATT-218FS-10	RF17	11/14/2024	11/13/2025		
Broadband Antenna	SCHWARZBECK	VULB 9168	9168-617	12/17/2024	12/16/2025		
Coaxial Cable	EMCI+Huber Suhner	RG 214/U+EMC104- SM-SM- 500+SUCOFLEX 104+16+EMC105- SM-SM- 11000+EMC106- SM-SM-2300	W22.01+W21.01+1 50707+MY969/4+1 6+190825+150702	11/14/2024	11/13/2025		
High Pass Filter	Titan Microwave	T04H30001800070 S01	RF188	11/14/2024	11/13/2025		
Horn Antenna	Schwarzbeck	BBHA9120D	1341	05/30/2024	05/29/2025		
Horn Antenna	Schwarzbeck	BBHA9170	184	12/20/2024	12/19/2025		
Pre-Amplifier	EMC Instruments	EMC12630SE	980273	11/14/2024	11/13/2025		
Pre-Amplifier	EMC Instruments	EMC184045SEE	980881	11/14/2024	11/13/2025		
Pre-Amplifier	EMC Instruments	EMC9135	980234	11/14/2024	11/13/2025		
Spectrum Analyzer	KEYSIGHT	N9010A	MY54510568	10/16/2024	10/15/2025		
H-Loop Near Field Antenna	LANGER EMV- Technik	LF-R 400	02-1597	N.C.R	N.C.R		
Test Software	audix	е3	E3 20923 SGS Ver.9 (C)	N.C.R	N.C.R		

NOTE: N.C.R refers to Not Calibrated Required.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.




Page: 15 of 48

PEAK OUTPUT POWER MEASUREMENT

7.1 Standard Applicable

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, The Limit: 1Watt. For all other frequency hopping systems in the 2400 2483.5MHz band: The Limit: 0.125 Watts. The power limit for 1Mbps is 1watt, and 2Mbps, 3Mbps and AFH mode are 0.125 watts.

7.2 **Test Setup**



7.3 **Measurement Procedure:**

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. The testing follows ANSI C63.10 Measurement Guidelines.
- 3. Duty cycle of test signal is < 98 %, duty factor shall be considered.
- 4. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter or spectrum. (Max Hold, Detector = Peak, RBW >= 20dB bandwidth)
- 5. Record the max. reading.
- 6. Repeat above procedures until all default test channel is completed.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.

台灣檢驗科技股份有限公司



Page: 16 of 48

Peak & Average Power Measurement Result

Mode	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) =10*log (1/Duty Cycle)
DH5	76.80	1.15
2DH5	76.80	1.15
3DH5	76.80	1.15

1M BR mode (Peak):

СН	Freq. (MHz)	Power Setting	Peak Output Power (dBm)	Output Power (mW)	Limit (mW)
0	2402	5	5.68	3.698	1000
39	2441	5	5.74	3.750	1000
78	2480	5	5.75	3.758	1000

1M BR mode (Average):

	(* tro.ugo/.				
СН	Freq. (MHz)	Power Setting	Avg. Output Power (dBm)	Output Power (mW)	Limit (mW)
0	2402	5	4.95	3.123	1000
39	2441	5	4.97	3.138	1000
78	2480	5	5.03	3.182	1000

2M EDR mode (Peak):

СН	Freq. (MHz)	Power Setting	Peak Output Power (dBm)	Output Power (mW)	Limit (mW)
0	2402	4	5.44	3.499	125
39	2441	4	5.58	3.614	125
78	2480	4	5.63	3.656	125

2M EDR mode (Average):

СН	Freq. (MHz)	Power Setting	Avg. Output Power (dBm)	Output Power (mW)	Limit (mW)
0	2402	4	2.32	1.705	125
39	2441	4	2.35	1.716	125
78	2480	4	2.38	1.728	125

3M EDR mode (Peak):

СН	Freq. (MHz)	Power Setting	Peak Output Power (dBm)	Output Power (mW)	Limit (mW)
0	2402	4	5.46	3.516	125
39	2441	4	5.62	3.648	125
78	2480	4	5.66	3.681	125

3M EDR mode (Average):

СН	Freq. (MHz)	Power Setting	Avg. Output Power (dBm)	Output Power (mW)	Limit (mW)
0	2402	4	2.40	1.736	125
39	2441	4	2.42	1.744	125
78	2480	4	2.37	1.724	125

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 17 of 48

RADIATED BANDEDGE AND SPURIOUS EMISSION MEASUREMENT

8.1 Standard Applicable

8.1.1 **Duty Cycle Correction Factor**

According to 15. 35(c), the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification.

8.1.2 Spurious Emission

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands must also comply with the §15.209 and limit as below. And according to §15.33(a) (1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

Frequency (MHz)	Field strength (microvolts/meter)	Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

t (886-2) 2299-3279

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.




Page: 18 of 48




Test Setup

Duty Cycle Correction Factor 8.2.1




8.2.2 **Radiated Emission**

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz.



(B) Radiated Emission Test Set-Up, Frequency From 30MHz to 1000MHz.



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd.

台灣檢驗科技股份有限公司



Page: 19 of 48

(C) Radiated Emission Test Set-Up, Frequency Above 1 GHz.



8.3 **Measurement Procedure**

8.3.1 **Duty Cycle Correction Factor**

- 1. Adjust and configure any EUT switches, controls, or input data streams to ensure that the EUT is transmitting or encoded to obtain the "worst-case" pulse ON time.
- 2. The testing follows ANSI C63.10:2013.
- 3. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 4. Set center frequency of spectrum analyzer = operating frequency.
- 5. Set the spectrum analyzer as RBW, VBW=1MHz, 3MHz, Span = 0Hz, Detector = Peak, Adjust Sweep=100ms.
- 6. Repeat above procedures until all frequency of the interest measured were complete.

8.3.2 Radiated Emission

- The testing follows the Measurement Procedure of ANSI C63.10:2013.
- 2. The EUT was placed on a turn table with 0.8m for frequency< 1GHz and 1.5m for frequency> 1GHz above ground plane.
- 3. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 4. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 5. Set the spectrum analyzer as RBW=100 kHz and VBW=300 kHz for Peak Detector (PK) at frequency between 30MHz and 1 GHz.
- 6. Use receiver mode as RBW=120 kHz for Quasi-peak (QP) at frequency between 30MHz and 1 GHz.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號

SGS Taiwan Ltd.

www.sgs.com.tw



Page: 20 of 48

- 7. Set the spectrum analyzer as RBW=1 MHz, VBW=3 MHz for Maximum Emission Measurements at frequency above 1 GHz.
- 8. According to C63.10:2013 Section 7.5 Procedure for determining the average value of pulsed emissions with duty cycle correction factor 20 log (Ton/100ms).
- 9. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 10. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 11. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 12. Repeat above procedures until all default test channel measured were complete.

Field Strength Calculation 8.4

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

The limit of the emission level is expressed in dBuV/m, which converts 20*log(uV/m)

Actual FS(dB μ V/m) = SPA. Reading level(dB μ V) + Factor(dB)

Factor(dB) = Antenna Factor(dB/m) + Cable Loss(dB) - Pre Amplifier Gain(dB)

Average value(dBµV/m)=Peak Actual FS(dBµV/m)+ Duty Cycle Correction Factor(dB)

Duty Cycle Correction Factor(dB) = $20 \log (T_{on}/100 \text{ ms})$

8.5 Test Results of Radiated Spurious Emissions form 9 kHz to 30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit per 15.31(o) was not reported.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 21 of 48

Measurement Result:

8.6.1 **Duty Cycle Correction Factor**

Bluetooth 1M

Time ON of 100ms: 2.600 Duty Cycle=2.6ms / 100ms= 0.026

Duty Cycle correction factor=20 LOG 0.026 = -31.7 dB

Bluetooth 3M

Time ON of 100ms: 5.800 Duty Cycle=5.8ms / 100ms= 0.058

Duty Cycle correction factor=20 LOG 0.058 = -24.73 dB

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.


SGS Taiwan Ltd.

台灣檢驗科技股份有限公司



Page: 22 of 48

8.6.2 **Duty Cycle test plot**



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd



Page: 23 of 48

Bandedge Result


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode Test Date :2025-05-14 :BR

:2402 MHz :21.6°C/67% Test Frequency Temp./Humi.

Test Mode :Bandedge Antenna Pol. :Vertical

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
2333.21	Peak	50.60	2.94	53.54	74.00	-20.46
2333.21	Average	-	-	21.84	54.00	-32.16
2402.00	Peak	93.84	2.96	96.80	-	-
2402.00	Average	-	-	65.10	-	-
2499.26	Peak	50.53	3.02	53.55	74.00	-20.45
2499.26	Average	-	-	21.85	54.00	-32.15

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 24 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :BR Test Date :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6℃/67%

Test Mode :Bandedge Antenna Pol. :Horizontal

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
2314.13	Peak	51.27	3.11	54.38	74.00	-19.62
2314.13	Average	-	-	22.68	54.00	-31.32
2402.00	Peak	92.83	2.96	95.79	-	-
2402.00	Average	-	-	64.09	-	-
2488.44	Peak	51.22	2.99	54.21	74.00	-19.79
2488.44	Average	-	-	22.51	54.00	-31.49

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除业只有约明,此程生处用度影响经少锋中乌害,同时此类早度原列的主,大型企业等等。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 25 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :BR **Test Date** :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6°C/67%

Test Mode Antenna Pol. :Bandedge :Vertical

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
2317.28	Peak	51.24	3.11	54.35	74.00	-19.65
2317.28	Average	-	-	22.65	54.00	-31.35
2480.00	Peak	86.71	2.97	89.68	-	-
2480.00	Average	-	-	57.98	-	-
2497.68	Peak	50.41	3.02	53.43	74.00	-20.57
2497.68	Average	-	-	21.73	54.00	-32.27

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 26 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :BR Test Date :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6℃/67%

Test Mode :Bandedge Antenna Pol. :Horizontal

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBμV	dB	dBµV/m	dBµV/m	dB
2322.79	Peak	50.35	3.07	53.42	74.00	-20.58
2322.79	Average	-	-	21.73	54.00	-32.27
2480.00	Peak	82.73	2.97	85.70	-	-
2480.00	Average	-	-	54.00	-	-
2498.27	Peak	50.40	3.02	53.42	74.00	-20.58
2498.27	Average	-	-	21.72	54.00	-32.28

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除此只有验明,此就是结果既是为键与合善,同时此键与原况如何工,才就是主领于八司事而统可,不可如以推制。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 27 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M **Test Date** :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6°C/67%

Test Mode :Vertical :Bandedge Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
						_
2338.13	Peak	50.54	2.96	53.50	74.00	-20.50
2338.13	Average	-	-	28.77	54.00	-25.23
2402.00	Peak	94.48	2.96	97.44	-	-
2402.00	Average	-	-	72.71	-	-
2491.19	Peak	50.81	3.00	53.81	74.00	-20.19
2491.19	Average	-	-	29.08	54.00	-24.92

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 28 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :EDR 3M Test Date :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6°C/67%

Test Mode :Bandedge Antenna Pol. :Horizontal

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
2351.12	Peak	51.00	2.98	53.98	74.00	-20.02
2351.12	Average	-	-	29.25	54.00	-24.75
2402.00	Peak	90.12	2.96	93.08	-	-
2402.00	Average	-	-	68.35	-	-
2494.14	Peak	50.49	3.01	53.50	74.00	-20.50
2494.14	Average	-	-	28.77	54.00	-25.23

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除业只有约明,此程生处用度影响经少锋中乌害,同时此类早度原列的主,大型企业等等。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 29 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :EDR 3M Test Date :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6℃/67%

Test Mode :Bandedge Antenna Pol. :Vertical

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
2363.51	Peak	50.84	2.86	53.70	74.00	-20.30
2363.51	Average	-	-	28.97	54.00	-25.03
2480.00	Peak	85.43	2.97	88.40	-	-
2480.00	Average	-	-	63.67	-	-
2495.91	Peak	50.67	3.01	53.68	74.00	-20.32
2495.91	Average	-	-	28.95	54.00	-25.05

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除业只有约明,此程生处用度影响经少锋中乌害,同时此类早度原列的主,大型企业等等。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 30 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M **Test Date** :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6°C/67%

Test Mode :Bandedge Antenna Pol. :Horizontal

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dΒμV/m	dBμV/m	dB
2337.15	Peak	50.72	2.96	53.68	74.00	-20.32
2337.15	Average	-	-	28.95	54.00	-25.05
2480.00	Peak	78.88	2.97	81.85	-	-
2480.00	Average	-	-	57.12	-	-
2498.27	Peak	50.24	3.02	53.26	74.00	-20.74
2498.27	Average	-	-	28.53	54.00	-25.47

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 31 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :BR Hopping Test Date :2025-05-14

Test Frequency :2402~2480 MHz Temp./Humi. :21.6°C/67%

Test Mode :Bandedge Antenna Pol. :Vertical

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
2344.43	Peak	51.38	2.97	54.35	74.00	-19.65
2344.43	Average	-	-	22.65	54.00	-31.35
2496.31	Peak	50.52	3.01	53.53	74.00	-20.47
2496.31	Average	-	-	21.83	54.00	-32.17

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 险非只有的明,此想些结果做新测验之缘具负责,同时此模具做是例如于。木型生主领水公司事面纯可,不可可以推测。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 32 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :BR Hopping **Test Date** :2025-05-14

Test Frequency :2402~2480 MHz Temp./Humi. :21.6°C/67%

Test Mode Antenna Pol. :Horizontal :Bandedge

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBμV	dB	dBµV/m	dBµV/m	dB
2371.77	Peak	51.47	2.82	54.29	74.00	-19.71
2371.77	Average	-	-	22.59	54.00	-31.41
2500.04	Peak	50.98	3.02	54.00	74.00	-20.00
2500.04	Average	-	-	22.30	54.00	-31.70

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 33 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M Hopping **Test Date** :2025-05-14

Test Frequency :2402~2480 MHz Temp./Humi. :21.6°C/67%

Test Mode Antenna Pol. :Vertical :Bandedge

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
2352.49	Peak	51.08	2.97	54.05	74.00	-19.95
2352.49	Average	-	-	29.32	54.00	-24.68
2499.65	Peak	49.91	3.02	52.93	74.00	-21.07
2499.65	Average	-	-	28.20	54.00	-25.80

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 34 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M Hopping **Test Date** :2025-05-14

Test Frequency :2402~2480 MHz Temp./Humi. :21.6°C/67%

Test Mode Antenna Pol. :Horizontal :Bandedge

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
2348.36	Peak	50.02	2.97	52.99	74.00	-21.01
2348.36	Average	-	-	28.26	54.00	-25.74
2492.57	Peak	49.74	3.00	52.74	74.00	-21.26
2492.57	Average	-	-	28.01	54.00	-25.99

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 35 of 48

Radiated Spurious Emission


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode Test Date :2025-05-14

Test Frequency :2441 MHz Temp./Humi. :21.6°C/67%

Test Mode Antenna Pol. :Vertical :Tx

EUT Pol :E2 Plane :Temo Chen Engineer



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
					_
Peak	47.58	-17.74	29.84	40.00	-10.16
Peak	49.02	-21.67	27.35	43.50	-16.15
Peak	48.26	-13.57	34.69	46.00	-11.31
Peak	45.71	-12.25	33.46	46.00	-12.54
Peak	40.99	-6.05	34.94	46.00	-11.06
QP	43.50	-4.12	39.38	54.00	-14.62
	Mode PK/QP/AV Peak Peak Peak Peak Peak	Mode PK/QP/AV Reading Level dBµV Peak 47.58 Peak 49.02 Peak 48.26 Peak 45.71 Peak 40.99	Mode PK/QP/AV Reading Level dBμV dB Peak 47.58 -17.74 Peak 49.02 -21.67 Peak 48.26 -13.57 Peak 45.71 -12.25 Peak 40.99 -6.05	Mode PK/QP/AV Reading Level dBμV FS dBμV/m Peak 47.58 -17.74 29.84 Peak 49.02 -21.67 27.35 Peak 48.26 -13.57 34.69 Peak 45.71 -12.25 33.46 Peak 40.99 -6.05 34.94	Mode PK/QP/AV Reading Level dBμV FS dBμV/m @3m dBμV/m Peak 47.58 -17.74 29.84 40.00 Peak 49.02 -21.67 27.35 43.50 Peak 48.26 -13.57 34.69 46.00 Peak 45.71 -12.25 33.46 46.00 Peak 40.99 -6.05 34.94 46.00

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd. 台灣檢驗科技股份有限公司



Page: 36 of 48


Report Number Test Site :SAC D :TERF2504001583E2

Operation Mode :BR **Test Date** :2025-05-14

Test Frequency :2441 MHz Temp./Humi. :21.6°C/67%

Test Mode Antenna Pol. :Horizontal :Tx

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
35.82	Peak	47.68	-18.92	28.76	40.00	-11.24
197.81	Peak	51.00	-19.63	31.37	43.50	-12.13
593.57	Peak	40.66	-9.54	31.12	46.00	-14.88
866.14	Peak	42.54	-5.90	36.64	46.00	-9.36
924.34	Peak	41.17	-4.84	36.33	46.00	-9.67
990.30	QP	44.90	-4.12	40.78	54.00	-13.22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 37 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :BR **Test Date** :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6°C/67%

Test Mode :Tx :Vertical Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
4804.00	Peak	35.40	9.47	44.87	74.00	-29.13
4804.00	Average	-	-	13.17	54.00	-40.83
7206.00	Peak	32.74	16.80	49.54	74.00	-24.46
7206.00	Average	-	-	17.84	54.00	-36.16

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 38 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :BR **Test Date** :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6°C/67%

Test Mode :Horizontal :Tx Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
4804.00	Peak	34.85	9.47	44.32	74.00	-29.68
4804.00	Average	-	-	12.62	54.00	-41.38
7206.00	Peak	32.70	16.80	49.50	74.00	-24.50
7206.00	Average	-	-	17.80	54.00	-36.20

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 39 of 48

Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :BR Test Date :2025-05-14

Test Frequency :2441 MHz Temp./Humi. :21.6°C/67%

Test Mode :Tx Antenna Pol. :Vertical

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBμV	dB	dBµV/m	dΒμV/m	dB
						_
4882.00	Peak	34.60	9.54	44.14	74.00	-29.86
4882.00	Average	-	-	12.44	54.00	-41.56
7323.00	Peak	32.58	17.44	50.02	74.00	-23.98
7323.00	Average	-	-	18.32	54.00	-35.68

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 40 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :BR **Test Date** :2025-05-14

Test Frequency :2441 MHz Temp./Humi. :21.6°C/67%

Test Mode :Horizontal :Tx Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
4882.00	Peak	34.75	9.54	44.29	74.00	-29.71
4882.00	Average	-	-	12.59	54.00	-41.41
7323.00	Peak	33.34	17.44	50.78	74.00	-23.22
7323.00	Average	-	-	19.08	54.00	-34.92

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 41 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :BR Test Date :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6℃/67%

Test Mode :Tx Antenna Pol. :Vertical

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
4960.00	Peak	34.94	9.91	44.85	74.00	-29.15
4960.00	Average	-	-	13.15	54.00	-40.85
7440.00	Peak	32.49	17.73	50.22	74.00	-23.78
7440.00	Average	-	-	18.52	54.00	-35.48

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 42 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :BR **Test Date** :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6°C/67%

Test Mode :Tx Antenna Pol. :Horizontal

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
4960.00	Peak	35.19	9.91	45.10	74.00	-28.90
4960.00	Average	-	-	13.40	54.00	-40.60
7440.00	Peak	32.42	17.73	50.15	74.00	-23.85
7440.00	Average	-	-	18.45	54.00	-35.55

Average Duty Cycle Factor=-31.70 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 43 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M **Test Date** :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6°C/67%

Test Mode :Vertical :Tx Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
						_
4804.00	Peak	35.64	9.47	45.11	74.00	-28.89
4804.00	Average	-	-	20.38	54.00	-33.62
7206.00	Peak	32.05	16.80	48.85	74.00	-25.15
7206.00	Average	-	-	24.12	54.00	-29.88

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 44 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :EDR 3M Test Date :2025-05-14

Test Frequency :2402 MHz Temp./Humi. :21.6℃/67%

Test Mode :Tx Antenna Pol. :Horizontal

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dΒμV/m	dB
4804.00	Peak	35.25	9.47	44.72	74.00	-29.28
4804.00	Average	-	-	19.99	54.00	-34.01
7206.00	Peak	31.95	16.80	48.75	74.00	-25.25
7206.00	Average	-	-	24.02	54.00	-29.98

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 45 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M **Test Date** :2025-05-14

:2441 MHz **Test Frequency** Temp./Humi. :21.6°C/67%

Test Mode :Vertical :Tx Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
						_
4882.00	Peak	35.76	9.54	45.30	74.00	-28.70
4882.00	Average	-	-	20.57	54.00	-33.43
7323.00	Peak	33.84	17.44	51.28	74.00	-22.72
7323.00	Average	-	-	26.55	54.00	-27.45

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 46 of 48


Report Number :TERF2504001583E2 Test Site :SAC D

Operation Mode :EDR 3M Test Date :2025-05-14

Test Frequency :2441 MHz Temp./Humi. :21.6℃/67%

Test Mode :Tx Antenna Pol. :Horizontal

EUT Pol :E2 Plane Engineer :Temo Chen



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
4882.00	Peak	35.30	9.54	44.84	74.00	-29.16
4882.00	Average	-	-	20.11	54.00	-33.89
7323.00	Peak	33.18	17.44	50.62	74.00	-23.38
7323.00	Average	-	-	25.89	54.00	-28.11

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除业只有约明,此程生处用度影响经少锋中乌害,同时此类早度原列的主,大型企业等等。

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留的天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 47 of 48


Report Number Test Site :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M **Test Date** :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6°C/67%

Test Mode :Vertical :Tx Antenna Pol.

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
4960.00	Peak	35.88	9.91	45.79	74.00	-28.21
4960.00	Average	-	-	21.06	54.00	-32.94
7440.00	Peak	32.52	17.73	50.25	74.00	-23.75
7440.00	Average	-	-	25.52	54.00	-28.48

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.



Page: 48 of 48


Test Site Report Number :TERF2504001583E2 :SAC D

Operation Mode :EDR 3M **Test Date** :2025-05-14

Test Frequency :2480 MHz Temp./Humi. :21.6°C/67%

Test Mode :Tx Antenna Pol. :Horizontal

EUT Pol :E2 Plane :Temo Chen Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
4960.00	Peak	35.66	9.91	45.57	74.00	-28.43
4960.00	Average	-	-	20.84	54.00	-33.16
7440.00	Peak	32.63	17.73	50.36	74.00	-23.64
7440.00	Average	-	-	25.63	54.00	-28.37

Average Duty Cycle Factor=-24.73 (dB)

Average Level= Peak Level+ Duty Cycle Factor

~ End of Report ~

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Taiwan Ltd.