



Test Report No.:  
FCC2025-0007-RF1

## TEST REPORT

**FCC ID** : 2BG9T-TCLSMARTD2B  
**Applicant** : Shenzhen TCL Smart Home Technology Co., Ltd  
**Product Name** : TCL D2 Series Smart Door Lock  
**Model No.** : D2 Pro,D2X Pro,D2XX Pro,D2 Pro X

**CVC Testing Technology Co., Ltd.**

<b>Product Name</b>	TCL D2 Series Smart Door Lock					
<b>Type/Model</b>	D2 Pro,D2X Pro,D2XX Pro,D2 Pro X	<b>Trade Mark</b>	TCL			
<b>Applicant</b>	Shenzhen TCL Smart Home Technology Co., Ltd					
<b>Applicant Address</b>	7/F,TCL G1 Building. TCL International E City, No.1001 Zhongshan Yuan Road, Nanshan					
<b>Manufacturer</b>	Shenzhen TCL Smart Home Technology Co., Ltd					
<b>Manufacturer Address</b>	7/F,TCL G1 Building. TCL International E City, No.1001 Zhongshan Yuan Road, Nanshan					
<b>Factory</b>	Guangdong Yongding Technology Co., Ltd					
<b>Factory Address</b>	No.10 Chenglong Road, Qianlong Village, Sanxiang Town, Zhongshan City, Guangdong Province					
<b>Sample Identification</b>	1-1	<b>Test Item</b>	See page 9			
<b>Tested According To</b>	FCC CFR47 Part 15C Radio Frequency Devices ANSI C63.10-2020/Cor1-2023					
<b>Receiving Date</b>	2025-03-25	<b>Completing Date</b>	2025-04-26			
<b>Test conclusion</b>	<p>The equipment under test was found to comply with the requirements of the standards applied.</p> <p>Final Verdict: Pass.</p> <p>Seal of CVC</p> <p>Date of issue: <b>2025-05-13</b></p>					
Abbreviations: / Pass= passed Fail= failed N/A= not applicable						
This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of <b>CVC</b> .						

Approved by:

Chen Huawen



Reviewed by:

Xu Zhenfei



Tested by:

Lu Weiji



## TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	4
<b>1. GENERAL PRODUCT INFORMATION .....</b>	<b>5</b>
1.1 GENERAL INFORMATION .....	5
<b>2. TEST SITES .....</b>	<b>6</b>
2.1 TEST FACILITIES .....	6
2.2 DESCRIPTION OF NON-STANDARD METHOD AND DEVIATIONS .....	6
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS .....	6
<b>3. TEST CONFIGURATION .....</b>	<b>7</b>
3.1 TEST MODE .....	7
<b>4. SUMMARY OF MEASUREMENT RESULTS .....</b>	<b>8</b>
<b>5. MEASUREMENT PROCEDURE .....</b>	<b>9</b>
5.1 CONDUCTED EMISSION .....	9
5.2 RADIATED EMISSION .....	13
5.3 FREQUENCY TOLERANCE .....	21
5.4 20DB BANDWIDTH MEASUREMENT .....	23
<b>6. APPENDIX A .....</b>	<b>25</b>

**RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FCC2025-0007-RF3	Original release	May.13,2025

# 1. General Product Information

## 1.1 General information

Product Name	TCL D2 Series Smart Door Lock	
Model No.	D2 Pro	
Additional model	D2X Pro,D2XX Pro,D2 Pro X	
Power Supply	Rated voltage	DC 5.0V
	Battery voltage	DC 3.6V
Serial Number(SN)	/	
Hardware Version	V1.1	
Software Version	V7.1	
specific power settings	Default	
Antenna Type	Internal Antenna	
Antenna Connector	A permanently attached antenna	
Antenna Gain	0.0 dBi (provided by client)	
Beamforming gain	Unsupported (provided by client)	
Frequency Range	13.110-14.010MHz	
Channel Number	1 Channel	
Type of Modulation	ASK	
Max. Power	-47.35dBm	
Operate Temp.Range	-20°C~+70°C	

**Note:**

1. The information of the EUT is declared by the manufacturer.
2. The laboratory is not responsible for the product technical specification provided by the client.
3. EUT photo refer to report (Report NO.:FCC2025-0007-EUT).
4. The EUT have SISO function, provides 1 completed transmitter and 1 receiver.
5. All the models are electrical identical including the same software parameter and hardware design (i.e., circuit design, PCB Layout, RF module/circuit, antenna type(s) and antenna location, components on PCB, etc.,), same mechanical structure and design (including product enclosure, materials, etc.,), the only difference is the model name, color, package.

No.	Model	Difference	Remarks
1	D2 Pro	1. Only the appearance color difference is different, include Dark grey、Brushed Nickel、Obsidian Black、Aged Bronze.	Inspection model
2	D2X Pro	2. Only the printing style/label on the surface of the package is different, the product inside the package is the same.	Coverage model
3	D2XX Pro	3. D2X,D2XX, Pro X, the "X" is a number from 0~9, or is an alphabet in A~Z.	Coverage model
4	D2 Pro X		Coverage model

6. All the tests carried out on model D2 Pro.

## 2. Test Sites

### 2.1 Test Facilities

The tests and measurements refer to this report were performed by RF testing Lab. of CVC Testing Technology Co., Ltd.

Add.: No.3, Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, Guangdong, 510663, People's Republic of China

Telephone : +86-20-32293888

Fax : +86-20-32293889

FCC(Test firm designation number: CN1282)

IC(Test firm CAB identifier number: CN0103)

CNAS(Test firm designation number: L0095)

### 2.2 Description of Non-standard Method and Deviations

The testing and measurement methods used in this report are applied by all standard methods. Not any non-standard method or deviation from the used standards was used.

### 2.3 List of Test and Measurement Instruments

Refer to **Appendix A**.

## 3. Test Configuration

### 3.1 Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Test Mode	Antenna Delivery	Test Channel
Transmitting	1TX	13.56MHz

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate and different channels. Preliminary tests have been done on all the configurations for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates and channels are shown as following table.

Test Mode	Data Rate		
	Antenna 1	Antenna 2	MIMO
Transmitting	✓	/	/

Test Items	Test Antenna	Test Mode	Test Channel
Conducted Emissions	Antenna 1	Transmitting	13.56MHz
The field strength of Fundamental Emission	Antenna 1	Transmitting	13.56MHz
Radiated Emissions	Antenna 1	Transmitting	13.56MHz
Frequency tolerance	Antenna 1	Transmitting	13.56MHz
20dB Bandwidth	Antenna 1	Transmitting	13.56MHz

## 4. Summary of measurement results

Summary of measurements of results	Clause in FCC rules	Verdict	Note
Conducted Emissions	15.207	PASS	/
The field strength of Fundamental Emission	FCC 15.225(a)&(b)&(c)	PASS	/
Radiated Emissions	FCC 15.225 (d) FCC 15.209	PASS	/
Frequency tolerance	FCC 15.225 (e)	PASS	/
20dB Bandwidth	FCC 15.215 (c)	PASS	/
Antenna Requirement	15.203	PASS	See note 1

Note 1: According to 15.203, it is considered sufficient to comply with the provisions of this section.

## 5. Measurement procedure

### 5.1 Conducted Emission

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.3kPa

Method of Measurement:

The EUT was setup according to ANSI C63.10-2020/Cor1-2023 for compliance to FCC 47CFR 15.247 requirements. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs) Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.

The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.


Limits:

Frequency (MHz)	Conducted Limits(dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46*
0.5 - 5	56	46
5 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

## Test Setup:



## Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

### Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Level =Reading + Factor.

## Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .  $U = 3.12$  dB.


## Test Results:

During the test, the Conducted Emission from 150kHz to 30MHz was performed in all modes with all channels, and all antennas. Transmitting, 13.56MHz, Antenna 1 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.


Radiates Emission	150k~30MHz
Power Line	L
Test channel	Worst-Case

### Suspected List

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.542	---	31.6	46.0	14.4	L1	20.3
0.717	---	32.3	46.0	13.7	L1	20.3
2.085	44.3	---	56.0	11.7	L1	20.7
2.222	---	35.5	46.0	10.5	L1	20.8
2.243	45.1	---	56.0	10.9	L1	20.8
2.704	43.7	---	56.0	12.3	L1	20.9



Radiates Emission	150k~30MHz					
Power Line	N					
Test channel	Worst-Case					
<b>Suspected List</b>						
Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.159	47.9	---	65.5	17.7	N	20.1
0.200	44.8	---	63.6	18.8	N	20.2
0.238	42.0	---	62.2	20.2	N	20.2
1.894	---	28.7	46.0	17.3	N	20.6
3.109	---	29.9	46.0	16.1	N	21.1
4.063	---	30.3	46.0	15.7	N	21.5



## 5.2 Radiated Emission

Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.3kPa

Method of Measurement:

The EUT was setup and tested according to ANSI C63.10-2020/Cor1-2023.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from Antenna to the EUT was 3 meters.

The Antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the Antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2020/Cor1-2023 on radiated measurement.

The resolution bandwidth below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

The frequency range from 30MHz to 10th harmonic is checked.

Note: When doing emission measurement above 1GHz, the horn Antenna will be bended down a little (as horn Antenna has the narrow beamwidth) in order to keeping the Antenna in the “cone of radiation” of EUT.

The 3dB beamwidth is 10~60 degrees for H-plane and 10~90 degrees for E-plane.

Limits:

§15.225

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters. (124.00dB $\mu$ V/m@3m)

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. (90.50dB $\mu$ V/m@3m)

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters. (80.50dB $\mu$ V/m@3m)


(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).


Frequency	Limit ( $\mu$ V/m )	Limit (dB $\mu$ V/m @3m)	Remark
0.009MHz-0.490MHz	2400/F(kHz)@300m	20lg(24000000/F(kHz))	Quasi-peak Level
0.490MHz~1.705MHz	24000/F(kHz)@30m	20lg(2400000/F(kHz))	Quasi-peak Level
1.705MHz~30.0MHz	30@30m	69.54	Quasi-peak Level
30MHz-88MHz	100@3m	40.0	Quasi-peak Level
88MHz-216MHz	150@3m	43.5	Quasi-peak Level
216MHz-960MHz	200@3m	46.0	Quasi-peak Level
960MHz-1GHz	500@3m	54.0	Quasi-peak Level
Above 1GHz	500@3m	54.0	Average Level
	5000@3m	74.0	Peak Level

## Test Setup:

Below 30MHz Test Setup:



Below 1GHz Test Setup:



## Measurement Data:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Level =Reading - Factor

Factor = Preamplifier Factor – Antenna Factor–Cable Loss

## Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .


Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.19 dB
200MHz-1GHz	3.63 dB
Above 1GHz	3.68 dB

## Test Results:

### Result of The field strength of Fundamental Emission

During the test, the Radiates Emission from 9kHz to 1GHz was performed in NFC all modes with all channels and all antennas. Transmitting, 13.56MHz, Antenna 1, X Polarity are selected as the worst condition. The test data of the worst-case condition was recorded in this report.


Test channel	13.56MHz								
Polarity	X								
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/Fail
13.0172	20.94	13.83	34.77	69.85	35.08	PK	100	77	PASS
13.5588	20.98	26.87	47.85	124.00	76.15	PK	100	245	PASS
13.8403	20.99	13.52	34.51	80.50	45.99	PK	100	193	PASS
14.2839	21.00	13.48	34.48	69.50	35.02	PK	100	159	PASS
<b>Final Data List</b>									
Frequency [MHz]	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail		
13.0172	20.94	33.87	69.85	35.98	180	77	PASS		
13.5588	20.98	46.95	124.00	77.05	280	245	PASS		
13.8403	20.99	33.53	80.50	46.97	129	193	PASS		
14.2839	21.00	33.68	69.50	35.82	325	159	PASS		




## Result of Radiated Emissions

During the test, the Radiates Emission from 9kHz to 1GHz was performed in NFC all modes with all channels and all antennas. Transmitting, 13.56MHz, Antenna 1 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.


Radiates Emission	9k~30M								
Test channel	13.56MHz								
Polarity	X								
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/Fail
0.6106	20.52	13.77	34.29	71.89	37.60	PK	100	224	PASS
4.8286	20.79	14.96	35.75	69.50	33.75	PK	100	189	PASS
13.5588	20.98	26.87	47.85	69.50	21.65	PK	100	245	PASS
22.7326	20.63	13.88	34.51	69.50	34.99	PK	100	198	PASS
<b>Final Data List</b>									
Frequency [MHz]	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail		
0.6106	20.52	33.63	71.89	38.26	157	224	PASS		
4.8286	20.79	35.09	69.50	34.41	350	189	PASS		
13.5588	20.98	47.19	69.50	22.31	160	245	PASS		
22.7326	20.63	33.53	69.50	35.97	210	198	PASS		



Radiates Emission	30M~1G								
Test channel	13.56MHz								
Polarity	Horizontal								
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/Fail
51.6332	12.95	8.46	21.41	40.00	18.59	PK	100	330	PASS
102.0782	11.80	8.27	20.07	43.50	23.43	PK	100	20	PASS
188.4168	12.59	8.73	21.32	43.50	22.18	PK	100	240	PASS
<b>Final Data List</b>									
Frequency [MHz]	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail		
51.6332	12.95	20.16	40.00	19.84	167	330	PASS		
102.0782	11.80	18.82	43.50	24.68	326	20	PASS		
188.4168	12.59	20.07	43.50	23.43	281	240	PASS		



Radiates Emission	30M~1G								
Test channel	13.56MHz								
Polarity	Vertical								
<b>Suspected List</b>									
Frequency [MHz]	Factor [dB]	Reading [dB $\mu$ V/m]	Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Detector	Height [cm]	Angle deg	Pass/Fail
50.372	13.06	7.90	20.96	40.00	19.04	PK	100	10	PASS
100.138	11.85	8.46	20.31	43.50	23.19	PK	100	140	PASS
365.1685	17.06	9.89	26.95	46.00	19.05	PK	100	20	PASS
<b>Final Data List</b>									
Frequency [MHz]	Factor [dB]	QP Value [dB $\mu$ V/m]	QP Limit [dB $\mu$ V/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pass/Fail		
50.372	13.06	19.89	40.00	20.11	319	10	PASS		
100.138	11.85	19.10	43.50	24.40	287	140	PASS		
365.1685	17.06	25.74	46.00	20.26	162	20	PASS		



## 5.3 FREQUENCY TOLERANCE


Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.3kPa

Method of Measurement:

- a. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step c) and d) with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

Test Setup:



### LIMITS OF FREQUENCY TOLERANCE

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  (100ppm) of the operating frequency over a temperature variation of -20 degrees to + 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 936$  Hz.

## Test Results:

FREQUEMCY STABILITY VERSUS TEMP.												
TEMP. (°C)	POWER SUPPLY (V)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE		Limit (ppm)	PASS/ FAIL	
		Measured Frequency (MHz)	Frequency Drift ppm	Measured Frequency (MHz)	Frequency Drift ppm	Measured Frequency (MHz)	Frequency Drift ppm	Measured Frequency (MHz)	Frequency Drift ppm			
		(MHz)	ppm	(MHz)	ppm	(MHz)	ppm	(MHz)	ppm			
50	3.6	13.5600	2.4540	13.5600	3.1854	13.5600	2.2246	13.5600	2.9046	100	PASS	
40	3.6	13.5600	2.6441	13.5600	2.5001	13.5600	3.5294	13.5600	2.9559	100	PASS	
30	3.6	13.5600	2.2439	13.5600	3.3813	13.5600	3.2690	13.5600	2.8677	100	PASS	
20	3.6	13.5600	2.8979	13.5600	2.3324	13.5600	2.7931	13.5600	2.8182	100	PASS	
10	3.6	13.5600	3.4670	13.5600	3.1249	13.5600	3.3010	13.5600	3.2029	100	PASS	
0	3.6	13.5600	2.8280	13.5600	3.4993	13.5600	3.5236	13.5600	2.7027	100	PASS	
-10	3.6	13.5600	3.1688	13.5600	2.4026	13.5600	3.5501	13.5600	2.4569	100	PASS	
-20	3.6	13.5600	2.8441	13.5600	2.9822	13.5600	3.5027	13.5600	3.5199	100	PASS	
20	3.06	13.5600	2.4066	13.5600	3.1256	13.5600	2.3157	13.5600	3.1973	100	PASS	
	4.14	13.5600	3.1839	13.5600	3.3609	13.5600	3.5616	13.5600	2.4863	100	PASS	

## 5.4 20dB BANDWIDTH MEASUREMENT


Ambient condition:

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.3kPa

Method of Measurement:

The spectrum analyzer was receiving the maximum emission level. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Setup:



### LIMITS OF 20dB BANDWIDTH MEASUREMENT

The 20dB bandwidth shall be specified in operating frequency band. (13.11MHz ~ 14.01MHz)


Measurement Uncertainty:

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 936$  Hz.

## Test Results:

Frequency (MHz)	20dB Bandwidth (kHz)	Lower (MHz)	Upper (MHz)	Limit (MHz)	PASS/FAIL
13.56	4.182	13.557959	13.562142	13.11~14.01	PASS

The plots of test results are attached as below.



## 6. Appendix A

Test Equipment	Type/Mode	SERIAL NO.	Equipment No.	Manufacturer	Cal. Due
Spectrum Analyzer	FSV40	101580	DZ-000238-3	R&S	2025/04/22
5m Semi-Anechoic Chamber	SAC-5	SAC-5-2.0	EM-000557	COMTEST	2027/02/01
EMI Test Receiver	N9038A-508	MY532290079	EM-000397	Agilent	2025/12/26
EMI Test Receiver	ESR7	102235	EM-000574	R&S	2026/01/05
loop antenna	HLA 6121	540046	EM-000546	TESEQ	2025/06/04
Broadband Antenna	VULB 9163	9163-530	EM-000342	SCHWARZBECK	2025/06/09
Constant temperature and humidity (high and low temperature) test chamber	LGH-80LA	LG20210902-A10	DZ-000328	/	2025/10/08
Temperature and humidity meter	UT330THC	C231446122	DZ-000249-2	UNI-T	2025/07/28
SuperCharge	HW-100400C01	/	/	HUAWEI	/

Dynacomm	Software Release	Software Developer
TS+ (5m,Radiation test)	JS32-RE 5.0.0	Tonscend

————— No Body Text Below —————

## Important

1. The test report is invalid without the official stamp of CVC;
2. Any part photocopies of the test report are forbidden without the written permission from CVC;
3. The test report is invalid without the signatures of Author and Reviewer;
4. The test report is invalid if altered;
5. Objections to the test report must be submitted to CVC within 15 days;
6. Generally, commission test is responsible for the tested samples only;
7. As for the test result, “—” or “N” means “not applicable”, “ / ” means “not testing”, “P” means “pass” and “F” means “fail”.

Address: No.3,Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, China (Test location)

Post Code: 510663 Tel: 020-32293888

FAX: 020 32293889 E-mail: [office@cvc.org.cn](mailto:office@cvc.org.cn)