

TEST REPORT

FCC ID.	2BGAJ-ED007BICW
Test Report No.	TCT240429E017
Date of issue	May 20, 2024
Testing laboratory	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name	SHENZHEN EEGUARD TECHNOLOGY CO., LIMITED
Address	201, Building A, Jingang Technology Industrial Park, Qiaotou Community, Fuhai Street, Baoan District, Shenzhen, China
Manufacturer's name	SHENZHEN EEGUARD TECHNOLOGY CO., LIMITED
Address	201, Building A, Jingang Technology Industrial Park, Qiaotou Community, Fuhai Street, Baoan District, Shenzhen, China
Standard(s)	FCC CFR Title 47 Part 15 Subpart C Section 15.225
Test item description	VIDEO DOOR PHONE
Trade Mark	N/A
Model/Type reference	Refer to model(s) list of page 3
Rating(s)	POE DC 15-48V AC 12-36V
Date of receipt of test item	Apr. 29, 2024
Date (s) of performance of test	Apr. 29, 2024 ~ May 20, 2024
Tested by (+signature)	Yannie ZHONG
Check by (+signature)	Beryl ZHAO
Approved by (+signature) :	Tomsin



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
2. Test Result Summary	4
3. General Information.....	5
3.1. Test Environment and Mode.....	5
3.2. Description of Support Units.....	5
4. Facilities and Accreditations	6
4.1. Facilities	6
4.2. Location	6
4.3. Measurement Uncertainty.....	6
5. Test Results and Measurement Data	7
5.1. Antenna Requirement	7
5.2. Conducted Emission.....	8
5.3. Radiated Emission Measurement	12
5.4. Occupied Bandwidth.....	20
5.5. Frequency stability.....	22

Appendix A: Photographs of Test Setup

Appendix B: Photographs of EUT

1. General Product Information

1.1. EUT description

Test item description	VIDEO DOOR PHONE
Model/Type reference.....	ED007BICW
Sample Number.....	TCT240429E005-0101
Operation Frequency	13.56MHz
Antenna Type.....	PCB Antenna
Antenna Gain.....	2dBi
Rating(s).....	POE DC 15-48V AC 12-36V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

No.	Model No.	Tested with
1	ED007BICW	<input checked="" type="checkbox"/>
Other models	ED007B, ED007BW, ED007BID, ED007BIC, ED007BIDW, ER012ATW, ER010ATW, ER009ATW, ER015ATW, ER012BTW, ER010BTW, ER009BTW, ER015BTW, ER015HBTW, ER012HBTW, ER010HBTW, ER009HBTW, ER015AT, ER015BT, ER012AT, ER012BT, ER010AT, ER010BT, ER009AT, ER009BT	<input type="checkbox"/>

Note: ED007BICW is tested model, other models are derivative models. The models are identical in circuit and PCB layout, only different on the model names. So the test data of ED007BICW can represent the remaining models.

2. Test Result Summary

Requirement	CFR 47 Section IC Paragraph	Result
Antenna requirement	§15.203	PASS
AC Power Line Conducted Emission	§15.207	PASS
Spurious emissions	§15.225/ §15.209	PASS
Occupied Bandwidth	§15.215 (c)	PASS
Frequency stability	§15.225	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. General Information

3.1. Test Environment and Mode

Operating Environment:		
Condition	Conducted Emission	Radiated Emission
Temperature:	22.8 °C	24.3 °C
Humidity:	49 % RH	49 % RH
Test Mode:		
Operation mode:	Keep the EUT in continuous transmitting with modulation	
<p>The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case(Z axis) are shown in Test Results of the following pages.</p>		

3.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Adapter	R122-1500800ID	/	/	Rongweixin
Access Card	D8038	/	/	GS0N

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.


No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.	

E.U.T Antenna:	
The NFC antenna is PCB antenna which permanently attached, and the best case gain of the antenna is 2dBi.	



5.2. Conducted Emission

5.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	<p>Reference Plane</p> <p>40cm</p> <p>E.U.T</p> <p>AC power</p> <p>Test table/Insulation plane</p> <p>80cm</p> <p>LISN</p> <p>Filter</p> <p>AC power</p> <p>EMI Receiver</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test Mode:	Transmitting Mode														
Test Procedure:	<ol style="list-style-type: none"> The E.U.T is connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 														
Test Result:	PASS														


5.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI3	100898	Jun. 29, 2024
Line Impedance Stabilisation Newtork(LISN)	Schwarzbeck	NSLK 8126	8126453	Jan. 31, 2025
Line-5	TCT	CE-05	/	Jul. 03, 2024
EMI Test Software	Shurple Technology	EZ-EMC	/	/

5.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **L1**

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 15 V(Adapter Input AC 120 V/60 Hz)

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dB μ V	dB	dB μ V				
1		0.1500	47.79	10.02	57.81	66.00	-8.19	QP	
2		0.1500	30.32	10.02	40.34	56.00	-15.66	AVG	
3		0.5380	36.92	9.30	46.22	56.00	-9.78	QP	
4 *		0.5380	31.65	9.30	40.95	46.00	-5.05	AVG	
5		0.8379	33.47	9.04	42.51	56.00	-13.49	QP	
6		0.8379	22.86	9.04	31.90	46.00	-14.10	AVG	
7		1.5180	33.52	9.97	43.49	56.00	-12.51	QP	
8		1.5180	22.73	9.97	32.70	46.00	-13.30	AVG	
9		2.1979	27.46	10.05	37.51	56.00	-18.49	QP	
10		2.1979	17.38	10.05	27.43	46.00	-18.57	AVG	
11		13.5580	32.03	10.63	42.66	60.00	-17.34	QP	
12		13.5580	27.46	10.63	38.09	50.00	-11.91	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)


Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) – Limits (dB μ V)

Q.P. = Quasi-Peak, AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site 844 Shielding Room

Phase: **N**

Temperature: 22.8 (°C)

Humidity: 49 %

Limit: FCC Part 15C Conduction(QP)

Power: DC 15 V(Adapter Input AC 120 V/60 Hz)

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
			dB μ V	dB	dB μ V	dB			
1		0.1500	48.05	10.00	58.05	66.00	-7.95	QP	
2		0.1500	31.14	10.00	41.14	56.00	-14.86	AVG	
3		0.2260	32.79	9.82	42.61	62.60	-19.99	QP	
4		0.2260	27.56	9.82	37.38	52.60	-15.22	AVG	
5		0.5380	35.10	9.28	44.38	56.00	-11.62	QP	
6	*	0.5380	29.80	9.28	39.08	46.00	-6.92	AVG	
7		1.4578	34.09	9.92	44.01	56.00	-11.99	QP	
8		1.4578	20.85	9.92	30.77	46.00	-15.23	AVG	
9		4.2857	30.60	10.25	40.85	56.00	-15.15	QP	
10		4.2857	16.68	10.25	26.93	46.00	-19.07	AVG	
11		13.5619	33.85	10.61	44.46	60.00	-15.54	QP	
12		13.5619	29.25	10.61	39.86	50.00	-10.14	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dB μ V) = Receiver reading

Corr. Factor (dB) = LISN factor + Cable loss

Measurement (dB μ V) = Reading level (dB μ V) + Corr. Factor (dB)

Limit (dB μ V) = Limit stated in standard

Margin (dB) = Measurement (dB μ V) – Limits (dB μ V)

QP. = Quasi-Peak

AVG = average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz



5.3. Radiated Emission Measurement

5.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.225				
Test Method:	ANSI C63.10: 2013				
Frequency Range:	9 kHz to 1000 MHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	FCC Part15 C Section 15.225				
	Frequency (MHz)	Limit (uV/m @30m)	Limit (dBuV/m @3m)	Detector	
	13.110-13.410	106	80.5	QP	
	13.410-13.553	334	90.5	QP	
	13.553-13.567	15848	124.0	QP	
	13.567-13.7110	224	90.5	QP	
	13.710-14.010	106	80.5	QP	
	<p>Note: RF Voltage (dBuV) = 20 log RF Voltage (uV) Limit (dBuV/m @3m) = 20log(Limit (uV/m @30m)) + 40</p>				
Limit:	FCC Part15 C Section 15.209				
	Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)	Detector	
	0.009-0.490	3	20log 2400/F (kHz) + 80	QP	
	0.490-1.705	3	20log 24000/F (kHz) + 40	QP	
	1.705-30	3	20log 30 + 40	QP	
	30-88	3	40.0	QP	
	88-216	3	43.5	QP	
	216-960	3	46.0	QP	
	Above 960	3	54.0	QP	
	<p>Note:</p> <ol style="list-style-type: none"> 1. RF Voltage (dBuV) = 20 log RF Voltage (uV) 2. In the Above Table, the tighter limit applies at the band edges. 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT 4. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand). After pre-test. It was found that the worse radiated emission was get at the lying position. 5. If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula $Ld1 = Ld2 * (d2/d1)$ 				

Test Procedure:

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber in below 1GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

For radiated emissions below 30MHz

Test setup:
30MHz to 1GHz

Test Mode:

Refer to section 3.1 for details

Test results:	PASS
---------------	------

5.3.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESIB7	100197	Jun. 29, 2024
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 29, 2024
Pre-amplifier	SKET	LNPA_0118G-45	SK2021012 102	Jan. 31, 2025
Pre-amplifier	SKET	LNPA_1840G-50	SK2021092 03500	Jan. 31, 2025
Pre-amplifier	HP	8447D	2727A05017	Jun. 27, 2024
Loop antenna	Schwarzbeck	FMZB1519B	00191	Jul. 02, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 01, 2024
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 02, 2025
Coaxial cable	SKET	RC-18G-N-M	/	Jan. 31, 2025
Coaxial cable	SKET	RC_40G-K-M	/	Jan. 31, 2025
EMI Test Software	Shurples Technology	EZ-EMC	/	/

5.3.3. Test Data

Field Strength of Fundamental

Frequency (MHz)	Emission Level dBuV/m@3m	Emission Level dBuV/m@30m	Limits dBuV/m@30m	Result
13.560	54.82	14.82	84	PASS

Field Strength Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz

Frequency (MHz)	Emission Level dBuV/m@3m	Emission Level dBuV/m@30m	Limits dBuV/m@30m	Result
13.457	28.29	-11.71	50.47	PASS
13.673	28.14	-11.86	50.47	PASS


Field Strength Within the bands 13.110-13.410 MHz and 13.710-14.010

Frequency (MHz)	Emission Level dBuV/m@3m	Emission Level dBuV/m@30m	Limits dBuV/m@30m	Result
13.256	28.16	-11.84	40.50	PASS
13.985	28.46	-11.54	40.50	PASS

Spurious Emissions

9KHz-30MHz

9KHz-150KHz:



Site: 3m Anechoic Chamber

Polarization: *Coaxial*

Temperature: 23.3(°C)


Humidity: 52 %

Limit: FCC Part15.209(9K-30M)

Power:DC 15 V(Adapter Input AC 120 V/60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	0.0108	39.33	20.33	59.66	126.94	-67.28	peak	P	
2	0.0153	37.31	20.32	57.63	123.91	-66.28	peak	P	
3	0.0239	31.91	20.28	52.19	120.04	-67.85	peak	P	
4	0.0401	28.51	20.29	48.80	115.54	-66.74	peak	P	
5	0.0560	26.04	20.30	46.34	112.64	-66.30	peak	P	
6 *	0.0719	26.36	20.25	46.61	110.47	-63.86	peak	P	

150KHz-30MHz:



Site: 3m Anechoic Chamber

Polarization: **Coaxial**

Temperature: 23.3(°C)

Humidity: 52 %


Limit: FCC Part15.209(9K-30M)

Power: DC 15 V(Adapter Input AC 120 V/60 Hz)

No.	Frequency (MHz)	Reading (dB _{uV})	Factor (dB/m)	Level (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)	Detector	P/F	Remark
1	0.1539	28.96	20.12	49.08	103.86	-54.78	peak	P	
2	0.2810	24.39	20.33	44.72	98.63	-53.91	peak	P	
3	0.4409	21.84	20.62	42.46	94.72	-52.26	peak	P	
4	1.8366	9.58	23.30	32.88	69.50	-36.62	peak	P	
5	5.4013	0.67	30.42	31.09	69.50	-38.41	peak	P	
6 *	13.5724	8.32	46.50	54.82	69.50	-14.68	peak	P	

Note : 1) Emission Level=Peak Reading + Correction Factor;
Correction Factor=Antenna Factor + Cable loss – Pre-amplifier

Horizontal:



Site: 3m Anechoic Chamber

 Polarization: **Horizontal**


Temperature: 24.3(C) Humidity: 49 %

Limit: FCC Part 15C RE_3m

Power: DC 15 V(Adapter Input AC 120 V/60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	68.1514	43.95	-14.20	29.75	40.00	-10.25	QP	P	
2	160.3456	48.63	-11.09	37.54	43.50	-5.96	QP	P	
3	221.3921	45.34	-14.32	31.02	46.00	-14.98	QP	P	
4	543.2742	38.64	-5.87	32.77	46.00	-13.23	QP	P	
5	578.6699	45.80	-5.03	40.77	46.00	-5.23	QP	P	
6	938.8326	35.19	0.85	36.04	46.00	-9.96	QP	P	

Vertical:



Site: 3m Anechoic Chamber

 Polarization: *Vertical*

Temperature: 24.3(C) Humidity: 49 %

Limit: FCC Part 15C RE_3m

Power: DC 15 V(Adapter Input AC 120 V/60 Hz)

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 !	69.6004	50.06	-14.40	35.66	40.00	-4.34	QP	P	
2	135.5061	48.15	-12.23	35.92	43.50	-7.58	QP	P	
3	141.3296	48.57	-11.87	36.70	43.50	-6.80	QP	P	
4 *	162.6105	51.24	-11.12	40.12	43.50	-3.38	QP	P	
5	222.9502	45.60	-14.24	31.36	46.00	-14.64	QP	P	
6	578.6700	42.94	-5.03	37.91	46.00	-8.09	QP	P	

Note : 1) Emission Level=Peak Reading + Correction Factor;
 Correction Factor= Antenna Factor + Cable loss – Pre-amplifier

5.4. Occupied Bandwidth

5.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.215(c)
Test Method:	ANSI C63.10: 2013
Limit:	N/A
Test Procedure:	<ol style="list-style-type: none"> According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. Set to the maximum power setting and enable the EUT transmit continuously. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW\geq1% of the 20 dB bandwidth; VBW\geqRBW; Sweep = auto; Detector function = peak; Trace = max hold. Measure and record the results in the test report.
Test setup:	<p>The diagram shows a green rectangular box labeled "Spectrum Analyzer" on the left. A horizontal line extends from its right side to a yellow rectangular box labeled "EUT" on the right. The line has two small circular ports near the analyzer and one small square port near the EUT. The text "Spectrum Analyzer" is centered below the analyzer, and "EUT" is centered below the EUT.</p>
Test Mode:	Refer to section 3.1 for details
Test results:	PASS


5.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Jun. 28, 2024

5.4.3. Test data

Frequency(MHz)	20dB Occupy Bandwidth (kHz)	Limit (kHz)	Conclusion
13.56	4.84	---	PASS

Test plots as follows:



5.5. Frequency stability

5.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.225
Test Method:	ANSI C63.10 : 2013
Operation mode:	Refer to item 3.1
Limit:	+/-0.01%
Test Setup:	<p>The diagram shows a 'Spectrum Analyzer' on the left with a green display and two knobs. A horizontal line with a small square connector extends from its output to a yellow rectangular box labeled 'EUT'. Below the 'EUT' box is the text 'Thermal Chamber'.</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The equipment under test was connected to an external DC power supply and input rated voltage. 2. RF output was connected to a spectrum analyzer. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +55°C reached. 7. Repeat step measure with a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C
Test Result:	PASS

5.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Jun. 28, 2024
DC power supply	Kingrang	KR3005K	/	Jun. 28, 2024

5.5.3. Test Data



Voltage (Vdc)	Temperature (°C)	Frequency (MHz)	Deviation (%)	Limit (%)
15	-20	13.560258	0.00190	+/-0.01%
15	-10	13.560216	0.00159	
15	0	13.560146	0.00108	
15	10	13.560270	0.00199	
15	20	13.560166	0.00122	
15	30	13.560288	0.00212	
15	40	13.560210	0.00155	
15	50	13.560218	0.00161	
15	55	13.560212	0.00156	
48	20	13.560172	0.00127	
15	20	13.560166	0.00122	

Appendix A: Photographs of Test Setup


Product: VIDEO DOOR PHONE

Model: ED007BICW

Radiated Emission



Conducted Emission



Appendix B: Photographs of EUT

Refer to the test report No. TCT240429E005

*******END OF REPORT*******