

RF Exposure Evaluation Report

1 RF EXPOSURE

Product Name: Touch all in one pc
 Model No.: SK-15A, SK-10.4A, SK-12.1A, SK-17A, SK-19A, SK-21.5A, SK-32A, SK-43A, SK-50A, SK-55A
 FCC ID: 2BGDB-SK-15A

2. RF Exposure Evaluation

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

2.1 LIMITS

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1 to [§ 1.1310\(e\)\(1\)](#)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6

(ii) Limits for General Population/Uncontrolled Exposure

0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

F= Frequency in MHz Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$ Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2 EUT RF EXPOSURE EVALUATION

BT ANT1: 2.5dBi; 2.4G- ANT1&ANT2:2.5dBi; MIMO: 5.51dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

The Max Conducted Peak Output Power data refer to report DACE240418005RL002 & DACE240418005RL001

BT worst mode and channel:						
Test channel (MHz)	PK Power (dBm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (mW)	Calculated value (mW/cm ²)	Limit (mW/cm ²)
3DH5-2402	4.02	4.0±1	5.0	3.162	0.0124	1.0
3DH5-2441	3.38	4.0±1	5.0	3.162	0.0124	1.0
3DH5-2480	3.79	4.0±1	5.0	3.162	0.0124	1.0

Remark: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (3.162 \cdot 1.7783) / (4 \cdot 3.1415 \cdot 6 \cdot 6) = 0.0124$, $G = 10^{\text{gain}/10} = 1.7783$

2.4GWIFI worst mode and channel:

Test channel (MHz)	PK Power (dBm)	Maximum tune-up Power (dbm)		Max.MIMO tune-up Power (dbm)	Max.MIMO tune-up Power (mW)	Calculated value (mW/cm ²)	Limit (mW/cm ²)
	ANT1	ANT2	ANT1	ANT2	(mW)	(mW/cm ²)	(mW/cm ²)
802.11n – 2412MHz	15.62	15.40	16±1	16±1	20.01	100.24	0.788
802.11n – 2437MHz	15.48	15.23	16±1	16±1	20.01	100.24	0.788
802.11n – 2462MHz	15.90	15.79	16±1	16±1	20.01	100.24	0.788

Remark: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (100.24 \cdot 3.5563) / (4 \cdot 3.1415 \cdot 6 \cdot 6) = 0.788$, $G = 10^{\text{gain}/10} = 3.5563$

RF Exposure Evaluation simultaneous transmission operations:

According to 865664D02 2.2 d) 1):

The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits :

Simultaneous transmission mode	The sum of the ratios	SUM	Limit
2.4G WIFI + BT	0.0124+0.788	≈0.8004	1.0
Conclusion: $0.8004 < 1.0$, So there is no sar requirement			

NOTE: EUT BT & wifi-2.4G module and antenna is more than 6cm away from the human body.

Conclusion:

the sum of the ratios is less than the limit value of 1.0, so there is no sar requirement.