

FCC TEST REPORT

FCC ID: 2BGDO-V23

On Behalf of

Shenzhen Huasheng Jiahe Electronic Technology Co., Ltd

Mobile device rotation charging device

Model No.: V23

Prepared for : Shenzhen Huasheng Jiahe Electronic Technology Co., Ltd
Address : C301, Building 78, Fourth Industrial Zone, Mashantou Community, Matian Street, Guangming District, Shenzhen, China

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2505028-C01-R03
Date of Receipt : May 7, 2025
Date of Test : May 7, 2025 to May 23, 2025
Date of Report : May 23, 2025
Version Number : V0

TABLE OF CONTENTS

	Description	Page
1.	Test Result Summary	5
2.	EUT Description	6
2.1.	DESCRIPTION OF DEVICE (EUT)	6
2.2.	ACCESSORIES OF DEVICE (EUT)	7
2.3.	TESTED SUPPORTING SYSTEM DETAILS	7
2.4.	BLOCK DIAGRAM OF CONNECTION BETWEEN EUT AND SIMULATORS	7
2.5.	DESCRIPTION OF TEST MODES	8
2.6.	TEST CONDITIONS	9
2.7.	TEST FACILITY	9
2.8.	MEASUREMENT UNCERTAINTY	9
3.	Test Results and Measurement Data	10
3.1.	RF EXPOSURE TEST	10
4.	Photos of test setup	13

TEST REPORT DECLARATION

Applicant : Shenzhen Huasheng Jiahe Electronic Technology Co., Ltd
Address : C301, Building 78, Fourth Industrial Zone, Mashantou Community, Matian Street,
Guangming District, Shenzhen, China
Manufacturer : Shenzhen Huasheng Jiahe Electronic Technology Co., Ltd
Address : C301, Building 78, Fourth Industrial Zone, Mashantou Community, Matian Street,
Guangming District, Shenzhen, China
EUT Description : Mobile device rotation charging device
(A) Model No. : V23
(B) Trademark : /

Measurement Standard Used:

FCC CFR 47 PART 1, FCC CFR 47 part1, 1.1307(b), 1.1310

KDB 680106 D01 Wireless Power Transfer v04

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness test. Also, this report shows that the EUT is technically compliant with the KDB 680106 D01 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....: Felix Pang
Test Engineer 

Approved by (name + signature).....: Simple Guan
Project Manager 

Date of issue.....: May 23, 2025

Revision History

Revision	Issue Date	Revisions	Revised By
V0	May 23, 2025	Initial released Issue	Felix Pang

1. Test Result Summary

Requirement	CFR 47 Section	Result
RF EXPOSURE	§1.1307(b)(1), §1.1310& KDB680106	PASS

Note:

1. *PASS: Test item meets the requirement.*
2. *Fail: Test item does not meet the requirement.*
3. *N/A: Test case does not apply to the test object.*
4. *The test result judgment is decided by the limit of test standard.*
5. Decision rules for the conclusion of this test report: decision by actual test data without considering measurement uncertainty.

2. EUT Description

2.1. Description of Device (EUT)

EUT Name : Mobile device rotation charging device

Model No. : V23

DIFF. : /

Power supply : Input USB-C: 9 V  2 A, 9 V  3 A
Wireless output:
Phone: 15W (MAX)
Watch: 2.5W (MAX)
Earphone: 3W (MAX)

Radio Technology : Wireless power transmission systems

Operation frequency : Mobile phone: 111-205KHz
Earphone: 111-205KHz
iWatch: 300-350KHz

Modulation : MSK

Antenna Type : Coil Antenna

Connector cable loss : 0dB

Software version : V1.0

Hardware version : V1.0

Note : Antenna information is provided by applicant.
Testing lab is not responsible for the accuracy of the information.


2.2. Accessories of Device (EUT)

Accessories	:	AC ADAPTER
Manufacturer	:	ShenZhen Huoniu Technology Co.,Ltd.
Model	:	HNFCQC3024UK
specifications	:	N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification
E-1	AC Adapter	Xiaomi	MDY-12-ED	N/A	N/A
E-2	Mobile phone	Xiaomi	Xiaomi 12S Pro	N/A	N/A
E-3	Earphone	Apple	A2031	N/A	N/A
E-4	Apple watch	Apple	ultra 2	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Description of Test Modes

Modes:	
Mode 1	Adapter+Wireless charging mode (Phone: Battery Status: $\leq 1\%$)
Mode 2	Adapter+Wireless charging mode (Phone: Battery Status:50%)
Mode 3	Adapter+Wireless charging mode (Phone: Battery Status: $\geq 98\%$)
Mode 4	Adapter+Wireless charging mode (Earphone: Battery Status: $\leq 1\%$)
Mode 5	Adapter+Wireless charging mode (Earphone: Battery Status:50%)
Mode 6	Adapter+Wireless charging mode (Earphone: Battery Status: $\geq 98\%$)
Mode 7	Adapter+Wireless charging mode (iWatch: Battery Status: $\leq 1\%$)
Mode 8	Adapter+Wireless charging mode (iWatch: Battery Status:50%)
Mode 9	Adapter+Wireless charging mode (iWatch: Battery Status: $\geq 98\%$)
Mode 10	Adapter+Wireless charging mode (Phone: Battery Status: $\leq 1\%$) + (Earphone: Battery Status: $\leq 1\%$)
Mode 11	Adapter+Wireless charging mode (Phone: Battery Status: $\leq 1\%$) + (iWatch: Battery Status: $\leq 1\%$)
Mode 12	Adapter+Wireless charging mode (Earphone: Battery Status: $\leq 1\%$) + (iWatch: Battery Status: $\leq 1\%$)
Mode 13	Adapter+Wireless charging mode (Phone: Battery Status: $\leq 1\%$) + (Earphone: Battery Status: $\leq 1\%$) + (iWatch: Battery Status: $\leq 1\%$)

Note: All modes and coil were tested, only the worst-case was recorded in the report. Mode 13 is the worst mode.

2.6. Test Conditions

Items	Required
Temperature range:	15-35°C
Humidity range:	25-75%
Pressure range:	86-106kPa

2.7. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.8. Measurement Uncertainty


(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for H-Field	2.39dB
Uncertainty for E-Field	2.45dB
Uncertainty for conducted RF Power	0.65dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

3. Test Results and Measurement Data

3.1. RF EXPOSURE TEST

3.1.1. Test Specification

Test Requirement:	FCC Rules and Regulations KDB680106
Test Method:	§1.1307(b)(1) & KDB680106
Limits:	According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1091 RF exposure is calculated. According KDB 680106 D01 Wireless Power Transfer v04: RF Exposure Wireless Charging.
Test Setup:	 E to position is 20cm, F is the bottom of the product
Test Mode:	Transmitting Mode (Mobile phone will be charge at zero charge, intermediate charge, and full charge.)
Test Procedure:	1. The RF exposure test was carried out on a non-metallic table top 80cm high in the shielding darkroom. 2. The measurement probe was placed at test distance (20 cm for Top side) which is between the edge of the charger and the geometric centre of probe. 3. The test time is maintained for more than one minute. 4. The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed. 5. The EUT were measured according to the dictates of KDB 680106 D01 Wireless Power Transfer v04.
Test Result:	PASS

3.1.2. Test Instruments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Exposure Level Tester	narda	ELT-400	O-0729	2025.05.22	1 Year
2	Magnetic field probe 100cm2	narda	ELT probe 100cm2	M-2116	2025.05.22	1 Year

3.1.3. Test data



Frequency Range (MHz)	Unit	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E	Test Position F	50%Limits (A/m)	Limits (A/m)	test result
0.111-0.205	A (uT)	0.32	0.28	0.34	0.34	0.27	0.3	0.815	1.63	PASS
	(A/m)	0.26	0.22	0.24	0.27	0.22	0.24			
0.111-0.205	A (uT)	0.31	0.3	0.24	0.33	0.29	0.32			
	(A/m)	0.25	0.24	0.19	0.26	0.23	0.26			
0.300-0.350	A (uT)	0.32	0.31	0.3	0.35	0.29	0.29			
	(A/m)	0.26	0.25	0.24	0.28	0.23	0.23			


The device could support transmission with ANT1, ANT2, ANT3 simultaneously.



$MPE1/LIMIT + MPE2/LIMIT + MPE3/LIMIT = 0.27/0.815 + 0.26/0.815 + 0.28/0.815 = 0.99 \leq 1$

Note: Calculation: $A/m = uT/1.25$

4. Photos of test setup







-----END OF REPORT-----