



FCC PART 15B

TEST REPORT

For

WOUXUN COMMUNICATIONS LIMITED

11/F OFFICE A HARVARD COMMERCIAL BUILDING 105-111 THOMSON RD WAN CHAI
HK, 999077 HONGKONG

FCC ID: 2BGESWX001

Report Type: Original Report	Product Name: TWO WAY RADIO(GMRS RADIO)
Report Number: 2407A21468E-EM-01	
Report Date:	2025-01-13
Reviewed By:	Ash Lin
Approved By:	Miles Chen
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST FACILITY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
TEST MODE AND VOLTAGE.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §15.107 - CONDUCTED EMISSION	12
APPLICABLE STANDARD	12
TEST SYSTEM SETUP.....	12
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
RESULT & MARGIN CALCULATION.....	13
TEST DATA	14
FCC §15.109 - RADIATED EMISSION IN FREQUENCY	22
APPLICABLE STANDARD	22
TEST SYSTEM SETUP.....	22
EMI TEST RECEIVER SETUP.....	23
TEST PROCEDURE	23
RESULT & MARGIN CALCULATION.....	23
TEST DATA	24
FCC §15.121(B) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS.....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST DATA	41
EXHIBIT A - EUT PHOTOGRAPHS.....	42
EXHIBIT B – TEST SETUP PHOTOGRAPHS.....	43

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2407A21468E-EM-01	R1V1	2025-01-13	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	WOUXUN COMMUNICATIONS LIMITED
Product Name:	TWO WAY RADIO(GMRS RADIO)
Tested Model:	KG-915G
Multiple Model(s):	KG-915G+, KG-915G Plus, KG-915GR, KG-915GX, KG-905G+, KG-905G Plus, KG-905GR, KG-905GX, KG-910G, KG-910G+, KG-910G Plus, KG-910GR, KG-910GX
Charger Information	Model: 1A26KG-8
	Input: DC 12V, 0.8A
	Output: DC 8.4V, 0.8A
Adapter Information	Model: DSX-120100-US
	Input: AC100-240V, 50-60Hz, 0.3A
	Output: DC 12V, 1A
Power Supply:	DC 7.4V from battery or DC 8.4V from charger
★Highest Operating Frequency:	480MHz
EUT Receive Status:	Good

Note:

1. The highest operating frequency is provided by the applicant.
2. The test model is identify with the series model except for the model name, please refer to declaration letter for more detail.
3. All measurement and test data in this report was gathered from production sample serial number:
2WQK-1 (Assigned by the BACL (Xiamen). The EUT was received on 2024-12-27).

Objective

This report is prepared for *WOUXUN COMMUNICATIONS LIMITED* in accordance with Part 2-Subpart J, and Part 15-Subparts A and B of the Federal Communication Commission's rules.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on Unit 102, No. 902 Meifeng South Road, Binhai West Avenue, Science and Technology Innovation Park, Torch High tech Zone XiaMen.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the product as specified in CISPR 16-4-2. This uncertainty represents expanded uncertainty expressed at 95% confidence level using a coverage factor of k=2.

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

Item	Frequency Range	$U_{lab} = 2 u_c(y)$ (Confidence of 95%)
Conducted Emission	150kHz-30MHz	2.33dB
Radiated Emission	30MHz~200MHz	4.38dB
	200MHz~1GHz	4.50dB
	1GHz~6GHz	4.58dB
Unwanted Emissions, conducted		1.5dB
Humidity		5%
Temperature		1°C

SYSTEM TEST CONFIGURATION

Test Mode and Voltage

The system was configured for testing in a typical mode (as normally used by a typical user).	
Test mode:	Test Mode 1: Charging & Scanning Test Mode 2: Charging & Receiving
Test voltage:	Test Mode 1: DC 8.4V from charger(AC 120V/60Hz) Test Mode 2: DC 8.4V from charger(AC 120V/60Hz)
Remark:	During all emission tests, the EUT was configured to measure its highest possible emission level and the worst case's test data was presented in this test report.

Description of Test Configuration

Operation Modes	Operation Frequency Range (MHz)	Test Frequency (MHz)
Scanning	400-480	400-480
UHF Receiving	400-480	400.0125, 440, 479.9875

EUT Exercise Software

No exercise software was used to test.

Special Accessories

No special accessory was used.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HP	RF Communications test set	8920A	3524A07202
Unknown	Antenna	Unknown	Unknown


External I/O Cable

Cable Description	Length (m)	From Port	To Port
Antenna Cable	3.0	8920A	Antenna


Block Diagram of Test Setup

Conducted Emission:

Test Mode 1:




Test Mode 2:




Radiated Emission:

Test Mode 1:



Test Mode 2:



SUMMARY OF TEST RESULTS

Rule Part	Description of Test	Results
FCC§15.107	Conducted Emission	Compliant
FCC§15.109	Radiated Emission	Compliant
FCC §15.121(b)	Scanning receivers and frequency converters used with scanning receivers	Compliant

TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission					
EMI Test Receiver	Rohde & Schwarz	ESR	103105	2024/03/29	2025/03/28
LISN	Rohde & Schwarz	ENV216	100129	2024/03/29	2025/03/28
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	0357.8810.54	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC001	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emission 30 MHz to 1 GHz					
EMI Test Receiver	Rohde & Schwarz	ESR	103103	2024/03/29	2025/03/28
Antenna	Sunol Sciences	JB6	A122022-5	2023/07/27	2026/07/26
Amplifier	Sonoma	310B	120903	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC002	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH460B-N-2M	CC006	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH460B-N-12M	CC007	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emission Above 1 GHz					
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2025/02/20	2026/02/19
Horn Antenna	EMCO	3115	9002-3355	2024/11/19	2027/11/18
Preamplifier	A.H.Systems	PAM-0118P	489	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH800A-N-6M	CC003	2024/03/29	2025/03/28
Coaxial Cable	XINHANGWEIBO	XH800A-N-1M	CC005	2024/03/29	2025/03/28
Test Software	Audix	E3	18621a	N/A	N/A
Scanning Receiver					
Coaxial Cable	WEIHE	WH316	RFCC002	Each time	Each time
RF Communications test set	HP	8920A	3524A07202	2024/04/26	2025/04/25
Power Splitter	narda	4426LB-2	1661	N/A	N/A
Microwave Analog Signal Generator	Agilent	N5183A	MY47420335	2024/03/29	2025/03/28
Attenuator	Electronic Corporation	30-WA-FFN-30	1172435	2024/03/29	2025/03/28

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 - CONDUCTED EMISSION

Applicable Standard


FCC §15.107

(a) Except for Class A digital devices, for equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Test System Setup



The measurement procedure of test setup is according with ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Result & Margin Calculation

The Result is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Result (dB μ V) = Reading (dB μ V) + Factor (dB)


The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V) –Result (dB μ V)

Test Data

Project No.: 2407A21468E-EM
 Test Mode: Mode 1(400-480MHz)
 EUT Model: KG-915G

Temp/Humi/ATM: 21°C/45%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)




Trace: 1
 Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	21.73	20.78	42.51	55.05	12.54	Line	Average
0.17	35.55	20.78	56.33	65.05	8.72	Line	QP
0.21	18.09	20.55	38.64	53.23	14.59	Line	Average
0.21	32.04	20.55	52.59	63.23	10.64	Line	QP
0.25	12.03	20.49	32.52	51.70	19.18	Line	Average
0.25	25.60	20.49	46.09	61.70	15.61	Line	QP
0.33	6.77	20.41	27.18	49.33	22.15	Line	Average
0.33	21.67	20.41	42.08	59.33	17.25	Line	QP
0.46	2.26	20.32	22.58	46.68	24.10	Line	Average
0.46	16.46	20.32	36.78	56.68	19.90	Line	QP
3.97	-2.15	20.67	18.52	46.00	27.48	Line	Average
3.97	5.93	20.67	26.60	56.00	29.40	Line	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: KG-915G


Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	16.56	20.70	37.26	55.06	17.80	Neutral	Average
0.17	30.32	20.70	51.02	65.06	14.04	Neutral	QP
0.21	13.71	20.65	34.36	53.07	18.71	Neutral	Average
0.21	26.29	20.65	46.94	63.07	16.13	Neutral	QP
0.25	12.41	20.59	33.00	51.64	18.64	Neutral	Average
0.25	20.63	20.59	41.22	61.64	20.42	Neutral	QP
0.60	15.03	20.34	35.37	46.00	10.63	Neutral	Average
0.60	21.71	20.34	42.05	56.00	13.95	Neutral	QP
0.63	11.48	20.33	31.81	46.00	14.19	Neutral	Average
0.63	18.52	20.33	38.85	56.00	17.15	Neutral	QP
0.74	7.11	20.39	27.50	46.00	18.50	Neutral	Average
0.74	14.62	20.39	35.01	56.00	20.99	Neutral	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: KG-915G


Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	23.69	20.78	44.47	55.05	10.58	Line	Average
0.17	35.80	20.78	56.58	65.05	8.47	Line	QP
0.21	17.42	20.56	37.98	53.38	15.40	Line	Average
0.21	31.30	20.56	51.86	63.38	11.52	Line	QP
0.25	13.37	20.50	33.87	51.78	17.91	Line	Average
0.25	25.79	20.50	46.29	61.78	15.49	Line	QP
0.29	8.97	20.45	29.42	50.39	20.97	Line	Average
0.29	22.40	20.45	42.85	60.39	17.54	Line	QP
0.33	9.94	20.41	30.35	49.35	19.00	Line	Average
0.33	22.33	20.41	42.74	59.35	16.61	Line	QP
0.63	9.48	20.44	29.92	46.00	16.08	Line	Average
0.63	16.62	20.44	37.06	56.00	18.94	Line	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: KG-915G


Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	18.70	20.70	39.40	55.13	15.73	Neutral	Average
0.17	30.41	20.70	51.11	65.13	14.02	Neutral	QP
0.17	13.19	20.70	33.89	54.83	20.94	Neutral	Average
0.17	26.04	20.70	46.74	64.83	18.09	Neutral	QP
0.21	14.09	20.65	34.74	53.08	18.34	Neutral	Average
0.21	25.35	20.65	46.00	63.08	17.08	Neutral	QP
0.26	12.60	20.59	33.19	51.59	18.40	Neutral	Average
0.26	19.73	20.59	40.32	61.59	21.27	Neutral	QP
0.60	13.82	20.35	34.17	46.00	11.83	Neutral	Average
0.60	21.58	20.35	41.93	56.00	14.07	Neutral	QP
0.63	13.81	20.33	34.14	46.00	11.86	Neutral	Average
0.63	20.63	20.33	40.96	56.00	15.04	Neutral	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 2(440MHz)
EUT Model: KG-915G

Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Trace: 1
Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	11.27	20.75	32.02	54.83	22.81	Line	Average
0.17	23.19	20.75	43.94	64.83	20.89	Line	QP
0.21	10.50	20.55	31.05	53.08	22.03	Line	Average
0.21	21.28	20.55	41.83	63.08	21.25	Line	QP
0.26	6.92	20.49	27.41	51.53	24.12	Line	Average
0.26	17.19	20.49	37.68	61.53	23.85	Line	QP
0.34	2.45	20.41	22.86	49.21	26.35	Line	Average
0.34	14.85	20.41	35.26	59.21	23.95	Line	QP
0.59	7.21	20.40	27.61	46.00	18.39	Line	Average
0.59	12.80	20.40	33.20	56.00	22.80	Line	QP
1.56	0.33	21.06	21.39	46.00	24.61	Line	Average
1.56	7.27	21.06	28.33	56.00	27.67	Line	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 2(440MHz)
EUT Model: KG-915G

Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Trace: 1
Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	14.24	20.70	34.94	55.05	20.11	Neutral	Average
0.17	27.72	20.70	48.42	65.05	16.63	Neutral	QP
0.21	12.35	20.65	33.00	53.21	20.21	Neutral	Average
0.21	24.95	20.65	45.60	63.21	17.61	Neutral	QP
0.29	11.76	20.55	32.31	50.41	18.10	Neutral	Average
0.29	16.06	20.55	36.61	60.41	23.80	Neutral	QP
0.61	11.91	20.34	32.25	46.00	13.75	Neutral	Average
0.61	19.94	20.34	40.28	56.00	15.72	Neutral	QP
0.72	9.99	20.34	30.33	46.00	15.67	Neutral	Average
0.72	17.14	20.34	37.48	56.00	18.52	Neutral	QP
1.63	5.41	21.00	26.41	46.00	19.59	Neutral	Average
1.63	13.25	21.00	34.25	56.00	21.75	Neutral	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: KG-915G

Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Trace: 1

Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	10.48	20.78	31.26	55.03	23.77	Line	Average
0.17	22.74	20.78	43.52	65.03	21.51	Line	QP
0.21	6.48	20.55	27.03	53.18	26.15	Line	Average
0.21	19.52	20.55	40.07	63.18	23.11	Line	QP
0.26	4.33	20.49	24.82	51.47	26.65	Line	Average
0.26	15.47	20.49	35.96	61.47	25.51	Line	QP
0.30	2.34	20.44	22.78	50.15	27.37	Line	Average
0.30	13.63	20.44	34.07	60.15	26.08	Line	QP
0.60	7.72	20.41	28.13	46.00	17.87	Line	Average
0.60	13.53	20.41	33.94	56.00	22.06	Line	QP
1.86	-3.54	21.11	17.57	46.00	28.43	Line	Average
1.86	3.98	21.11	25.09	56.00	30.91	Line	QP

Project No.: 2407A21468E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: KG-915G

Temp/Humi/ATM: 21°C/45%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)



Trace: 1
Condition: QP/AV IF B/W:9kHz

Freq MHz	Reading dBuV	Factor dB	Result dBuV	Limit dBuV	Margin dB	Phase	Remark
0.17	9.77	20.70	30.47	54.84	24.37	Neutral	Average
0.17	22.33	20.70	43.03	64.84	21.81	Neutral	QP
0.21	6.32	20.65	26.97	53.22	26.25	Neutral	Average
0.21	19.99	20.65	40.64	63.22	22.58	Neutral	QP
0.26	10.21	20.59	30.80	51.47	20.67	Neutral	Average
0.26	13.97	20.59	34.56	61.47	26.91	Neutral	QP
0.60	25.08	20.34	45.42	56.00	10.58	Neutral	QP
0.60	17.04	20.34	37.38	46.00	8.62	Neutral	Average
0.60	17.19	20.34	37.53	46.00	8.47	Neutral	Average
0.60	22.89	20.34	43.23	56.00	12.77	Neutral	QP
1.58	3.87	21.00	24.87	46.00	21.13	Neutral	Average
1.58	12.53	21.00	33.53	56.00	22.47	Neutral	QP

FCC §15.109 - RADIATED EMISSION IN FREQUENCY

Applicable Standard


FCC§15.109

(a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:


Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

Test System Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance

with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW	Measurement	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	PK	PK
	120 kHz	/	QP	QP
Above 1 GHz	1 MHz	3 MHz	PK	PK
	1 MHz	10 Hz	AV	PK

Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Result & Margin Calculation

The Result is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

Result (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) - Result (dB μ V/m)


Test Data

Please refer to below plots:

1) 30MHz-1GHz:

Project No.: 2407A21468E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: KG-915G
Test distance: 3m


Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.39	25.85	-5.70	20.15	40.00	19.85	Horizontal	Peak
205.18	32.84	-12.09	20.75	43.50	22.75	Horizontal	Peak
688.73	27.33	-0.46	26.87	46.00	19.13	Horizontal	Peak
765.45	27.36	0.73	28.09	46.00	17.91	Horizontal	Peak
887.19	25.97	2.42	28.39	46.00	17.61	Horizontal	Peak
907.37	26.46	2.62	29.08	46.00	16.92	Horizontal	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 1(400-480MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
64.05	40.88	-17.35	23.53	40.00	16.47	Vertical	Peak
80.93	45.13	-17.06	28.07	40.00	11.93	Vertical	Peak
203.44	35.91	-11.96	23.95	43.50	19.55	Vertical	Peak
759.25	27.06	0.58	27.64	46.00	18.36	Vertical	Peak
837.33	26.74	1.79	28.53	46.00	17.47	Vertical	Peak
945.78	26.55	3.12	29.67	46.00	16.33	Vertical	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.39	27.10	-5.70	21.40	40.00	18.60	Horizontal	Peak
273.96	31.05	-9.67	21.38	46.00	24.62	Horizontal	Peak
743.14	27.22	0.39	27.61	46.00	18.39	Horizontal	Peak
783.40	27.26	1.09	28.35	46.00	17.65	Horizontal	Peak
888.45	26.94	2.47	29.41	46.00	16.59	Horizontal	Peak
914.25	25.66	2.70	28.36	46.00	17.64	Horizontal	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 2(400.0125MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
80.83	45.20	-17.06	28.14	40.00	11.86	Vertical	Peak
117.49	34.36	-10.59	23.77	43.50	19.73	Vertical	Peak
204.60	36.41	-12.05	24.36	43.50	19.14	Vertical	Peak
273.96	34.30	-9.67	24.63	46.00	21.37	Vertical	Peak
789.70	27.68	1.11	28.79	46.00	17.21	Vertical	Peak
880.79	25.92	2.36	28.28	46.00	17.72	Vertical	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 2(440MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
31.55	26.16	-6.16	20.00	40.00	20.00	Horizontal	Peak
205.28	31.75	-12.10	19.65	43.50	23.85	Horizontal	Peak
273.96	30.41	-9.67	20.74	46.00	25.26	Horizontal	Peak
484.83	28.04	-3.61	24.43	46.00	21.57	Horizontal	Peak
688.73	27.42	-0.46	26.96	46.00	19.04	Horizontal	Peak
825.40	26.77	1.66	28.43	46.00	17.57	Horizontal	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 2(440MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
64.44	40.47	-17.31	23.16	40.00	16.84	Vertical	Peak
80.73	44.01	-17.06	26.95	40.00	13.05	Vertical	Peak
117.79	32.46	-10.53	21.93	43.50	21.57	Vertical	Peak
204.50	36.39	-12.04	24.35	43.50	19.15	Vertical	Peak
273.96	35.27	-9.67	25.60	46.00	20.40	Vertical	Peak
813.76	28.32	1.40	29.72	46.00	16.28	Vertical	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
32.04	26.25	-6.42	19.83	40.00	20.17	Horizontal	Peak
204.79	32.79	-12.06	20.73	43.50	22.77	Horizontal	Peak
273.96	33.79	-9.67	24.12	46.00	21.88	Horizontal	Peak
666.03	27.59	-0.72	26.87	46.00	19.13	Horizontal	Peak
808.81	27.22	1.36	28.58	46.00	17.42	Horizontal	Peak
838.50	27.63	1.80	29.43	46.00	16.57	Horizontal	Peak

Project No.: 2407A21468E-EM
Test Mode: Mode 2(479.9875MHz)
EUT Model: KG-915G
Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
Tested by: Jason Hu
Power Source: DC 8.4V from charger
(AC 120V/60Hz)




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
80.54	42.38	-17.06	25.32	40.00	14.68	Vertical	Peak
115.07	33.17	-10.89	22.28	43.50	21.22	Vertical	Peak
204.70	36.47	-12.06	24.41	43.50	19.09	Vertical	Peak
273.96	37.24	-9.67	27.57	46.00	18.43	Vertical	Peak
783.79	27.56	1.09	28.65	46.00	17.35	Vertical	Peak
825.98	26.61	1.67	28.28	46.00	17.72	Vertical	Peak

2) 1GHz~5GHz

Project No.: 2407A21468E-EM
 Test Mode: Mode 1(400-480MHz)
 EUT Model: KG-915G
 Test distance: 3m


Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)



Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2602.00	25.46	-2.69	22.77	54.00	31.23	horizontal	Average
2602.00	46.49	-2.69	43.80	74.00	30.20	horizontal	Peak
3101.20	25.55	-2.35	23.20	54.00	30.80	horizontal	Average
3101.20	46.91	-2.35	44.56	74.00	29.44	horizontal	Peak
3388.40	27.47	-2.92	24.55	54.00	29.45	horizontal	Average
3388.40	47.63	-2.92	44.71	74.00	29.29	horizontal	Peak
3494.80	27.62	-3.31	24.31	54.00	29.69	horizontal	Average
3494.80	47.34	-3.31	44.03	74.00	29.97	horizontal	Peak
4008.40	28.10	-3.60	24.50	54.00	29.50	horizontal	Average
4008.40	47.46	-3.60	43.86	74.00	30.14	horizontal	Peak
4131.60	26.54	-3.76	22.78	54.00	31.22	horizontal	Average
4131.60	46.16	-3.76	42.40	74.00	31.60	horizontal	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 1(400-480MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
1809.20	31.26	-11.01	20.25	54.00	33.75	vertical	Average
1809.20	51.91	-11.01	40.90	74.00	33.10	vertical	Peak
2620.40	25.85	-2.72	23.13	54.00	30.87	vertical	Average
2620.40	46.41	-2.72	43.69	74.00	30.31	vertical	Peak
3150.80	28.11	-2.25	25.86	54.00	28.14	vertical	Average
3150.80	47.83	-2.25	45.58	74.00	28.42	vertical	Peak
3236.80	27.83	-2.79	25.04	54.00	28.96	vertical	Average
3236.80	47.01	-2.79	44.22	74.00	29.78	vertical	Peak
3424.80	25.17	-2.90	22.27	54.00	31.73	vertical	Average
3424.80	46.59	-2.90	43.69	74.00	30.31	vertical	Peak
3995.60	27.98	-3.64	24.34	54.00	29.66	vertical	Average
3995.60	47.14	-3.64	43.50	74.00	30.50	vertical	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 2 (400.0125MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 ((AC 120V/60Hz))




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2167.20	27.42	-6.02	21.40	54.00	32.60	horizontal	Average
2167.20	47.92	-6.02	41.90	74.00	32.10	horizontal	Peak
2528.40	30.21	-3.16	27.05	54.00	26.95	horizontal	Average
2528.40	50.00	-3.16	46.84	74.00	27.16	horizontal	Peak
2889.60	26.18	-3.78	22.40	54.00	31.60	horizontal	Average
2889.60	46.76	-3.78	42.98	74.00	31.02	horizontal	Peak
3147.60	26.12	-2.25	23.87	54.00	30.13	horizontal	Average
3147.60	46.13	-2.25	43.88	74.00	30.12	horizontal	Peak
3442.00	26.12	-2.89	23.23	54.00	30.77	horizontal	Average
3442.00	46.60	-2.89	43.71	74.00	30.29	horizontal	Peak
3596.40	26.22	-3.71	22.51	54.00	31.49	horizontal	Average
3596.40	46.92	-3.71	43.21	74.00	30.79	horizontal	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 2(400.0125MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
1819.20	34.17	-10.96	23.21	54.00	30.79	vertical	Average
1819.20	54.82	-10.96	43.86	74.00	30.14	vertical	Peak
2528.00	29.05	-3.17	25.88	54.00	28.12	vertical	Average
2528.00	49.20	-3.17	46.03	74.00	27.97	vertical	Peak
2775.20	27.43	-4.12	23.31	54.00	30.69	vertical	Average
2775.20	47.28	-4.12	43.16	74.00	30.84	vertical	Peak
3052.00	26.24	-2.88	23.36	54.00	30.64	vertical	Average
3052.00	46.32	-2.88	43.44	74.00	30.56	vertical	Peak
3220.00	25.16	-2.54	22.62	54.00	31.38	vertical	Average
3220.00	46.00	-2.54	43.46	74.00	30.54	vertical	Peak
3548.80	26.22	-3.67	22.55	54.00	31.45	vertical	Average
3548.80	46.83	-3.67	43.16	74.00	30.84	vertical	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 2(440MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2005.60	28.52	-6.15	22.37	54.00	31.63	horizontal	Average
2005.60	48.35	-6.15	42.20	74.00	31.80	horizontal	Peak
2407.20	27.36	-4.61	22.75	54.00	31.25	horizontal	Average
2407.20	47.48	-4.61	42.87	74.00	31.13	horizontal	Peak
2663.20	26.19	-3.09	23.10	54.00	30.90	horizontal	Average
2663.20	46.32	-3.09	43.23	74.00	30.77	horizontal	Peak
2808.00	27.19	-4.03	23.16	54.00	30.84	horizontal	Average
2808.00	47.82	-4.03	43.79	74.00	30.21	horizontal	Peak
3230.40	26.24	-2.70	23.54	54.00	30.46	horizontal	Average
3230.40	46.83	-2.70	44.13	74.00	29.87	horizontal	Peak
3427.60	26.30	-2.90	23.40	54.00	30.60	horizontal	Average
3427.60	46.74	-2.90	43.84	74.00	30.16	horizontal	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 2(440MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2005.60	32.06	-6.15	25.91	54.00	28.09	vertical	Average
2005.60	52.93	-6.15	46.78	74.00	27.22	vertical	Peak
2620.40	26.35	-2.72	23.63	54.00	30.37	vertical	Average
2620.40	46.45	-2.72	43.73	74.00	30.27	vertical	Peak
2840.80	27.16	-3.92	23.24	54.00	30.76	vertical	Average
2840.80	47.27	-3.92	43.35	74.00	30.65	vertical	Peak
3146.40	27.03	-2.26	24.77	54.00	29.23	vertical	Average
3146.40	47.11	-2.26	44.85	74.00	29.15	vertical	Peak
3434.80	27.40	-2.91	24.49	54.00	29.51	vertical	Average
3434.80	47.56	-2.91	44.65	74.00	29.35	vertical	Peak
3580.40	27.15	-3.69	23.46	54.00	30.54	vertical	Average
3580.40	47.00	-3.69	43.31	74.00	30.69	vertical	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 2(479.9875MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2205.60	34.38	-5.70	28.68	54.00	25.32	horizontal	Average
2205.60	54.22	-5.70	48.52	74.00	25.48	horizontal	Peak
2449.60	27.59	-4.53	23.06	54.00	30.94	horizontal	Average
2449.60	47.19	-4.53	42.66	74.00	31.34	horizontal	Peak
2646.80	27.36	-2.74	24.62	54.00	29.38	horizontal	Average
2646.80	47.06	-2.74	44.32	74.00	29.68	horizontal	Peak
3088.00	28.15	-2.49	25.66	54.00	28.34	horizontal	Average
3088.00	48.79	-2.49	46.30	74.00	27.70	horizontal	Peak
3180.40	26.28	-2.24	24.04	54.00	29.96	horizontal	Average
3180.40	46.33	-2.24	44.09	74.00	29.91	horizontal	Peak
3441.60	26.21	-2.90	23.31	54.00	30.69	horizontal	Average
3441.60	46.98	-2.90	44.08	74.00	29.92	horizontal	Peak

Project No.: 2407A21468E-EM
 Test Mode: Mode 2 (479.9875MHz)
 EUT Model: KG-915G
 Test distance: 3m

Temp/Humi/ATM: 23.8°C/52%/100.1kPa
 Tested by: Jason Hu
 Power Source: DC 8.4V from charger
 (AC 120V/60Hz)



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2206.00	28.28	-5.70	22.58	54.00	31.42	vertical	Average
2206.00	48.37	-5.70	42.67	74.00	31.33	vertical	Peak
2332.00	26.15	-5.46	20.69	54.00	33.31	vertical	Average
2332.00	46.43	-5.46	40.97	74.00	33.03	vertical	Peak
2594.80	27.15	-2.70	24.45	54.00	29.55	vertical	Average
2594.80	47.10	-2.70	44.40	74.00	29.60	vertical	Peak
3088.40	28.58	-2.49	26.09	54.00	27.91	vertical	Average
3088.40	48.87	-2.49	46.38	74.00	27.62	vertical	Peak
3198.80	26.56	-2.24	24.32	54.00	29.68	vertical	Average
3198.80	46.66	-2.24	44.42	74.00	29.58	vertical	Peak
3448.80	26.36	-2.91	23.45	54.00	30.55	vertical	Average
3448.80	46.47	-2.91	43.56	74.00	30.44	vertical	Peak

FCC §15.121(b) – SCANNING RECEIVERS AND FREQUENCY CONVERTERS USED WITH SCANNING RECEIVERS


Applicable Standard

FCC §15.121(b).

(b) Except as provided in paragraph (c) of this section, scanning receivers shall reject any signals from the Cellular Radiotelephone Service frequency bands that are 38 dB or lower based upon a 12 dB SINAD measurement, which is considered the threshold where a signal can be clearly discerned from any interference that may be present.

Test Procedure

1. Connected the EUT as the below block diagram;



2. Apply a signal to the EUT antenna port at lowest, middle, highest channel frequencies of the operating band;
3. Adjust the audio output level of the EUT to it's rated value with the distortion less than 10%;
4. Adjust the 8920A output power to produce 12 dB SINAD without the audio output power dropping by more than 3 dB; These output level of the 8920A at each channel frequency is the sensitivity of the EUT;
5. Select the lowest or worst case sensitivity level for all of the bands as the reference sensitivity;
6. Adjust the Signal Generator output to a level of +60 dB above the reference sensitivity obtained in step 5 and its frequency to the frequency point in the Cellular Band;
7. Set the EUT squelch to threshold, the signal required to open the squelch must be lower than the reference sensitivity level;
8. Set the EUT in a scanning mode and allow it to scan through it's complete receiving range;
9. If the EUT un-squelched or stopped on any frequency, receiving at this frequency, then adjust the signal generator output level until 12 dB SINAD is produced, this level is the spurious value and the difference between the reference sensitivity and the spurious value is the rejection ratio and must be at least 38 dB;
10. Repeat above procedure at the frequencies 824, 836, 849 MHz for the mobile band, and 869, 881.5 and 894 MHz for the Cellular Base Band.

Test Data

Test Mode:	Scanning	Test Engineer:	Lucas Lin
Test Date:	2025-01-10	Test Result:	Pass

Environment Conditions:					
Temperature: (°C)	22.5	Relative Humidity: (%)	42	ATM Pressure: (kPa)	100.1

Scanning Frequency Range (MHz)	Test Frequency (MHz)	Measurement Result (Worst Case) (dB)	Limit (dB)
400-480	824, 836, 849 869, 881.5, 894	48	>38

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2407A21468E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2407A21468E-RF-INP EUT INTERNAL PHOTOGRAPHS

EXHIBIT B – TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2407A21468E-EM-TSP TEST SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95 % confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

*****END OF REPORT*****