

---

**FCC ID: 2BGFQ-Y5**

**Portable device**

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

EDR:

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.47	1.11	0 $\pm$ 1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	0.35	1.08	0 $\pm$ 1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	0.087	1.02	0 $\pm$ 1	1.00	1.26	<5	0.39651	3.00	YES
$\pi$ /4DQPSK	2.402	0.267	1.06	0 $\pm$ 1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	0.094	1.02	0 $\pm$ 1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	-0.412	0.91	0 $\pm$ 1	1.00	1.26	<5	0.39651	3.00	YES
8DQPSK	2.402	0.58	1.14	0 $\pm$ 1	1.00	1.26	<5	0.39023	3.00	YES
	2.441	0.385	1.09	0 $\pm$ 1	1.00	1.26	<5	0.39338	3.00	YES
	2.480	-0.135	0.97	0 $\pm$ 1	1.00	1.26	<5	0.39651	3.00	YES

**Conclusion:**

For the max result :  $0.39651 \leq$  FCC Limit 3.0 for 1g SAR.