

TÜV

Certificate No.: 3745.01

Report No: 709502402016-00C

MPE Calculation

Applicant:	Zhejiang Cainiao Supply Chain Management Co., Ltd.			
Address:	No.168 Wuchang Avenue, Wuchang Street, Yuhang District			
	Hangzhou China			
FCC ID:	2BGGH-CNR1			
Product:	UHF-RFID			
Model No.:	CNR1			
Reference RF report #	709502402016-00B			

According to subpart 15.247(i)and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)		
0.3–1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f²)	30		
30–300	27.5	0.073	0.2	30		
300–1,500	/	/	f/1500	30		
1,500–100,000	/	/	1.0	30		

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4 \pi R^2 = power density (in appropriate units, e.g. mW/cm²);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

EMC_SHA_F_R_02.06E



TÜV

Certificate No.: 3745.01

Report No: 709502402016-00C

Calculated Data

Maximum peak output power at antenna input terminal (dBm):	26.84
Maximum peak output power at antenna input terminal (mW):	483.05880
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	5.5
Maximum Antenna Gain (numeric):	3.5481
The worst case is power density at predication frequency at 20 cm (mW/cm²):	0.3410
MPE limit for general population exposure at prediction frequency (mW/cm²):	1.0

The max power density 0.3410 (mW/cm²) < 1 (mW/cm²)

Result: Compliant

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by: Prepared by: Tested by:

Hui TONG

Jiaxi XU

Cheng Huali

EMC Section Manager

EMC Project Engineer

EMC Test Engineer

Date: 2024-05-20 Date: 2024-05-20 Date: 2024-05-20