

## RF Exposure Evaluation

According to KDB 447498 D01 General RF Exposure Guidance v06 and part 2.1091, Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied.

### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### Test Result of RF Exposure Evaluation

	Modulation	Frequency MHz	Output power to antenna (dBm)	Target power W/tolerance (dBm)	Max Output power to antenna (dBm)	Max Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
WIFI 2.4G	802.11b	2412	15.59	15±1	16	39.811	0.0125	1.0	PASS
		2437	15.75	15±1	16	39.811	0.0125	1.0	PASS
		2462	15.82	15±1	16	39.811	0.0125	1.0	PASS
	802.11g	2412	14.16	14±1	15	31.623	0.0099	1.0	PASS
		2437	13.58	13±1	14	25.119	0.0079	1.0	PASS
		2462	13.74	13±1	14	25.119	0.0079	1.0	PASS
	802.11n (HT20)	2412	13.92	13±1	14	25.119	0.0079	1.0	PASS
		2437	13.85	13±1	14	25.119	0.0079	1.0	PASS
		2462	13.47	13±1	14	25.119	0.0079	1.0	PASS
	802.11n (HT40)	2422	12.96	12±1	13	19.953	0.0063	1.0	PASS
		2437	12.74	12±1	13	19.953	0.0063	1.0	PASS
		2452	12.88	12±1	13	19.953	0.0063	1.0	PASS

Remark: 1. wifi2.4G Antenna gain is 2.0dBi

The Max Calc. Thresholds : 0.0125≤ 1

So a SAR test is not required