

Maximum Permissible Exposure

RF Exposure Limit

According to KDB 447498D01 v06:

The 1g and 10g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$

$\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Device category	:	Portable device
Transmitting mode	:	Single transmitting
Max. transmitting frequency	:	2 480 MHz
Min. test separation distance	:	5 mm
Max. Antenna Gain	:	1.6 dBi
Max. Average power	:	1.49 dBm
Max. power with turn-up tolerance	:	2 dBm
		1.59 mW

Maximum Permissible Exposure

For this device:

$$1.0 \text{ mW} [\text{maximum average output power}] / 5 \text{ mm} [\text{minimum separation distance}] \times \sqrt{2.48 \text{ GHz}} \\ = 0.6$$

Note. The calculation result was rounded to one decimal place for comparison.

Test Result :

This is less than 3.0 for 1-g SAR.

SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.