

Test Report

Report No.: MTi240416006-01E1
Date of issue: 2024-05-15
Applicant: Vegepod LLC.
Product: WIFI EDK LED
Model(s): EDK-SM-36W , EDK-SM-18W
FCC ID: 2BGLP-EDK-SM-18W

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.cn>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.




Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Environmental Conditions	7
1.4	Description of support units	7
1.5	Measurement uncertainty	7
2	Summary of Test Result	8
3	Test Facilities and accreditations	9
3.1	Test laboratory	9
4	List of test equipment.....	10
5	Evaluation Results (Evaluation).....	12
5.1	Antenna requirement	12
6	Radio Spectrum Matter Test Results (RF)	13
6.1	Conducted Emission at AC power line	13
6.2	Occupied Bandwidth	18
6.3	Maximum Conducted Output Power.....	19
6.4	Power Spectral Density	20
6.5	RF conducted spurious emissions and band edge measurement	21
6.6	Band edge emissions (Radiated)	22
6.7	Radiated emissions (below 1GHz)	27
6.8	Radiated emissions (above 1GHz).....	33
	Photographs of the test setup	37
	Photographs of the EUT.....	38
	Appendix A: DTS Bandwidth	40
	Appendix B: Maximum conducted output power.....	45
	Appendix C: Maximum power spectral density.....	46
	Appendix D: Band edge measurements	51
	Appendix E: Conducted Spurious Emission	54
	Appendix F: Duty Cycle	66

Test Result Certification	
Applicant:	Vegepod LLC.
Address:	PO Box 2454, Misison Viejo, CA, 92690
Manufacturer:	Shenzhen Sunlight Lighting Co., Ltd.
Address:	Area B, 7 / F, Building 22, Shapuwei Community Entrepreneurial Industrial Zone, Songgang Street, Shenzhen, China
Product description	
Product name:	WIFI EDK LED
Trademark:	N/A
Model name:	EDK-SM-36W
Series Model(s):	EDK-SM-18W
Standards:	47 CFR Part 15.247
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02
Date of Test	
Date of test:	2024-04-20 to 2024-05-13
Test result:	Pass

Test Engineer	:	
		(Maleah Deng)
Reviewed By	:	
		(David Lee)
Approved By	:	
		(Leon Chen)

1 General Description

1.1 Description of the EUT

Product name:	WIFI EDK LED
Model name:	EDK-SM-36W
Series Model(s):	EDK-SM-18W
Model difference:	All the models are the same circuit and module, except the model name, lighting power, LED Light bar Length, power board, and shell size.
Electrical rating:	Input: 100-240Vac 50-60Hz Power: 36W
Accessories:	N/A
Hardware version:	V1.0
Software version:	V1.0
Test sample(s) number:	MTi240416006-01S1001 MTi240416006-01S1002
RF specification	
Operating frequency range:	802.11b/g/n20:2412~2462 MHz 802.11n40:2422~2452 MHz
Channel number:	11 channels for 20MHz bandwidth; 7 channels for 40MHz bandwidth
Modulation type:	IEEE 802.11b: DSSS (DBPSK, DQPSK, CCK) IEEE 802.11g/n (HT20/HT40) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna(s) type:	PCB Antenna
Antenna(s) gain:	1.82dBi

1.2 Description of test modes

No.	Emission test modes
Mode1	TX-802.11b
Mode2	TX-802.11g
Mode3	TX-802.11n(HT20)
Mode4	TX-802.11n(HT40)

1.2.1 Operation channel list

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Test Channel List

Bandwidth (MHz)	Lowest Channel (LCH) (MHz)	Middle Channel (MCH) (MHz)	Highest Channel (HCH) (MHz)
20	2412	2437	2462
40	2422	2437	2452

Note: The test software provided by manufacturer is used to control EUT for working in engineering mode, that enables selectable channel, and capable of continuous transmitting mode.

Test Software:

For power setting, refer to below table.

Software:	Beken WIFI Test Tool V1.6.0		
Mode	2412MHz	2437MHz	2462MHz
802.11b	15	15	15
802.11g	20	20	20
802.11n(HT20)	20	20	20
/	2422MHz	2437MHz	2452MHz
802.11n(HT40)	20	20	20

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

Support equipment list			
Description	Model	Serial No.	Manufacturer
/	/	/	/
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
RF output power, conducted	±1 dB
Power Spectral Density, conducted	±1 dB
Unwanted Emissions, conducted	±1 dB
Radiated spurious emissions (above 1GHz)	±5.3dB
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Requirement	Result
1	Antenna requirement	47 CFR 15.203	Pass
2	Conducted Emission at AC power line	47 CFR 15.207(a)	Pass
3	Occupied Bandwidth	47 CFR 15.247(a)(2)	Pass
4	Maximum Conducted Output Power	47 CFR 15.247(b)(3)	Pass
5	Power Spectral Density	47 CFR 15.247(e)	Pass
6	RF conducted spurious emissions and band edge measurement	47 CFR 15.247(d), 15.209, 15.205	Pass
7	Band edge emissions (Radiated)	47 CFR 15.247(d), 15.209, 15.205	Pass
8	Radiated emissions (below 1GHz)	47 CFR 15.247(d), 15.209, 15.205	Pass
9	Radiated emissions (above 1GHz)	47 CFR 15.247(d), 15.209, 15.205	Pass

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2024-03-20	2025-03-19
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2024-03-21	2025-03-20
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2024-03-20	2025-03-19
Emissions in non-restricted frequency bands Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2024-03-20	2025-03-19
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2024-03-21	2025-03-20
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2024-03-21	2025-03-20
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2024-03-21	2025-03-20
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2024-03-21	2025-03-20
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2024-03-21	2025-03-20
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2024-03-21	2025-03-20
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2024-03-20	2025-03-19
9	DC Power Supply	Agilent	E3632A	MY40027695	2024-03-21	2025-03-20
Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-04-25	2025-04-24
2	Double Ridged Broadband Horn Antenna	schwarabeck	BBHA 9120 D	2278	2023-06-17	2025-06-16
3	Amplifier	Agilent	8449B	3008A01120	2023-06-26	2024-06-25
4	Multi-device Controller	TuoPu	TPMDC	/	2024-05-04	2025-05-03
5	MXA signal analyzer	Agilent	N9020A	MY54440859	2023-06-01	2024-05-31
6	Horn antenna	Schwarzbeck	BBHA 9170	00987	2023-06-17	2025-06-16
7	Pre-amplifier	Space-Dtronics	EWLAN1840 G	210405001	2024-05-04	2025-05-03
8	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2024-04-25	2025-04-24
Emissions in frequency bands (below 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-04-25	2025-04-24
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2023-06-11	2025-06-10
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-04-25	2025-04-24

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
5	Multi-device Controller	TuoPu	TPMDC	/	2024-05-04	2025-05-03

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached.
The EUT complies with the requirement of FCC PART 15.203.

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2013 section 6.2		
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.9 °C	Humidity:	40.7 %	Atmospheric Pressure:	99 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1(AC 120V/60Hz)) is recorded in the report				


6.1.2 Test Setup Diagram:



6.1.3 Test Data:


Mode: EDK-SM-36W

Mode1(AC 120V/60Hz) / Line: Line/ Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1700	47.37	10.77	58.14	64.96	-6.82	QP	
2		0.1740	41.66	10.77	52.43	54.77	-2.34	AVG	
3		0.2300	40.31	9.18	49.49	52.45	-2.96	AVG	
4		0.2420	48.12	8.38	56.50	62.03	-5.53	QP	
5		0.2860	38.80	5.47	44.27	50.64	-6.37	AVG	
6		0.2900	48.94	5.19	54.13	60.52	-6.39	QP	
7		1.6980	36.22	14.26	50.48	56.00	-5.52	QP	
8		2.1580	29.22	10.85	40.07	46.00	-5.93	AVG	
9		2.6580	39.81	10.82	50.63	56.00	-5.37	QP	
10		4.3139	31.40	10.72	42.12	46.00	-3.88	AVG	
11		5.2579	44.34	10.66	55.00	60.00	-5.00	QP	
12	*	5.3900	38.75	10.65	49.40	50.00	-0.60	AVG	


Mode1(AC 120V/60Hz) / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1780	49.33	10.77	60.10	64.58	-4.48	QP	
2	*	0.1780	42.11	10.77	52.88	54.58	-1.70	AVG	
3		0.2300	40.11	9.18	49.29	52.45	-3.16	AVG	
4		0.2340	47.51	8.92	56.43	62.31	-5.88	QP	
5		0.2860	48.80	5.47	54.27	60.64	-6.37	QP	
6		0.2860	39.28	5.47	44.75	50.64	-5.89	AVG	
7		1.0780	34.83	13.04	47.87	56.00	-8.13	QP	
8		1.0780	26.87	13.04	39.91	46.00	-6.09	AVG	
9		2.1580	36.00	10.85	46.85	56.00	-9.15	QP	
10		2.1580	29.60	10.85	40.45	46.00	-5.55	AVG	
11		4.8540	31.85	10.68	42.53	46.00	-3.47	AVG	
12		5.3940	40.98	10.65	51.63	60.00	-8.37	QP	


Mode: EDK-SM-18W

Mode1(AC 120V/60Hz) / Line: Line/ Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1740	50.03	10.38	60.41	64.77	-4.36	QP	
2	*	0.1740	42.31	10.38	52.69	54.77	-2.08	AVG	
3		0.2300	37.87	10.85	48.72	52.45	-3.73	AVG	
4		0.2380	45.47	10.88	56.35	62.17	-5.82	QP	
5		0.2860	42.67	11.01	53.68	60.64	-6.96	QP	
6		0.2860	33.02	11.01	44.03	50.64	-6.61	AVG	
7		1.0780	34.74	12.78	47.52	56.00	-8.48	QP	
8		1.0780	26.95	12.78	39.73	46.00	-6.27	AVG	
9		2.1580	29.96	10.63	40.59	46.00	-5.41	AVG	
10		4.3140	30.59	10.65	41.24	46.00	-4.76	AVG	
11		4.3180	37.90	10.65	48.55	56.00	-7.45	QP	
12		5.3859	41.53	10.66	52.19	60.00	-7.81	QP	

Mode1(AC 120V/60Hz) / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1740	41.95	10.38	52.33	54.77	-2.44	AVG	
2		0.1780	48.82	10.37	59.19	64.58	-5.39	QP	
3		0.2300	38.13	10.85	48.98	52.45	-3.47	AVG	
4		0.2420	44.78	10.88	55.66	62.03	-6.37	QP	
5		0.2860	42.74	11.01	53.75	60.64	-6.89	QP	
6		0.2860	33.02	11.01	44.03	50.64	-6.61	AVG	
7		1.0780	34.31	12.78	47.09	56.00	-8.91	QP	
8		1.0780	26.52	12.78	39.30	46.00	-6.70	AVG	
9		2.1580	35.17	10.63	45.80	56.00	-10.20	QP	
10		2.1580	29.77	10.63	40.40	46.00	-5.60	AVG	
11		5.3900	42.29	10.66	52.95	60.00	-7.05	QP	
12	*	5.3900	37.43	10.66	48.09	50.00	-1.91	AVG	


6.2 Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2013, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	a) Set RBW = 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.9 °C	Humidity:	40.7 %	Atmospheric Pressure:	99 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.2.2 Test Setup Diagram:



6.2.3 Test Data:

Please Refer to Appendix for Details.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2013, section 11.9.1.3 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.9.1.3 Maximum peak conducted output power

6.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.9 °C	Humidity:	40.7 %	Atmospheric Pressure:	99 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.3.2 Test Setup Diagram:



6.3.3 Test Data:

Please Refer to Appendix for Details.


6.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2013, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013, section 11.10, Maximum power spectral density level in the fundamental emission

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.9 °C	Humidity:	40.7 %	Atmospheric Pressure:	99 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.4.2 Test Setup Diagram:



6.4.3 Test Data:

Please Refer to Appendix for Details.


6.5 RF conducted spurious emissions and band edge measurement

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2013 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2013 Section 11.11.1, Section 11.11.2, Section 11.11.3

6.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	25.9 °C	Humidity:	40.7 %	Atmospheric Pressure:	99 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	Mode1, Mode2, Mode3, Mode4				

6.5.2 Test Setup Diagram:



6.5.3 Test Data:

Please Refer to Appendix for Details.


6.6 Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2013 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.10.5.2		

6.6.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	54 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode3, Mode4) is recorded in the report				
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.					

6.6.2 Test Setup Diagram:



6.6.3 Test Data:

Mode3 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	52.92	-12.92	40.00	74.00	-34.00	peak
2		2310.000	43.64	-12.92	30.72	54.00	-23.28	AVG
3		2390.000	73.90	-12.49	61.41	74.00	-12.59	peak
4	*	2390.000	58.02	-12.49	45.53	54.00	-8.47	AVG

Mode3 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	52.90	-12.92	39.98	74.00	-34.02	peak
2		2310.000	42.61	-12.92	29.69	54.00	-24.31	AVG
3		2390.000	62.70	-12.49	50.21	74.00	-23.79	peak
4	*	2390.000	47.52	-12.49	35.03	54.00	-18.97	AVG

Mode3 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	64.67	-12.50	52.17	74.00	-21.83	peak
2	*	2483.500	53.24	-12.50	40.74	54.00	-13.26	AVG
3		2500.000	56.94	-12.41	44.53	74.00	-29.47	peak
4		2500.000	47.98	-12.41	35.57	54.00	-18.43	AVG

Mode3 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	54.96	-12.50	42.46	74.00	-31.54	peak
2	*	2483.500	44.93	-12.50	32.43	54.00	-21.57	AVG
3		2500.000	52.94	-12.41	40.53	74.00	-33.47	peak
4		2500.000	44.32	-12.41	31.91	54.00	-22.09	AVG

Mode4 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 40 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	53.42	-12.92	40.50	74.00	-33.50	peak
2		2310.000	43.79	-12.92	30.87	54.00	-23.13	AVG
3		2390.000	69.46	-12.49	56.97	74.00	-17.03	peak
4	*	2390.000	58.02	-12.49	45.53	54.00	-8.47	AVG

Mode4 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 40 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2310.000	50.24	-12.92	37.32	74.00	-36.68	peak
2		2310.000	41.24	-12.92	28.32	54.00	-25.68	AVG
3		2390.000	60.23	-12.49	47.74	74.00	-26.26	peak
4	*	2390.000	48.36	-12.49	35.87	54.00	-18.13	AVG

Mode4 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 40 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	70.71	-12.50	58.21	74.00	-15.79	peak
2	*	2483.500	57.28	-12.50	44.78	54.00	-9.22	AVG
3		2500.000	59.60	-12.41	47.19	74.00	-26.81	peak
4		2500.000	49.81	-12.41	37.40	54.00	-16.60	AVG

Mode4 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 40 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		2483.500	59.77	-12.50	47.27	74.00	-26.73	peak
2	*	2483.500	49.12	-12.50	36.62	54.00	-17.38	AVG
3		2500.000	53.25	-12.41	40.84	74.00	-33.16	peak
4		2500.000	43.57	-12.41	31.16	54.00	-22.84	AVG


6.7 Radiated emissions (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	54 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				
Note: The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.					

6.7.2 Test Setup Diagram:






6.7.3 Test Data:


Mode: EDK-SM-36W

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		72.0843	42.00	-11.27	30.73	40.00	-9.27	QP	
2		155.9101	46.26	-10.28	35.98	43.50	-7.52	QP	
3		239.9874	44.34	-6.89	37.45	46.00	-8.55	QP	
4		372.0045	42.75	-4.58	38.17	46.00	-7.83	QP	
5		541.3725	39.58	-3.17	36.41	46.00	-9.59	QP	
6	*	721.7259	38.61	0.47	39.08	46.00	-6.92	QP	


Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	59.8588	42.95	-9.79	33.16	40.00	-6.84	QP	
2		143.8295	40.18	-10.56	29.62	43.50	-13.88	QP	
3		239.9874	41.51	-6.89	34.62	46.00	-11.38	QP	
4		300.3672	37.67	-4.75	32.92	46.00	-13.08	QP	
5		444.8514	42.93	-4.27	38.66	46.00	-7.34	QP	
6		721.7259	34.47	0.47	34.94	46.00	-11.06	QP	


Mode: EDK-SM-18W

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	77.3212	41.19	-17.50	23.69	40.00	-16.31	QP	
2	116.5401	36.60	-14.17	22.43	43.50	-21.07	QP	
3	132.6850	40.33	-16.00	24.33	43.50	-19.17	QP	
4	178.1327	50.28	-14.98	35.30	43.50	-8.20	QP	
5 *	207.1226	50.01	-12.51	37.50	43.50	-6.00	QP	
6	313.2760	44.68	-9.79	34.89	46.00	-11.11	QP	

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		37.8121	43.07	-14.09	28.98	40.00	-11.02	QP	
2		76.7808	49.48	-17.42	32.06	40.00	-7.94	QP	
3		114.5146	36.20	-14.08	22.12	43.50	-21.38	QP	
4	*	184.4898	53.68	-14.68	39.00	43.50	-4.50	QP	
5		207.1226	50.00	-12.51	37.49	43.50	-6.01	QP	
6		313.2760	35.12	-9.79	25.33	46.00	-20.67	QP	


6.8 Radiated emissions (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2013 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2013 section 6.6.4		

6.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	24 °C	Humidity:	54 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode1) is recorded in the report				
Note: Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported. All modes of operation of the EUT were investigated, and only the worst-case results are reported.					

6.8.2 Test Setup Diagram:



6.8.3 Test Data:

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	62.62	-7.75	54.87	74.00	-19.13	peak
2	*	4824.000	54.96	-7.75	47.21	54.00	-6.79	AVG
3		7236.000	46.82	0.61	47.43	74.00	-26.57	peak
4		7236.000	39.71	0.61	40.32	54.00	-13.68	AVG
5		9648.000	50.33	1.99	52.32	74.00	-21.68	peak
6		9648.000	43.28	1.99	45.27	54.00	-8.73	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4824.000	60.12	-7.75	52.37	74.00	-21.63	peak
2	*	4824.000	53.13	-7.75	45.38	54.00	-8.62	AVG
3		7236.000	46.30	0.61	46.91	74.00	-27.09	peak
4		7236.000	39.13	0.61	39.74	54.00	-14.26	AVG
5		9648.000	47.39	1.99	49.38	74.00	-24.62	peak
6		9648.000	40.37	1.99	42.36	54.00	-11.64	AVG

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4874.000	63.07	-7.83	55.24	74.00	-18.76	peak
2	*	4874.000	57.18	-7.83	49.35	54.00	-4.65	AVG
3		7311.000	46.69	0.53	47.22	74.00	-26.78	peak
4		7311.000	40.73	0.53	41.26	54.00	-12.74	AVG
5		9748.000	50.08	2.55	52.63	74.00	-21.37	peak
6		9748.000	43.80	2.55	46.35	54.00	-7.65	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4874.000	62.56	-7.83	54.73	74.00	-19.27	peak
2	*	4874.000	56.48	-7.83	48.65	54.00	-5.35	AVG
3		7311.000	46.98	0.53	47.51	74.00	-26.49	peak
4		7311.000	40.82	0.53	41.35	54.00	-12.65	AVG
5		9748.000	48.36	2.55	50.91	74.00	-23.09	peak
6		9748.000	42.29	2.55	44.84	54.00	-9.16	AVG

Mode1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	58.80	-7.83	50.97	74.00	-23.03	peak
2	*	4924.000	52.69	-7.83	44.86	54.00	-9.14	AVG
3		7386.000	46.68	0.86	47.54	74.00	-26.46	peak
4		7386.000	40.50	0.86	41.36	54.00	-12.64	AVG
5		9848.000	47.81	2.14	49.95	74.00	-24.05	peak
6		9848.000	41.55	2.14	43.69	54.00	-10.31	AVG

Mode1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		4924.000	57.10	-7.83	49.27	74.00	-24.73	peak
2		4924.000	50.95	-7.83	43.12	54.00	-10.88	AVG
3		7386.000	46.81	0.86	47.67	74.00	-26.33	peak
4		7386.000	40.70	0.86	41.56	54.00	-12.44	AVG
5		9848.000	47.96	2.14	50.10	74.00	-23.90	peak
6	*	9848.000	42.21	2.14	44.35	54.00	-9.65	AVG

Photographs of the test setup

Refer to Appendix - Test Setup Photos

Photographs of the EUT

Refer to Appendix - EUT Photos

Appendix

Appendix A: DTS Bandwidth

Test Result

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	11.040	0.5	PASS
		2437	10.720	0.5	PASS
		2462	11.000	0.5	PASS
11G	Ant1	2412	16.280	0.5	PASS
		2437	17.560	0.5	PASS
		2462	17.120	0.5	PASS
11N20SISO	Ant1	2412	17.600	0.5	PASS
		2437	15.680	0.5	PASS
		2462	16.840	0.5	PASS
11N40SISO	Ant1	2422	35.760	0.5	PASS
		2437	35.440	0.5	PASS
		2452	30.960	0.5	PASS

Test Graphs





11G Ant1 2437



11G Ant1 2462



11N20SISO Ant1 2412




11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



11N40SISO_Ant1_2422



Appendix B: Maximum conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Peak Power [dBm]	Conducted Limit [dBm]	Verdict
11B	Ant1	2412	13.62	≤30.00	PASS
		2437	14.01	≤30.00	PASS
		2462	13.30	≤30.00	PASS
11G	Ant1	2412	12.50	≤30.00	PASS
		2437	12.17	≤30.00	PASS
		2462	12.08	≤30.00	PASS
11N20SISO	Ant1	2412	11.87	≤30.00	PASS
		2437	12.00	≤30.00	PASS
		2462	11.65	≤30.00	PASS
11N40SISO	Ant1	2422	13.16	≤30.00	PASS
		2437	12.54	≤30.00	PASS
		2452	11.74	≤30.00	PASS


Appendix C: Maximum power spectral density


Test Result


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3-100kHz]	Limit [dBm/3kHz]	Verdict
11B	Ant1	2412	-13.51	≤8.00	PASS
		2437	-12.30	≤8.00	PASS
		2462	-13.06	≤8.00	PASS
11G	Ant1	2412	-18.81	≤8.00	PASS
		2437	-19.23	≤8.00	PASS
		2462	-19.31	≤8.00	PASS
11N20SISO	Ant1	2412	-12.56	≤8.00	PASS
		2437	-14.21	≤8.00	PASS
		2462	-18.46	≤8.00	PASS
11N40SISO	Ant1	2422	-22.76	≤8.00	PASS
		2437	-21.21	≤8.00	PASS
		2452	-22.52	≤8.00	PASS

Test Graphs










Appendix D: Band edge measurements


11B Ant1 Low 2412




11B Ant1 High 2462



11G Ant1 Low 2412




11G Ant1 High 2462




11N20SISO Ant1 Low 2412




11N20SISO Ant1 High 2462





11N40SISO Ant1 Low 2422





Appendix E: Conducted Spurious Emission
































Appendix F: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Factor
11B	Ant1	2437	8.38	43.35	19.33	7.14
11G	Ant1	2437	1.39	13.98	9.94	10.03
11N20SISO	Ant1	2437	1.29	13.05	9.89	10.05
11N40SISO	Ant1	2437	0.65	6.54	9.94	10.03


Notes:

Duty Cycle [%] = Transmission Duration [ms] / Transmission Period [ms] * 100

Factor = $10 * \log (\text{Duty Cycle})$

Test Graphs





----End of Report----