



Shenzhen Lejin radio frequency technology Co., LTD

SPECIFICATIONS FOR APPROVAL

Customer Name: _____

Product Name: 2.4GHz Antenna

Product Model: _____

Part Number: LJW01-17091602-R0A

Write By : Huxuwen

Issued Date: 2021-04-08

CUSTOMER

ENGINEER R&D DEPT	BUSSINESS DEPT	APPROVAL

LEJIN

R&D DEPT	ENGINEER DEPT	APPROVAL

REV	MODIFIED DESCRIPTION	DATE	REMARK
V1.0	Initial Draft Release	2021/04/08	



Index

1. Cover	1
2. Index	2
3. Product Specification	3
4. Test Equipment & Conditions	3
5. Test Report	4
6. Reliability Test	5
7. Assemble type	6
8. Product Drawing	8

3.Product Specification

A. Electrical Characteristics	
Frequency	2400MHz ~2500 MHz
VSWR	<2.0
Efficiency	>40%
Impedance	50Ohm
Polarization	Linear
Gain	≤1.65dBi
B. Material & Mechanical Characteristics	
Material of Radiator	Metal
Cable Type	N/A
Connector Type	N/A
Dimension	19.0*3.50*3.75(H)mm
C. Environmental	
Operation Temperature	- 20 °C ~ + 70 °C
Storage Temperature	- 30 °C ~ + 85 °C
Humidity	40%~95%

4.Test Equipment & Conditions

- 1.Network Analyzers Agilent 8753D/5071C
- 2.HSPA and LTE protocol test set R&S CMW500 -PT
- 3.Communications Test Set Agilent 8960
- 4.3D Chamber Test System




Chart 1 Test topology

5.Test Report

5.1 Voltage Standing Wave Ratio(VSWR).





Chart 2 VSWR

5.2 Efficient and gain.

Passive	Freq(MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500
Test For WIFI 2.4G	Effi(%)	42.62	46.84	51.47	55.07	53.54	48.06	51.80	49.38	44.21	42.77	40.64
	Gain(dBi)	1.47	1.44	1.56	1.65	1.54	1.09	1.62	1.59	1.62	1.37	0.36

5.3 Radiation pattern.






6. Reliability Test


Test Item		Test condition	Equipment	Specification	Result
1	Low Temp. Storage Test	Temperature: -30℃ , Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-down the temp. to -30℃ in one hour, store antenna for 44 hours; step-up temp to 25℃, test antenna after 2 hours.	Temp.&Hum. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
2	High Temp./High Humid Storage Test	Temperature: 85℃ Humidity: 85% RH Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25℃ and humidity is 65% for one hour, then step-up the temp. to 80℃ and the humidity up to 85% in one hour, store antenna for 44 hours; step-down temp to 25℃ ,test antenna after 2 hours.	Temp.&Hum. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
3	Salt-Spray 6 pray Test	Placing antenna in the Salt-Spray Tester ,set the test condition , Temp: 35±2℃ Humidity: 85% NaCl salt spray :5±1%.PH value :6.5~7.2 Testtime:24hours	Salt-Spray Tester	No color change No appear rusting	PASS

7. Assemble type(omitted)

8. Product Drawing



尺寸

三视图	符号	尺寸(mm)
 The three-view drawing shows the front, top, and side views of the component. The front view is a rectangle with a black center and gray sides, with dimensions $a=0.5\text{mm}$, $W=1.7\text{mm}$, and $L=3.3\text{mm}$. The top view is a rectangle with a black center and gray sides, with dimensions $L=3.3\text{mm}$ and $T=1.2\text{mm}$. The side view is a rectangle with a black center and gray sides, with dimensions $T=1.2\text{mm}$ and $a=0.5\text{mm}$.	L	3.3 ± 0.2
	w	1.7 ± 0.1
	T	1.2 ± 0.1
	a	0.5 ± 0.1