



# Aibo Standard Technology (Shenzhen) Co., Ltd.

101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China  
Tel.: +(86) 0755 85250797    E-mail: [Aibonorm@aibonorm.com](mailto:Aibonorm@aibonorm.com)    Website: [www.Aibonorm.com](http://www.Aibonorm.com)

## FCC TEST REPORT

Report No.....	AB25080072FW02
FCC ID.....	<b>2BGNG-SYITRENN200</b>
Applicant.....	Shenzhen Round Technology Co., Ltd
Address.....	502, No.18-1 Fuxin Road, Central Community, Pingdi Street, Longgang District, Shenzhen
Manufacturer.....	Shenzhen Round Technology Co., Ltd
Address.....	502, No.18-1 Fuxin Road, Central Community, Pingdi Street, Longgang District, Shenzhen
Product Name.....	BLUETOOTH SPEAKER
Trade Mark.....	syitren
Test Model.....	Syitren N200
Additional Model(s).....	/
Standard.....	FCC 47 CFR §1.1310; FCC 47 CFR §2.1093 KDB 447498 D01 General RF Exposure Guidance v06
Date of Receipt.....	2025.08.28
Date of Test Date.....	2025.08.29-2025.09.11
Date of Issue.....	2025.09.11
Test Result.....	Pass

Compiled by: (Printed Name + Signature)	Huajie Li	
Supervised by: (Printed Name + Signature)	David Huang	
Approved by: (Printed Name + Signature)	Jay Liu	

Testing Laboratory Name.....	Aibo Standard Technology (Shenzhen) Co., Ltd.
Address.....	101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

## FCC TEST REPORT

EUT.....	: BLUETOOTH SPEAKER
Test Model.....	: Syitren N200
<b>Applicant</b> .....	: Shenzhen Round Technology Co., Ltd
Address.....	: 502, No.18-1 Fuxin Road, Central Community, Pingdi Street, Longgang District, Shenzhen
<b>Manufacturer</b> .....	: Shenzhen Round Technology Co., Ltd
Address.....	: 502, No.18-1 Fuxin Road, Central Community, Pingdi Street, Longgang District, Shenzhen
<b>Factory</b> .....	: Shenzhen Round Technology Co., Ltd
Address.....	: 502, No.18-1 Fuxin Road, Central Community, Pingdi Street, Longgang District, Shenzhen

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**REPORT VERSION**

Version No.	Issue Date	Description
01	2025.09.11	Initial Issue

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. GENERAL DESCRIPTION OF EUT .....	5
1.2. DESCRIPTION OF TEST FACILITY .....	6
<b>2. RF EXPOSURE EVALUATION .....</b>	<b>7</b>
2.1 LIMIT .....	7
2.2 EVALUATION RESULT .....	8
2.3 CONCLUSION .....	8

## 1. GENERAL INFORMATION

### 1.1. GENERAL DESCRIPTION OF EUT

Product Name:	BLUETOOTH SPEAKER
Trade Mark:	syitren
Test Model:	Syitren N200
Additional Model(s):	/
Hardware Version:	/
Software Version:	/
Power Supply:	DC 3.7V supply by battery(2000mAh)
EUT Supports Function: (Provided by the customer)	2.4GHz ISM Bands:
Test Sample(s) Number:	AB25080072-01 (Engineer Sample)

#### Radio Specification Subject to this Report

Frequency Range:	2402MHz~2480MHz
Modulation Type:	GFSK,π/4 DQPSK, 8DPSK
Channel Spacing:	1MHz for BR
Channel Number(s):	79 for BR
Antenna Type:	Internal Antenna
Antenna Gain:	-0.58dBi(Max.)

## 1.2. DESCRIPTION OF TEST FACILITY

**Test Lab:** Aibo Standard Technology (Shenzhen) Co., Ltd.

**Address:** 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: Aibonorm@aibonorm.com

Website: [www.Aibonorm.com](http://www.Aibonorm.com)

The test facility is recognized, certified, or accredited by the following organizations:

### **A2LA-Lab Certificate No.: 7514.01**

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### **FCC Accredited Lab.**

Designation Number: CN1411

Test Firm Registration Number: 567066

### **ISED Wireless Device Testing Laboratories**

CAB identifier: CN0185

## 2. RF EXPOSURE EVALUATION

### 2.1 Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.<sup>22</sup> The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.<sup>23</sup> "

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})]$   $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f$  (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

## 2.2 Evaluation Result

Band/ Mode	f (GHz)	Evaluation Distance (mm)	RF Output Power (dBm)	Tolerance (dBm)	Max Tune-up Power(dBm)	Max. Tune-up Power(mW)	Calc. thresholds	SAR Test Exclusion Threshold
BR+EDR	2480	5	1.43	1( $\pm 1$ )	2	1.58	0.4991785	3.0

## 2.3 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01 v06. No SAR test is required.

\*\*\*\*\*THE END\*\*\*\*\*