



TEST REPORT



Report No. : RF-230632

Page 1 / 33

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

■ FCC TEST REPORT

1. Client

- Name : The Little Cat. Co., Ltd.
- Address : Douzone BI center, 130, Beodeul 1-gil, Namsan-myeon, Chuncheon-si, Gangwon-do, Republic of Korea

2. Sample Description

- Product item : INPET
- Model name : INPET CV1
- Manufacturer etc. : The Little Cat. Co., Ltd.

3. Date of test : 2024.03.20 ~ 2024.03.27

p

4. Location of Test : Permanent Testing Lab On Site Testing

- Address : 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea

5. Test method used : Part 15 Subpart C 15.247

6. Test result : PASS

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

This laboratory is not accredited for the test results marked*.

This test report is not related to KOLAS accreditation.

| | | |
|-------------|--|--|
| Affirmation | Tested by Name : Bong-Seok Kim (Signature) | Technical Manager Name : Yeong-Jun Cho (Signature) |
|-------------|--|--|

2024. 07. 03.

KES Co., Ltd.

Accredited by KOLAS, Republic of KOREA



REPORT REVISION HISTORY

| Date | Test Report No. | Revision History |
|-------------|-----------------|------------------|
| 2024.07.03. | RF-230632 | Initial |
| | | |
| | | |
| | | |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

Use of uncertainty of measurement for decisions on conformity (decision rule):

- No decision rule is specified by the standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty("simple acceptance" decision rule, previously known as "accuracy method").
- Other (to be specified, for example when required by the standard or client)



TABLE OF CONTENTS

| | | |
|------|--|----|
| 1. | General information | 4 |
| 1.1. | EUT description | 4 |
| 1.2. | Test configuration..... | 5 |
| 1.3. | Information about derivative model | 5 |
| 1.4. | Accessory information | 5 |
| 1.5. | Sample calculation | 5 |
| 1.6. | Measurement Uncertainty | 5 |
| 1.7. | Frequency/channel operations | 6 |
| 2. | Summary of tests | 7 |
| 3. | Test results | 8 |
| 3.1. | Output power | 8 |
| 3.2. | Radiated restricted band and emissions | 10 |
| 3.3. | AC conducted emissions | 30 |
| 3.4. | Antenna Requirement..... | 32 |
| | Appendix A. Measurement equipment..... | 33 |



1. General information

Applicant: The Little Cat. Co., Ltd.
Applicant address: Douzone BI center, 130, Beodeul 1-gil, Namsan-myeon, Chuncheon-si, Gangwon-do, Republic of Korea
Test site: KES Co., Ltd.
Test site address: #3002, #3503, #3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, Korea
Test Facility FCC Accreditation Designation No.: KR0100, Registration No.: 444148
FCC rule part(s): FCC: 15.247
FCC ID: 2BGOV-INPETCV1
Test device serial No.: Production Pre-production Engineering

1.1. EUT description

Equipment under test INPET
Frequency range 2 402 MHz ~ 2 480 MHz (LE 1,2 Mbps)
Model INPET CV1
Modulation technique GFSK
Number of channels 2 402 MHz ~ 2 480 MHz (LE 1,2 Mbps) : 40 ch
Antenna specification PCB Antenna // Peak gain: -6.96 dBi
Power source AC 120 V (Adapter Output DC 5 V)
H/W Version V.1.0
S/W Version V.1.0



1.2. Test configuration

The The Little Cat. Co., Ltd. / INPET / INPET CV1 / FCC ID:2BGOV-INPETCV1 was tested according to the specification of EUT, the EUT must comply with following standards and KDB documents.

FCC Part 15.247
KDB 558074 D01 v05 r02
ANSI C63.10-2013

1.3. Information about derivative model

N/A

1.4. Accessory information

| Equipment | Manufacturer | Model | Serial No. | Power source |
|-----------|--------------|-------|------------|--------------|
| - | - | - | - | - |

1.5. Sample calculation

Where relevant, the following sample calculation is provided
For all conducted test items :

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.77 + 10 = 10.77 \text{ (dB)}\end{aligned}$$

For Radiation test :

Field strength level ($\text{dB}_{\mu\text{V}/\text{m}}$) = Measured level ($\text{dB}_{\mu\text{V}}$) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)

1.6. Measurement Uncertainty

| Test Item | Uncertainty | |
|---|----------------------------|--------------------|
| Uncertainty for Conduction emission test | 2.22 dB (SHIELD ROOM #6) | |
| Uncertainty for Radiation emission test (include Fundamental emission) | Below 1GHz | 4.04 dB (SAC #6) |
| | Above 1GHz | 5.32 dB (SAC #5) |
| Note. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. | | |



1.7. Frequency/channel operations

| Ch. | Frequency (MHz) | Rate(Mbps) |
|-----|-----------------|-------------|
| 00 | 2 402 | LE 1,2 Mbps |
| : | : | : |
| 20 | 2 442 | LE 1,2 Mbps |
| : | : | : |
| 39 | 2 480 | LE 1,2 Mbps |



2. Summary of tests

| Section in FCC Part 15 | Test description | Test results |
|------------------------|---|-------------------------|
| 15.247(a)(2) | 6 dB bandwidth | N/T ^{note(1)} |
| 15.247(b)(3) | Output power | Pass |
| 15.247(e) | Power spectral density | N/T ^{note(1)} |
| 15.205 15.209 | Radiated restricted band and emission | Pass |
| 15.247(d) | Conducted spurious emission and band edge | N/T ^{note(1)} |
| 15.207(a) | AC Conducted emissions | Pass |
| 15.203 | Antenna Requirement | Pass ^{note(2)} |

N/T: Not Tested

Note.

1. This product is equipped with an approved module, please refer to Module Report below for details.
Report No. : T200824W09-RP

2..Please check the antenna spec. for the Antenna Requirement.

3. The Power Setting values for the EUT are as follows:

LE 1 Mbps: 5 dBm

LE 2 Mbps: 5 dBm




3. Test results

3.1. Output power

Test procedure

ANSI C63.10-2013 - Section 11.9.1.3 and 11.9.2.3.2

Test setup



ANSI C63.10-2013 - Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

ANSI C63.10-2013 - Section 11.9.2.3.2

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

Limit

According to §15.247(b)(3), For systems using digital modulation in the 902~928 MHz, 2 400~2 483.5 MHz, and 5 725~5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted out-put power. Maximum Conducted Out-put Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

**Test results**


| Mode | 2 402 MHz | | 2 442 MHz | | 2 480 MHz | |
|-----------|---------------|------------|---------------|------------|---------------|------------|
| | Average (dBm) | Peak (dBm) | Average (dBm) | Peak (dBm) | Average (dBm) | Peak (dBm) |
| LE 1 Mbps | 3.10 | 3.22 | 3.24 | 3.34 | 3.26 | 3.36 |
| LE 2 Mbps | 3.07 | 3.16 | 3.17 | 3.27 | 3.25 | 3.35 |




3.2. Radiated restricted band and emissions

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz emissions.





The diagram below shows the test setup that is utilized to make the measurements for emission from 1 GHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz emissions, whichever is lower.



Test procedure

Radiated emissions from the EUT were measured according to the dictates in section 11.11 & 11.12 of ANSI C63.10-2013.

Test procedure below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel, ground parallel and perpendicular of the antenna are set to make the measurement. It was determined that parallel was worst-case orientation; therefore, all final radiated testing was performed with the EUT in parallel.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum hold mode.

Test procedure above 30 MHz ~ 1 000 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**Test procedure above 1 000 MHz**

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The antenna is a bi-log antenna, a horn antenna, and its height are varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
5. Spectrum analyzer settings for $f < 1 \text{ GHz}$:
 - ① Span = wide enough to fully capture the emission being measured
 - ② RBW = 100 kHz
 - ③ VBW \geq RBW
 - ④ Detector = quasi peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
6. Spectrum analyzer settings for $f \geq 1 \text{ GHz}$: Peak
 - ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
 - ② RBW = 1 MHz
 - ③ VBW \geq 3 MHz
 - ④ Detector = peak
 - ⑤ Sweep time = auto
 - ⑥ Trace = max hold
 - ⑦ Trace was allowed to stabilize

7. Spectrum analyzer settings for $f \geq 1 \text{ GHz}$: Average

- ① Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- ② RBW = 1 MHz
- ③ VBW $\geq 3 \times$ RBW
- ④ Detector = RMS, if span/(# of points in sweep) \leq (RBW/2). Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- ⑤ Averaging type = power(i.e., RMS)
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- ⑥ Sweep = auto
- ⑦ Trace = max hold
- ⑧ Perform a trace average of at least 100 traces. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step ⑤, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step ⑤, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

**Note.**

1. $f < 30 \text{ MHz}$, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$
2. $f \geq 30 \text{ MHz}$, extrapolation factor of 20 dB/decade of distance. $F_d = 20 \log(D_m/D_s)$

Where:

F_d = Distance factor in dB

D_m = Measurement distance in meters

D_s = Specification distance in meters

2. Field strength(dB μ V/m) = Level(dB μ V) + CF (dB) + or DCF(dB)
3. Margin(dB) = Limit(dB μ V/m) - Field strength(dB μ V/m)
4. Emissions below 18 GHz were measured at a 3 meter test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
5. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z, it was determined that X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in X orientation.
6. The worst-case emissions are reported however emissions whose levels were not within 20 dB of respective limits were not reported.
7. According to exploratory test no any obvious emission were detected from 9 kHz to 30 MHz. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Limit

According to 15.209(a), for an intentional radiator devices, the general required of field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

| Frequency (MHz) | Distance (Meters) | Radiated (μ V/m) |
|-----------------|-------------------|-----------------------|
| 0.009 ~ 0.490 | 300 | $2400/F(\text{kHz})$ |
| 0.490 ~ 1.705 | 30 | $24000/F(\text{kHz})$ |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 3 | 100** |
| 88 ~ 216 | 3 | 150** |
| 216 ~ 960 | 3 | 200** |
| Above 960 | 3 | 500 |

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 ~ 72 MHz, 76 ~ 88 MHz, 174 ~ 216 MHz or 470 ~ 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.



Duty cycle


Regarding to KDB 558074 D01_v05 r02, 6. Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on- and off-times of the transmitted signal.
- The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on- and off-times of the transmitted signal.

| Mode | T _{on} time (ms) | Period (ms) | Duty cycle (Linear) | Duty cycle (%) | Duty cycle correction factor (dB) |
|-----------|---------------------------|-------------|---------------------|----------------|-----------------------------------|
| LE 1 Mbps | 2.16 | 2.50 | 0.86 | 86.40 | 0.63 |
| LE 2 Mbps | 1.10 | 1.87 | 0.59 | 58.82 | 2.30 |


Duty cycle (Linear) = T_{on} time/Period

DCF(Duty cycle correction factor (dB)) = 10log(1/duty cycle)



**Test results (Below 30 MHz)**

Mode: LE 1 Mbps (Worst Case)
Distance of measurement: 3 meter
Channel: 39 (Worst case)




Note.

No spurious emission were detected under 30 MHz, Above data is peak result.

**Test results (Below 1 000 MHz)**

Mode: LE 1 Mbps (Worst Case)
Distance of measurement: 3 meter
Channel: 39 (Worst case)





**Test results (Above 1 000 MHz)**

Mode: LE 1 Mbps
 Distance of measurement: 3 meter
 Channel: 00

- Spurious

| Frequency (MHz) | Level (dB μ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 331.40 | 47.47 | Peak | V | -7.33 | - | 40.14 | 74.00 | 33.86 |
| 1 563.00 | 46.38 | Peak | H | -5.72 | - | 40.66 | 74.00 | 33.34 |
| 2 337.61 | 44.01 | Peak | V | -0.52 | - | 43.49 | 74.00 | 30.51 |
| 2 338.06 | 45.11 | Peak | H | -0.51 | - | 44.60 | 74.00 | 29.40 |



**Note.**


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 1 Mbps
 Distance of measurement: 3 meter
 Channel: 20

- Spurious

| Frequency (MHz) | Level (dB μ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 331.40 | 47.24 | Peak | V | -7.33 | - | 39.91 | 74.00 | 34.09 |
| 1 693.20 | 46.45 | Peak | H | -4.47 | - | 41.98 | 74.00 | 32.02 |



Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: LE 1 Mbps
 Distance of measurement: 3 meter
 Channel: 39

- Spurious

| Frequency (MHz) | Level (dB μ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB μ N/m) | Limit (dB μ N/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 021.70 | 48.54 | Peak | H | -9.27 | - | 39.27 | 74.00 | 34.73 |
| 1 331.40 | 47.45 | Peak | V | -7.33 | - | 40.12 | 74.00 | 33.88 |
| 2 483.50 | 57.76 | Peak | H | -0.26 | | 57.50 | 74.00 | 16.50 |
| 2 483.50 | 34.23 | Average | H | -0.26 | 0.63 | 34.60 | 54.00 | 19.40 |
| 2 483.50 | 49.44 | Peak | V | -0.26 | | 49.18 | 74.00 | 24.82 |





Note.


1. No spurious emission were detected above 3 GHz.

**Test results (18 GHz to 30 GHz)**

Mode: LE 1 Mbps

Distance of measurement: 3 meter

Channel: 39 (Worst Case)



Note.


No spurious emission were detected above 18 GHz.




Mode: LE 2 Mbps
Distance of measurement: 3 meter
Channel: 00

- Spurious

| Frequency (MHz) | Level (dB μ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB μ N/m) | Limit (dB μ N/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 128.80 | 46.99 | Peak | H | -8.59 | - | 38.40 | 74.00 | 35.60 |
| 1 331.40 | 49.00 | Peak | V | -7.33 | - | 41.67 | 74.00 | 32.33 |
| 2 337.91 | 45.36 | Peak | H | -0.51 | - | 44.85 | 74.00 | 29.15 |
| 2 364.96 | 42.95 | Peak | V | -0.42 | - | 42.53 | 74.00 | 31.47 |



**Note.**


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



Mode: LE 2 Mbps
 Distance of measurement: 3 meter
 Channel: 20

- Spurious

| Frequency (MHz) | Level (dB μ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 010.13 | 47.40 | Peak | H | -9.34 | - | 38.06 | 74.00 | 35.94 |
| 1 331.40 | 48.00 | Peak | V | -7.33 | - | 40.67 | 74.00 | 33.33 |



Note.


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.




Mode: LE 2 Mbps
Distance of measurement: 3 meter
Channel: 39

- Spurious

| Frequency (MHz) | Level (dB μ V) | Detect mode | Ant. Pol. (H/V) | CF (dB) | DCF (dB) | Field strength (dB μ N/m) | Limit (dB μ N/m) | Margin (dB) |
|-----------------|--------------------|-------------|-----------------|---------|----------|-------------------------------|----------------------|-------------|
| 1 018.81 | 46.82 | Peak | H | -9.28 | - | 37.54 | 74.00 | 36.46 |
| 1 331.40 | 46.81 | Peak | V | -7.33 | - | 39.48 | 74.00 | 34.52 |
| 2 483.50 | 46.22 | Peak | H | -0.26 | - | 45.96 | 74.00 | 28.04 |
| 2 483.50 | 53.59 | Peak | V | -0.26 | - | 53.33 | 74.00 | 20.67 |



**Note.**


1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

**Test results (18 GHz to 30 GHz)**

Mode: LE 2 Mbps

Distance of measurement: 3 meter

Channel: 20



Note.

No spurious emission were detected above 18 GHz.




3.3. AC conducted emissions

Limit

According to 15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50uH/50 ohm line impedance stabilization network (LISN). Compliance with the provision of this paragraph shall be on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

| Frequency of Emission (MHz) | Conducted limit (dB μ V) | |
|-----------------------------|------------------------------|----------|
| | Quasi-peak | Average |
| 0.15 – 0.50 | 66 - 56* | 56 - 46* |
| 0.50 – 5.00 | 56 | 46 |
| 5.00 – 30.00 | 60 | 50 |

*Decreases with the logarithm of the frequency.

**Test results****Mode : LE 1 Mbps (Worst Case)**



3.4. Antenna Requirement

According to 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

**Appendix A. Measurement equipment**

| Equipment | Manufacturer | Model | Serial No. | Calibration interval | Calibration due |
|---------------------------|-------------------|-----------|------------|----------------------|-----------------|
| SPECTRUM ANALYZER | R&S | FSV3044 | 101272 | 1 year | 2024.03.16 |
| SPECTRUM ANALYZER | | | | | 2025.03.12 |
| SIGNAL GENERATOR | KEYSIGHT | N5182B | MY59100115 | 1 year | 2024.06.15 |
| SIGNAL GENERATOR | | | | | 2025.06.12 |
| AC POWER SOURCE/ ANALYZER | Anritsu | 68369B | 002118 | 1 year | 2024.04.19 |
| Power Meter | | | | | 2025.04.15 |
| Pulse Power Sensor | Anritsu | MA2411B | 1911111 | 1 year | 2024.04.18 |
| ATTENUATOR | | | | | 2025.04.15 |
| Loop Antenna | Schwarzbeck | FMZB1513 | 1513-257 | 2 years | 2025.11.16 |
| BILOG ANTENNA | Schwarzbeck | VULB 9163 | 714 | 2 years | 2024.04.19 |
| Attenuator | HUBER+SHHNER | 6806.17.A | NONE | 1 year | 2024.03.21 |
| Horn Antenna | A.H. | SAS-571 | 414 | 1 year | 2025.02.13 |
| Horn Antenna | | | | | 2024.01.16 |
| Amplifier | SONOMA INSTRUMENT | 310N | 401123 | 1 year | 2025.01.16 |
| PREAMPLIFIER | HP | 8449B | 3008A00538 | 1 year | 2024.05.31 |
| BROADBAND AMPLIFIER | | | | | 2025.04.30 |
| EMI Test Receiver | R&S | ESU26 | 100517 | 1 year | 2024.07.31 |
| EMI TEST RECEIVER | R & S | ESR3 | 101783 | 1 year | 2024.11.08 |
| LISN | R & S | ENV216 | 101787 | 1 year | 2024.11.08 |
| LISN | ESH2-Z5 | R & S | 100450 | 1 year | 2024.11.08 |
| PULSE LIMITER | R & S | ESH3-Z2 | 101915 | 1 year | 2024.11.08 |

* Statement of Traceability: KES Co., Ltd. attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Peripheral devices

| Device | Manufacturer | Model No. | Serial No. |
|-------------------|----------------------|-----------|---------------|
| Notebook computer | LG Electronics Inc., | LGS53 | 306QCZP560949 |

The end of test report.