


TEST REPORT

Applicant: MATTER INNOVATION PTE. LTD.
Address: 1 KIM SENG PROMENADE #17-04 GREAT WORLD CITY SINGAPORE (237994)
Equipment Type: AI device
Model Name: G001
Brand Name: JARVIS
FCC ID: 2BGOW-G001
Test Standard: 47 CFR Part 1
(refer to section 3.1)
Sample Arrival Date: Jun. 25, 2024
Test Date: Jul. 23, 2024
Date of Issue: Oct. 09, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Zhang Jiwei**Checked by:** Xu Rui**Approved by:** Tolan Tu

(Testing Director)



Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Oct. 09, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location.....	4
2	PRODUCT INFORMATION.....	5
2.1	Applicant Information.....	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Ancillary Equipment.....	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Radiofrequency Radiation Exposure Limit	8
3.3	Measurement Uncertainly	9
4	DEVICE CATEGORY AND LEVELS LIMITS	10
4.1	Test Setup Photo.....	10
4.2	Measurement procedure	10
4.3	Mobile Condition.....	10
4.4	Equipment Approval Considerations item 5.2 of KDB 680106 D01 v04.	11
4.5	Test Equipment	11
4.6	Test Configuration	12
5	TEST RESULT	13
5.1	E-field	13
5.2	H-field	13
6	Test Conclusion	13

6.1	E-field	13
6.2	H-field	13

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China <input checked="" type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	MATTER INNOVATION PTE. LTD.
Address	1 KIM SENG PROMENADE #17-04 GREAT WORLD CITY SINGAPORE (237994)

2.2 Manufacturer Information

Manufacturer	MATTER INNOVATION PTE. LTD.
Address	1 KIM SENG PROMENADE #17-04 GREAT WORLD CITY SINGAPORE (237994)

2.3 General Description for Equipment under Test (EUT)

EUT Name	AI device
Model Name Under Test	G001
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	Cdk8A
Software Version	QL7282A_FAC_USERDEBUG_0615_01
Dimensions (Approx.)	98.43mm*65.41mm*4.93mm
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No.	AB255942-202401
	Serial No.	N/A
	Capacity	900mAh/3.52Wh
	Rated Voltage	3.91 V
	Limit Charge Voltage	4.5 V

2.5 Technical Information

Network and Wireless connectivity	Bluetooth-Qualcomm (BR+EDR+BLE) Bluetooth-Actions (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n and 802.11ac Galileo, GPS, SBAS, WPC
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Frequency	ASK	
Antenna Type	111 kHz -148 kHz	
About Product	Coil Antenna	
Exposure Category	Mobile Device	
EUT Type	<input checked="" type="checkbox"/> Production unit	<input type="checkbox"/> Identical prototype

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 1	Practice and Procedure
2	KDB 680106 D01 v04	EQUIPMENT AUTHORIZATION OF WIRELESS POWER TRANSFER DEVICES

3.2 Radiofrequency Radiation Exposure Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW / cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

*f = frequency in MHz * = Plane-wave equivalent power density*

NOTE:

Limits: According KDB 680106 D01, emissions between 100 kHz to 300 kHz should be assessed versus the limits at 300 kHz in Table 1 of Section 1.1310: 614 V/m and 1.63 A/m.

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Measurement Uncertainty


Measurement uncertainty evaluation for electric field strength and magnetic field strength test
This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Magnetic Filed Strength	1.18 dB
Electric Filed Strength	1.13 dB

4 DEVICE CATEGORY AND LEVELS LIMITS

4.1 Test Setup Photo

Maximum H-field and E-field measurements were made on each of five sides of the EUT that could come in contact with a user. The five sides are defined as follows: A, B, C, D, E. Refer to the test position diagram below.



4.2 Measurement procedure

1. The RF exposure test was performed in anechoic chamber.
2. The measurement probe was placed at test distance 20 cm for Front, Back, Left, Right, Top and Bottom(Screen) which is between the edge of the charger and the geometric edge of probe.
3. The highest emission level was recorded and compared with limit as soon as measurement of each points were completed.
4. The EUT was measured according the dictates of KDB 680106 D01v04.

4.3 Mobile Condition

Probe	Condition	Test Distance (cm) Front, Back, Left, Right, Top, Bottom
E&H-field	Mobile	20

4.4 Equipment Approval Considerations item 5.2 of KDB 680106 D01 v04.

1. Power transfer frequency is less than 1 MHz.
 - The device operates at a frequency 111 kHz ~ 148 kHz
2. Output power from each primary coil is less than or equal to 15 watts.
 - Output power from primary coil 50 watts.
3. The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.
 - The transfer system including a charging system with one coils that is able to detect receiver device.
4. Client device is placed directly in contact with the transmitter.
 - Client device is placed directly in contact with the transmitter.
5. Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
 - According safety guide, on the wireless power sharing function this DUT should be operate with a minimum distance of 20cm between the DUT and human body, so this EUT only support mobile exposure condition.
6. The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit.
 - Refer to following test results.

The EUT H-Field Strength levels at 20 cm < 50 % of the MPE H-Field Strength limit
1.63 A/m (Max. at 20 cm) < 0.815 A/m

4.5 Test Equipment

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
PC	Lenovo	E4-ARR	MP1K4PCW	N/A	N/A
Test Software	Narda	WinEP600	N/A	N/A	N/A
E&H-field Probe	Wavecontrol	WP400	22WP100980	2023.08.25	2024.08.25
E-Field Probe	Narda	EP 602	611WX80276	2023.09.12	2024.09.12
Anechoic Chamber	YiHeng	9m*6m*6m	1900/5/21	2021.08.19	2024.08.18
Mobile phone	HuaWei	Mate 40E	8QM0221302 020005	N/A	N/A

4.6 Test Configuration

To check all kinds of possible modes, the EUT was support reverse charging function, so the EUT was evaluated in reverse charge mode with appropriate client and under each charging condition as the below table:

Test Mode No.	Description
1	EUT(reverse charging mode) + Mobile Phone which has Less than 10 % of battery
2	EUT(reverse charging mode) + Mobile Phone which has Less than 50 % of battery
3	EUT(reverse charging mode) + Mobile Phone which has 90 % of battery

5 TEST RESULT

5.1 E-field

Distance (cm)	Test Mode	EUT Edges						Limit (V/m)
		Front (V/m)	Back (V/m)	Left (V/m)	Right (V/m)	Bottom (V/m)	Top (V/m)	
20	1	0.285	0.292	0.268	0.280	0.276	0.284	614.00
20	2	0.286	0.297	0.276	0.276	0.279	0.287	614.00
20	3	0.282	0.284	0.265	0.279	0.274	0.289	614.00

5.2 H-field

Distance (cm)	Test Mode	EUT Edges						Limit (A/m)
		Front (A/m)	Back (A/m)	Left (A/m)	Right (A/m)	Bottom (A/m)	Top (A/m)	
20	1	0.280	0.301	0.275	0.276	0.273	0.275	1.63
20	2	0.284	0.308	0.275	0.275	0.278	0.273	1.63
20	3	0.276	0.296	0.273	0.270	0.275	0.272	1.63

6 Test Conclusion

6.1 E-field

Distance (cm)	Worst-case Test Mode	EUT Edge	Limit (V/m)	50% Limit (V/m)	Verdict
		(V/m)			
20	1	0.292	614.00	307.00	Pass
20	2	0.297	614.00	307.00	Pass
20	3	0.289	614.00	307.00	Pass

6.2 H-field

Distance (cm)	Worst-case Test Mode	EUT Edge	Limit (A/m)	50% Limit (A/m)	Verdict
		(A/m)			
20	1	0.301	1.63	0.815	Pass
20	2	0.308	1.63	0.815	Pass
20	3	0.296	1.63	0.815	Pass

According KDB 680106 D01v04, the EUT is compliant with the 50% of the MPE limits.

Note: Test setup photos please refer the document "BL-SZ2460995-AS-2.pdf".

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--