



Certificate # 2861.01

GRGTEST

Page 1 of 9

Test Report

Verified code: 130605

Report No.: E202403143863-6

Customer: Hangzhou Moyu Technology Co., Ltd

Address: Room 4069, Building 2, Xixi Lotte City, Wuchang Street, Yuhang District hangzhou Zhejiang 311122 China (Peoples Republic Of)

Sample Name: Pet Tracker

Sample Model: M200d

Receive Sample Date: Mar.21,2024

Test Date: Mar.27,2024 ~ Apr.08,2024

Reference Document: CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.

Test Result: Pass

Prepared by:

Wen Wenwen

Wen Wenwen

Reviewed by:

Peng Huarui

Peng Huarui

Approved by:

Zhao Zetian

Zhao Zetian

GRG METROLOGY & TEST GROUP CO., LTD.

Issued Date: 2024-06-13

GRG METROLOGY & TEST GROUP CO., LTD.

Address: No.163, Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.
6. The test report without CMA approval mark is only used for scientific research, teaching, internal quality control and other purposes.

----- The following blanks -----

TABLE OF CONTENTS

1. GENERAL DESCRIPTION OF EUT	5
1.1 APPLICANT	5
1.2 MANUFACTURER	5
1.3 FACTORY	5
1.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST	5
2. LABORATORY	7
2.1 ACCREDITATIONS	7
3. EVALUATION METHOD	8
4. LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	8
5. CALCULATION METHOD	9
6. ESTIMATION RESULT	9
6.1. MEASUREMENT RESULTS	9
7. CONCLUSION	9

----- The following blanks -----

REPORT ISSUED HISTORY

Report Version	Report No.	Description	Compile Date
1.0	E202403143863-6	Original Issue	2024-05-29

----- The following blanks -----

1. GENERAL DESCRIPTION OF EUT

1.1 APPLICANT

Name: Hangzhou Moyu Technology Co., Ltd
Address: Room 4069, Building 2, Xixi Lotte City, Wuchang Street, Yuhang District
hangzhou Zhejiang 311122 China (Peoples Republic Of)

1.2 MANUFACTURER

Name: Hangzhou Moyu Technology Co., Ltd
Address: Room 4069, Building 2, Xixi Lotte City, Wuchang Street, Yuhang District
hangzhou Zhejiang 311122 China (Peoples Republic Of)

1.3 FACTORY

Name: Hangzhou Moyu Technology Co., Ltd
Address: Room 4069, Building 2, Xixi Lotte City, Wuchang Street, Yuhang District
hangzhou Zhejiang 311122 China (Peoples Republic Of)

1.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Pet Tracker
Model No.: M200d
Trade Name: /
Adding Model: /
FCC ID: 2BGPO-M200D
Power Supply: DC 3.85V by battery, DC 5V by USB cable for charging
Battery: DC 3.85V/790mAh
Hardware Version: V1.0.0.2
Software Version: V1.0.0.1
Antenna type: Internal antenna
Maximum Antenna Gain: LTE Band 2: 1.64dBi
Category: Category 1
Power Class: 3
Frequency range: LTE Band 2: Tx 1850MHz~1910MHz, Rx 1930MHz ~ 1990MHz
Bandwidth: LTE Band 2: 1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz
Modulation: QPSK, 16QAM
Sample No.: E202403143863-0001, E202403143863-0002

IMEI: 861261029936727

Temperature Range: -20°C ~ +70°C

Voltage Range: DC 3.5V ~ 4.2V

Sample Submitting Way : Provided by customer Sampling

Note: The basic description of the EUT is provided by the applicant. The antenna gain is provided by applicant. This report is made solely on the basis of such data and/or information. We accept no responsibility for the authenticity and completeness of the above data and information and the validity of the results and/or conclusions.

----- The following blanks -----

2. LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of GRG METROLOGY & TEST GROUP CO., LTD.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District
Shenzhen, 518110, People's Republic of China.

P.C.: 518110

Tel : 0755-61180008

Fax: 0755-61180008

2.1 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	A2LA(Certificate #2861.01)
-----	----------------------------

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada	ISED (Company Number: 24897, CAB identifier:CN0069)
--------	-----------------------------------------------------

USA	FCC (Registration Number: 759402, Designation Number:CN1198)
-----	--------------------------------------------------------------

Copies of granted accreditation certificates are available for downloading from our web site,

<http://www.grgtest.com>

----- The following blanks -----

3. EVALUATION METHOD

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D04 Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (*Evaluated_k* term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1)

$$\sum_{k=1}^c \frac{\text{Evaluated}_k}{\text{Exposure Limit}_k} \leq 1 \quad (\text{C.1})$$

Evaluated_k the maximum reported SAR or MPE of fixed, mobile, or portable RF source *k* either in the device or at the transmitter site from an existing evaluation.

Exposure Limit_k either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

the sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE shall be less than 1, to determine simultaneous transmission exposure compliance

4. LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

For mobile devices at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in Table B.2 is necessary if the ERP of the device is greater than *ERP_{20cm}* in Formula (B.1)

$$P_{th} (\text{mW}) = \text{ERP}_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

(B.2) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100,000	/	/	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

5. CALCULATION METHOD

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to anisotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, d=20cm, as well as the maximum gain of the used as following information, the RF power density can be obtained.

Table 1 Antenna Specification

Frequency Band	Antenna type	Maximum antenna Gain (dBi)
FDD LTE Band 2	Internal antenna	1.64

Table 2 Transmit Power

Frequency Band	Mode	Maximum Output Power (dBm)	Tune-up maximum output power (dBm)
FDD LTE Band 2	15MHz	24.31	25.00

Note: The maximum output Power of LTE were refer to the report E202403143863-5.

6. ESTIMATION RESULT

6.1. MEASUREMENT RESULTS

STANDALONE MPE

Mode	Frequency (MHz)	Tune-up maximum output power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
FDD LTE Band 2	1850 - 1910	25.00	1.64	26.64	461.32	0.13	1.0

Remark: MPE use distance is 20cm from manufacturer declaration of user manual.

7. CONCLUSION

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- End of Report -----