



USER MANUAL

Exclusive 4 channels camera



Press and hold the flip button to turn on the WiFi hotspot
SSID: Starting with S7 S9
Password: 12345678

13	Light source frequency	50HZ/60HZ	Choose the Light source frequency
14	format	Confirm/ cancel	format TF card
15	Screen saver	Off/3minutes/5minutes / 10minutes	
16	Default setting	Confirm/ cancel	
17	version	Machine software version number	

1	Shooting method	Single shooting/2 seconds timer / 5 seconds timer / 10 seconds timer
2	Resolution	2M/3M/5M/8M/10M/12M
3	Continuous shooting	on/ off
4	Picture quality	High quality/standard/economy
5	Acutance	Strong/standard/soft
6	White balance	Automatic/sunlight/cloudy/tungsten lamp/fluorescent lamp
7	ISO	Automatic/100/200
8	Exposure compensation	-3, -2, -1, 0, 1, 2, 3
9	Time stamp	Off/ Date

【OK】 Turn on/off the power button.
 【M】 For the menu key, long press to enter the menu and short press to view files.
 【A】 To flip up the button, long press to turn on and off the night vision lights, and short press to switch the lens interface.
 【V】 To scroll down, long press to open the WiFi interface and long press to exit the WiFi interface.
 【OK】 To confirm, short press on the menu interface is the confirm button, and short press on the recording interface is the start/stop switching function for recording.

Rear view lens (optional)
 In case of video recording, 4 pin plug of rear view lens insert AV-in hole of device, then the rear view image in topright of the screen, that means connected successfully; short press OK button to pause, long press ▲ button to switch front/rear view image, When hang up "R" gear, it will show full image of rear view

Note: This device can only support dual cameras to video record at the same time instead of 3 channels camera, that is front-inside camera or front-rear camera; if installed a rearview

一、Product Specification

DDR	Built-in 64M
FLASH	8M SPI norflash
Display Screen	2.4 inch IPS HD screen
LCD resolution	480X320 pixels
External port	MINI USB 5V/2A power adapter port Max support 64G Class10 TF card 2.5mm digital 720P rear view lens port
Speaker	Monophonic 15*10mm speaker
MIC	4015 Standard Omnidirectional Microphone

Features:

Front camera	6-glass/F2.0aperture/170°wide angle
Inside camera (optional)	VGA 120°
GPS tracker	NO
AV OUT	NO
Rear camera	6M cable/2.5mm port
Photo	Support
Lens rotates	Adjust manually
WDR	Support
HDR	Support
Reversing visual	Support
Video format	AVI
Image format	JPG
Compression format	H.264
Battery	150mAh polymer lithium battery
Language	support multi-language
G-sensor	Support

Motion Detection	Support
Delay shutdown	Support
Loop recording	Support,Do not leak seconds
Sound record	Support
Fill light for night vision	Support(Open manually)
Parking monitoring	Support
Front camera	1920x1080P
In-car camera resolution	HD1280x720
Camera resolution	Max support 3M

Working Environment

Operating temperature	-40°C~70°C
Operating humidity	15-65%RH
Storage temperature	-40°C~70°C

二、Key Features (picture for reference only, mainly in kind)



1) Power button
 2) Menu keys
 3) Confirm key OK key
 4) Flip up button, long press to turn on night vision light
 5) Flip down key
 6) Display screen
 7) In car camera
 8) Bracket clamp
 9) Power interface
 10) Reset key
 11) TF card slot
 12) Rear view camera (optional)
 13) Front camera
 14) Front camera

In video mode ,long press 【M】 to enter video menu settings as follows:

Recorder Menu

1 Resolution	1080P FHD/720P
2 Loop recording	Off/1minutes/2minutes/3minutes/5minutes
3 Exposure compensation	-3,-2,-1.0,1,2,3
4 Movement detection	on/off
5 Sound record	on/off
6 Time stamp	on/off
7 G-sensor	Off/2G/4G/8G
8 Parking monitor	on/off
9 Date/time	Adjustment Years months date/Hours Minutes seconds
10 Automatic shut-down	Off/1minutes/3minutes
11 Keypad tone	on/off
12 OSD language	Support multilingual

Night shooting screen is not clear enough	Recorder shooting depends on the outside strong light source (such as streetlights or car light)
The machine always reverts to the default date and time	Shutdown in the first case full of electricity, you can use car charger or mobile power supply to add power
what is the reason for video file leak seconds	(Turn off motion detection. Turn on the loop recording function) With a certain choice of their own genuine card C10 high-speed card
Why during recording, the machine automatically shut down suddenly	Please turn off the parking monitoring function first/Ambient temperature exceeds 70 °C will cause automatic shutdown
【Note】 Practice proof	Most of the problems sources from the memory card, a small part cause of power cord

The information provided in this manual is for reference only. Please prevail in kind (some special features depend on different models) . All rights reserved.

camera and choose front-inside view mode, it will automatically indicate full image of car reversing visual when you hang up "R" gear, but won't affect front-inside video record, also will automatically switch back front-inside view after cancel "R" gear. As for system update to support 3 channels camera to video record at the same time, please prevail in kind and we're sorry for no further notice.

Reset key【RESET】

If the recorder crashes and accidental operation is not a normal fault, press 【RESET】 to shutdown the device, then press 【OK】 to reboot the device.

Installation Notes

1. Please test the rear view camera firstly, if it works well then install (package without rear view lens can be ignored).

2. Turn on the car engine.

3. The TF card insert the recorder slot.

【Note】 Please use the high-speed TF card (Class10 above), capacity of not less than 4GB, TF card maximum support 64GB.

4. Fix the recorder on the original.

5. Insert the car charger into the car lighter.

【Note】 When wiring, extend the charging line along the edge of the car door frame and fix it with the original.

6. Install the rear camera at the rear of the vehicle, and pay attention to the up and down direction. Wiring can be buried along the edge of the car roof laying. 【Note】 There are two ways to install the rear camera:

A. Adhesive on the glass above and behind the car, hands-on self-installation (Reversing visual function can not be achieved, only real-time recording rear video).

B. To find a professional installation staff installed in the license plate above the car, at the same time need to connect the power reversing lights (Reversing visual function can be achieved).

7. Adjust the lens position to ensure the best viewing angle.

8. Start the engine and check that the machine is operating properly.

Features

1. Use the automatic recording function. Start the car engine, the recorder automatically starts to open the recording function.

Close the car engine, the recorder automatically saves the contents of the log and shuts down. Recorded video segments are stored on the TF card. When the TF card is full, the recorder will overwrite the oldest recorded image preferentially.

【Note】

a. The segment of record can be set 1/2/3 minutes in the menu.

b. The video individually saved in the folder named "DCIMA" and "DCIMB" in TF card (package include rear view lens).

3. Use motion detection

In standby mode, enter the menu screen open the motion detection mode. When the lens is sensitive to the peripheral area of a moving object, the state machine into the camera, recording 30 seconds after the system stops recording. To exit the motion detection mode, in standby mode to enter the menu screen close motion detection mode.

4. G-sensor

The built-in gravity sensor (G-sensor), if serious vehicle collision, the recorder will lock the first 5 seconds and 10 seconds after the image date when the accident occurred while the bottom left of the display screen displays a lock icon ;locked images will be saved as a special file, the file

Installation Notes

First, you must connect the dvr with car charger, rear-view camera connect the reversing lights. Insert the car charger, machine will automatically start recording status, screen switch R position in the recording mode automatically switches to the rear-view camera, display reverse image. After reversing visual machine automatically return to video mode.

Reminder: Please test the rearview camera is normal before installation.

8. Reversing visual function

First, you must connect the dvr with car charger, rear-view camera connect the reversing lights. Insert the car charger, machine will automatically start recording status, screen switch R position in the recording mode automatically switches to the rear-view camera, display reverse image. After reversing visual machine automatically return to video mode.

【Note】 Practice proof

To achieve this function must be connected to the machine in the case of electricity, in the main menu to open the motion detection and parking monitoring function, in the standby state of the vehicle under vibration or moving objects in front, the recorder according to G-sensor to sense automatically start the machine and automatically locks the video for 30 seconds, and automatically save the video file, the video 30 seconds after 5 seconds without the operation will automatically shut down.

【note】 This function is only used when stopping. Please turn off the motion detection and stop monitoring function during normal driving.

FAQ

Machine appears "file error" message Settings menu -> Restore factory settings and format the memory card, the general problem is TF card

The screen appears horizontal stripes interference Please select the correct power supply

How to properly turn on the 24-hour parking monitoring function While in normal driving, please do not open, it is easily lead to automatic shutdown, crash, after parking is required to open, configure the buckline or mobile power please

FCC Warning**15.19 Labeling requirements.**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

15.21 Information to user.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.105 Information to the user.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio

communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio /TV technician for help.

FCC RF Radiation Exposure Statement:

1. This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.
2. This equipment complies with RF

radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.