



Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: 802.11a Mode Middle Channel 5200MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5951.000	34.49	10.06	44.55	68.20	23.65	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: horizontal
Note: 802.11a Mode Middle Channel 5200MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10400.000	34.58	13.61	48.19	68.20	20.01	Peak
2	15600.000	37.68	16.57	54.25	74.00	19.75	Peak
3	15600.000	25.33	16.57	41.90	54.00	12.10	Average
4	17707.200	33.77	25.89	59.66	74.00	14.34	Peak
5	17707.200	21.47	25.89	47.36	54.00	6.64	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: vertical
Note: 802.11a Mode Middle Channel 5200MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10400.000	35.23	13.61	48.84	68.20	19.36	Peak
2	15600.000	36.14	16.57	52.71	74.00	21.29	Peak
3	15600.000	24.52	16.57	41.09	54.00	12.91	Average
4	17740.800	33.35	25.85	59.20	74.00	14.80	Peak
5	17740.800	21.51	25.85	47.36	54.00	6.64	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: 802.11n ht20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5971.000	35.55	10.15	45.70	68.20	22.50	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: 802.11n ht20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5823.000	35.21	9.42	44.63	68.20	23.57	Peak

Project No.: 2403Z107562E-RF
 Tester: Mack Huang
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
 Polarization: horizontal
 Note: 802.11n ht20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10360.000	35.13	13.24	48.37	68.20	19.83	Peak
2	15540.000	35.21	17.27	52.48	74.00	21.52	Peak
3	15540.000	23.33	17.27	40.60	54.00	13.40	Average
4	17719.200	33.27	25.89	59.16	74.00	14.84	Peak
5	17719.200	21.35	25.89	47.24	54.00	6.76	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: vertical
Note: 802.11n ht20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10360.000	34.96	13.24	48.20	68.20	20.00	Peak
2	15540.000	34.78	17.27	52.05	74.00	21.95	Peak
3	15540.000	22.50	17.27	39.77	54.00	14.23	Average
4	17796.000	33.59	25.78	59.37	74.00	14.63	Peak
5	17796.000	21.76	25.78	47.54	54.00	6.46	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: 802.11n ht40 Mode High Channel 5230MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5796.000	35.40	9.54	44.94	68.20	23.26	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: 802.11n ht40 Mode High Channel 5230MHz Band1




Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: horizontal
Note: 802.11n ht40 Mode High Channel 5230MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10460.000	34.81	14.00	48.81	68.20	19.39	Peak
2	15690.000	37.22	15.99	53.21	74.00	20.79	Peak
3	15690.000	25.31	15.99	41.30	54.00	12.70	Average
4	17798.400	33.58	25.78	59.36	74.00	14.64	Peak
5	17798.400	21.77	25.78	47.55	54.00	6.45	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: vertical
Note: 802.11n ht40 Mode High Channel 5230MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10460.000	35.17	14.00	49.17	68.20	19.03	Peak
2	15690.000	36.49	15.99	52.48	74.00	21.52	Peak
3	15690.000	24.75	15.99	40.74	54.00	13.26	Average
4	17908.800	34.28	25.60	59.88	74.00	14.12	Peak
5	17908.800	21.71	25.60	47.31	54.00	6.69	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: 802.11ac80 Mode Middle Channel 5210MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5767.000	35.08	9.45	44.53	68.20	23.67	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: 802.11ac80 Mode Middle Channel 5210MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5934.000	34.52	9.92	44.44	68.20	23.76	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: horizontal
Note: 802.11ac80 Mode Middle Channel 5210MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10420.000	35.22	13.74	48.96	68.20	19.24	Peak
2	15630.000	36.32	16.37	52.69	74.00	21.31	Peak
3	15630.000	24.11	16.37	40.48	54.00	13.52	Average
4	17788.800	33.73	25.78	59.51	74.00	14.49	Peak
5	17788.800	21.61	25.78	47.39	54.00	6.61	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: vertical
Note: 802.11ac80 Mode Middle Channel 5210MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10420.000	34.89	13.74	48.63	68.20	19.57	Peak
2	15630.000	35.89	16.37	52.26	74.00	21.74	Peak
3	15630.000	23.74	16.37	40.11	54.00	13.89	Average
4	17810.400	33.29	25.76	59.05	74.00	14.95	Peak
5	17810.400	21.78	25.76	47.54	54.00	6.46	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: 802.11ax20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5586.000	34.81	9.85	44.66	68.20	23.54	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: 802.11ax20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5782.000	34.59	9.49	44.08	68.20	24.12	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: horizontal
Note: 802.11ax20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10360.000	34.52	13.24	47.76	68.20	20.44	Peak
2	15540.000	36.85	17.27	54.12	74.00	19.88	Peak
3	15540.000	24.51	17.27	41.78	54.00	12.22	Average
4	17808.000	33.43	25.76	59.19	74.00	14.81	Peak
5	17808.000	21.88	25.76	47.64	54.00	6.36	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
Polarization: vertical
Note: 802.11ax20 Mode Low Channel 5180MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10360.000	35.10	13.24	48.34	68.20	19.86	Peak
2	15540.000	35.87	17.27	53.14	74.00	20.86	Peak
3	15540.000	23.44	17.27	40.71	54.00	13.29	Average
4	17743.200	33.46	25.85	59.31	74.00	14.69	Peak
5	17743.200	21.59	25.85	47.44	54.00	6.56	Average

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: horizontal
Note: 802.11ax40 Mode Low Channel 5190MHz Band1




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5788.000	34.73	9.52	44.25	68.20	23.95	Peak

Project No.: 2403Z107562E-RF
Tester: Mack Huang
Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec
Polarization: vertical
Note: 802.11ax40 Mode Low Channel 5190MHz Band1



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	5809.000	34.60	9.50	44.10	68.20	24.10	Peak

Project No.: 2403Z107562E-RF
 Tester: Mack Huang
 Condition: PK trace RBW:1MHz; VBW:3MHz; SWT:0.3sec AV trace RBW:1MHz; VBW:5kHz; SWT:auto
 Polarization: horizontal
 Note: 802.11ax40 Mode Low Channel 5190MHz Band1



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	10380.000	35.20	13.43	48.63	68.20	19.57	Peak
2	15570.000	37.14	16.93	54.07	74.00	19.93	Peak
3	15570.000	25.63	16.93	42.56	54.00	11.44	Average
4	17726.400	33.76	25.87	59.63	74.00	14.37	Peak
5	17726.400	21.42	25.87	47.29	54.00	6.71	Average