



MPE ESTIMATION

FCC ID: 2BGVA-DPD01

1, Per FCC Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices, the limit for General Population/ Uncontrolled Exposures

| Frequency | Power density (mW/ cm ²) | Averaging time(minutes) |
|------------------|--------------------------------------|-------------------------|
| 300MHz----1.5GHz | F/1500 | 30 |
| 1.5GHz---100GHz | 1.0 | 30 |

Note: F= Frequency in MHz

2, Estimation Result

| Frequency (MHz) | Max PK Output power(dBm) | Tune Up Power(dBm) | Max Tune Up power(mW) | Antenna Gain(dBi) | Antenna Gain (linear) | MPE (mW/cm ²) |
|---|--------------------------|--------------------|-----------------------|-------------------|-----------------------|---------------------------|
| 2402 | -0.49 | 0±1(1) | 1.26 | 1.08 | 1.28 | 0.00032 |
| $Pd = \frac{P_{out} * G}{4\pi r^2}$; | | | | | | |
| Note: | | | | | | |
| Note: The estimation distance is 20cm | | | | | | |
| Note: | | | | | | |
| PK Output power= conducted power. | | | | | | |
| Conducted power see the test report DL-240611003ER , antenna gain=1.08dBi, | | | | | | |

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.00032 mW/cm² which is < 1.0mW/cm², RF Exposure testing is not required.

-----The End-----