



## RF Exposure Evaluation

### Limits

According to 447498 D01 General RF Exposure Guidance v06

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

**R** = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



FCC ID: 2BGVI-CRT401

### Manufacturing tolerance

GFSK			
Frequency	2402MHz	2440MHz	2480MHz
Rated (dBm)	4.50	4.50	4.50
Tolerance $\pm$ (dB)	1	1	1

802.11b			
Frequency	2412MHz	2437MHz	2462MHz
Rated (dBm)	14.00	14.00	14.00
Tolerance $\pm$ (dB)	1	1	1

802.11g			
Frequency	2412MHz	2437MHz	2462MHz
Rated (dBm)	14.00	14.00	14.00
Tolerance $\pm$ (dB)	1	1	1

802.11n20			
Frequency	2412MHz	2437MHz	2462MHz
Rated (dBm)	14.00	14.00	14.00
Tolerance $\pm$ (dB)	1	1	1

802.11n40			
Frequency	2422MHz	2437MHz	2452MHz
Rated (dBm)	14.00	14.00	14.00
Tolerance $\pm$ (dB)	1	1	1



FCC ID: 2BGVI-CRT401

### Test Result of RF Exposure Evaluation

The source of the evaluation data results is based on the test report ET-24010040E01/02

Antenna gain=2dBi

#### FOR BLE

Mode	Output power (dBm) (including tune-up tolerance)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
GFSK	5.50	3.55	1.58	0.0011	1.0	PASS

#### FOR 2.4GWIFI

Mode	Output power (dBm) (including tune-up tolerance)	Output power (mW)	Numeric antenna gain	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
802.11b	15.00	31.62	1.58	0.0100	1.0	PASS
802.11g	15.00	31.62	1.58	0.0100	1.0	PASS
802.11n20	15.00	31.62	1.58	0.0100	1.0	PASS
802.11n40	15.00	31.62	1.58	0.0100	1.0	PASS

Maximum power density=0.0100 <1. Then SAR evaluation is not require .