




# FCC RF Exposure Report

**FCC ID** : 2BGXJ-UWRB301  
**Equipment** : Smart Baby Tag  
**Model No.** : UW-RB-301  
**Brand Name** : UniWhale  
**Applicant** : SIRIUXENSE INC  
**Address** : 16192 Coastal Hwy, Lewes, DE 19958 United States  
**Standard** : 47 CFR FCC Part 2.1093  
**Received Date** : Feb. 07, 2024  
**Tested Date** : Jul. 28 ~ Aug. 03, 2022

We, International Certification Corporation, would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:

  
\_\_\_\_\_  
Along Chen / Assistant Manager

Approved by:

  
\_\_\_\_\_  
Gary Chang / Manager

## Table of Contents

<b>1</b>	<b>RF EXPOSURE TEST EXEMPTIONS.....</b>	<b>4</b>
1.1	1-mW TEST EXEMPTION .....	4
1.2	SAR-BASED EXEMPTION .....	4
1.3	MPE-BASED EXEMPTION.....	4
1.4	REFERENCE GUIDANCE .....	5
1.5	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE .....	5
1.7	EXEMPTION CALCULATION .....	5
1.8	MPE EVALUATION RESULTS .....	6
1.9	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION.....	6
<b>2</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>7</b>

## Release Record

Report No.	Version	Description	Issued Date
FA260204-01	Rev. 01	Initial issue	Jun. 13, 2024

## 1 RF Exposure Test Exemptions

### 1.1 1-mW TEST EXEMPTION

Available maximum time-averaged power is no more than 1 mW.

### 1.2 SAR-BASED EXEMPTION

This exemption is applicable to the frequency range between 300 MHz and 6 GHz, with test separation distances between 0.5 cm and 40 cm, and for all RF sources in fixed, mobile, and portable device exposure conditions.

The maximum time-averaged power or effective radiated power (ERP), whichever is greater,  $\leq P_{th}$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}}(d/20)^x \quad d \leq 20\text{cm}$$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}} \quad 20 \text{ cm} < d \leq 40\text{cm}$$

Where  $x = -\log_{10}\left(\frac{60}{\text{ERP}_{20\text{cm}}\sqrt{f}}\right)$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}}(\text{mW}) = 2040f \quad 0.3\text{GHz} \leq f < 1.5 \text{ GHz}$$

$$P_{th} (\text{mW}) = \text{ERP}_{20\text{cm}}(\text{mW}) = 3060 \quad 1.5\text{GHz} \leq f < 6 \text{ GHz}$$

Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

### 1.3 MPE-BASED EXEMPTION

For a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters.

Radio Source Frequency		Minimum Distance			Threshold ERP	
$F_L$ MHz	$F_H$ MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W		
0.3	-	1.34	159 m	-	35.6 m	$1920 R^2$
1.34	-	30	35.6 m	-	1.6 m	$3450 R^2/f^2$
30	-	300	1.6 m	-	159 mm	$3.83 R^2$
300	-	1500	159 mm	-	31.8 mm	$0.0128 R^2 f$
1500	-	100000	31.8 mm	-	0.5 mm	$19.2 R^2$

Note: R is the antenna-person separation distance.

## 1.4 REFERENCE GUIDANCE

447498 D04 Interim General RF Exposure Guidance v01

## 1.5 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

## 1.6 MEASUREMENT UNCERTAINTY

The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Parameters	Uncertainty
Conducted power	±0.808 dB

### Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

### Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

## 1.7 EXEMPTION CALCULATION

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Maximum Tune Up Limit		Antenna Gain (dBi)	EIRP (dBm)	ERP		Exemption Thresholds (mW)	Pass/ Fail
		dBm	mW			dBm	mW		
2402 ~ 2480	3.92	4	2.51	-0.65	3.35	1.2	1.32	3	Pass

## 1.8 MPE EVALUATION RESULTS

Frequency Range (MHz)	Maximum Tune Up Limit (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	*Ratio	Pass / Fail
2402~2480	4	-0.65	20	0.0004	1	0.0004	Pass

### For WPT

Modulation Mode	Max E-Field (V/m)	Max H-Field (A/m)
WPT	0.4271	0.0195
Limit	614	1.63
Ratio	0.0007	0.012

Note: Test results of WPT are from test report no.: FA260823-01NF

## 1.9 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Mode	Max Ratio of Each Mode
BT	0.0004
WPT	0.012
Sum	0.0124
Limit	1
Pass / Fail	Pass

Note: Below formula is for Simultaneous Transmission.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

## 2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corporation (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

### Linkou

Tel: 886-2-2601-1640  
No.30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan  
(R.O.C.)

### Kwei Shan

Tel: 886-3-271-8666  
No.3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)  
No.2-1, Lane 6, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

### Kwei Shan Site II

Tel: 886-3-271-8640  
No.14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Dist., Tao Yuan  
City 33381, Taiwan (R.O.C.)

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666  
Fax: 886-3-318-0345  
Email: ICC\_Service@icertifi.com.tw

—END—