

**FCC ID:2BGYF-BY001**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE-1M	2.402	-3.87	0.41	-4±1	-3	0.50	<5	0.15535	3.00	YES
	2.440	-4.49	0.36	-4.5±1	-3.5	0.45	<5	0.13955	3.00	YES
	2.480	-5.75	0.27	-5±1	-4	0.40	<5	0.12539	3.00	YES
BLE-2M	2.402	-3.86	0.41	-4±1	-3	0.50	<5	0.15535	3.00	YES
	2.440	-4.58	0.35	-4.5±1	-3.5	0.45	<5	0.13955	3.00	YES
	2.480	-5.77	0.26	-5±1	-4	0.40	<5	0.12539	3.00	YES

**Conclusion:**

For the max result :  $0.15535 \leq 3.0$  for 1g SAR, SAR is not required.



**Signature:**

**Date:** 2024-10-18

**NAME AND TITLE** (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.