
RF EXPOSURE EVALUATION

EUT Specification

EUT	Cell Phone Signal Booster																										
Model Number	15A																										
FCC ID	2BGYG15A																										
Antenna gain (Max)	<table><tr><th>Mode</th><th>Frequency(MHz)</th><th>Antenna Gain(dBi)</th><th>Cable loss(dB)</th></tr><tr><td rowspan="3">UP LINK</td><td>824 - 849</td><td>10</td><td>3</td></tr><tr><td>699 - 716</td><td>10</td><td>3</td></tr><tr><td>777-787</td><td>10</td><td>3</td></tr><tr><td rowspan="3">DOWNLINK</td><td>869 - 894</td><td>9</td><td>3</td></tr><tr><td>729-746</td><td>9</td><td>3</td></tr><tr><td>746-756</td><td>9</td><td>3</td></tr></table>			Mode	Frequency(MHz)	Antenna Gain(dBi)	Cable loss(dB)	UP LINK	824 - 849	10	3	699 - 716	10	3	777-787	10	3	DOWNLINK	869 - 894	9	3	729-746	9	3	746-756	9	3
Mode	Frequency(MHz)	Antenna Gain(dBi)	Cable loss(dB)																								
UP LINK	824 - 849	10	3																								
	699 - 716	10	3																								
	777-787	10	3																								
DOWNLINK	869 - 894	9	3																								
	729-746	9	3																								
	746-756	9	3																								
Operation Frequency	Cellular:Uplink: 824MHz - 849MHz, Downlink: 869MHz - 894MHz Lower A-E Blocks: Uplink: 699MHz-716MHz, Downlink: 729MH-746MHzBroadband 700 MHz Upper C Block: Uplink: 777MHz-787MHz, Downlink: 746MHz-756MHz																										
Input Rating	DC 5V from AC/DC ADAPTER																										
Max. output power	Cellular: Uplink: 824MHz - 849MHz,22.04dBm, Downlink: 869MHz-894MHz,15.58dBm Lower A-E Blocks: Uplink: 699-716MHz, 25.04dBm, Downlink: 729-746MHz, 15.08dBm 700 MHz Upper C Block: Uplink: 777-787MHz, 26.13dBm, Downlink:746-756MHz, 9.77dBm																										

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	..	..	F/300	6
1500-100000	..	..	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	..	..	F/1500	6
1500-100000	..	..	1	30

11.1 Friis transmission formula: $P_d = \frac{P_{out} G}{4\pi R^2}$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm=20cm

Pd the limit of MPE, $1\text{mW}/\text{cm}^2$. If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Operating Mode Frequency(MHz)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Cable loss	EIRP(mW)	Ant. Gain(dBi)	Power density at 20cm (mW/ cm ²)	Power density Limits(mW/cm ²)
UL824 -849	22 ± 1	23	3	1000	10	0.199045	0.54
DL 869-894	15 ± 1	16	3	199.526	9	0.039715	0.57
UL 699-716	25 ± 1	26	3	1995.262	10	0.397146	0.46
DL 729-746	15 ± 1	16	3	158.489	9	0.031546	0.48
UL 777-787	26 ± 1	27	3	2511.886	10	0.499977	0.51
DL 746-756	10 ± 1	11	3	50.119	9	0.009976	0.49

Signature:

Stone Tang

Stone Tang

Date: 2024-06-30