

# FCC RADIO TEST REPORT

Applicant..... :Shenzhen KSTAR New Energy Company Limited

Address..... :RD Building KSTAR Industrial Park 7th Road Western Area Hi-Tech Industrial Zone Guangming District, Shenzhen, China

Manufacturer..... :Shenzhen KSTAR New Energy Company Limited

Address..... :RD Building KSTAR Industrial Park 7th Road Western Area Hi-Tech Industrial Zone Guangming District, Shenzhen, China

Factory..... :Shenzhen KSTAR New Energy Company Limited

Address..... :RD Building KSTAR Industrial Park 7th Road Western Area Hi-Tech Industrial Zone Guangming District, Shenzhen, China

Product Name..... :Data Logger

Brand Name..... : **KSTAR**

Model No. .... :KSM-WIFI-PLUG3

FCC ID..... :2BGYM-WIFI-PLUG3


Measurement Standard..... :47 CFR FCC Part 15, Subpart C (Section 15.247)

Receipt Date of Samples.... :March 04, 2024

Date of Tested..... :March 04, 2024 to May 22, 2024

Date of Report..... :June 27, 2024

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Jenny Liu / Project Engineer



Iori Fan / Authorized Signatory

---

## Table of Contents

1. Summary of Test Result.....	4
2. General Description of EUT .....	5
3. Test Channels and Modes Detail .....	8
4. Configuration of EUT.....	8
5. Modification of EUT.....	8
6. Description of Support Device.....	9
7. Test Facility and Location .....	10
8. Applicable Standards and References.....	11
9. Deviations and Abnormalities from Standard Conditions .....	11
10. Test Conditions .....	12
11. Measurement Uncertainty .....	13
12. Sample Calculations .....	13
13. Test Items and Results .....	15
13.1 Conducted Emissions Measurement.....	15
13.2 Maximum Conducted Output Power Measurement.....	19
13.3 6dB Bandwidth Measurement.....	21
13.4 Power Spectral Density Measurement .....	26
13.5 Band Edge and Conducted Spurious Emissions Measurement.....	31
13.6 Radiated Spurious Emissions and Restricted Bands Measurement.....	37
13.7 Antenna Requirement .....	44
14. Test Equipment List.....	45

## Revision History

## 1. Summary of Test Result

FCC Rules	Description of Test	Result	Remarks
§15.207 (a)	AC Power Conducted Emission	PASS	---
§15.247(b)(3)	Maximum Conducted Output Power	PASS	---
§15.247(a)(2)	6dB Bandwidth	PASS	---
§15.247(e)	Power Spectral Density	PASS	---
§15.247(d)	Band Edge and Conducted Spurious Emissions	PASS	---
§15.247(d),§15.209, §15.205	Radiated Spurious Emissions and Restricted Bands	PASS	---
§15.203	Antenna Requirement	PASS	---

## 2. General Description of EUT

Product Information	
Product Name:	Data Logger
Main Model Name:	KSM-WIFI-PLUG3
Additional Model Name:	N/A
Model Difference:	N/A
S/N:	2403-0961
Brand Name:	<b>KSTAR</b>
Hardware Version:	Not Stated
Software Version:	Not Stated
Rating:	DC 5V 2A Max
Typical arrangement:	Tabletop
I/O Port:	Refer to user manual
Accessories Information	
Adapter:	N/A
Cable:	N/A
Other:	N/A
Additional Information	
Note:	N/A
Remark:	All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.

Technical Specification	
Frequency Range:	2412-2462MHz for IEEE 802.11b/g/n(HT20)/ax(HE20) 2422-2452MHz for IEEE 802.11n(HT40)/ax(HE40) (802.11ax Only support full RU Mode)
Modulation Technology:	DSSS, OFDM
Modulation Type:	CCK, DQPSK, DBPSK, QPSK, BPSK, 16-QAM, 64-QAM,
Number of Channel:	11 for IEEE 802.11b/g/n(HT20)/ax(HE20) 7 for IEEE 802.11n(HT40)/ax(HE40)
Channel Space:	5MHz
Antenna Type:	Dipole antenna
Number of Antenna	1
Antenna Gain:	4.31 dBi (Declared by the manufacturer)
Note: This report only applies to 2.4GHz WLAN feature of the EUT.	


Channel List			
IEEE 802.11b/ g/ n(HT20)/ax(HE20)		IEEE 802.11n(HT40)/ax(HE40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	---	---
2	2417	---	---
3	2422	3	2422
4	2427	4	2427
5	2432	5	2432
6	2437	6	2437
7	2442	7	2442
8	2447	8	2447
9	2452	9	2452
10	2457	----	----
11	2462	----	----

### 3. Test Channels and Modes Detail

Mode		Channel	Frequency (MHz)	Remark
1	TX	1	2412	IEEE 802.11b/ g/ n(HT20)/ax(HE20)
		3	2422	IEEE 802.11n(HT40)/ax(HE40)
		6	2437	IEEE 802.11b/ g/ n(HT20)/ n(HT40)/ ax(HE20)/ ax(HE40)
		9	2452	IEEE 802.11n(HT40) / ax(HE40)
		11	2462	IEEE 802.11b/ g/ n(HT20)/ ax(HE20)
2.	Normal	---	---	---

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

### 4. Configuration of EUT



### 5. Modification of EUT

No modifications are made to the EUT during all test items.

## 6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units.

The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Brand	M/N	S/N	Cable Specification	Remarks
1.	Laptop	DELL	VOSTR0 3400	H3K2XA01	I/P: AC 100-240V 50-60Hz, 1.3A O/P: DC 19.5V 2.31A 45W AC Line: 1.13m unshielded DC Line: 1.15m unshielded with a core	Provided by the Lab
2.	Adapter	DELL	HA45NM 140	---		Provided by the Lab
3.	Test fixture	---	---	---	----	Provide by the manufacturer
4.	Adapter	HUAWEI	HW-0502 00C01	---	Input: AC100-240V 50/60Hz, 0.5A Output: DC 5V 2A	Provide by the Lab.

Software	Power Setting	
	Mode	Setting
MobaXterm_Personal_23.2	IEEE 802.11b	7
	IEEE 802.11g	3
	IEEE 802.11n(HT20)	3
	IEEE 802.11n(HT40)	3
	IEEE 802.11ax(HE20)	3
	IEEE 802.11ax(HE40)	3

## 7. Test Facility and Location

Test Site	:	Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)
Accreditations and Authorizations	:	<p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>The Certificate is valid until December 31, 2025</p> <p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number is 907417</p> <p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number is 46405-9743A</p> <p>The CAB identifier number: CN0015</p>
Test Site Location	:	Building D, Gaosheng Science and Technology Park, Hongtu Road, Nancheng District, Dongguan City, Guangdong Province, China

---

## 8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

**Test Standards:**

47 CFR Part 15, Subpart C, 15.247

ANSI C63.10-2013

**References Test Guidance:**

DTS KDB 558074 D01 15.247 Meas Guidance v05r02

---

## 9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

## 10. Test Conditions

No.	Test Item	Test Mode	Test Voltage	Tested by	Remarks
1.	AC Power Conducted Emission	1	AC 120V 60Hz	Sean	See note 1
2.	Max. Conducted Output Power	1	AC 120V 60Hz	Sean	See note 1
3.	6dB Bandwidth	1	AC 120V 60Hz	Sean	See note 1
4.	Power Spectral Density	1	AC 120V 60Hz	Sean	See note 1
5.	Band Edge and Conducted Spurious Emissions	1	AC 120V 60Hz	Sean	See note 1
6.	Radiated Spurious Emissions and Restricted Bands	1, 2	AC 120V 60Hz	Sean	See note 1
7.	Antenna Requirement	---	---	---	---

**Note:**

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35°C, 30~70%, 86~106kPa.
2. For test voltage AC 120V 60Hz was come from adapter.

## 11. Measurement Uncertainty

No.	Test Item	Frequency	Uncertainty	Remarks
1.	Conducted Emission	150KHz ~ 30MHz	±2.52 dB	---
2.	Radiated Emission	9kHz ~ 30MHz	±5.66 dB	
		30MHz ~ 1GHz	±5.66 dB	---
		1GHz ~ 18GHz	±5.19 dB	---
		18GHz ~ 40GHz	±5.19 dB	
3.	Conducted Spurious Emissions	10Hz ~ 40GHz	±1.18 dB	---
4.	RF Output Power	10Hz ~ 40GHz	±1.18 dB	
5.	Power Spectral Density	10Hz ~ 40GHz	±1.06 dB	
6.	Occupied Channel Bandwidth	---	±0.72%	---

**Note:**

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

## 12. Sample Calculations

Conducted Emission						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.2540	22.47	10.03	32.50	61.63	-29.13	QP

Where,

Freq. = Emission frequency in MHz  
 Reading Level = Spectrum Analyzer/Receiver reading  
 Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation  
 Measurement = Reading + Corrector Factor  
 Limit = Limit stated in standard  
 Margin = Measurement - Limit  
 Detector = Reading for Quasi-Peak / Average / Peak

Radiated Spurious Emissions and Restricted Bands						
Freq. (MHz)	Reading Level (dBuV)	Correct Factor (dB/m)	Measurement (dBuV/m)	Limit (dBuV/m)	Over (dB)	Detector
176.4700	42.04	-9.54	32.50	43.50	-11.00	QP

Where,

Freq. = Emission frequency in MHz  
 Reading Level = Spectrum Analyzer/Receiver reading  
 Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier  
 Measurement = Reading + Corrector Factor  
 Limit = Limit stated in standard  
 Over = Margin, which calculated by Measurement - Limit  
 Detector = Reading for Quasi-Peak / Average / Peak

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

## 13. Test Items and Results

### 13.1 Conducted Emissions Measurement


#### LIMITS

According to the requirements of FCC PART 15.207, the limits are as follows:

Frequency (MHz)	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

Note: 1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.  
 2. The lower limit shall apply at the transition frequencies.  
 3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

#### BLOCK DIAGRAM OF TEST SETUP



---

## TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

## TEST RESULTS

PASS


Please refer to the following pages

M/N: KSM-WIFI-PLUG3	Testing Voltage: AC 120V/60Hz
Phase: L1	Detector: QP & AVG
Test Mode: 1	

### Conducted Emission Measurement

Date: 2024/3/6

Time: 9:33:29




No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1500	16.71	20.59	37.30	66.00	-28.70	QP	
2	0.1500	-2.39	20.59	18.20	56.00	-37.80	AVG	
3	0.1700	16.90	20.60	37.50	64.96	-27.46	QP	
4	0.1700	-3.00	20.60	17.60	54.96	-37.36	AVG	
5	0.2340	14.20	20.60	34.80	62.31	-27.51	QP	
6	0.2340	-3.10	20.60	17.50	52.31	-34.81	AVG	
7	0.3180	14.88	20.62	35.50	59.76	-24.26	QP	
8	0.3180	0.38	20.62	21.00	49.76	-28.76	AVG	
9	0.4661	15.29	20.61	35.90	56.58	-20.68	QP	
10	0.4661	5.69	20.61	26.30	46.58	-20.28	AVG	
11	0.5060	15.79	20.61	36.40	56.00	-19.60	QP	
12 *	0.5060	9.89	20.61	30.50	46.00	-15.50	AVG	

M/N: KSM-WIFI-PLUG3	Testing Voltage: AC 120V/60Hz
Phase: N	Detector: QP & AVG
Test Mode: 1	

### Conducted Emission Measurement

Date: 2024/3/6

Time: 9:38:12



No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
	MHz	dBuV	dB	dBuV	dB	Detector	Comment
1	0.1500	17.15	20.55	37.70	66.00	-28.30	QP
2	0.1500	-3.55	20.55	17.00	56.00	-39.00	AVG
3	0.1700	15.84	20.56	36.40	64.96	-28.56	QP
4	0.1700	-4.36	20.56	16.20	54.96	-38.76	AVG
5	0.2340	15.43	20.57	36.00	62.31	-26.31	QP
6	0.2340	-2.47	20.57	18.10	52.31	-34.21	AVG
7	0.3220	14.62	20.58	35.20	59.66	-24.46	QP
8	0.3220	-2.38	20.58	18.20	49.66	-31.46	AVG
9 *	0.4700	16.73	20.57	37.30	56.51	-19.21	QP
10	0.4700	2.13	20.57	22.70	46.51	-23.81	AVG
11	0.5060	15.33	20.57	35.90	56.00	-20.10	QP
12	0.5060	5.33	20.57	25.90	46.00	-20.10	AVG

## 13.2 Maximum Conducted Output Power Measurement

### LIMITS

For system using digital modulation in the 2400-2483.5 MHz bands, the limit for peak output power is 1 Watt.

If the transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6dBi.

In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of Antenna exceeds 6dBi.

### BLOCK DIAGRAM OF TEST SETUP



### TEST PROCEDURES

ANSI C63.10 - 2013, Section 11.9.1.3

ANSI C63.10 - 2013, Section 11.9.2.3.2

### TEST RESULTS

PASS

Please refer to the following table.


Channel	Frequency (MHz)	Data Rate (Mbps)	Peak Output Power (dBm)	Limit (dBm)	Result
<b>IEEE 802.11b</b>					
1	2412	1	18.138	≤30	PASS
6	2437	1	17.011	≤30	PASS
11	2462	1	18.107	≤30	PASS
<b>IEEE 802.11g</b>					
1	2412	6	10.446	≤30	PASS
6	2437	6	9.514	≤30	PASS
11	2462	6	10.692	≤30	PASS
<b>IEEE 802.11n(HT20)</b>					
1	2412	MCS0	10.246	≤30	PASS
6	2437	MCS0	9.273	≤30	PASS
11	2462	MCS0	10.559	≤30	PASS
<b>IEEE 802.11n(HT40)</b>					
3	2422	MCS0	9.274	≤30	PASS
6	2437	MCS0	9.425	≤30	PASS
9	2452	MCS0	9.861	≤30	PASS
<b>IEEE 802.11ax(HE20)</b>					
1	2412	MCS0	12.050	≤30	PASS
6	2437	MCS0	11.340	≤30	PASS
11	2462	MCS0	12.654	≤30	PASS
<b>IEEE 802.11ax(HE40)</b>					
3	2422	MCS0	10.606	≤30	PASS
6	2437	MCS0	10.880	≤30	PASS
9	2452	MCS0	11.297	≤30	PASS

### 13.3 6dB Bandwidth Measurement

#### LIMITS

The minimum 6dB bandwidth shall be at least 500 kHz

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to DTS KDB 558074 D01 15.247 Meas Guidance v05r02:

- a. Set the RBW = 100KHz.
- b. Set the VBW  $\geq 3 \times$  RBW
- c. Set the Detector = peak.
- d. Set the Sweep time = auto couple.
- e. Set the Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### TEST RESULTS

PASS

Please refer to the following tables.


Channel	Frequency (MHz)	Data Rate (Mbps)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Result
<b>IEEE 802.11b</b>						
1	2412	1	8.073	---	>0.5	PASS
6	2437	1	8.073	---	>0.5	PASS
11	2462	1	8.093	---	>0.5	PASS
<b>IEEE 802.11g</b>						
1	2412	6	16.37	---	>0.5	PASS
6	2437	6	16.39	---	>0.5	PASS
11	2462	6	16.37	---	>0.5	PASS
<b>IEEE 802.11n(HT20)</b>						
1	2412	MCS0	17.60	---	>0.5	PASS
6	2437	MCS0	17.62	---	>0.5	PASS
11	2462	MCS0	17.61	---	>0.5	PASS
<b>IEEE 802.11n(HT40)</b>						
3	2422	MCS0	36.42	---	>0.5	PASS
6	2437	MCS0	36.43	---	>0.5	PASS
9	2452	MCS0	36.39	---	>0.5	PASS
<b>IEEE 802.11ax(HE20)</b>						
1	2412	MCS0	19.02	---	>0.5	PASS
6	2437	MCS0	19.04	---	>0.5	PASS
11	2462	MCS0	19.02	---	>0.5	PASS
<b>IEEE 802.11ax(HE40)</b>						
3	2422	MCS0	38.04	---	>0.5	PASS
6	2437	MCS0	38.17	---	>0.5	PASS
9	2452	MCS0	38.10	---	>0.5	PASS

### Test Plots of 6dB Bandwidth

#### IEEE 802.11b - 2412MHz




#### IEEE 802.11b - 2437MHz



#### IEEE 802.11b - 2462MHz




#### IEEE 802.11g - 2412MHz




#### IEEE 802.11g - 2437MHz



#### IEEE 802.11g - 2462MHz








## 13.4 Power Spectral Density Measurement

### LIMITS

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

### BLOCK DIAGRAM OF TEST SETUP



### TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC DTS KDB 558074 D01 15.247 Meas Guidance v05r02:

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100\text{KHz}$
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Set the Detector = peak.
- f. Set the Sweep time = auto couple.
- g. Set the Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.
- j. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST RESULTS

PASS

Please refer to the following table.

Channel	Frequency (MHz)	Data Rate (Mbps)	PSD dBm / 3kHz	Limit dBm / 3kHz	Result
<b>IEEE 802.11b</b>					
1	2412	1	-6.980	8	PASS
6	2437	1	-7.424	8	PASS
11	2462	1	-7.084	8	PASS
<b>IEEE 802.11g</b>					
1	2412	6	-22.701	8	PASS
6	2437	6	-22.505	8	PASS
11	2462	6	-22.219	8	PASS
<b>IEEE 802.11n(HT20)</b>					
1	2412	MCS0	-22.706	8	PASS
6	2437	MCS0	-24.346	8	PASS
11	2462	MCS0	-23.058	8	PASS
<b>IEEE 802.11n(HT40)</b>					
3	2422	MCS0	-26.219	8	PASS
6	2437	MCS0	-27.094	8	PASS
9	2452	MCS0	-25.520	8	PASS
<b>IEEE 802.11ax(HE20)</b>					
1	2412	MCS0	-24.255	8	PASS
6	2437	MCS0	-24.689	8	PASS
11	2462	MCS0	-23.112	8	PASS
<b>IEEE 802.11ax(HE40)</b>					
3	2422	MCS0	-26.415	8	PASS
6	2437	MCS0	-26.195	8	PASS
9	2452	MCS0	-27.300	8	PASS

### Test Plots of Power Spectral Density


#### IEEE 802.11b - 2412MHz



#### IEEE 802.11b - 2437MHz




#### IEEE 802.11b - 2462MHz




#### IEEE 802.11g - 2412MHz





#### IEEE 802.11g - 2437MHz



#### IEEE 802.11g - 2462MHz








## 13.5 Band Edge and Conducted Spurious Emissions Measurement

### LIMITS

In any 100KHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### BLOCK DIAGRAM OF TEST SETUP



### TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to ANSI C63.10-2013, Section 11.11

#### Measurement Procedure REF

- a. Set the RBW = 100 kHz.
- b. Set the VBW  $\geq$  300 kHz.
- c. Set the Detector = peak.
- d. Set the Sweep time = auto couple.
- e. Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

---


## Measurement Procedure OOB

- a. Set RBW = 100 kHz.
- b. Set VBW  $\geq$  300 kHz.
- c. Set the Detector = peak.
- d. Set the Sweep = auto couple.
- e. Set the Trace Mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum amplitude level.

## TEST RESULTS


PASS

Please refer to the following test plots.




## Band Edge


### IEEE 802.11n(HT20) / Low Channel




### IEEE 802.11n(HT20) / High Channel



### IEEE 802.11n(HT40) / Low Channel



### IEEE 802.11n(HT40) / High Channel




## Band Edge


### IEEE 802.11ax(HE20) / Low Channel




### IEEE 802.11ax(HE20) / High Channel



### IEEE 802.11ax(HE40) / Low Channel



### IEEE 802.11ax(HE40) / High Channel




## Conducted Spurious Emissions – IEEE 802.11n(HT40) (The Worst Case)


### Lowest Channel



### Middle Channel



### Highest Channel



## 13.6 Radiated Spurious Emissions and Restricted Bands Measurement

### LIMIT of Radiated Band Edges and non-restricted bands

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

### LIMIT of Restricted bands

In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below:


Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)	
		μV/m	
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	
88 ~ 216	3	150	
216 ~ 960	3	200	
Above 960	3	500	

Remark: (1) Emission level (dB) $\mu$ V = 20 log Emission level  $\mu$ V/m


- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
- (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
- (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

## BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



## TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:

The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

g. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and packet type.

The worst case was found when the EUT was positioned on Z axis for radiated emission.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Frequency Band (MHz)	Detector	Resolution Bandwidth	Video Bandwidth
0.009~0.15	QP & AVG	200 Hz	1 kHz
0.15~30	QP & AVG	10 kHz	30 kHz
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	3 MHz
	Average	1 MHz	10 Hz

## TEST RESULTS

PASS


Please refer to the following pages of the worst case.

M/N: KSM-WIFI-PLUG3	Testing Voltage: AC 120V/60Hz
Polarization: Horizontal	Detector: QP
Test Mode: 1	Distance: 3m

## Radiated Emission Measurement

Date: 2024/3/18

Time: 13:33:30



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	Comment
1		84.3200	37.28	-10.88	26.40	40.00	-13.60	QP
2		184.2300	35.12	-8.82	26.30	43.50	-17.20	QP
3		247.2800	36.34	-6.44	29.90	46.00	-16.10	QP
4		480.0800	35.75	-2.05	33.70	46.00	-12.30	QP
5	*	720.6400	34.74	2.56	37.30	46.00	-8.70	QP
6		951.5000	29.22	6.28	35.50	46.00	-10.50	QP

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: KSM-WIFI-PLUG3

Testing Voltage: AC 120V/60Hz

Polarization: Vertical

Detector: QP


Test Mode: 1

Distance: 3m

## Radiated Emission Measurement

Date: 2024/3/18

Time: 13:25:32



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	85.2900	42.92	-10.72	32.20	40.00	-7.80	QP	
2		189.0800	42.22	-9.12	33.10	43.50	-10.40	QP	
3		299.6600	30.62	-6.52	24.10	46.00	-21.90	QP	
4		480.0800	37.55	-3.05	34.50	46.00	-11.50	QP	
5		600.3600	28.41	-0.31	28.10	46.00	-17.90	QP	
6		720.6400	26.64	2.56	29.20	46.00	-16.80	QP	

Note: Below 30MHz, the emissions are lower than 20dB below the allowable limit.

Modulation: TX (IEEE 802.11ax(HE20)the worst case)				Test Result: PASS			Test frequency range: 1-25GHz			
Freq. (MHz)	Ant. Pol. (H/V)	Reading Level(dBuV)		Factor (dB/m)	Emission Level (dBuV/m)		Limit 3m (dBuV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
<b>Operation Mode: TX Mode (Low)</b>										
4824	H	45.72	31.63	6.38	52.10	38.01	74.00	54.00	-21.90	-15.99
7236	H	45.64	29.84	10.48	56.12	40.32	74.00	54.00	-17.88	-13.68
---										
4824	V	45.58	31.65	6.38	51.96	38.03	74.00	54.00	-22.04	-15.97
7236	V	45.74	29.63	10.48	56.22	40.11	74.00	54.00	-17.78	-13.89
---										
<b>Operation Mode: TX Mode (Mid)</b>										
4874	H	45.73	32.08	6.56	52.29	38.64	74.00	54.00	-21.71	-15.36
7311	H	46.04	31.45	10.53	56.57	41.98	74.00	54.00	-17.43	-12.02
---										
4874	V	45.67	31.86	6.56	52.23	38.42	74.00	54.00	-21.77	-15.58
7311	V	46.44	30.74	10.53	56.97	41.27	74.00	54.00	-17.03	-12.73
---										
<b>Operation Mode: TX Mode (High)</b>										
4924	H	45.23	32.29	6.76	51.99	39.05	74.00	54.00	-22.01	-14.95
7386	H	46.64	31.75	10.57	57.21	42.32	74.00	54.00	-16.79	-11.68
---										
4924	V	44.99	32.20	6.76	51.75	38.96	74.00	54.00	-22.25	-15.04
7386	V	46.32	31.53	10.57	56.89	42.10	74.00	54.00	-17.11	-11.90
---										
<b>Spurious Emission in restricted band:</b>										
2390.000	H	63.72	36.17	0.09	63.81	36.26	74.00	54.00	-10.19	-17.74
2390.000	V	57.03	36.16	0.09	57.12	36.25	74.00	54.00	-16.88	-17.75
2483.500	H	67.89	38.45	0.34	68.23	38.79	74.00	54.00	-5.77	-15.21
2483.500	V	56.48	35.28	0.34	56.82	35.62	74.00	54.00	-17.18	-18.38
Remark: 1. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits. 2. Others emissions are attenuated 20dB below the limits, so it does not record in report.										

---

## 13.7 Antenna Requirement

### STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.247:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### ANTENNA CONNECTED CONSTRUCTION

The antenna is dipole antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is 4.31 dBi, Therefore, the antenna is considered to meet the requirement.

## 14. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI7	100837	Mar. 12, 2024	1 Year
2.	Antenna	Schwarzbeck	VULB9162	9162-010	Mar. 23, 2024	2 Year
3.	Spectrum Analyzer	Keysight	N9020A	MY54200831	Mar. 12, 2024	1 Year
4.	Spectrum Analyzer	Keysight	N9010B	MY62170254	Aug. 07, 2023	1 Year
5.	Power Sensor	DARE	RPR3006W	15I00041SNO 64	Mar. 12, 2024	1 Year
6.	Horn Antenna	COM-Power	AH-118	071078	Mar. 23, 2024	2 Year
7.	Pre-Amplifier	HP	HP 8449B	3008A00964	Mar. 12, 2024	1 Year
8.	Pre-Amplifier	HP	HP 8447D	1145A00203	Mar. 12, 2024	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1513	1513-272	Mar. 23, 2024	2 Year
10.	Horn Antenna	COM-Power	AH-840	10100020	Mar. 23, 2024	2 Year
11.	Test Receiver	Rohde & Schwarz	ESCI	101152	Mar. 12, 2024	1 Year
12.	L.I.S.N	Rohde & Schwarz	ENV 216	101317	Mar. 12, 2024	1 Year
13.	L.I.S.N	Rohde & Schwarz	ESH2-Z5	893606/014	Mar. 12, 2024	1 Year
14.	RF Switching Unit	Compliance Direction Systems Inc.	RSU-M2	38311	Mar. 12, 2024	1 Year
15.	Temperature & Humidity Chamber	Wanshun	SS-HWHS-80	N/A	Mar. 12, 2024	1 Year
16.	DC Source	Maynuo	MY8811	N/A	Mar. 12, 2024	1 Year
17.	Temporary antenna connector	TESCOM	SS402	N/A	N/A	N/A
18.	Chamber	SAEMC	9*7*7m	N/A	Apr. 21, 2023	2 Year
19.	Test Software	EZ	EZ_EMU, NTC-3A1.1	N/A	N/A	N/A
20.	Test Software	MWRF	MTS 8310, V2.0.0.0	N/A	N/A	N/A

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End--