



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20241202716E-02

Applicant: Fourth Space Co., LTD

Address of Applicant: Room 1002, Building C, Phase II, Unibuit Industrial Park, SHENZHEN, China

Equipment Under Test (EUT):

EUT Name: Outdoor Air Conditioner

Model No.: S2 Pro, S2 Pro-X, S2 Pro-E, S2 Pro-B, S2 Pro-W, S2 Pro-Y

Test Model No.: S2 Pro

Brand Name: Cybertake

FCC ID: 2BGZ7-S2PRO

Standards: 47 CFR Part 1.1307

47 CFR Part 1.1310

447498 D04 Interim General RF Exposure Guidance v01

Date of Receipt: 2024-12-25

Date of Test: 2024-12-25 to 2025-06-04

Date of Issue: 2025-06-18

Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: lewis zhou

(Lewis Zhou)

Reviewed By: Timo Lei

(Timo Lei)

Approved By: Jack Ai

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20241202716E-02	Rev.01	Initial report	2025-06-18

Model No.: S2 Pro, S2 Pro-X, S2 Pro-E, S2 Pro-B, S2 Pro-W, S2 Pro-Y

Their electrical circuit design, layout, components used and internal wiring are identical,

Only the Sales platforms and regions are different.

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
4 MPE EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 <i>Limits</i>	5
4.1.2 <i>Test Procedure</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Fourth Space Co., LTD
Address of Applicant:	Room 1002, Building C, Phase II, Unibuit Industrial Park, SHENZHEN,China
Manufacturer:	Fourth Space Co., LTD
Address of Manufacturer:	Room 1002, Building C, Phase II, Unibuit Industrial Park, SHENZHEN,China
Factory:	Fourth Space Co., LTD
Address of Factory:	Room 1002, Building C, Phase II, Unibuit Industrial Park, SHENZHEN,China

3.2 General Description of EUT

Product Name:	Outdoor Air Conditioner
Model No.:	S2 Pro, S2 Pro-X, S2 Pro-E, S2 Pro-B, S2 Pro-W, S2 Pro-Y
Test Model No.:	S2 Pro
Trade Mark:	Cybertake
Software Version:	V1.0
Hardware Version:	V1.0
EUT Power Supply:	AC/DC adapter: Model:GP600-4801150-F Input:230V~50Hz 7.0A Output:48V 11.5A 552W

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	<input checked="" type="checkbox"/> Mobile <input type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Antenna Type:	Serial
Antenna Gain:	PCB antenna
Cable loss:	2.499dBi

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda /2 \pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda /4$ or if the antenna gain is less than that of a half-wave Dipole).

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	1.129	-1.02	-1±1	0	1
Middle(2441MHz)	1.709	-0.44	-0.5±1	0.5	1.122
Highest(2480MHz)	2.069	-0.08	-1±1	0	1
π/4DQPSK mode					
Test channel	EIRP (dBm)	ERP (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
				(dBm)	(mW)
Lowest(2402MHz)	1.509	-0.64	-0.5±1	-0.5	0.891
Middle(2441MHz)	1.999	-0.15	-1±1	0	1
Highest(2480MHz)	2.319	0.17	-0.5±1	0.5	1.122

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20241202716E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

*** END OF REPORT ***