



Maximum Permissible Exposure Evaluation

FCC ID: 2BH2A-WWS15

1. Client Information

Applicant	:	Wanbang Electric (Shenzhen) Co., Ltd
Address	:	520, Henglong Building, Building M8, Maqueling Industrial Zone, Maling Community, Yuehai Street, Nanshan District, Shenzhen China
Manufacturer	:	YUEQING COMBO ELECTRLC, CO .,LTD
Address	:	FLOOR 5 NO 7 YONGXING FIRST RD CHENGDONG INDUSTRIAL ZONE YUEQING CITY ZHEJIANG PROVIENCE 325600 CHINA

2. General Description of EUT

EUT Name	:	Garbage Disposal Wireless Switch Kit
Models No.	:	WWS15, WWS15-DC, WWS20, WWS20-DC
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name.
Brand Name	:	N/A
Sample ID	:	HC-C-202405-0327-02-01
Product Description	:	Operation Frequency: 433.92MHz
Power Rating	:	Relay supply:DC 2.2V 13mA
Software Version	:	V1.0
Hardware Version	:	V1.2
Remark	:	The antenna gain provided by the manufacturer, the verified for the RF conduction test provided by TOBY test lab.

Method of Measurement for FCC

1. Max. Antenna Gain:

Mode	Antenna Type	Antenna Gain(dBi)
433.92	FPC	-6.52

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = (PG) / 4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

Simultaneous transmission MPE Considerations

According to KDB447498: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios} \leq 1.0$$



4. Test Result:

Worst MPE Result							
Frequency (MHz)	Max. Output Power (dBuV/m)	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	Max. ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]
433.92	67.46	-33.80	-33±1	-32	-6.52	20	0.000000028

Note: The antenna gain used max. antenna gain

Note: For conducted measurements below 1000 MHz, the field strength shall be computed as specified in item d), and then an additional 4.7 dB shall be added as an upper bound on the field strength that would be observed on a test range with a ground plane for frequencies between 30 MHz and 1000 MHz, or an additional 6 dB shall be added for frequencies below 30 MHz.

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

E is the electric field strength in dB μ V/m
 EIRP is the equivalent isotropically radiated power in dBm
 d is the specified measurement distance in m

So: $\text{EIRP} = E + 20 \log 3 - 104.8 - (4.7 \text{ or } 6)$

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For: 2402~2480MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as **0.000000028mW / cm² < limit 1mW / cm².**

So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091 (b). The RF Exposure Information page from the manual is included here for reference.

-----END OF REPORT-----

