

MAXIMUM PERMISSIBLE EXPOSURE

KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

EUT Specification

FCC ID	2BH39-7488000361
EUT	Klick&Show K-FleX
Frequency band (Operating)	☐ BT: 2.402GHz ~ 2.480GHz ☒ WLAN: 2.412GHz ~ 2.462GHz ☒ RLAN: 5.180GHz ~ 5.240GHz ☐ RLAN: 5.260GHz ~ 5.320GHz ☐ RLAN: 5.500GHz ~ 5.700GHz ☒ RLAN: 5.745GHz ~ 5.825GHz ☐ Others:
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	Module1: Wifi 2.4G: 2.68dBi WiFi 5.2G: 2.03dBi WiFi 5.8G: 3.88dBi Module2: Wifi 2.4G: Wifi 2.4G: ANT1: 2.68dBi Wifi 2.4G: ANT2: 2.68dBi WiFi 5.2G ANT1: 2.03dBi WiFi 5.2G ANT2: 2.03dBi WiFi 5.8G ANT1: 3.88dBi WiFi 5.8G ANT2: 3.88dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Shenzhen Anbotek Compliance Laboratory Limited

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	30
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operating Mode	Maximum output power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
WLAN Module1	14.98	14.98 ±1	15.98	2.68	0.0146	1
WLAN Module1 ANT 1	14.76	14.76 ±1	15.76	2.68	0.0139	1
WLAN Module1 ANT2	14.33	14.33 ±1	15.33	2.68	0.0126	1
WIFI 5.2G Module1	15.10	15.10 ±1	16.1	2.03	0.0129	1
WIFI 5.2G Module2 ANT 1	14.67	14.67 ±1	15.67	2.03	0.0117	1
WIFI 5.2G Module2 ANT 2	12.81	12.81 ±1	13.81	2.03	0.0076	1
WIFI 5.8G Module1	16.17	16.17 ±1	17.17	3.88	0.0253	1
WIFI 5.8G Module2 ANT 1	14.44	14.44 ±1	15.44	3.88	0.0170	1
WIFI 5.8G Module2 ANT 2	13.26	13.26 ±1	14.26	3.88	0.0130	1

The Maximum simultaneous transmission for WLAN Module1+WIFI 5.8G Module2
ANT 1+WIFI 5.8G Module2 ANT 2:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= \frac{S_{WLAN \text{ Module1}}}{S_{limit-2.4}} + \frac{S_{WIFI \ 5.8G \ \text{Module2 ANT 1}}}{S_{limit-5.8}} + \frac{S_{WIFI \ 5.8G \ \text{Module2 ANT 2}}}{S_{limit-5.8}} =$$

$$0.0146/1 + 0.0170/1 + 0.0130/1$$

$$= 0.0446$$

$$< 1.0$$

Result: No Standalone SAR test is required.

