



TEST REPORT

Applicant: Alejandro Munoz Hansker Design
Address of Applicant: Pontsteiger 57 1014ZP Amsterdam The Netherlands
Manufacturer/Factory: Alejandro Munoz Hansker Design
Address of Manufacturer/Factory: Pontsteiger 57 1014ZP Amsterdam The Netherlands
Product Name: Hansker mouse
Model No.: Hansker Ergonomic Mouse
Trade Mark: Hansker Design
FCC ID: 2BH55-HANSKER
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249
Date of Test: Jul.22,2024-Jul.30,2024
Date of report issued: Sept.20,2024

Remark:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver

Prepared By

Shenzhen ETR Standard Technology Co., Ltd.

Address: No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Compiled by:

Project Engineer

Reviewed by:

Project Manager

Approved by:

Authorized Signature



Report Revision History		
Report No.	Description	Issue Date
ET-24070948E02	Original	Sept.20,2024

Contents

	Page
1 TEST SUMMARY	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 TEST MODE	7
2.3 DESCRIPTION OF SUPPORT UNITS	7
2.4 DEVIATION FROM STANDARDS	7
2.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
2.6 TEST FACILITY	7
2.7 TEST LOCATION	7
2.8 ADDITIONAL INSTRUCTIONS	7
3 TEST INSTRUMENTS LIST	8
4 TEST RESULTS AND MEASUREMENT DATA	9
4.1 ANTENNA REQUIREMENT	9
4.2 CONDUCTED EMISSIONS	10
4.3 RADIATED EMISSION MEASUREMENT	13
4.3.1 <i>Field Strength of The Fundamental Signal</i>	15
4.3.2 <i>Spurious emissions</i>	16
4.4 20DB BANDWIDTH AND 99% BANDWIDTH	21
5 TEST SETUP PHOTO	23
6 EUT CONSTRUCTIONAL DETAILS	23

1 Test Summary

Test Item	Section in CFR 47	Result	Test by
Antenna requirement	15.203	Pass	/
AC Power Line Conducted Emission	15.207	Pass	Yao Zhou
Field strength of the fundamental signal	15.249 (a)	Pass	Yvan Fan
Spurious emissions	15.249 (a) (d)/15.209	Pass	Tianyu Huang
Band edge	15.249 (d)/15.205	Pass	Yvan Fan
20dB Occupied Bandwidth 99% Occupied Bandwidth	15.215 (c)	Pass	Yvan Fan

Remarks:

1. *Pass: The EUT complies with the essential requirements in the standard.*
2. *Test according to ANSI C63.10:2013*
3. *Note: Compliance determination rules*

1). *The Compliance determination of test results does not take into account measurement uncertainty. Measurement results are determined based on regulatory limitations or requirements specified by the applicant/manufacturer. If measurement uncertainty is taken into account, the applicant/manufacturer will bear all possible risks of non-compliance.*

2). *The measurement uncertainty please refer to each test result in the "Measurement Uncertainty"*

Measurement Uncertainty

Test Item	Uncertainty Criterion	Measurement Uncertainty	Notes
Occupied Channel Bandwidth	±5%	±0.55%	(1)
RF output power, conducted	±1.5dB	±0.99dB	(1)
Power Spectral Density, conducted	±3dB	±0.61dB	(1)
Unwanted Emissions, conducted	±3dB	±0.64dB	(1)
AC Power Line Conducted Emission	±6dB	± 2.64 dB	(1)
Radiated emissions Below 1GHz	±6dB	±4.32 dB	(1)
Radiated emissions Above 1GHz	±6dB	±4.56dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

2 General Information

2.1 General Description of EUT

Product Name:	Hansker mouse
Model No.:	Hansker Ergonomic Mouse
Model of difference:	N/A
Test model:	Hansker Ergonomic Mouse
Sample(s) Status:	Engineer sample
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	16
Channel separation:	2.5MHz
Modulation type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	1.2dBi (Note: Antenna information is provided by applicant, Testing lab is not responsible for the accuracy of the information.)
Battery:	DC 3.7V 600mAh
Power supply:	DC 3.7V From battery or DC 5V From Adapter

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402 MHz	11	2459 MHz	21	/	31	/
2	2426 MHz	12	2473 MHz	22	/	32	/
3	2440 MHz	13	2419 MHz	23	/	33	/
4	2463 MHz	14	2439 MHz	24	/	34	/
5	2407 MHz	15	2453 MHz	25	/	35	/
6	2422 MHz	16	2480 MHz	26	/	36	/
7	2445 MHz	17	/	27	/	37	/
8	2466 MHz	18	/	28	/	38	/
9	2414 MHz	19	/	29	/	39	/
10	2436 MHz	20	/	30	/	40	/

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402 MHz
The middle channel	2440 MHz
The Highest channel	2480 MHz

2.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: For battery operated equipment, the EUT was performed using a new DC 3.7V battery.</i>	

2.3 Description of Support Units

No.	Description	Manufacturer	Model	Serial Number
1	Adapter	Xiao mi	5V/2A	/

2.4 Deviation from Standards

None.

2.5 Abnormalities from Standard Conditions

None.

2.6 Test Facility

Test laboratory:	Shenzhen ETR Standard Technology Co., Ltd.
CNAS Registration Number:	L11864
A2LA Certificate Number:	6640.01
FCC Designation Number:	CN1326
FCC Test Firm Registration:	183064

2.7 Test Location

All tests were performed at:	
Laboratory location:	No.103, No.10, Phase I, Zone 3, Xinxing Industrial Park, Xinhe, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	+86 755 85259392
Fax:	+86 755 27219460

2.8 Additional Instructions

Test Software	Manufacturer's special fixed frequency mode
Power level setup	Default

3 Test Instruments list

Item	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	EMI Test Receiver	Rohde&schwarz	ESCI7	100605	2024.3.12	2025.3.11
2	EMI Test Receiver	Rohde&schwarz	ESCI3	102696	2024.3.12	2025.3.11
3	Loop Antenna	schwarabeck	FMZB 1519 B	FMZB 1519 B	2024.3.19	2026.3.18
4	Broadband antenna	schwarabeck	VULB9168	1064	2024.3.19	2026.3.18
5	Horn antenna	schwarabeck	BBHA9120D	9120D-1145	2024.3.19	2026.3.18
6	amplifier	EMtrace	RP01A	50117	2024.3.12	2025.3.11
7	Artificial power network	schwarabeck	NSLK8127	8127483	2024.3.12	2025.3.11
8	Artificial power network	ETS	3186/2NM	1132	2024.3.12	2025.3.11
9	10dB attenuator	HUBER+SUHN ER	10dB	/	2024.3.12	2025.3.11
10	amplifier	Space-Dtronics	EWLAN0118G-P40	19113001	2024.3.12	2025.3.11
11	Filter	Xingbo	XBLBQ-GTA19	210410-3-1	2024.3.12	2025.3.11
12	Spectrum analyzer	KEYSIGHT	N9020A	MY55370280	2024.3.12	2025.3.11
13	Power detector box	MWRFtest	MW100-PSB	MW201020JYT	2024.3.12	2025.3.11
14	Power meter	Rohde&Schwarz	NRP-Z11	1138.3004.02-117725-vh	2024.3.12	2025.3.11
15	amplifier	SKET	LNPA_1840-50 (18-40GHz)	SK2019040302	2024.3.12	2025.3.11
16	Horn antenna	schwarabeck	BBHA 9170	946	2024.3.19	2026.3.18
17	Spectrum analyzer	Rohde&schwarz	FSU40	1166.1660K43	2024.3.12	2025.3.11

Note: the calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to international system unit (SI).

Software Name	Manufacturer	Model	Version
RF test software	MWRFtest	MTS 8310	V2.0.0.0
Conducted test software	EZ-EMC	Farad	Ver.EMC-CON 3A1.1
Radiated test software	EZ-EMC	Farad	Ver.FA-03A2 RE

4 Test results and Measurement Data

4.1 Antenna requirement

Standard requirement:
FCC part 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:
The antenna is PCB antenna, the best case gain of the antenna is 1.20dBi, reference to the appendix II for details.

4.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207,		
Test Method:	ANSI C63.10:2013		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50

* Decreases with the logarithm of the frequency.


Test setup:	Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	- The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. - The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). - Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	24.1 °C	Humid.:	50%	Press.:	1012mbar
Test voltage:	AC 120V/60Hz					
Test results:	Pass					

Remark:


- Both high voltage and low voltage have been tested, and the report only shows the worst case data with AC 120V/60Hz.
- All mode have been tested, the report only shows the worst mode (2440MHz) data.

Measurement data

Line:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2310	14.90	9.82	24.72	62.41	-37.69	QP
2	0.2310	6.30	9.82	16.12	52.41	-36.29	AVG
3	0.4470	16.74	9.92	26.66	56.93	-30.27	QP
4	0.4470	4.36	9.92	14.28	46.93	-32.65	AVG
5	0.9464	10.73	9.96	20.69	56.00	-35.31	QP
6	0.9464	-2.10	9.96	7.86	46.00	-38.14	AVG
7	1.5043	10.97	9.90	20.87	56.00	-35.13	QP
8	1.5043	-0.97	9.90	8.93	46.00	-37.07	AVG
9	11.7690	13.01	9.81	22.82	60.00	-37.18	QP
10	11.7690	2.25	9.81	12.06	50.00	-37.94	AVG
11	17.7809	12.49	9.70	22.19	60.00	-37.81	QP
12	17.7809	1.71	9.70	11.41	50.00	-38.59	AVG


Neutral:


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4470	18.84	9.92	28.76	56.93	-28.17	QP
2	0.4470	10.43	9.92	20.35	46.93	-26.58	AVG
3	1.1624	11.84	9.94	21.78	56.00	-34.22	QP
4	1.1624	1.26	9.94	11.20	46.00	-34.80	AVG
5	1.5673	11.78	9.90	21.68	56.00	-34.32	QP
6	1.5673	0.96	9.90	10.86	46.00	-35.14	AVG
7	2.5485	11.42	9.85	21.27	56.00	-34.73	QP
8	2.5485	-0.06	9.85	9.79	46.00	-36.21	AVG
9	11.6519	15.95	9.82	25.77	60.00	-34.23	QP
10	11.6519	3.49	9.82	13.31	50.00	-36.69	AVG
11	17.9969	16.31	9.70	26.01	60.00	-33.99	QP
12	17.9969	5.39	9.70	15.09	50.00	-34.91	AVG

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Level = Receiver Read level + Factor (Factor = LISN Factor + Cable Loss + Attenuator Factor)
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

4.3 Radiated Emission measurement

Test Requirement:	FCC Part15 C Section 15.209 & 15.249 (a) &(d).								
Test Method:	ANSI C63.10: 2013								
Test Frequency Range:	9kHz to 25GHz								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value				
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
		Peak	1MHz	10Hz	Average Value				
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark					
	2400MHz-2483.5MHz		94.00	Average Value					
			114.00	Peak Value					
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)		Remark					
	0.009MHz-0.490MHz	2400/F(kHz) @300m		Quasi-peak Value					
	0.490MHz-1.705MHz	24000/F(kHz) @30m		Quasi-peak Value					
	1.705MHz-30.0MHz	30 @30m		Quasi-peak Value					
	30MHz-88MHz	100 @3m		Quasi-peak Value					
	88MHz-216MHz	150 @3m		Quasi-peak Value					
	216MHz-960MHz	200 @3m		Quasi-peak Value					
	960MHz-1GHz	500 @3m		Quasi-peak Value					
	Above 1GHz	500 @3m		Average Value					
		5000 @3m		Peak Value					
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.								
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to 1GHz								



For radiated emissions above 1GHz



Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 3.0 for details
Test mode:	Refer to section 2.2 for details
Test environment:	Temp.: 23.4 °C Humid.: 51% Press.: 1012mbar
Test voltage:	Below 1GHz: DC 5V Above 1GHz: DC 3.7V
Test results:	Pass

4.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	100.59	-14.43	86.16	114.00	-27.84	Vertical
2402.00	98.46	-14.43	84.03	114.00	-29.97	Horizontal
2440.00	103.40	-14.29	89.11	114.00	-24.89	Vertical
2440.00	101.30	-14.29	87.01	114.00	-26.99	Horizontal
2480.00	99.53	-14.13	85.40	114.00	-28.60	Vertical
2480.00	96.96	-14.13	82.83	114.00	-31.17	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	85.36	-14.43	70.93	94.00	-23.07	Vertical
2402.00	82.64	-14.43	68.21	94.00	-25.79	Horizontal
2440.00	83.73	-14.29	69.44	94.00	-24.56	Vertical
2440.00	81.64	-14.29	67.35	94.00	-26.65	Horizontal
2480.00	81.15	-14.13	67.02	94.00	-26.98	Vertical
2480.00	80.00	-14.13	65.87	94.00	-28.13	Horizontal


4.3.2 Spurious emissions

■ Below 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

■ Below 1GHz

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.4808	41.17	-21.18	19.99	40.00	-20.01	QP
2	93.1131	54.44	-25.35	29.09	43.50	-14.41	QP
3	154.2785	39.11	-20.54	18.57	43.50	-24.93	QP
4	199.9855	42.76	-23.38	19.38	43.50	-24.12	QP
5	345.5951	41.58	-19.40	22.18	46.00	-23.82	QP
6	968.9337	34.26	-3.64	30.62	54.00	-23.38	QP

Vertical:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	51.1208	44.06	-21.90	22.16	40.00	-17.84	QP
2	88.3421	59.28	-25.52	33.76	43.50	-9.74	QP
3	161.4739	44.48	-20.63	23.85	43.50	-19.65	QP
4	201.3930	44.00	-23.39	20.61	43.50	-22.89	QP
5	314.3763	40.30	-19.70	20.60	46.00	-25.40	QP
6	378.5842	39.72	-18.03	21.69	46.00	-24.31	QP

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV/m)	Correction Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	66.88	-9.88	57.00	74.00	-17.00	Horizontal
7206.00	57.64	-4.17	53.47	74.00	-20.53	Horizontal
9608.00	---	---	---	---	---	Horizontal
12010.00	---	---	---	---	---	Horizontal
4804.00	68.37	-9.88	58.49	74.00	-15.51	Vertical
7206.00	58.80	-4.17	54.63	74.00	-19.37	Vertical
9608.00	---	---	---	---	---	Vertical
12010.00	---	---	---	---	---	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV/m)	Correction Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	55.51	-9.88	45.63	54.00	-8.37	Horizontal
7206.00	46.65	-4.17	42.48	54.00	-11.52	Horizontal
9608.00	---	---	---	---	---	Horizontal
12010.00	---	---	---	---	---	Horizontal
4804.00	56.61	-9.88	46.73	54.00	-7.27	Vertical
7206.00	46.53	-4.17	42.36	54.00	-11.64	Vertical
9608.00	---	---	---	---	---	Vertical
12010.00	---	---	---	---	---	Vertical

Remark:

1. Final Level =Receiver Read level +Correction Factor(Antenna Factor + Cable Loss – Preamplifier Factor)
2. The emission levels of other frequencies are more than 20 dB below the limit and not show in test report.
3. **, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV/m)	Correction Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	67.29	-9.79	57.50	74.00	-16.50	Horizontal
7320.00	62.07	-3.83	58.24	74.00	-15.76	Horizontal
9760.00	---	---	---	---	---	Horizontal
12200.00	---	---	---	---	---	Horizontal
4880.00	66.03	-9.79	56.24	74.00	-17.76	Vertical
7320.00	61.99	-3.83	58.16	74.00	-15.84	Vertical
9760.00	---	---	---	---	---	Vertical
12200.00	---	---	---	---	---	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV/m)	Correction Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	56.51	-9.79	46.72	54.00	-7.28	Horizontal
7320.00	47.19	-3.83	43.36	54.00	-10.64	Horizontal
9760.00	---	---	---	---	---	Horizontal
12200.00	---	---	---	---	---	Horizontal
4880.00	55.67	-9.79	45.88	54.00	-8.12	Vertical
7320.00	46.24	-3.83	42.41	54.00	-11.59	Vertical
9760.00	---	---	---	---	---	Vertical
12200.00	---	---	---	---	---	Vertical

Remark:

1. Final Level = Receiver Read level + Correction Factor (Antenna Factor + Cable Loss – Preamplifier Factor)
2. The emission levels of other frequencies are more than 20 dB below the limit and not show in test report.
3. ** means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV/m)	Correction Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	66.63	-9.68	56.95	74.00	-17.05	Horizontal
7440.00	56.85	-3.50	53.35	74.00	-20.65	Horizontal
9920.00	---	---	---	---	---	Horizontal
12400.00	---	---	---	---	---	Horizontal
4960.00	68.13	-9.68	58.45	74.00	-15.55	Vertical
7440.00	56.01	-3.50	52.51	74.00	-21.49	Vertical
9920.00	---	---	---	---	---	Vertical
12400.00	---	---	---	---	---	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV/m)	Correction Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	53.77	-9.68	44.09	54.00	-9.91	Horizontal
7440.00	46.02	-3.50	42.52	54.00	-11.48	Horizontal
9920.00	---	---	---	---	---	Horizontal
12400.00	---	---	---	---	---	Horizontal
4960.00	53.84	-9.68	44.16	54.00	-9.84	Vertical
7440.00	46.34	-3.50	42.84	54.00	-11.16	Vertical
9920.00	---	---	---	---	---	Vertical
12400.00	---	---	---	---	---	Vertical

Remark:

1. Final Level =Receiver Read level + Correction Factor(Antenna Factor + Cable Loss – Preamplifier Factor)
2. The emission levels of other frequencies are more than 20 dB below the limit and not show in test report.
3. **, means this data is the too weak instrument of signal is unable to test.

4.4 20dB Bandwidth and 99% bandwidth




Test Requirement:	FCC Part15 C Section 15.215					
Test Method:	ANSI C63.10:2013					
Limit:	/					
Test setup:						
Test Instruments:	Refer to section 3.0 for details					
Test mode:	Refer to section 2.2 for details					
Test environment:	Temp.:	23.4 °C	Humid.:	51%	Press.:	1012mbar
Test voltage:	DC 3.7V					
Test Mode:	TX					

Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.049	Pass
Middle	1.064	
Highest	1.061	

Test channel	99% bandwidth(MHz)	Result
Lowest	0.99014	Pass
Middle	1.00030	
Highest	0.99754	

Test plot as follows:


Lowest channel

Middle channel

Highest channel

5 Test Setup Photo

Reference to the **appendix I** for details.

6 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----