

RF EXPOSURE EVALUATION METHOD**FCC ID:2BH5M-HCS-P1****According to KDB 447498 D01 General RF Exposure Guidance v06****SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	0.317	1.076
CH39	2441	1.527	1.421
CH78	2480	2.374	1.727
2Mbps			
CH00	2402	-1.136	0.770
CH39	2441	0.074	1.017
CH78	2480	1.030	1.268
3Mbps			
CH00	2402	-0.644	0.862
CH39	2441	0.594	1.147
CH78	2480	1.529	1.422

BLE

Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
1M			
CH00	2402	0.323	1.077
CH19	2440	1.483	1.407
CH39	2480	2.379	1.729
2M			
CH00	2402	0.321	1.077
CH19	2440	1.506	1.414
CH39	2480	2.387	1.733

Remark: The best case gain of the antenna is 1.2dBi.

1.2 dBi logarithmic terms convert to numeric result is nearly 1.32

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right]$$

Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)]	(min. test separation distance, mm)]	[f(GHz)]	Result	Limit
BT							
1Mbps							
CH00	2~0	2	1.585	5	2.402	0.491	3
CH39	2~0	2	1.585	5	2.441	0.495	3
CH78	3~1	3	1.995	5	2.480	0.628	3
2Mbps							
CH00	0~-2	0	1.000	5	2.402	0.310	3
CH39	1~-1	1	1.259	5	2.441	0.393	3
CH78	2~0	2	1.585	5	2.480	0.499	3
3Mbps							
CH00	0~-2	0	1.000	5	2.402	0.310	3
CH39	1~-1	1	1.259	5	2.441	0.393	3
CH78	2~0	2	1.585	5	2.480	0.499	3

BLE							
1M							
CH00	2~0	2	1.585	5	2.402	0.491	3
CH39	2~0	2	1.585	5	2.440	0.495	3
CH78	3~1	3	1.995	5	2.480	0.628	3
2M							
CH00	2~0	2	1.585	5	2.402	0.491	3
CH39	2~0	2	1.585	5	2.440	0.495	3
CH78	3~1	3	1.995	5	2.480	0.628	3

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.